

## MPE TEST REPORT

For

MODEL NO.: 1707 FCC ID: C3K1707 IC ID: 3048A-1707

Test Report No. R-TR371-FCCIC-MPE-3 Issue Date: 19 Oct 2016

FCC 47CFR Parts 1.1307, 1.1310, 2.1091 Innovation, Science and Economic Development Canada RSS-102 Issue 5

> Prepared by Microsoft EMC Laboratory 17760 NE 67th Ct, Redmond WA, 98052, U.S.A. 425-421-9799 sajose@microsoft.com





## 1 Record of Revisions

Revision	Date	Section	Page(s)	Summary of Changes	Author/Revised By:
1.0	09/23/2016	All	All	Version 1.0	Zack Gray
2.0	10/14/2016	4	6	- Updated product description. - Corrected frequency range typo for 2.4GHz WLAN.	Zack Gray
3.0	10/19/2016	7	11	- Corrected typo for standard reference from 1.1091 to 2.1091.	Zack Gray
	1				



## **Table of Contents**

1	Re	ecord of Revisions	2
2	De	eviations from Standards	5
3	Fa	acilities and Accreditations	5
	3.1	Test Facility	5
	3.2	Accreditations	5
4	Pr	roduct Description	6
5	MF	PE Requirements	7
	5.1	FCC MPE Requirements	7
	5.1	1.1 FCC RF Exposure Exemption Criteria	7
	5.2	ISED MPE Requirements	9
	5.2	2.1 ISED MPE Exemption Requirements from RSS-102 Section 2.5.2	9
6	Ma	aximum Device EIRP and ERP	10
7	Εv	valuation Against Exemption Criteria for RF Exposure Evaluation	11
8	MF	PE Calculations and Evaluation	12



## **Test Report Attestation**

#### Microsoft Corporation Model: 1707 FCC ID: C3K1707 ISED ID: 3048A-1707

#### Applicable Standards

Specification	Test Result
FCC CFR47 Rule Parts 1.1307, 1.1310, 2.1091	Pass
ISED RSS-102 Issue 5	Pass

Microsoft EMC Laboratory attests that the product model identified in this report has been tested to and meets the requirements identified in the above standards. The test results in this report solely pertains to the specific sample tested, under the conditions and operating modes as provided by the customer.

This report shall not be used to claim product certification, approval, or endorsement by A2LA or any agency of any Government. Reproduction, duplication or publication of extracts from this test report is prohibited and requires prior written approval of Microsoft EMC Laboratory.

This report replaces the previously issued report #R-TR371-FCCIC-MPE-2 issued by Microsoft EMC Labs on 10/14/2016.

Junte Dray

Written By: Zack Gray SAR Test Lead

Reviewed/ Issued By: Sajay Jose EMC/RF Compliance Lab Manager



### 2 Deviations from Standards

None.

#### **3** Facilities and Accreditations

#### 3.1 Test Facility

All test facilities used to collect the test data are located at Microsoft EMC Laboratory,

17760 NE 67<sup>th</sup> Ct, Redmond WA, 98052, USA

#### 3.2 Accreditations

The lab is established and follows procedures as outlined in IEC/ISO 17025 and A2LA accreditation requirements. A2LA Accredited Testing Certificate Number: 3472.01

FCC Registration Number: US1141

IC Site Registration Numbers: 3048A-3, 3048A-4



## 4 Product Description

Company Name:	Microsoft Corporation							
Address:	One Microsoft Way	One Microsoft Way						
City, State, Zip:	Redmond, WA 98052-6399							
Customer Contact:	Jennifer Liu							
Functional Description of the EUT:	PC with IEEE 802.11a/b/g/n/ac MIMO supporting 20/40/80 MHz bandwidths, Bluetooth and additional 802.11n Radio.							
RF Exposure Conditions:	Mobile Exposure Con	ditions (Separation dist	ance of ≥ 20	) cm)				
Model:	1707							
FCC ID:	C3K1707							
IC ID:	3048A-1707							
Radio Descriptions:	WLAN Main 2.4 GHz: 802.11b, 802.11g, 802.11n- 20 MHz BW's WLAN Main 5 GHz: 802.11a, 802.11n, 802.11ac- 20, 40, 80 MHz Accessory 5GHz: 802.11n- 20 MHz BW Bluetooth™ (Basic and Enhanced Data Rates) / Bluetooth LE							
	WLAN Main (MIMO): 2412 – 2472 MHz 5180 – 5825 MHz							
Frequency Range of Operation:	Accessory (SISO): 5180 – 5240 MHz 5745 – 5825 MHz							
	BT / BTLE: 2402 – 2480 MHz							
Modulations:	WLAN: CCK, BPSK, QPSK, 16-QAM, 64-QAM, 256-QAM Bluetooth: GFSK, $\frac{\pi}{4}$ DQPSK, and 8 DPSK							
Antenna Peak Gains:	Radio WLAN Main Accessory: BT / BTLE:	Band Chain A Chain B   2412 - 2472 MHz 6.20 dBi 5.75 dBi   5180 - 5240 MHz 5.59 dBi 5.37 dBi   5260 - 5320 MHz 6.41 dBi 6.19 dBi   5500 - 5700 MHz 6.89 dBi 6.71 dBi   5745 - 5825 MHz 5.05 dBi 5.56 dBi   5745 - 5825 MHz 0.1 dBi   2402 2480 MHz 1.01 dBi						
EUT Classification:	UNII, DTS, FHSS	, <u> ·</u>		,				
Equipment Design State:	quipment Design State: Prototype/Production Equivalent							
Equipment Condition:	Good							



### **5 MPE Requirements**

#### 5.1 FCC MPE Requirements

The FCC MPE limits from CFR 47 Part 1.1310 are shown in the table below.

Frequency range (MHz)	FrequencyElectric fieldNrangestrength(MHz)(V/m)		Power density (mW/cm²)	Averaging time (minutes)						
(A) Limits for Occupational/Controlled Exposure										
0.3-3.0	614	1.63	*100	6						
3.0-30	1842/f	4.89/f	*900/f <sup>2</sup>	6						
30-300	61.4	0.163	1.0	6						
300-1,500			f/300	6						
1,500-100,000			5	6						
	(B) Limits for Genera	I Population/Uncontrol	led Exposure							
0.3-1.34	614	1.63	*100	30						
1.34-30	824/f	2.19/f	*180/f <sup>2</sup>	30						
30-300	27.5	0.073	0.2	30						
300-1,500			f/1500	30						
1,500-100,000			1.0	30						

#### 5.1.1 FCC RF Exposure Exemption Criteria

The exemption criteria for RF exposure evaluation from CFR 47 Part 2.1091(c) are as follows:

(c)(1) Mobile devices that operate in the Commercial Mobile Radio Services pursuant to part 20 of this chapter; the Cellular Radiotelephone Service pursuant to part 22 of this chapter; the Personal Communications Services pursuant to part 24 of this chapter; the Satellite Communications Services pursuant to part 25 of this chapter; the Miscellaneous Wireless Communications Services pursuant to part 27 of this chapter; the Maritime Services (ship earth station devices only) pursuant to part 80 of this chapter; the Specialized Mobile Radio Service, and the 3650 MHz Wireless Broadband Service pursuant to part 96 of this chapter are subject to routine environmental evaluation for RF exposure prior to equipment authorization or use if:

(i) They operate at frequencies of 1.5 GHz or below and their effective radiated power (ERP) is 1.5 watts or more, or

(ii) They operate at frequencies above 1.5 GHz and their ERP is 3 watts or more.



(2) Unlicensed personal communications service devices, unlicensed millimeter wave devices and unlicensed NII devices authorized under §§15.253(f), 15.255(g), 15.257(g), 15.319(i), and 15.407(f) of this chapter are also subject to routine environmental evaluation for RF exposure prior to equipment authorization or use if their ERP is 3 watts or more or if they meet the definition of a portable device as specified in §2.1093(b) requiring evaluation under the provisions of that section.

(3) All other mobile and unlicensed transmitting devices are categorically excluded from routine environmental evaluation for RF exposure prior to equipment authorization or use, except as specified in §§1.1307(c) and 1.1307(d) of this chapter.

#### 5.2 **ISED MPE Requirements**

The ISED MPE limits from RSS-102 Issue 5 are shown in the table below.

<b>F</b>	Fla atria		Devuer	Deferreres	
Frequency	Electric	wagnetic	Power	Reference	
Range	Field (V/m	Field (A/m	Density	Period	
0.003-10 <sup>21</sup>	83	90	-	Instantaneous*	
0.1-10	-	0.73/ f	-	6**	
1.1-10	87/ f <sup>0.5</sup>	-	-	6**	
10-20	27.46	0.0728	2	6	
20-48	58.07/ f <sup>0.25</sup>	0.1540/ <i>f</i> <sup>0.25</sup>	8.944/ f <sup>0.5</sup>	6	
48-300	22.06	0.05852	1.291	6	
300-6000	3.142 f <sup>0.3417</sup>	0.008335 f	0.02619 <i>f</i> <sup>0.6834</sup>	6	
6000-15000	61.4	0.163	10	6	
15000-150000	61.4	0.163	10	616000/ f <sup>1.2</sup>	
150000-300000	0.158 f <sup>0.5</sup>	4.21 x 10 <sup>-4</sup> f <sup>0.5</sup>	6.67 x 10 <sup>-5</sup> f	616000/ f <sup>1.2</sup>	
<b>Note:</b> <i>f</i> is frequent *Based on nerve s	cy in MHz. timulation (NS).				

#### **RF Field Strength Limits for Devices Used by the General Public** (Uncontrolled Environment)

\*\* Based on specific absorption rate (SAR).

#### 5.2.1 ISED MPE Exemption Requirements from RSS-102 Section 2.5.2

RF exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is greater than 20 cm, except when the device operates as follows:

- below 20 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 1 W (adjusted for tune-up tolerance);
- at or above 20 MHz and below 48 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 22.48/f0.5 W (adjusted for tune-up tolerance), where *f* is in MHz;
- at or above 48 MHz and below 300 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 0.6 W (adjusted for tune-up tolerance);
- at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 1.31 x 10-2 f 0.6834 W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 5 W (adjusted for tune-up tolerance).



## 6 Maximum Device EIRP and ERP

The declared maximum output powers including tune-up tolerances are used in conjunction with the maximum antenna gains to find the maximum EIRP and ERP values.

For transmitters with multiple transmit chains, total EIRP and total ERP are calculated as:

 $EIRP_{TOT} = EIRP_1 + EIRP_2 + \cdots EIRP_n$ 

 $ERP_{TOT} (dBm) = EIRP_{TOT} (dBm) - 2.15 dB$ 

	Maximum EIRP and ERP of all Device Radios										
Radio	Band	Chain	Chain	Chain	Chain	Chain	Chain	Max	Max		
	(GHz)	А	А	А	В	В	В	Total	Total		
		Max	Max	Max	Max	Max	Max	EIRP	ERP		
		Power	Gain	EIRP	Power	Gain	EIRP	(dBm)	(dBm)		
		(dBm)	(dBi)	(dBm)	(dBm)	(dBi)	(dBm)				
WLAN	2.4	15.50	6.20	21.70	15.50	5.75	21.25	24.49	22.34		
WLAN	5.2	14.50	5.59	20.09	14.50	5.37	19.87	22.99	20.84		
	5.3	15.50	6.41	21.91	15.50	6.19	21.69	24.81	22.66		
	5.6	15.50	6.89	22.39	15.50	6.71	22.21	25.31	23.16		
	5.8	15.50	5.05	20.55	15.50	5.56	21.06	23.82	21.67		
Accessory	5.2	-0.50	0.30	-0.20				-0.20	-2.35		
	5.8	-0.50	0.10	-0.40				-0.40	-2.55		
BT / BLE	2.4	5.50	1.01	6.51				6.51	4.36		

## 7 Evaluation Against Exemption Criteria for RF Exposure Evaluation

Evaluati	on of D	evice Ra	adios Agair	nst FCC a	nd ISED Ex	cemption Cri	teria
Radio /	Band	Max	FCC	FCC	Max Total	ISED	ISED
Rulepart	(GHz) Total Exemption		Exemption	Exempt?	EIRP	Exemption	Exempt?
		ERP	ERP		(mW)	EIRP	
		(mW)	Limits			Limits	
			(mW)			(mW)	
WLAN 15.247	2.4	171.44	NA	Yes <sup>1</sup>	281.26	2702.91	Yes
WLAN 15.407	5.2	121.39	3000	Yes	199.14	4560.23	Yes
	5.3	184.57	3000	Yes	302.81	4608.31	Yes
	5.6	207.07	3000	Yes	339.72	4751.18	Yes
	5.8	146.99	3000	Yes	241.14	4895.01	Yes
Accessory	5.2	0.58	3000	Yes	0.95	4560.23	Yes
15.407	5.8	0.56	3000	Yes	0.91	4895.01	Yes
BT / BLE	2.4	2.73	NA	Yes <sup>1</sup>	4.48	2702.91	Yes
15.247							

<sup>1</sup>Since 2.1091(c) does not reference Part 15.247, Bluetooth and WLAN 2.4 GHz radios are categorically exempted from routine RF exposure evaluation.

#### All Radios are exempt from routine RF Exposure Evaluation for both FCC and ISED.



## 8 MPE Calculations and Evaluation

Power densities are calculated for all radios, and the sum totals are compared to the FCC and ISED limits to support the 20 cm minimum device-user separation distance.

Power density is calculated as:

$$S = \frac{EIRP}{\pi R^2}$$

For FCC, the power densities of all radios are calculated and summed to show that the worst case is less than the corresponding power density limits.

	MPE Power Density Evaluation at 20cm										
Antenna	Band	Max	Max	S	FCC	FCC	S	ISED	S	ISED	
	(GHz)	EIRP	EIRP	$\binom{mW}{m}$	Limit	Result	$(\overline{W})$	Limit	Limit	Result	
		(dBm)	(mW)	$(cm^2)$	$\left(\frac{mW}{m}\right)$		$m^2$	$\left(\frac{W}{W}\right)$			
					$(\overline{cm^2})$			$(m^2)$			
WLAN	2.4	24.49	281.26	0.22	1.0	Pass	2.24	5.37	0.42	Pass	
WLAN	5.2	22.99	199.14	0.16	1.0	Pass	1.58	9.05	0.18	Pass	
	5.3	24.81	302.81	0.24	1.0	Pass	2.41	9.14	0.26	Pass	
	5.6	25.31	339.72	0.27	1.0	Pass	2.70	9.43	0.29	Pass	
	5.8	23.82	241.14	0.19	1.0	Pass	1.92	9.71	0.2	Pass	
Accessory	5.2	-0.20	0.95	0.001	1.0	Pass	0.01	9.05	0.001	Pass	
	5.8	-0.40	0.91	0.001	1.0	Pass	0.01	9.71	0.001	Pass	
BT / BLE	2.4	6.51	4.48	0.004	1.0	Pass	0.04	5.37	0.01	Pass	
Total			345.15	0.275	1.0	Pass			0.431	Pass	

- Since all FCC Bands have the same limit, Max EIRP and power densities are summed and the sum is compared to the FCC MPE limit.
- For FCC evaluation, the WLAN band with the highest EIRP is chosen for the worst-case total since the device can only transmit in one WLAN band at a time.
- ISED limits are calculated as (from table in section 5.2):  $ISED \ Limit = 0.02619 * f^{0.6834} \frac{W}{m^2}$
- For ISED in accordance with RSS-102 Section 3.2, the fractions of the applicable limits are summed and the sum shown to be below 1 since the limits differ by band.
- For ISED evaluation, The WLAN band with the highest fraction of the applicable limit is chosen for the worst-case total since the device can only transmit in one WLAN band at a time.



# End of Report