

TAF Testing Laboratory 2021

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.



Table of Contents

Rele	ase Control Record	3
1	Certificate of Conformity	. 4
2	RF Exposure	5
2.2	Limits For Maximum Permissible Exposure (MPE) MPE Calculation Formula Classification	. 5
3	Calculation Result Of Maximum Conducted Power	. 5



Release Control Record				
Issue No.	Description		Date Issued	
SA150814C23	Original release		Nov. 23, 2015	



1 Certificate of Conformity

Product:	Wireless Display Adapter	
Brand:	Microsoft®	
Test Model:	1733	
Sample Status:	Engineering sample	
Applicant:	Microsoft Corporation	
Test Date:	Nov. 03 ~ Nov. 06, 2015	
Standards:	FCC Part 2 (Section 2.1091)	
	KDB 447498 D03	
	IEEE C95.1	

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by :

Pettie Chen / Senior Specialist

Date: Nov. 23, 2015

Date:

Nov. 23, 2015

Approved by :

en Lin

Ken Liu / Senior Manager



2 RF Exposure

2.1 Limits For Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)	
Limits For General Population / Uncontrolled Exposure					
300-1500			F/1500	30	
1500-100,000			1.0	30	

F = Frequency in MHz

2.2 MPE Calculation Formula

 $Pd = (Pout^{*}G) / (4^{*}pi^{*}r^{2})$

where

 $Pd = power density in mW/cm^{2}$

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

3 Calculation Result Of Maximum Conducted Power

Frequency Band	Max Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
WLAN: 2412-2462 MHz	23.43	3.43	20	0.097	1
WLAN: 5180-5240 MHz	15.13	2.25	20	0.011	1
WLAN: 5745-5825 MHz	15.02	2.25	20	0.011	1

*The 2.4 and 5GHz cannot transmit simultaneously.

---END----