

RF Exposure Report

Report No.: SA170326E02

FCC ID: C3K1803

Test Model: 1803

Received Date: Mar. 26, 2017

Test Date: May 16, 2017

Issued Date: June 22, 2017

Applicant: Microsoft Corporation

- Address: One Microsoft Way Redmond WA 98052
- **Issued By:** Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch Hsin Chu Laboratory
- Lab Address: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300, Taiwan R.O.C.

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.



Table of Contents

Relea	se Control Record	. 3
1	Certificate of Conformity	. 4
	RF Exposure	
2.2 2.3 2.4	Classification Antenna Gain	. 5 . 5 . 5



Release Control Record						
Issue No.	Description	Date Issued				
SA170326E02	Original release.	June 22, 2017				



1 Certificate of Conformity

Product:	1T1R dual-band wireless accessory radio
Brand:	Microsoft
Test Model:	1803
Sample Status:	ENGINEERING SAMPLE
Applicant:	Microsoft Corporation
Test Date:	May 16, 2017
Standards:	FCC Part 2 (Section 2.1091)
	KDB 447498 D01 General RF Exposure Guidance v06
	IEEE C95.1-1992

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by :	Wondy	Mu,	Date:	June 22, 2017
_	Wendy Wu / Sp	ecialist		
Approved by : _	May Chen / Ma	anager ,	Date:	June 22, 2017



2 RF Exposure

2.1 Limits For Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	in a group i character a chara		Average Time (minutes)				
Limits For General Population / Uncontrolled Exposure								
300-1500 F/1500 30								
1500-100,000			1.0	30				

F = Frequency in MHz

2.2 MPE Calculation Formula

 $Pd = (Pout^*G) / (4^*pi^*r^2)$

where

 $Pd = power density in mW/cm^{2}$

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

2.4 Antenna Gain

Antenna No.	Brand	Model	Gain (dBi)	Antenna Type	Connector Type	Frequency range (GHz to GHz)	Function
Ant. 1 (for WLAN 2.4GHz)			5.2			2.4~2.4835	TX/RX
Ant. 2 (for WLAN 5GHz) Chan (0)	Microsoft	NA	4.7	PCB	NA	5.15~5.85	RX
Ant. 3 (for WLAN 5GHz) Chan (1)			6.1			5.15~5.85	TX/RX



2.5 Calculation Result

Frequency Band (MHz)	Max Power (dBm)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (W/cm ²)
2412-2462	8.50	7.079	5.2	20	0.00466	1
5180-5240	9.00	7.943	6.1	20	0.00644	1
5745-5825	9.00	7.943	6.1	20	0.00644	1

NOTE: 1. This power include tune-up tolerance range that specified in 1803 Tune Up power table

Conclusion:

The formula of calculated the MPE is:

CPD1 / LPD1 + CPD2 / LPD2 +etc. < 1

CPD = Calculation power density

LPD = Limit of power density

WLAN 2.4GHz + WLAN 5GHz = 0.00466 / 1 + 0.00644 / 1 = 0.0111Therefore the maximum calculations of above situations are less than the "1" limit.

--- END ----