



ELEMENT WASHINGTON DC LLC

7185 Oakland Mills Road, Columbia, MD 21046 USA
Tel. 410.290.6652 / Fax 410.290.6654
<http://www.element.com>

PART 22 & 90 MEASUREMENT REPORT

Applicant Name:
Microsoft Corporation
One Microsoft way
Redmond, WA, 98052
United States

Date of Testing:
03/16/2022- 04/26/2022
Test Report Issue Date:
07/06/2022
Test Site/Location:
Element Lab., Columbia, MD, USA
Test Report Serial No.:
1M2204040049-09-R1.C3K

FCC ID:	C3K1997
APPLICANT:	Microsoft Corporation

Application Type: Certification
Model: 1997
EUT Type: Portable Computing Device
FCC Classification: PCS Licensed Transmitter (PCB)
FCC Rule Part: §22(H), §90(S), §90(R)
Test Procedure(s): ANSI C63.26-2015, KDB 648474 D03 v01r04

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in §2.947. Test results reported herein relate only to the item(s) tested.

Note: This revised Test Report (S/N: 1M2204040049-09-R1.C3K) supersedes and replaces the previously issued test report on the same subject device for the same type of testing as indicated. Please discard or destroy the previously issued test report(s) and dispose of it accordingly.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

RJ Ortanez
Executive Vice President



FCC ID: C3K1997	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2204040049-09-R1.C3K	Test Dates: 3/16/2022 - 4/26/2022	EUT Type: Portable Computing Device	Page 1 of 50

V3.0 1/6/2022

TABLE OF CONTENTS

1.0	INTRODUCTION	4
1.1	Scope	4
1.2	Element Test Location.....	4
1.3	Test Facility / Accreditations.....	4
2.0	PRODUCT INFORMATION.....	5
2.1	Equipment Description	5
2.2	Device Capabilities.....	5
2.3	Test Configuration	5
2.4	Software and Firmware	5
2.5	EMI Suppression Device(s)/Modifications	5
3.0	DESCRIPTION OF TESTS	6
3.1	Evaluation Procedure	6
3.2	Radiated Power and Radiated Spurious Emissions	6
4.0	MEASUREMENT UNCERTAINTY	7
5.0	TEST EQUIPMENT CALIBRATION DATA	8
6.0	SAMPLE CALCULATIONS	9
7.0	TEST RESULTS	10
7.1	Summary.....	10
7.2	Conducted Output Power Data	12
7.3	Occupied Bandwidth	14
7.4	Spurious and Harmonic Emissions at Antenna Terminal	22
7.5	Band Edge Emissions at Antenna Terminal	27
7.6	Radiated Power (ERP).....	37
7.7	Radiated Spurious Emissions Measurements.....	40
7.8	Frequency Stability / Temperature Variation	46
8.0	CONCLUSION.....	50

FCC ID: C3K1997	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2204040049-09-R1.C3K	Test Dates: 3/16/2022 - 4/26/2022	EUT Type: Portable Computing Device	Page 2 of 50

MEASUREMENT REPORT

FCC Part 22 & 90

Mode	Bandwidth	Modulation	Tx Frequency Range [MHz]	Measurement	Max. Power [W]	Max. Power [dBm]	Emission Designator
LTE Band 14	10 MHz	QPSK	793.0	ERP	0.130	21.15	9M00G7D
		16QAM	793.0	ERP	0.109	20.38	8M99W7D
	5 MHz	QPSK	790.5 - 795.5	ERP	0.130	21.14	4M58G7D
		16QAM	790.5 - 795.5	ERP	0.110	20.43	4M53W7D
LTE Band 26	15 MHz	QPSK	821.5	ERP	0.132	21.22	13M5G7D
		16QAM	821.5	ERP	0.111	20.46	13M5W7D
	15 MHz	QPSK	821.5	Conducted	0.302	24.80	13M5G7D
		16QAM	821.5	Conducted	0.259	24.14	13M5W7D
	10 MHz	QPSK	819.0	Conducted	0.305	24.84	9M03G7D
		16QAM	819.0	Conducted	0.256	24.08	9M01W7D
	5 MHz	QPSK	816.5 - 821.5	Conducted	0.314	24.97	4M51G7D
		16QAM	816.5 - 821.5	Conducted	0.266	24.25	4M51W7D
	3 MHz	QPSK	815.5 - 822.5	Conducted	0.311	24.93	2M72G7D
		16QAM	815.5 - 822.5	Conducted	0.259	24.13	2M70W7D
	1.4 MHz	QPSK	814.7 - 823.3	Conducted	0.302	24.80	1M10G7D
		16QAM	814.7 - 823.3	Conducted	0.261	24.16	1M09W7D

FCC ID: C3K1997	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2204040049-09-R1.C3K	Test Dates: 3/16/2022 - 4/26/2022	EUT Type: Portable Computing Device	Page 3 of 50

1.0 INTRODUCTION

1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Innovation, Science and Economic Development Canada.

1.2 Element Test Location

These measurement tests were conducted at the Element Laboratory located at 7185 Oakland Mills Road, Columbia, MD 21046. The measurement facility is compliant with the test site requirements specified in ANSI C63.4-2014.

1.3 Test Facility / Accreditations

Measurements were performed at Element Lab located in Columbia, MD 21046, U.S.A.

- Element Washington DC LLC is an ISO 17025-2017 accredited test facility under the American Association for Laboratory Accreditation (A2LA) with Certificate number 2041.01 for Specific Absorption Rate (SAR), Hearing Aid Compatibility (HAC) testing, where applicable, and Electromagnetic Compatibility (EMC) testing for FCC and Innovation, Science, and Economic Development Canada rules.
- Element Washington DC LLC TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC 17065-2012 by A2LA (Certificate number 2041.03) in all scopes of FCC Rules and ISED Standards (RSS).
- Element Washington DC LLC facility is a registered (2451B) test laboratory with the site description on file with ISED.
- Element Washington DC LLC is a Recognized U.S. Certification Assessment Body (CAB # US0110) for ISED Canada as designated by NIST under the U.S. and Canada Mutual Recognition Agreement.

FCC ID: C3K1997	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2204040049-09-R1.C3K	Test Dates: 3/16/2022 - 4/26/2022	EUT Type: Portable Computing Device	Page 4 of 50

V3.0 1/6/2022

2.0 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **Microsoft Corporation Portable Computing Device FCC ID: C3K1997**. The test data contained in this report pertains only to the emissions due to the EUT's licensed transmitters that operate under the provisions of Part 90 and 22H.

Test Device Serial No.: JP220, 5S220, JS220, JT220

2.2 Device Capabilities

This device contains the following capabilities:

850/1900 WCDMA/HSPA, Multi-band LTE, 5G NR (FR1 and FR2), 802.11b/g/n/ax WLAN, 802.11a/n/ac/ax UNII (5,6GHz), Bluetooth (1x, EDR, LE)

2.3 Test Configuration

The EUT was tested per the guidance of ANSI C63.26-2015. See Section 7.0 of this test report for a description of the radiated and antenna port conducted emissions tests.

2.4 Software and Firmware

Testing was performed on device(s) using software/firmware version 1.930.0 installed on the EUT.

2.5 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and no modifications were made during testing.

FCC ID: C3K1997	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2204040049-09-R1.C3K	Test Dates: 3/16/2022 - 4/26/2022	EUT Type: Portable Computing Device	Page 5 of 50

V3.0 1/6/2022

3.0 DESCRIPTION OF TESTS

3.1 Evaluation Procedure

The measurement procedures described in the “American National Standard for Compliance Testing of Transmitters Used in Licensed Radio Services” (ANSI C63.26-2015) were used in the measurement of the EUT.

Deviation from Measurement Procedure.....None

3.2 Radiated Power and Radiated Spurious Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Figure 5.7 of Clause 5 in ANSI C63.4-2014. Absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections for measurements above 1GHz. For measurements below 1GHz, the absorbers are removed. A raised turntable is used for radiated measurement. The turn table is a continuously rotatable, remote-controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. An 80cm tall test table made of Styrodur is placed on top of the turn table. A Styrodur pedestal is placed on top of the test table to bring the total table height to 1.5m.

The equipment under test was transmitting while connected to its integral antenna and is placed on a turntable 3 meters from the receive antenna. The receive antenna height is adjusted between 1 and 4 meter height, the turntable is rotated through 360 degrees, and the EUT is manipulated through all orthogonal planes representative of its typical use to achieve the highest reading on the receive spectrum analyzer.

For radiated power measurements, substitution method is used per the guidance of ANSI C63.26-2015. For emissions below 1GHz, a half-wave dipole is substituted in place of the EUT. For emissions above 1GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator with the level of the signal generator being adjusted to obtain the same receive spectrum analyzer level previously recorded from the spurious emission from the EUT. The power of the emission is calculated using the following formula:

$$P_d \text{ [dBm]} = P_g \text{ [dBm]} - \text{cable loss [dB]} + \text{antenna gain [dBd/dBi];}$$

where P_d is the dipole equivalent power, P_g is the generator output into the substitution antenna, and the antenna gain is the gain of the substitute antenna used relative to either a half-wave dipole (dBd) or an isotropic source (dBi). The substitute level is equal to $P_g \text{ [dBm]} - \text{cable loss [dB]}$.

For radiated spurious emissions measurements, the field strength conversion method is used per the formulas in Section 5.2.7 of ANSI C63.26-2015. Field Strength (EIRP) is calculated using the following formulas:

$$E_{\text{[dB}\mu\text{V/m]}} = \text{Measured amplitude level}_{\text{[dBm]}} + 107 + \text{Cable Loss}_{\text{[dB]}} + \text{Antenna Factor}_{\text{[dB/m]}}$$

And

$$\text{EIRP}_{\text{[dBm]}} = E_{\text{[dB}\mu\text{V/m]}} + 20\log D - 104.8; \text{ where } D \text{ is the measurement distance in meters.}$$

All radiated measurements are performed in a chamber that meets the site requirements per ANSI C63.4-2014. Additionally, radiated emissions below 30MHz are also validated on an Open Area Test Site to assert correlation with the chamber measurements per the requirements of KDB 414788 D01 v01r01.

Radiated power and radiated spurious emission levels are investigated with the receive antenna horizontally and vertically polarized per ANSI C63.26-2015.

FCC ID: C3K1997	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2204040049-09-R1.C3K	Test Dates: 3/16/2022 - 4/26/2022	EUT Type: Portable Computing Device	Page 6 of 50

4.0 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4-2014. All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95% level of confidence. The measurement uncertainty shown below meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Contribution	Expanded Uncertainty (\pm dB)
Conducted Bench Top Measurements	1.13
Radiated Disturbance (<1GHz)	4.98
Radiated Disturbance (>1GHz)	5.07
Radiated Disturbance (>18GHz)	5.09

FCC ID: C3K1997	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2204040049-09-R1.C3K	Test Dates: 3/16/2022 - 4/26/2022	EUT Type: Portable Computing Device	Page 7 of 50

V3.0 1/6/2022

5.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST). Measurements antennas used during testing were calibrated in accordance to the requirements of ANSI C63.5-2017.

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
-	AP2-001	EMC Cable and Switch System	1/4/2022	Annual	1/4/2023	AP2-001
-	AP2-002	EMC Cable and Switch System	3/11/2022	Annual	3/11/2023	AP2-002
-	ETS-001	EMC Cable and Switch System	12/9/2021	Annual	12/9/2022	ETS-001
-	ETS-002	EMC Cable and Switch System	3/10/2022	Annual	3/10/2023	ETS-002
-	LTx1	Licensed Transmitter Cable Set	12/19/2021	Annual	12/19/2022	LTx1
-	LTx3	Licensed Transmitter Cable Set	8/18/2021	Annual	8/18/2022	LTx3
-	LTx5	Licensed Transmitter Cable Set	12/19/2021	Annual	12/19/2022	LTx5
-	LTx6-40	Licensed Transmitter Cable Set	12/19/2021	Annual	12/19/2022	LTx6-40
-	WL40-1	WLAN Cable Set (40GHz)	12/19/2021	Annual	12/19/2022	WL40-1
Anritsu	MT8000A	Radio Communication Test Station	8/2/2021	Annual	8/2/2022	6272337437
Anritsu	MT8821C	Radio Communication Analyzer	N/A			6201525694
Espec	ESX-2CA	Environmental Chamber	8/27/2020	Annual	8/27/2022	17620
ETS-Lindgren	3116C	DRG Horn Antenna	5/11/2021	Biennial	5/11/2023	218893
ETS Lindgren	3117	1-18 GHz DRG Horn (Medium)	4/20/2021	Biennial	4/20/2023	00125518
Keysight Technologies	N9030A	PXA Signal Analyzer (44GHz)	7/21/2021	Annual	7/21/2022	MY49430494
Keysight Technologies	N9030A	PXA Signal Analyzer (44GHz)	2/14/2022	Annual	2/14/2023	MY52350166
Keysight Technologies	N9030B	PXA Signal Analyzer, Multi-touch	1/7/2022	Annual	1/7/2023	MY57141001
Keysight Technologies	N9038A	MXE EMI Receiver	1/21/2022	Annual	1/21/2023	MY51210133
Rohde & Schwarz	CMW500	Radio Communication Tester	N/A			100976
Rohde & Schwarz	CMW500	Radio Communication Tester	N/A			112347
Rohde & Schwarz	FSU40	FMI Test Receiver (40GHz)	5/25/2021	Annual	5/25/2022	100348
Rohde & Schwarz	ESW44	EMI Test Receiver 2Hz to 44 GHz	3/28/2022	Annual	3/28/2023	101716
Rohde & Schwarz	TC-TA18	Cross Polarized Vivaldi Test Antenna	8/13/2020	Biennial	8/13/2022	101073
Sunol	JB5	Bi-Log Antenna (30M - 5GHz)	7/27/2020	Biennial	7/27/2022	A051107
Sunol	JB6	LB6 Antenna	11/13/2020	Biennial	11/13/2022	A082816

Table 5-1. Test Equipment

Notes:

1. For equipment listed above that has a calibration date or calibration due date that falls within the test date range, care was taken to ensure that this equipment was used after the calibration date and before the calibration due date.
2. Equipment with a calibration date of "N/A" shown in this list was not used to make direct calibrated measurements.

FCC ID: C3K1997	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2204040049-09-R1.C3K	Test Dates: 3/16/2022 - 4/26/2022	EUT Type: Portable Computing Device	Page 8 of 50

6.0 SAMPLE CALCULATIONS

Emission Designator

QPSK Modulation

Emission Designator = 8M62G7D

LTE BW = 8.62 MHz

G = Phase Modulation

7 = Quantized/Digital Info

D = Data transmission, telemetry, telecommand

QAM Modulation

Emission Designator = 8M45W7D

LTE BW = 8.45 MHz

W = Amplitude/Angle Modulated

7 = Quantized/Digital Info

D = Data transmission, telemetry, telecommand

Spurious Radiated Emission – LTE Band

Example: Middle Channel LTE Mode 2nd Harmonic (1564 MHz)

The average spectrum analyzer reading at 3 meters with the EUT on the turntable was -81.0 dBm. The gain of the substituted antenna is 8.1 dBi. The signal generator connected to the substituted antenna terminals is adjusted to produce a reading of -81.0 dBm on the spectrum analyzer. The loss of the cable between the signal generator and the terminals of the substituted antenna is 2.0 dB at 1564 MHz. So 6.1 dB is added to the signal generator reading of -30.9 dBm yielding -24.80 dBm. The fundamental EIRP was 25.501 dBm so this harmonic was 25.501 dBm – (-24.80).

FCC ID: C3K1997	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2204040049-09-R1.C3K	Test Dates: 3/16/2022 - 4/26/2022	EUT Type: Portable Computing Device	Page 9 of 50

V3.0 1/6/2022

7.0 TEST RESULTS

7.1 Summary

Company Name: Microsoft Corporation
 FCC ID: C3K1997
 FCC Classification: PCS Licensed Transmitter (PCB)
 Mode(s): LTE

Test Condition	Test Description	FCC Part Section(s)	RSS Section(s)	Test Limit	Test Result	Reference
CONDUCTED	Transmitter Conducted Output Power*	2.1046(a), 90.635(b)	RSS-Gen(6.12)	< 100 Watts	PASS	Section 7.2
	Occupied Bandwidth	2.1049(h)	RSS-Gen(6.7)	N/A	PASS	Section 7.3
	Conducted Band Edge / Spurious Emissions (LTE Band 14)	2.1051, 90.543(c)(e)	RSS-Gen(6.13), RSS-140(4.4)	On all frequencies between 769-775 MHz and 799-805 MHz, attenuation by a factor not less than $65 + 10 \log(P)$ dB in a 6.25 kHz band segment, for mobile and portable stations. On any frequency between 775-788 MHz, above 805 MHz, and below 750 MHz, attenuation by at least $43 + 10 \log(P)$ dB > $43 + 10 \log_{10}(P[\text{Watts}])$ for all out-of-band emissions outside of those specified in 90.543(e)	PASS	Sections 7.4, 7.5
	Conducted Band Edge / Spurious Emissions (LTE Band 26)	2.1051, 90.691(a)	N/A	> $43 + 10 \log_{10}(P[\text{Watts}])$ for all out-of-band emissions except emissions beyond 37.5kHz from the block edge > $50 + 10 \log_{10}(P[\text{Watts}])$ at Band Edge and for all out-of-band emissions within 37.5kHz of Block Edge	PASS	Sections 7.4, 7.5
	Peak-to-Average Ratio	N/A	RSS-140(4.3)	≤ 13 dB	PASS	Section 7.6
	Frequency Stability	2.1055, 90.213	RSS-Gen(6.11), RSS-140(4.2)	< 2.5 ppm **Fundamental emissions stay within authorized frequency block	PASS	Section 7.9
RADIATED	Effective Radiated Power (LTE Band 14)	90.542(a)(7)	RSS-Gen(6.12), RSS-140(4.3)	< 3 Watts max. ERP	PASS	Section 7.7
	Effective Radiated Power (LTE Band 26)	22.913(a)(2)	N/A	< 7 Watts max. ERP	PASS	Section 7.7
	Radiated Spurious Emissions (LTE Band 14)	2.1053, 90.543(e)(f)	RSS-Gen(7.3), RSS-140(4.4)	> $43 + 10 \log_{10}(P[\text{Watts}])$ for all out-of-band emissions except emissions in the 1559 - 1610MHz band are subject to a limit of -40dBm/MHz for wideband signals	PASS	Section 7.8
	Radiated Spurious Emissions (LTE Band 26)	2.1053, 90.691(a)	N/A	> $43 + 10 \log_{10}(P[\text{Watts}])$ for all out-of-band emissions except emissions beyond 37.5kHz from the block edge > $50 + 10 \log_{10}(P[\text{Watts}])$ at Band Edge and for all out-of-band emissions within 37.5kHz of Block Edge	PASS	Section 7.8

* The only transmitter output conducted powers included in this report are those where the Pmax value, per the tune-up document, is higher than any of the DSI power levels. For the remaining conducted power measurements, see the **RF Exposure Report**

Table 7-1. Summary of Test Results

FCC ID: C3K1997	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2204040049-09-R1.C3K	Test Dates: 3/16/2022 - 4/26/2022	EUT Type: Portable Computing Device	Page 10 of 50

Notes:

- 1) All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.
- 2) The analyzer plots shown in Section 7.0 were taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables, directional couplers, and attenuators used as part of the system to maintain a link between the call box and the EUT at all frequencies of interest.
- 3) All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables, attenuators, and couplers.
- 4) For conducted spurious emissions, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is EMC Software Tool v1.0.

FCC ID: C3K1997	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2204040049-09-R1.C3K	Test Dates: 3/16/2022 - 4/26/2022	EUT Type: Portable Computing Device	Page 11 of 50

V3.0 1/6/2022

7.2 Conducted Output Power Data

Test Overview

All emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst-case configuration. All modes of operation were investigated and the worst-case configuration results are reported in this section.

Test Procedure Used

ANSI C63.26-2015 – Section 5.2

Test Settings

1. Span = 2 x OBW to 3 x OBW
2. Detector = RMS
3. Trace mode = trace average for continuous emissions, max hold for pulse emissions
4. Sweep time = auto couple
5. The trace was allowed to stabilize
6. Please see test notes below for RBW and VBW settings

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-1. Test Instrument & Measurement Setup

Test Notes

1. For LTE mode, the device was tested under all modulations, RB sizes and offsets, and channel bandwidth configurations and the worst case emissions are reported with 1 RB.
2. This unit was tested with its standard battery.
3. Conducted power measurements were evaluated using various combinations of RB size, RB offset, modulation, and channel bandwidth. Channel bandwidth data is shown in the tables below based only on the channel bandwidths that were supported in this device.
4. All other conducted power measurements are contained in the RF exposure report for this filing.

FCC ID: C3K1997	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2204040049-09-R1.C3K	Test Dates: 3/16/2022 - 4/26/2022	EUT Type: Portable Computing Device	Page 12 of 50

V3.0 1/6/2022

Bandwidth	Modulation	Channel	Frequency [MHz]	RB Size/Offset	Conducted Power [dBm]	Conducted Power [Watts]	Conducted Power Limit [dBm]	Margin [dB]
15 MHz	QPSK	26765	821.5	1 / 0	24.80	0.302	50.00	-25.20
	16-QAM	26765	821.5	1 / 0	24.14	0.259	50.00	-25.86
10 MHz	QPSK	26740	819.0	1 / 0	24.84	0.305	50.00	-25.16
	16-QAM	26740	819.0	1 / 0	24.08	0.256	50.00	-25.92
5 MHz	QPSK	26715	816.5	1 / 0	24.97	0.314	50.00	-25.03
		26765	821.5	1 / 0	24.81	0.302	50.00	-25.19
	16-QAM	26715	816.5	1 / 0	24.25	0.266	50.00	-25.75
		26765	821.5	1 / 0	24.14	0.260	50.00	-25.86
3 MHz	QPSK	26705	815.5	1 / 0	24.93	0.311	50.00	-25.07
		26775	822.5	1 / 0	24.85	0.305	50.00	-25.15
	16-QAM	26705	815.5	1 / 0	24.13	0.259	50.00	-25.87
		26775	822.5	1 / 0	24.13	0.259	50.00	-25.87
1.4 MHz	QPSK	26697	814.7	1 / 0	24.80	0.302	50.00	-25.20
		26783	823.3	1 / 3	24.73	0.297	50.00	-25.27
	16-QAM	26697	814.7	1 / 0	24.02	0.253	50.00	-25.98
		26783	823.3	1 / 3	24.16	0.261	50.00	-25.84

Table 7-2. Conducted Power Output Data (LTE Band 26)

FCC ID: C3K1997	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2204040049-09-R1.C3K	Test Dates: 3/16/2022 - 4/26/2022	EUT Type: Portable Computing Device	Page 13 of 50

7.3 Occupied Bandwidth

Test Overview

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured. All modes of operation were investigated and the worst case configuration results are reported in this section.

Test Procedure Used

ANSI C63.26-2015 – Section 5.4.4

Test Settings

1. The signal analyzer's automatic bandwidth measurement capability was used to perform the 99% occupied bandwidth and the 26dB bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 1 – 5% of the expected OBW
3. VBW \geq 3 x RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize
8. If necessary, steps 2 – 7 were repeated after changing the RBW such that it would be within 1 – 5% of the 99% occupied bandwidth observed in Step 7

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-2. Test Instrument & Measurement Setup

Test Notes


None

FCC ID: C3K1997	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2204040049-09-R1.C3K	Test Dates: 3/16/2022 - 4/26/2022	EUT Type: Portable Computing Device	Page 14 of 50

LTE Band 26




Plot 7-1. Occupied Bandwidth Plot (LTE Band 26 - 15MHz QPSK - Full RB)




Plot 7-2. Occupied Bandwidth Plot (LTE Band 26 - 15MHz 16-QAM - Full RB)

FCC ID: C3K1997	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2204040049-09-R1.C3K	Test Dates: 3/16/2022 - 4/26/2022	EUT Type: Portable Computing Device	Page 15 of 50




Plot 7-3. Occupied Bandwidth Plot (LTE Band 26 - 10MHz QPSK - Full RB)




Plot 7-4. Occupied Bandwidth Plot (LTE Band 26 - 10MHz 16-QAM - Full RB)

FCC ID: C3K1997	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2204040049-09-R1.C3K	Test Dates: 3/16/2022 - 4/26/2022	EUT Type: Portable Computing Device	Page 16 of 50




Plot 7-5. Occupied Bandwidth Plot (LTE Band 26 - 5MHz QPSK - Full RB)




Plot 7-6. Occupied Bandwidth Plot (LTE Band 26 - 5MHz 16-QAM - Full RB)

FCC ID: C3K1997	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2204040049-09-R1.C3K	Test Dates: 3/16/2022 - 4/26/2022	EUT Type: Portable Computing Device	Page 17 of 50




Plot 7-7. Occupied Bandwidth Plot (LTE Band 26 - 3MHz QPSK - Full RB)




Plot 7-8. Occupied Bandwidth Plot (LTE Band 26 - 3MHz 16-QAM - Full RB)

FCC ID: C3K1997	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2204040049-09-R1.C3K	Test Dates: 3/16/2022 - 4/26/2022	EUT Type: Portable Computing Device	Page 18 of 50




Plot 7-9. Occupied Bandwidth Plot (LTE Band 26 - 1.4MHz QPSK - Full RB)




Plot 7-10. Occupied Bandwidth Plot (LTE Band 26 - 1.4MHz 16-QAM - Full RB)

FCC ID: C3K1997	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2204040049-09-R1.C3K	Test Dates: 3/16/2022 - 4/26/2022	EUT Type: Portable Computing Device	Page 19 of 50

LTE Band 14




Plot 7-11. Occupied Bandwidth Plot (LTE Band 14 - 10MHz QPSK - Full RB)




Plot 7-12. Occupied Bandwidth Plot (LTE Band 14 - 10MHz 16-QAM - Full RB)

FCC ID: C3K1997	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2204040049-09-R1.C3K	Test Dates: 3/16/2022 - 4/26/2022	EUT Type: Portable Computing Device	Page 20 of 50



Plot 7-13. Occupied Bandwidth Plot (LTE Band 14 - 5MHz QPSK - Full RB)



Plot 7-14. Occupied Bandwidth Plot (LTE Band 14 - 5MHz 16-QAM - Full RB)

FCC ID: C3K1997	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2204040049-09-R1.C3K	Test Dates: 3/16/2022 - 4/26/2022	EUT Type: Portable Computing Device	Page 21 of 50

7.4 Spurious and Harmonic Emissions at Antenna Terminal

Test Overview

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic. All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst-case configuration. All modes of operation were investigated and the worst-case configuration results are reported in this section.

The minimum permissible attenuation level of any spurious emission is $43 + 10 \log_{10}(P_{[Watts]})$, where P is the transmitter power in Watts.

Test Procedure Used

ANSI C63.26-2015 – Section 5.7.4

Test Settings

1. Start frequency was set to 30MHz and stop frequency was set to 10GHz (separated into at least two plots per channel)
2. RBW \geq 100kHz
3. VBW \geq 3 x RBW
4. Detector = RMS
5. Trace mode = max hold
6. Sweep time = auto couple
7. The trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-3. Test Instrument & Measurement Setup


Test Notes

Per Part 22H and 90, compliance with the applicable limits is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater.


FCC ID: C3K1997	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2204040049-09-R1.C3K	Test Dates: 3/16/2022 - 4/26/2022	EUT Type: Portable Computing Device	Page 22 of 50

V3.0 1/6/2022

LTE Band 26



Plot 7-15. Conducted Spurious Plot (LTE Band 26 - 15MHz QPSK - RB Size 1, RB Offset 0)




Plot 7-16. Conducted Spurious Plot (LTE Band 26 - 15MHz QPSK - RB Size 1, RB Offset 0)

FCC ID: C3K1997	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2204040049-09-R1.C3K	Test Dates: 3/16/2022 - 4/26/2022	EUT Type: Portable Computing Device	Page 23 of 50

LTE Band 14




Plot 7-18. Conducted Spurious Plot (LTE Band 14 - 10MHz QPSK - RB Size 1, RB Offset 0)



Plot 7-19. Conducted Spurious Plot (LTE Band 14 - 10MHz QPSK - RB Size 1, RB Offset 0)

FCC ID: C3K1997	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2204040049-09-R1.C3K	Test Dates: 3/16/2022 - 4/26/2022	EUT Type: Portable Computing Device	Page 25 of 50



Plot 7-20. Conducted Spurious Plot (LTE Band 14 - 10MHz QPSK - RB Size 1, RB Offset 0)

FCC ID: C3K1997	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2204040049-09-R1.C3K	Test Dates: 3/16/2022 - 4/26/2022	EUT Type: Portable Computing Device	Page 26 of 50

7.5 Band Edge Emissions at Antenna Terminal

Test Overview

All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst-case configuration. All modes of operation were investigated and the worst-case configuration results are reported in this section.

For LTE B26 operation under Part 90.691, the minimum permissible attenuation level of any spurious emission removed from the EA licensee's frequency block by greater than 37.5 kHz is $43 + 10\log_{10}(P_{[Watts]})$, where P is the transmitter power in Watts. The minimum permissible attenuation level of any spurious emission removed from the EA licensee's frequency block by up to and including 37.5 kHz is $50 + 10\log_{10}(P_{[Watts]})$, where P is the transmitter power in Watts.

For LTE Band 14 operation under Part 90.543, the power of any emission must be reduced below the mean output power (P) by at least $43 + 10\log(P)$ dB measured in a 100 kHz bandwidth for frequencies less than 1 GHz, and in a 1 MHz bandwidth for frequencies greater than 1 GHz.

Additionally, for LTE Band 14 operation, on all frequencies between 769-775 MHz and 799-805 MHz, the power of any emission shall be attenuated by a factor not less than $65 + 10 \log(P)$ dB in a 6.25 kHz band segment, for mobile and portable stations.

Test Procedure Used

ANSI C63.26-2015 – Section 5.7.3

Test Settings

1. Span was set large enough so as to capture all out of band emissions near the band edge
2. RBW = 100 kHz
3. VBW = 300 kHz
4. Detector = RMS
5. Trace mode = trace average
6. Sweep time = auto couple
7. The trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-4. Test Instrument & Measurement Setup

FCC ID: C3K1997	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2204040049-09-R1.C3K	Test Dates: 3/16/2022 - 4/26/2022	EUT Type: Portable Computing Device	Page 27 of 50

V3.0 1/6/2022


Test Notes

1. For channel edge emission, the signal analyzer's "ACP" measurement capability is used.
2. Per 22.917(b) in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed to demonstrate compliance with the out-of-band emissions limit. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.


FCC ID: C3K1997	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2204040049-09-R1.C3K	Test Dates: 3/16/2022 - 4/26/2022	EUT Type: Portable Computing Device	Page 28 of 50

V3.0 1/6/2022

LTE Band 26




Plot 7-21. Channel Edge Plot (LTE Band 26 - 15MHz QPSK - Mid Channel)




Plot 7-22. Channel Edge Plot (LTE Band 26 - 10MHz QPSK - Mid Channel)

FCC ID: C3K1997		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2204040049-09-R1.C3K	Test Dates: 3/16/2022 - 4/26/2022	EUT Type: Portable Computing Device	Page 29 of 50	




Plot 7-23. Channel Edge Plot (LTE Band 26 - 5MHz QPSK - Low Channel)




Plot 7-21. Channel Edge Plot (LTE Band 26 - 5MHz QPSK - High Channel)

FCC ID: C3K1997		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2204040049-09-R1.C3K	Test Dates: 3/16/2022 - 4/26/2022	EUT Type: Portable Computing Device	Page 30 of 50	




Plot 7-22. Channel Edge Plot (LTE Band 26 - 3MHz QPSK - Low Channel)




Plot 7-23. Channel Edge Plot (LTE Band 26 - 3MHz QPSK - High Channel)

FCC ID: C3K1997		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2204040049-09-R1.C3K	Test Dates: 3/16/2022 - 4/26/2022	EUT Type: Portable Computing Device	Page 31 of 50	




Plot 7-24. Channel Edge Plot (LTE Band 26 - 1.4MHz QPSK - Low Channel)




Plot 7-25. Channel Edge Plot (LTE Band 26 - 1.4MHz QPSK - High Channel)

MEASUREMENT REPORT (CERTIFICATION)			Approved by: Technical Manager
FCC ID: C3K1997	Test Dates: 3/16/2022 - 4/26/2022	EUT Type: Portable Computing Device	Page 32 of 50
Test Report S/N: 1M2204040049-09-R1.C3K			

LTE Band 14



Plot 7-26. Lower Band Edge Plot (LTE Band 14, 10MHz QPSK - RB Size 50)




Plot 7-27. Lower Emission Mask Plot (LTE Band 14, 10MHz QPSK - RB Size 50)

FCC ID: C3K1997	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2204040049-09-R1.C3K	Test Dates: 3/16/2022 - 4/26/2022	EUT Type: Portable Computing Device	Page 33 of 50




Plot 7-28. Upper Band Edge Plot (LTE Band 14, 10MHz QPSK - RB Size 50)




Plot 7-29. Upper Emission Mask Plot (LTE Band 14, 10MHz QPSK - RB Size 50)

FCC ID: C3K1997	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2204040049-09-R1.C3K	Test Dates: 3/16/2022 - 4/26/2022	EUT Type: Portable Computing Device	Page 34 of 50



Plot 7-30. Lower Band Edge Plot (LTE Band 14, 5MHz QPSK - RB Size 25)



Plot 7-31. Lower Emission Mask Plot (LTE Band 14, 5MHz QPSK - RB Size 25)

FCC ID: C3K1997	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2204040049-09-R1.C3K	Test Dates: 3/16/2022 - 4/26/2022	EUT Type: Portable Computing Device	Page 35 of 50



Plot 7-32. Upper Band Edge Plot (LTE Band 14, 5MHz QPSK - RB Size 25)



Plot 7-33. Upper Emission Mask Plot (LTE Band 14, 5MHz QPSK - RB Size 25)

FCC ID: C3K1997	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2204040049-09-R1.C3K	Test Dates: 3/16/2022 - 4/26/2022	EUT Type: Portable Computing Device	Page 36 of 50

7.6 Radiated Power (ERP)

Test Overview

Effective Radiated Power (ERP) measurements are performed using the substitution method described in ANSI C63.26-2015 with the EUT transmitting into an integral antenna. Measurements are performed using vertically and horizontally polarized broadband horn antennas. All measurements are performed as RMS average measurements while the EUT is operating at maximum power, and at the appropriate frequencies.

Test Procedures Used

ANSI C63.26-2015 – Section 5.2.4.4

Test Settings

1. Radiated power measurements are performed using the signal analyzer's "channel power" measurement capability for signals with continuous operation.
2. RBW = 1 – 5% of the expected OBW
3. VBW \geq 3 x RBW
4. Span = 1.5 times the OBW
5. No. of sweep points \geq 2 x span / RBW
6. Detector = RMS
7. Trigger is set to "free run" for signals with continuous operation with the sweep times set to "auto".
8. The integration bandwidth was roughly set equal to the measured OBW of the signal for signals with continuous operation.
9. Trace mode = trace averaging (RMS) over 100 sweeps
10. The trace was allowed to stabilize.

FCC ID: C3K1997	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2204040049-09-R1.C3K	Test Dates: 3/16/2022 - 4/26/2022	EUT Type: Portable Computing Device	Page 37 of 50

V3.0 1/6/2022

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-5. Radiated Test Setup <1GHz




Figure 7-6. Radiated Test Setup > 1GHz

Test Notes

- 1) The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case emissions are reported with the EUT positioning, modulations, RB sizes and offsets, and channel bandwidth configurations shown in the tables below.
- 2) This unit was tested with its standard battery.

FCC ID: C3K1997	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2204040049-09-R1.C3K	Test Dates: 3/16/2022 - 4/26/2022	EUT Type: Portable Computing Device	Page 38 of 50



Bandwidth	Mod.	Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Ant. Gain [dBi]	RB Size/Offset	Substitute Level [dBm]	ERP [dBm]	ERP [Watts]	ERP Limit [dBm]	Margin [dB]	EIRP [dBm]	EIRP [Watts]	EIRP Limit [dBm]	Margin [dB]
15 MHz	QPSK	821.5	H	200	116	6.62	1 / 74	16.75	21.22	0.132	38.45	-17.23	23.37	0.217	40.61	-17.24
	16-QAM	821.5	H	200	116	6.62	1 / 74	15.99	20.46	0.111	38.45	-17.99	22.61	0.182	40.61	-18.00
15 MHz	QPSK	821.5	V	166	294	6.12	1 / 74	16.04	20.01	0.100	38.45	-18.44	22.16	0.164	40.61	-18.45

Table 7-3. ERP Data (LTE Band 26)

Bandwidth	Mod.	Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Ant. Gain [dBi]	RB Size/Offset	Substitute Level [dBm]	ERP [dBm]	ERP [Watts]	ERP Limit [dBm]	Margin [dB]	EIRP [dBm]	EIRP [Watts]	EIRP Limit [dBm]	Margin [dB]
10 MHz	QPSK	793.0	V	165	311	6.21	1 / 0	17.09	21.15	0.130	34.77	-13.62	23.30	0.214	40.61	-17.30
	16-QAM	793.0	V	165	311	6.21	1 / 0	16.32	20.38	0.109	34.77	-14.39	22.53	0.179	40.61	-18.07
	QPSK	790.5	V	165	311	6.19	1 / 12	17.08	21.12	0.129	34.77	-13.65	23.27	0.212	40.61	-17.34
5 MHz	QPSK	793.0	V	165	311	6.21	1 / 12	17.07	21.14	0.130	34.77	-13.64	23.29	0.213	40.61	-17.32
	QPSK	795.5	V	165	311	6.24	1 / 0	16.95	21.04	0.127	34.77	-13.73	23.19	0.208	40.61	-17.42
	16-QAM	795.5	V	165	311	6.24	1 / 0	16.34	20.43	0.110	34.77	-14.34	22.58	0.181	40.61	-18.03
5 MHz	QPSK	795.5	H	103	335	6.21	1 / 0	12.88	16.94	0.049	34.77	-17.83	19.09	0.081	40.61	-21.51

Table 7-4. ERP Data (LTE Band 14)

FCC ID: C3K1997	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2204040049-09-R1.C3K	Test Dates: 3/16/2022 - 4/26/2022	EUT Type: Portable Computing Device	Page 39 of 50

V3.0 1/6/2022

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



7.7 Radiated Spurious Emissions Measurements

Test Overview

Radiated spurious emissions measurements are performed using the field strength conversion method described in ANSI C63.26-2015 with the EUT transmitting into an integral antenna. Measurements on signals operating below 1GHz are performed using hybrid (biconical/log) antennas. Measurements on signals operating above 1GHz are performed using vertically and horizontally polarized broadband horn antennas. All measurements are performed as RMS measurements while the EUT is operating at maximum power, and at the appropriate frequencies.

Test Procedures Used

ANSI C63.26-2015 – Section 5.5.4

Test Settings

1. RBW = 100kHz for emissions below 1GHz and 1MHz for emissions above 1GHz
2. VBW $\geq 3 \times$ RBW
3. Span = 1.5 times the OBW
4. No. of sweep points $\geq 2 \times$ span / RBW
5. Detector = RMS
6. Trace mode = Average (Max Hold for pulsed emissions)
7. The trace was allowed to stabilize

FCC ID: C3K1997	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2204040049-09-R1.C3K	Test Dates: 3/16/2022 - 4/26/2022	EUT Type: Portable Computing Device	Page 40 of 50

V3.0 1/6/2022

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-7. Test Instrument & Measurement Setup < 1GHz




Figure 7-8. Test Instrument & Measurement Setup >1 GHz


FCC ID: C3K1997	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2204040049-09-R1.C3K	Test Dates: 3/16/2022 - 4/26/2022	EUT Type: Portable Computing Device	Page 41 of 50

Test Notes

- 1) Field strengths are calculated using the Measurement quantity conversions in ANSI C63.26-2015 Section 5.2.7:
 - a) $E(\text{dB}\mu\text{V}/\text{m}) = \text{Measured amplitude level (dBm)} + 107 + \text{Cable Loss (dB)} + \text{Antenna Factor (dB/m)}$
 - b) $\text{EIRP (dBm)} = E(\text{dB}\mu\text{V}/\text{m}) + 20\log D - 104.8$; where D is the measurement distance in meters.
- 2) The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst-case emissions are reported with the EUT positioning, modulations, RB sizes and offsets, and channel bandwidth configurations shown in the tables below.
- 3) This unit was tested with its standard battery.
- 4) The spectrum is measured from 9kHz to the 10th harmonic of the fundamental frequency of the transmitter. The worst-case emissions are reported.
- 5) Emissions below 18GHz were measured at a 3-meter test distance while emissions above 18GHz were measured at a 1-meter test distance with the application of a distance correction factor.
- 6) The "-" shown in the following RSE tables are used to denote a noise floor measurement.

FCC ID: C3K1997	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2204040049-09-R1.C3K	Test Dates: 3/16/2022 - 4/26/2022	EUT Type: Portable Computing Device	Page 42 of 50

LTE Band 26




Plot 7-34. Radiated Spurious Plot Below 1GHz (LTE Band 26)

Bandwidth (MHz):	10
Frequency (MHz):	819
Modulation Signal:	QPSK
RB Config (Size / Offset):	1 / 25

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dB μ V/m]	ERP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
112.75	H	-	-	-98.35	19.75	28.40	-69.01	-13.00	-56.01
962.48	H	-	-	-96.17	31.69	42.52	-54.88	-13.00	-41.88

Table 7-5. Radiated Spurious Data (LTE Band 26)

FCC ID: C3K1997	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2204040049-09-R1.C3K	Test Dates: 3/16/2022 - 4/26/2022	EUT Type: Portable Computing Device	Page 43 of 50



Plot 7-35. Radiated Spurious Plot Above 1GHz (LTE Band 26)


Bandwidth (MHz):	10
Frequency (MHz):	819
Modulation Signal:	QPSK
RB Config (Size / Offset):	1 / 25

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1638.00	H	-	-	-77.15	-3.86	25.99	-69.26	-13.00	-56.26
2457.00	H	-	-	-77.45	0.35	29.90	-65.36	-13.00	-52.36
3276.00	H	-	-	-78.53	2.16	30.63	-64.63	-13.00	-51.63

Table 7-6. Radiated Spurious Data (LTE Band 26 – Mid Channel)

FCC ID: C3K1997	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2204040049-09-R1.C3K	Test Dates: 3/16/2022 - 4/26/2022	EUT Type: Portable Computing Device	Page 44 of 50

LTE Band 14




Plot 7-36. Radiated Spurious Plot Below 1GHz (LTE Band 14)

Bandwidth (MHz):	5
Frequency (MHz):	793
Modulation Signal:	QPSK
RB Config (Size / Offset):	1 / 12

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	ERP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
780.50	H	-	-	-97.44	29.69	39.25	-58.16	-13.00	-45.16
869.74	H	-	-	-97.05	30.68	40.63	-56.78	-13.00	-43.78

Table 7-7. Radiated Spurious Data (LTE Band 14)

FCC ID: C3K1997	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2204040049-09-R1.C3K	Test Dates: 3/16/2022 - 4/26/2022	EUT Type: Portable Computing Device	Page 45 of 50



Plot 7-37. Radiated Spurious Plot Above 1GHz (LTE Band 14)

Bandwidth (MHz):	5
Frequency (MHz):	790.5
Modulation Signal:	QPSK
RB Config (Size / Offset):	1 / 12

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1581.00	H	183	168	-76.41	-4.07	26.52	-68.73	-40.00	-28.73
2371.50	H	141	146	-77.13	0.79	30.66	-64.60	-13.00	-51.60
3162.00	H	-	-	-78.17	2.13	30.96	-64.30	-13.00	-51.30
3952.50	H	-	-	-78.69	3.17	31.48	-63.78	-13.00	-50.78
4743.00	H	-	-	-78.73	4.93	33.20	-62.05	-13.00	-49.05

Table 7-8. Radiated Spurious Data (LTE Band 14 – Low Channel)

Bandwidth (MHz):	5
Frequency (MHz):	793
Modulation Signal:	QPSK
RB Config (Size / Offset):	1 / 12

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1586.00	H	185	171	-75.75	-4.08	27.17	-68.09	-40.00	-28.09
2379.00	H	134	258	-77.18	0.84	30.66	-64.60	-13.00	-51.60
3172.00	H	-	-	-77.71	2.20	31.49	-63.77	-13.00	-50.77
3965.00	H	-	-	-78.78	3.29	31.51	-63.75	-13.00	-50.75
4758.00	H	-	-	-78.89	4.77	32.88	-62.38	-13.00	-49.38

Table 7-9. Radiated Spurious Data (LTE Band 14 – Mid Channel)

Bandwidth (MHz):	5
Frequency (MHz):	795.5
Modulation Signal:	QPSK
RB Config (Size / Offset):	1 / 12

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1591.00	H	-	-	-77.37	-4.11	25.52	-69.73	-40.00	-29.73
2386.50	H	-	-	-77.91	0.85	29.94	-65.31	-13.00	-52.31
3182.00	H	-	-	-77.93	2.27	31.34	-63.92	-13.00	-50.92
3977.50	H	307	244	-75.46	3.25	34.79	-60.46	-13.00	-47.46
4773.00	H	-	-	-79.01	4.53	32.52	-62.74	-13.00	-49.74

Table 7-10. Radiated Spurious Data (LTE Band 14 – High Channel)

FCC ID: C3K1997	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2204040049-09-R1.C3K	Test Dates: 3/16/2022 - 4/26/2022	EUT Type: Portable Computing Device	Page 46 of 50



7.8 Frequency Stability / Temperature Variation

Test Overview and Limit

Frequency stability testing is performed in accordance with the guidelines of ANSI C63.26-2015. The frequency stability of the transmitter is measured by:

- a.) **Temperature:** The temperature is varied from -30°C to +50°C in 10°C increments using an environmental chamber.
- b.) **Primary Supply Voltage:** The primary supply voltage is varied from 85% to 115% of the nominal value for non hand-carried battery and AC powered equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

The frequency stability of the transmitter shall be maintained within ±0.00025% (±2.5 ppm) of the center frequency.

Test Procedure Used

ANSI C63.26-2015 – Section 5.6

Test Settings

1. The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).
2. The equipment is turned on in a “standby” condition for fifteen minutes before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
3. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

Test Setup

The EUT was connected via an RF cable to a spectrum analyzer with the EUT placed inside an environmental chamber.

Test Notes

None

FCC ID: C3K1997	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2204040049-09-R1.C3K	Test Dates: 3/16/2022 - 4/26/2022	EUT Type: Portable Computing Device	Page 47 of 50


V3.0 1/6/2022

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

Frequency Stability / Temperature Variation

LTE Band 14					
		Operating Frequency (Hz):		793,000,000	
		Ref. Voltage (VDC):		7.60	
Voltage (%)	Power (VDC)	Temp (°C)	Frequency (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	7.60	- 30	793,087,428	-435	-0.0000548
		- 20	793,087,153	-710	-0.0000895
		- 10	793,086,354	-1,509	-0.0001903
		0	793,087,403	-460	-0.0000581
		+ 10	793,087,547	-316	-0.0000399
		+ 20 (Ref)	793,087,863	0	0.0000000
		+ 30	793,088,423	559	0.0000705
		+ 40	793,086,691	-1,172	-0.0001478
Battery Endpoint	7.20	+ 20	793,087,894	31	0.0000039

Table 7-11. LTE Band 14 Frequency Stability Data



Plot 7-38. LTE Band 14 Frequency Stability Chart


FCC ID: C3K1997	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2204040049-09-R1.C3K	Test Dates: 3/16/2022 - 4/26/2022	EUT Type: Portable Computing Device	Page 48 of 50

LTE Band 26

Operating Frequency (Hz):	819,000,000
Ref. Voltage (VDC):	7.60
Deviation Limit:	± 0.00025% or 2.5 ppm

Voltage (%)	Power (VDC)	Temp (°C)	Frequency (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	7.60	- 30	831,595,147	536	0.0000645
		- 20	831,595,369	758	0.0000911
		- 10	831,595,224	613	0.0000738
		0	831,595,720	1,109	0.0001334
		+ 10	831,594,693	82	0.0000099
		+ 20 (Ref)	831,594,611	0	0.0000000
		+ 30	831,594,662	51	0.0000061
		+ 40	831,594,303	-307	-0.0000370
Battery Endpoint	7.20	+ 20	831,594,649	38	0.0000046

Table 7-12. LTE Band 26 Frequency Stability Data



Plot 7-39. LTE Band 26 Frequency Stability Chart

FCC ID: C3K1997	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2204040049-09-R1.C3K	Test Dates: 3/16/2022 - 4/26/2022	EUT Type: Portable Computing Device	Page 49 of 50

8.0 CONCLUSION

The data collected relate only to the item(s) tested and show that the **Microsoft Corporation Portable Computing Device FCC ID: C3K1997** complies with all the requirements of Parts 22(H) and 90 of the FCC rules.

FCC ID: C3K1997	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2204040049-09-R1.C3K	Test Dates: 3/16/2022 - 4/26/2022	EUT Type: Portable Computing Device	Page 50 of 50

V3.0 1/6/2022