

ELEMENT MATERIALS TECHNOLOGY

(formerly PCTEST)
7185 Oakland Mills Road, Columbia, MD 21046 USA
Tel. +1.410.290.6652 / Fax +1.410.290.6654
<http://www.element.com>



COMPLIANCE SUMMARY REPORT

Applicant Name:
Microsoft Corporation
One Microsoft Way
Redmond, WA 98052 USA
Microsoft Corporation

Test Site/Location:
Element, Columbia, MD, USA
Document Serial No.:
1M2312040120-03.C3K

FCC ID: C3K2077

APPLICANT: MICROSOFT CORPORATION

Report Type: Compliance Summary
DUT Type: Portable Computing Device
Model: 2077



FCC ID: C3K2077	COMPLIANCE SUMMARY REPORT	Approved by: Technical Manager
Document S/N: 1M2312040120-03.C3K	DUT Type: Portable Computing Device	Page 1 of 10

REV 1.1
04/11/2022

TABLE OF CONTENTS

1	STRATEGY FOR COMPLIANCE DEMONSTRATION	3
1.1	RF Exposure Evaluation Strategy	3
1.2	Nomenclature	4
1.3	Bibliography	4
2	TIME AVERAGING ALGORITHM	5
2.1	Algorithm Description	5
2.2	Basic concept of the algorithm	6
2.3	Configurable Parameters	8
3	DUT DESCRIPTION	9
3.1	Device Overview	9
4	COMPLIANCE SUMMARY	10
4.1	RF Exposure Compliance Summary	10

FCC ID: C3K2077	COMPLIANCE SUMMARY REPORT	Approved by: Technical Manager
Document S/N: 1M2312040120-03.C3K	DUT Type: Portable Computing Device	Page 2 of 10

REV 1.1
04/11/2022

1 STRATEGY FOR COMPLIANCE DEMONSTRATION

1.1 RF Exposure Evaluation Strategy

The FCC RF exposure limits defined based on time-averaged RF exposure. The device under test (DUT) uses the Qualcomm Smart Transmit feature to control and manage transmitting power in real time and to ensure at all times the time-averaged RF exposure is in compliance with the FCC requirement for WWAN operations and via FastConnect TAS for WLAN operations. Additionally, this device supports BT technologies but the output power of these modems is not controlled by the TAS algorithm.

Demonstrating compliance of DUT enabled with Qualcomm Smart Transmit feature is completed in three parts:

0. RF Exposure Compliance Test Report Part 0: SAR Characterization and PD Characterization

The SAR Characterization, denoted as SAR Char, determines the power limit that meets FCC exposure requirement after accounting for device design related uncertainties for each supported radio configuration and RF exposure usage scenario. The determined power limits will be loaded and stored in the EUT via the Embedded File System (EFS) for Smart Transmit and the Board Data File (BDF) for Fast Connect, and then used as inputs for Smart Transmit and FastConnect to operate.

For WWAN and WLAN SAR Char is derived from SAR test measurements and conducted power measurements to determine P_{Limit} for each technology/band. The P_{Limit} and *input.power.limit* represents the maximum time-averaged power level for the corresponding radio/antenna configuration.

1. RF Exposure Compliance Test Report Part 1: Test in Static Transmission Condition

Part 1 demonstrates that DUT meets FCC SAR limits when transmitting at pre-determined maximum time-averaged power level: P_{Limit} for WWAN, WLAN. The SAR measurement in Part 1 is under static transmission condition.

The compliance for BT radio is demonstrated at a fixed power level (fixed = maximum RF tune-up level or power-back off level).

The exposure from the simultaneous transmission of WWAN and WLAN is evaluated in Part 2 report.

2. RF Exposure Compliance Test Report Part 2: Test in Dynamic Transmission Condition

Part 2 demonstrates compliance in Tx varying transmission conditions and validates Qualcomm Smart Transmit and FastConnect algorithm. The test results reported in Part 2 demonstrates that DUT complies with FCC RF exposure requirement under Tx varying transmission scenarios, thereby validity of Qualcomm Smart Transmit and FastConnect algorithms.

FCC ID: C3K2077	COMPLIANCE SUMMARY REPORT	Approved by: Technical Manager
Document S/N: 1M2312040120-03.C3K	DUT Type: Portable Computing Device	Page 3 of 10

REV 1.1
04/11/2022

1.2 Nomenclature

Applicable Technologies	Term	Description
WWAN, WLAN	P_{Limit}	Power level that corresponds to the exposure design target (SAR_{design_target}) after accounting for all device design related uncertainties
	P_{Max}	Maximum tune up output power
	T_{SAR}	Defined time averaging window for $f < 6$ GHz
	SAR_{design_target}	Target SAR level resulting in maximum time-averaged exposure optimized from total uncertainty
	SAR_{Char}	Table containing P_{Limit} for all technologies
WWAN, WLAN	<i>regulatory body</i>	Regulatory body that the algorithm is designed to comply. Algorithm's time averaging window is dependent on either FCC or ICNIRP requirements.
	<i>reserve_power_margin</i>	Margin below P_{Limit} reserved for future transmission
	$P_{reserve}$	Minimum transmit power with a designated margin below P_{Limit}

1.3 Bibliography

Report Type	Report Serial Number
SAR Evaluation Report (Part 1)	1M2312040120-01.C3K
SAR Evaluation Report (Part 0)	1M2312040120-02.C3K
RF Exposure Part 2 Test Report	1M2312040120-04.C3K

FCC ID: C3K2077	COMPLIANCE SUMMARY REPORT	Approved by: Technical Manager
Document S/N: 1M2312040120-03.C3K	DUT Type: Portable Computing Device	Page 4 of 10

2 TIME AVERAGING ALGORITHM

2.1 Algorithm Description

The FCC RF exposure limit is defined based on time-averaged RF exposure. When running in a wireless device, Qualcomm Smart Transmit and FastConnect algorithm enables more elegant power control mechanisms for RF exposure management. It ensures at all times the wireless device is in compliance with the FCC limit of RF exposure time-averaged over a defined time window, denoted as T_{SAR} and T_{PD} for specific absorption rate (SAR for transmit frequency < 6 GHz) and power density (PD for transmit frequency > 6 GHz) time windows, respectively.

The Qualcomm Smart Transmit and FastConnect algorithm not only ensures the wireless device complies with RF exposure requirement, but also improves the user experience and network performance.

For a given wireless device, RF exposure is proportional to the transmitting power.

- Once the SAR of the wireless device is characterized at a transmit power level, RF exposure at a different power level for the characterized configurations can be scaled by the change in the corresponding power level.
- Therefore, for a characterized device, RF exposure compliance can be achieved through transmit power control and management.

The Qualcomm Smart Transmit and FastConnect algorithm embedded in Qualcomm modems reliably controls the transmit power of the wireless device in real time to maintain the time-averaged transmit power, in turn, time-averaged RF exposure, below the predefined time-averaged power limit for each characterized technology and band.

- This predefined time-averaged power limit is denoted as P_{Limit} corresponding SAR limit (frequency < 6 GHz) in this report.
- The wireless device continuously transmitting at P_{Limit} level complies with the FCC RF exposure requirement.

In a simultaneous transmission scenario, the algorithm manages all active transmitters and make sure the total exposure ratio from each transmitter not exceeding to 1.

FCC ID: C3K2077	COMPLIANCE SUMMARY REPORT	Approved by: Technical Manager
Document S/N: 1M2312040120-03.C3K	DUT Type: Portable Computing Device	Page 5 of 10

REV 1.1
04/11/2022

2.2 Basic concept of the algorithm


The Qualcomm Smart Transmit and FastConnect algorithm controls and manages the instantaneous transmit power (Tx) to maintain the time-averaged Tx power and therefore, time-averaged RF exposure in compliance with FCC limits.

- If time-averaged transmit power approaches P_{Limit} , then the modem needs to limit instantaneous transmit power to ensure the time-averaged transmit power does not exceed P_{Limit} in any T_{SAR} time windows since the time-averaged RF exposure is required to comply with the FCC RF exposure limit in any T_{SAR} time window.
- The wireless device can instantaneously transmit at high transmit powers and exceed the P_{Limit} level for a short duration before limiting the power to maintain the time-averaged transmit power under P_{Limit} .
- If the wireless device transmits at high power for a long time, then the radio link needs to be dropped to be compliant with time-averaged Tx power requirement (see Figure 2-1).
- To avoid dropping the radio link, TAS algorithm starts the power limiting enforcement earlier in time to back off the Tx power to a reserve level (denoted as $P_{reserve}$), so the wireless device can maintain the radio link at a minimum reserve power level for as long as needed, and at the same time ensure the time-averaged Tx power over any defined time window is less than P_{Limit} at all times (see Figure 2-2). At all times, TAS meets the below equation:

$$time. avg. Tx power = \frac{1}{T_{SAR}} \int_{t-T_{SAR}}^t inst. Tx power(t) dt \leq P_{limit}$$

Equation 2-1


where, *time. avg. Tx power* is the transmit power averaged between $t-T_{SAR}$ and t time period; T_{SAR} is the time window defined by FCC for time-averaging RF exposure for Tx frequency less than 6GHz (sub6); *inst. Tx power (t)* is the instantaneous transmit power at t time instant; P_{Limit} is the predefined time-averaged power limit.



(a)

Figure 2-1
Transmit at high power when needed and permitted

FCC ID: C3K2077	COMPLIANCE SUMMARY REPORT	Approved by: Technical Manager
Document S/N: 1M2312040120-03.C3K	DUT Type: Portable Computing Device	Page 6 of 10



(b)

Figure 2-2

Transmit with reserve power to support continuous transmission at a minimum power level ($P_{reserve}$)

- In the case of simultaneous transmission, TAS manages all active transmitters and make sure the total exposure ratio is less than 1

$$\sum \frac{1}{T_{SAR}} \int_{t-T_{SAR}}^t SAR(t) dt \leq 1$$

Equation 2-2

FCC ID: C3K2077	COMPLIANCE SUMMARY REPORT	Approved by: Technical Manager
Document S/N: 1M2312040120-03.C3K	DUT Type: Portable Computing Device	Page 7 of 10

2.3 Configurable Parameters

The following input parameters are required for functionality of Qualcomm Smart Transmit and FastConnect algorithm. These parameters cannot be accessed by the end user, because at the factory they are entered through the embedded file system (EFS) entries by the OEM

Input Parameter	Description
<i>regulatory_body</i>	<ul style="list-style-type: none"> Inputs of “0” and “1” corresponding to FCC and ICNIRP requirements for the averaging time windows. For FCC, algorithm uses an averaging window of 100 seconds for $f < 3$ GHz, 60 seconds for $3 \text{ GHz} < f < 6 \text{ GHz}$, and 4 seconds for $24 \text{ GHz} < f < 42 \text{ GHz}$.
<i>Tx_power_at_SAR_design_target</i> (P_{Limit} in dBm) $f < 6 \text{ GHz}$	<p>The maximum time-averaged transmit power, in dBm, corresponding to the <i>SAR_design_target</i>.</p> <p><i>SAR_design_target</i> is pre-determined for this DUT and it is less than regulatory SAR limit after accounting for all design related tolerances. The time-averaged SAR is assessed against this <i>SAR_design_target</i> in real time to determine the compliance.</p> <p>P_{Limit} could vary with technology, band and Device State Index (DSI) and therefore, it has the unique value for each technology, band and DSI.</p>
<i>reserve_power_margin</i> ($P_{reserve}$ in dBm)	<p>The margin below P_{Limit} reserved for future transmission with a minimum transmit power $P_{reserve}$</p> $P_{reserve} \text{ (dBm)} = P_{limit} \text{ (dBm)} - Reserve_power_margin \text{ (dB)}$ <p>When the <i>Reserve_power_margin</i> is set to 0 dB, TAS effectively limits the upper bound of the transmit power to P_{limit} and the DUT transmits continuously at P_{limit} without utilizing TAS dynamic control feature.</p>

FCC ID: C3K2077	COMPLIANCE SUMMARY REPORT	Approved by: Technical Manager
Document S/N: 1M2312040120-03.C3K	DUT Type: Portable Computing Device	Page 8 of 10

3 DUT DESCRIPTION

3.1 Device Overview

Band & Mode	Operating Modes	Tx Frequency
UMTS 850	Data	826.40 - 846.60 MHz
UMTS 1750	Data	1712.4 - 1752.6 MHz
UMTS 1900	Data	1852.4 - 1907.6 MHz
LTE Band 71	Data	665.5 - 695.5 MHz
LTE Band 12	Data	699.7 - 715.3 MHz
LTE Band 13	Data	779.5 - 784.5 MHz
LTE Band 14	Data	790.5 - 795.5 MHz
LTE Band 26	Data	814.7 - 848.3 MHz
LTE Band 5	Data	824.7 - 848.3 MHz
LTE Band 66	Data	1710.7 - 1779.3 MHz
LTE Band 4	Data	1710.7 - 1754.3 MHz
LTE Band 25	Data	1850.7 - 1914.3 MHz
LTE Band 2	Data	1850.7 - 1909.3 MHz
LTE Band 30	Data	2307.5 - 2312.5 MHz
LTE Band 41	Data	2498.5 - 2687.5 MHz
LTE Band 48	Data	3552.5 - 3697.5 MHz
NR Band n71	Data	665.5 - 695.5 MHz
NR Band n12	Data	701.5 - 713.5 MHz
NR Band n14	Data	790.5 - 795.5 MHz
NR Band n26	Data	816.5 - 846.5 MHz
NR Band n5	Data	826.5 - 846.5 MHz
NR Band n66	Data	1712.5 - 1777.5 MHz
NR Band n25	Data	1852.5 - 1912.5 MHz
NR Band n2	Data	1852.5 - 1907.5 MHz
NR Band n30	Data	2307.5 - 2312.5 MHz
NR Band n41	Data	2506.02 - 2679.99 MHz
NR Band n48	Data	3555 - 3694.98 MHz
NR Band n77	Data	3460.02 - 3540 MHz; 3710.01 - 3969.99 MHz
2.4 GHz WIFI	Data	2412 - 2472 MHz
5 GHz WIFI	Data	U-NII-1: 5180 - 5240 MHz U-NII-2A: 5260 - 5320 MHz U-NII-2C: 5500 - 5720 MHz U-NII-3: 5745 - 5825 MHz U-NII-4: 5845 - 5885 MHz
6 GHz WIFI	Data	U-NII-5: 5945 - 6415 MHz U-NII-6: 6435 - 6515 MHz U-NII-7: 6535 - 6855 MHz U-NII-8: 6875 - 7115 MHz
2.4 GHz Bluetooth	Data	2402 - 2480 MHz

This device uses the Qualcomm Smart Transmit and FastConnect features to control and manage transmitting power in real time and to ensure at all times the time-averaged RF exposure is in compliance with the FCC requirement for WWAN and WLAN operations. Additionally, this device supports BT technologies but the output power of these modems is not controlled by the FastConnect algorithm.

FCC ID: C3K2077	COMPLIANCE SUMMARY REPORT	Approved by: Technical Manager
Document S/N: 1M2312040120-03.C3K	DUT Type: Portable Computing Device	Page 9 of 10

4 COMPLIANCE SUMMARY

4.1 RF Exposure Compliance Summary

All transmission scenarios that the DUT supports comply with FCC time-averaged RF exposure requirements, as shown in Table 4-1.

**Table 4-1
Reported RF Exposure Levels**

	RFx Evaluation	Power Level	FCC Limit	<i>Reported</i> RF Exposure Level	Test Report
SAR (W/kg)	Standalone 1g SAR	P_{limit}	1.6	1.18	FCC SAR Evaluation Report (Part 1)
	Simultaneous Tx 1g SAR	P_{limit}	1.6	1.58	

FCC ID: C3K2077	COMPLIANCE SUMMARY REPORT	Approved by: Technical Manager
Document S/N: 1M2312040120-03.C3K	DUT Type: Portable Computing Device	Page 10 of 10

REV 1.1
04/11/2022