



Plot 7-113. Power Spectral Density Plot MIMO ANT1 (80MHz BW 802.11ac (UNII Band 3) – Ch. 155)




Plot 7-114. Power Spectral Density Plot MIMO ANT1 (80MHz BW 802.11ax/be (UNII Band 3) – Ch. 155)

FCC ID: C3K2085	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2311170118-09.C3K	Test Dates: 01/03/2024 - 03/18/2024	EUT Type: Portable Computing Device	Page 85 of 155




Plot 7-115. Power Spectral Density Plot MIMO ANT1 (20MHz BW 802.11a (UNII Band 4) – Ch. 177)




Plot 7-116. Power Spectral Density Plot MIMO ANT1 (20MHz BW 802.11n (UNII Band 3/4) – Ch. 169)

FCC ID: C3K2085	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2311170118-09.C3K	Test Dates: 01/03/2024 - 03/18/2024	EUT Type: Portable Computing Device	Page 86 of 155




Plot 7-117. Power Spectral Density Plot MIMO ANT1 (20MHz BW 802.11ax/be (UNII Band 3/4) – Ch. 169)




Plot 7-118. Power Spectral Density Plot MIMO ANT1 (40MHz BW 802.11n (UNII Band 4) – Ch. 175)

FCC ID: C3K2085	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2311170118-09.C3K	Test Dates: 01/03/2024 - 03/18/2024	EUT Type: Portable Computing Device	Page 87 of 155




Plot 7-119. Power Spectral Density Plot MIMO ANT1 (40MHz BW 802.11ax/be (UNII Band 3/4) – Ch. 167)




Plot 7-120. Power Spectral Density Plot MIMO ANT1 (80MHz BW 802.11ac (UNII Band 3/4) – Ch. 171)

FCC ID: C3K2085		MEASUREMENT REPORT		Approved by:
				Technical Manager
Test Report S/N:	Test Dates:	EUT Type:		
1M2311170118-09.C3K	01/03/2024 - 03/18/2024	Portable Computing Device	Page 88 of 155	




Plot 7-121. Power Spectral Density Plot MIMO ANT1 (80MHz BW 802.11ax/be (UNII Band 3/4) – Ch. 171)



Plot 7-122. Power Spectral Density Plot MIMO ANT1 (160MHz BW 802.11ac (UNII Band 3/4) – Ch. 163)


FCC ID: C3K2085	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2311170118-09.C3K	Test Dates: 01/03/2024 - 03/18/2024	EUT Type: Portable Computing Device	Page 89 of 155




Plot 7-123. Power Spectral Density Plot MIMO ANT1 (160MHz BW 802.11ax/be (UNII Band 3/4) – Ch. 163)

FCC ID: C3K2085	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2311170118-09.C3K	Test Dates: 01/03/2024 - 03/18/2024	EUT Type: Portable Computing Device	Page 90 of 155

7.5.2 MIMO Antenna-2 Power Spectral Density Measurements




Plot 7-124. Power Spectral Density Plot MIMO ANT2 (802.11a (UNII Band 1) – Ch. 48)




Plot 7-125. Power Spectral Density Plot MIMO ANT2 (20MHz BW 802.11n (UNII Band 1) – Ch. 48)

FCC ID: C3K2085	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2311170118-09.C3K	Test Dates: 01/03/2024 - 03/18/2024	EUT Type: Portable Computing Device	Page 91 of 155




Plot 7-126. Power Spectral Density Plot MIMO ANT2 (20MHz BW 802.11ax/be (UNII Band 1) – Ch. 40)




Plot 7-127. Power Spectral Density Plot MIMO ANT2 (40MHz BW 802.11n (UNII Band 1) – Ch. 46)

FCC ID: C3K2085	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2311170118-09.C3K	Test Dates: 01/03/2024 - 03/18/2024	EUT Type: Portable Computing Device	Page 92 of 155




Plot 7-128. Power Spectral Density Plot MIMO ANT2 (40MHz BW 802.11ax/be (UNII Band 1) – Ch. 46)




Plot 7-129. Power Spectral Density Plot MIMO ANT2 (80MHz BW 802.11ac (UNII Band 1) – Ch. 42)

FCC ID: C3K2085	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2311170118-09.C3K	Test Dates: 01/03/2024 - 03/18/2024	EUT Type: Portable Computing Device	Page 93 of 155




Plot 7-130. Power Spectral Density Plot MIMO ANT2 (80MHz BW 802.11ax/be (UNII Band 1) – Ch. 42)




Plot 7-131. Power Spectral Density Plot MIMO ANT2 (160MHz BW 802.11ac (UNII Band 1/2A) – Ch. 50)

FCC ID: C3K2085	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2311170118-09.C3K	Test Dates: 01/03/2024 - 03/18/2024	EUT Type: Portable Computing Device	Page 94 of 155




Plot 7-132. Power Spectral Density Plot MIMO ANT2 (160MHz BW 802. 11ax/be (UNII Band 1/2A) – Ch. 50)




Plot 7-133. Power Spectral Density Plot MIMO ANT2 (802.11a (UNII Band 2A) – Ch. 52)

FCC ID: C3K2085	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2311170118-09.C3K	Test Dates: 01/03/2024 - 03/18/2024	EUT Type: Portable Computing Device	Page 95 of 155




Plot 7-134. Power Spectral Density Plot MIMO ANT2 (20MHz BW 802.11n (UNII Band 2A) – Ch. 64)




Plot 7-135. Power Spectral Density Plot MIMO ANT2 (20MHz BW 802.11ax/be (UNII Band 2A) – Ch. 56)

FCC ID: C3K2085	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2311170118-09.C3K	Test Dates: 01/03/2024 - 03/18/2024	EUT Type: Portable Computing Device	Page 96 of 155




Plot 7-136. Power Spectral Density Plot MIMO ANT2 (40MHz BW 802.11n (UNII Band 2A) – Ch. 62)




Plot 7-137. Power Spectral Density Plot MIMO ANT2 (40MHz BW 802.11ax/be (UNII Band 2A) – Ch. 54)

FCC ID: C3K2085	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2311170118-09.C3K	Test Dates: 01/03/2024 - 03/18/2024	EUT Type: Portable Computing Device	Page 97 of 155




Plot 7-138. Power Spectral Density Plot MIMO ANT2 (80MHz BW 802.11ac (UNII Band 2A) – Ch. 58)




Plot 7-139. Power Spectral Density Plot MIMO ANT2 (80MHz BW 802.11ax/be (UNII Band 2A) – Ch. 58)

FCC ID: C3K2085	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2311170118-09.C3K	Test Dates: 01/03/2024 - 03/18/2024	EUT Type: Portable Computing Device	Page 98 of 155




Plot 7-140. Power Spectral Density Plot MIMO ANT2 (802.11a (UNII Band 2C) – Ch. 144)




Plot 7-141. Power Spectral Density Plot MIMO ANT2 (20MHz BW 802.11n (UNII Band 2C) – Ch. 144)

FCC ID: C3K2085	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2311170118-09.C3K	Test Dates: 01/03/2024 - 03/18/2024	EUT Type: Portable Computing Device	Page 99 of 155




Plot 7-142. Power Spectral Density Plot MIMO ANT2 (20MHz BW 802.11ax/be (UNII Band 2C) – Ch. 100)




Plot 7-143. Power Spectral Density Plot MIMO ANT2 (40MHz BW 802.11n (UNII Band 2C) – Ch. 142)

FCC ID: C3K2085	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2311170118-09.C3K	Test Dates: 01/03/2024 - 03/18/2024	EUT Type: Portable Computing Device	Page 100 of 155




Plot 7-144. Power Spectral Density Plot MIMO ANT2 (40MHz BW 802.11ax/be (UNII Band 2C) – Ch. 142)




Plot 7-145. Power Spectral Density Plot MIMO ANT2 (80MHz BW 802.11ac (UNII Band 2C) – Ch. 138)

FCC ID: C3K2085	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2311170118-09.C3K	Test Dates: 01/03/2024 - 03/18/2024	EUT Type: Portable Computing Device	Page 101 of 155




Plot 7-146. Power Spectral Density Plot MIMO ANT2 (80MHz BW 802.11ax/be (UNII Band 2C) – Ch. 138)




Plot 7-147. Power Spectral Density Plot MIMO ANT2 (160MHz BW 802.11ac (UNII Band 2C) – Ch. 114)

FCC ID: C3K2085	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2311170118-09.C3K	Test Dates: 01/03/2024 - 03/18/2024	EUT Type: Portable Computing Device	Page 102 of 155




Plot 7-148. Power Spectral Density Plot MIMO ANT2 (160MHz BW 802.11ax/be (UNII Band 2C) – Ch. 114)




Plot 7-149. Power Spectral Density Plot MIMO ANT2 (802.11a (UNII Band 3) – Ch. 149)

FCC ID: C3K2085	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2311170118-09.C3K	Test Dates: 01/03/2024 - 03/18/2024	EUT Type: Portable Computing Device	Page 103 of 155




Plot 7-150. Power Spectral Density Plot MIMO ANT2 (20MHz BW 802.11n (UNII Band 3) – Ch. 149)




Plot 7-151. Power Spectral Density Plot MIMO ANT2 (20MHz BW 802.11ax/be (UNII Band 3) – Ch. 149)

FCC ID: C3K2085	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2311170118-09.C3K	Test Dates: 01/03/2024 - 03/18/2024	EUT Type: Portable Computing Device	Page 104 of 155




Plot 7-152. Power Spectral Density Plot MIMO ANT2 (40MHz BW 802.11n (UNII Band 3) – Ch. 151)




Plot 7-153. Power Spectral Density Plot MIMO ANT2 (40MHz BW 802.11ax/be (UNII Band 3) – Ch. 151)

FCC ID: C3K2085	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2311170118-09.C3K	Test Dates: 01/03/2024 - 03/18/2024	EUT Type: Portable Computing Device	Page 105 of 155




Plot 7-154. Power Spectral Density Plot MIMO ANT2 (80MHz BW 802.11ac (UNII Band 3) – Ch. 155)




Plot 7-155. Power Spectral Density Plot MIMO ANT2 (80MHz BW 802.11ax/be (UNII Band 3) – Ch. 155)

FCC ID: C3K2085	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2311170118-09.C3K	Test Dates: 01/03/2024 - 03/18/2024	EUT Type: Portable Computing Device	Page 106 of 155




Plot 7-156. Power Spectral Density Plot MIMO ANT2 (20MHz BW 802.11a (UNII Band 4) – Ch. 177)




Plot 7-157. Power Spectral Density Plot MIMO ANT2 (20MHz BW 802.11n (UNII Band 3/4) – Ch. 169)

FCC ID: C3K2085	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2311170118-09.C3K	Test Dates: 01/03/2024 - 03/18/2024	EUT Type: Portable Computing Device	Page 107 of 155




Plot 7-158. Power Spectral Density Plot MIMO ANT2 (20MHz BW 802.11ax/be (UNII Band 3/4) – Ch. 169)




Plot 7-159. Power Spectral Density Plot MIMO ANT2 (40MHz BW 802.11n (UNII Band 4) – Ch. 175)

FCC ID: C3K2085		MEASUREMENT REPORT		Approved by:
				Technical Manager
Test Report S/N:	Test Dates:	EUT Type:		
1M2311170118-09.C3K	01/03/2024 - 03/18/2024	Portable Computing Device	Page 108 of 155	




Plot 7-160. Power Spectral Density Plot MIMO ANT2 (40MHz BW 802.11ax/be (UNII Band 3/4) – Ch. 167)




Plot 7-161. Power Spectral Density Plot MIMO ANT2 (80MHz BW 802.11ac (UNII Band 3/4) – Ch. 171)

FCC ID: C3K2085	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2311170118-09.C3K	Test Dates: 01/03/2024 - 03/18/2024	EUT Type: Portable Computing Device	Page 109 of 155




Plot 7-162. Power Spectral Density Plot MIMO ANT2 (80MHz BW 802.11ax/be (UNII Band 3/4) – Ch. 171)



Plot 7-163. Power Spectral Density Plot MIMO ANT2 (160MHz BW 802.11ac (UNII Band 3/4) – Ch. 163)


FCC ID: C3K2085	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2311170118-09.C3K	Test Dates: 01/03/2024 - 03/18/2024	EUT Type: Portable Computing Device	Page 110 of 155




Plot 7-164. Power Spectral Density Plot MIMO ANT2 (160MHz BW 802.11ax/be (UNII Band 3/4) – Ch. 163)

FCC ID: C3K2085	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2311170118-09.C3K	Test Dates: 01/03/2024 - 03/18/2024	EUT Type: Portable Computing Device	Page 111 of 155

7.5.3 MIMO Antenna-1 Power Spectral Density Measurements - Punctured




Plot 7-165. Power Spectral Density Plot MIMO ANT1 (80MHz BW 802.11be (UNII Band 1) – Ch. 42)




Plot 7-166. Power Spectral Density Plot MIMO ANT1 (160MHz BW 802.11be (UNII Band 1/2A) – Ch. 50)

FCC ID: C3K2085	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2311170118-09.C3K	Test Dates: 01/03/2024 - 03/18/2024	EUT Type: Portable Computing Device	Page 112 of 155




Plot 7-167. Power Spectral Density Plot MIMO ANT1 (80MHz BW 802.11be (UNII Band 2A) – Ch. 58)




Plot 7-168. Power Spectral Density Plot MIMO ANT1 (160MHz BW 802.11be (UNII Band 2C) – Ch. 114)

FCC ID: C3K2085	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2311170118-09.C3K	Test Dates: 01/03/2024 - 03/18/2024	EUT Type: Portable Computing Device	Page 113 of 155




Plot 7-169. Power Spectral Density Plot MIMO ANT1 (80MHz BW 802.11be (UNII Band 3) – Ch. 155)



Plot 7-170. Power Spectral Density Plot MIMO ANT1 (80MHz BW 802.11be (UNII Band 3/4) – Ch. 171)


FCC ID: C3K2085	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2311170118-09.C3K	Test Dates: 01/03/2024 - 03/18/2024	EUT Type: Portable Computing Device	Page 114 of 155




Plot 7-171. Power Spectral Density Plot MIMO ANT1 (160MHz BW 802.11be (UNII Band 3/4) – Ch. 163)

FCC ID: C3K2085	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2311170118-09.C3K	Test Dates: 01/03/2024 - 03/18/2024	EUT Type: Portable Computing Device	Page 115 of 155

7.5.4 MIMO Antenna-2 Power Spectral Density Measurements - Punctured




Plot 7-172. Power Spectral Density Plot MIMO ANT2 (80MHz BW 802.11be (UNII Band 1) – Ch. 42)




Plot 7-173. Power Spectral Density Plot MIMO ANT2 (160MHz BW 802.11be (UNII Band 1/2A) – Ch. 50)

FCC ID: C3K2085	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2311170118-09.C3K	Test Dates: 01/03/2024 - 03/18/2024	EUT Type: Portable Computing Device	Page 116 of 155




Plot 7-174. Power Spectral Density Plot MIMO ANT2 (80MHz BW 802.11be (UNII Band 2A) – Ch. 58)




Plot 7-175. Power Spectral Density Plot MIMO ANT2 (160MHz BW 802.11be (UNII Band 2C) – Ch. 114)

FCC ID: C3K2085	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2311170118-09.C3K	Test Dates: 01/03/2024 - 03/18/2024	EUT Type: Portable Computing Device	Page 117 of 155




Plot 7-176. Power Spectral Density Plot MIMO ANT2 (80MHz BW 802.11be (UNII Band 3) – Ch. 155)



Plot 7-177. Power Spectral Density Plot MIMO ANT2 (80MHz BW 802.11be (UNII Band 3/4) – Ch. 171)

FCC ID: C3K2085	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2311170118-09.C3K	Test Dates: 01/03/2024 - 03/18/2024	EUT Type: Portable Computing Device	Page 118 of 155



Plot 7-178. Power Spectral Density Plot MIMO ANT2 (160MHz BW 802.11be (UNII Band 3/4) – Ch. 163)

FCC ID: C3K2085	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2311170118-09.C3K	Test Dates: 01/03/2024 - 03/18/2024	EUT Type: Portable Computing Device	Page 119 of 155



Note:

Per ANSI C63.10-2013 Section 14.3.2.2 the power spectral density at Antenna-1 and Antenna-2 were first measured separately as shown in the section above. The measured values were then summed in linear power units then converted back to dBm.

Sample MIMO Calculation:

At 5845MHz in 802.11a (20MHz BW) mode, the average conducted power spectral density was measured to be 3.51 dBm for Antenna 1 and 3.07 dBm for Antenna 2.

$$\text{Antenna 1} + \text{Antenna 2} = \text{MIMO}$$

$$(3.51 \text{ dBm} + 3.07 \text{ dBm}) = (2.24 \text{ mW} + 2.03 \text{ mW}) = 4.27 \text{ mW} = 6.31 \text{ dBm}$$

Sample e.i.r.p Power Spectral Density Calculation:

At 5845MHz in 802.11a (20MHz BW) mode, the average MIMO power density was calculated to be 6.31 dBm with directional gain of 7.27 dBi.

$$\text{e.i.r.p. Power Spectral Density(dBm)} = \text{Power Spectral Density (dBm)} + \text{Ant gain (dBi)}$$

$$6.31 \text{ dBm} + 7.27 \text{ dBi} = 13.57 \text{ dBm}$$

FCC ID: C3K2085	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2311170118-09.C3K	Test Dates: 01/03/2024 - 03/18/2024	EUT Type: Portable Computing Device	Page 120 of 155

7.6 Radiated Emission Measurements

Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at its maximum duty cycle, at its maximum power control level, as defined in ANSI C63.10-2013, and at the appropriate frequencies. All channels, modes, and modulations/data rates were investigated among all UNII bands. Only the radiated emissions of the configuration that produced the worst-case emissions are reported in this section.

For transmitters operating in the 5.15-5.25 GHz and 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an EIRP of -27 dBm/MHz.

For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an EIRP of -27 dBm/MHz.

For transmitters operating in the 5.725-5.85 GHz band: All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

For transmitters operating in the 5.850 – 5.895 GHz band: all emissions at or above 5.895GHz shall not exceed an e.i.r.p. of -5dBm/MHz and shall decrease linearly up to an e.i.r.p. of -27dBm/MHz at or above 5.925GHz, and all emissions below 5.725 GHz shall not exceed an e.i.r.p. of -27dBm/MHz at 5.65 GHz increasing linearly to 10dBm/MHz at 5.7GHz and from 5.7GHz increasing linearly to a level of 15.6dBm/MHz at 5.72GHz, and from 5.72GHz increasing linearly to a level of 27dBm/MHz at 5.725GHz.

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR and Table 6 of RSS-Gen (8.10) must not exceed the limits shown in the table below per FCC §15.209 and RSS-Gen (8.9).

Frequency	Field Strength [μ V/m]	Measured Distance [Meters]
0.009 – 0.490 MHz	2400\F (kHz)	300
0.490 – 1.705 MHz	24000\F (kHz)	30
1.705 – 30.00 MHz	30	30
30.00 – 88.00 MHz	100	3
88.00 – 216.0 MHz	150	3
216.0 – 960.0 MHz	200	3
Above 960.0 MHz	500	3

Table 7-29. Radiated Limits

Test Procedures Used

ANSI C63.10-2013 – Sections 12.7.7.2, 12.7.6, 12.7.5 (Radiated Spurious Emissions)

ANSI C63.10-2013 – Section 12.7.4.4 (Band Edge Measurements)

FCC ID: C3K2085	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2311170118-09.C3K	Test Dates: 01/03/2024 - 03/18/2024	EUT Type: Portable Computing Device	Page 121 of 155



Test Settings – Above 1GHz

Average Field Strength Measurements (Method AD – Average Detection)

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest.
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = power average (RMS)
5. Number of measurement points = 1001 (Number of points must be $\geq 2 \times \text{span} \backslash \backslash \text{RBW}$)
6. Sweep time = auto
7. Trace (RMS) averaging was performed over at least 100 traces.

Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest.
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize.

Test Settings – Below 1GHz

Quasi-Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest.
2. RBW = 120kHz (for emissions from 30MHz – 1GHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize.

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.

FCC ID: C3K2085	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2311170118-09.C3K	Test Dates: 01/03/2024 - 03/18/2024	EUT Type: Portable Computing Device	Page 122 of 155




Figure 7-5. Radiated Test Setup < 30MHz




Figure 7-6. Radiated Test Setup < 1GHz

FCC ID: C3K2085	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2311170118-09.C3K	Test Dates: 01/03/2024 - 03/18/2024	EUT Type: Portable Computing Device	Page 123 of 155




Figure 7-7. Radiated Test Setup > 1GHz

FCC ID: C3K2085	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2311170118-09.C3K	Test Dates: 01/03/2024 - 03/18/2024	EUT Type: Portable Computing Device	Page 124 of 155

Test Notes

1. All spurious emissions lying in restricted bands specified in §15.205 are below the limits shown in §15.209. All spurious emissions that do not lie in a restricted band are subject to an average limit of -27dBm/MHz. At 3 meters, the field strength limit in dB μ V/m can be determined by adding a “conversion” factor of 95.2dB to the EIRP limit of -27dBm/MHz to obtain the limit for out of band spurious emissions of 68.2dB μ V/m.
2. All spurious emissions that do not lie in a restricted band are subject to a peak limit not to exceed 20dB of the average limit [68.2dB μ V/m]. If a peak measurement passes the average limit, it was determined no further investigation is necessary.
3. The antenna is manipulated through typical positions, polarity, and length during the tests. The EUT is manipulated through three orthogonal planes.
4. This unit was tested with its standard battery.
5. The spectrum is measured from 9kHz to the 10th harmonic of the fundamental frequency of the transmitter using CISPR quasi peak detector below 1GHz. Above 1 GHz, average and peak measurements were taken using linearly polarized horn antennas. The worst-case emissions are reported, however emissions whose levels were not within 20dB of the respective limits were not reported.
6. Emissions below 18GHz were measured at a 3-meter test distance while emissions above 18GHz were measured at a 1-meter test distance with the application of a distance correction factor.
7. The wide spectrum spurious emissions plots shown on the following pages are used only for the purpose of emission identification. Any emissions found to be within 20dB of the limit are fully investigated and the results are shown in this section.
8. The "-" shown in the following RSE tables are used to denote a noise floor measurement.
9. In the case where a peak-detector measurement passed the given RMS limit it was determined sufficient to demonstrate compliance.
10. The results recorded using the broadband antenna are known to correlate with the results obtained by using a tuned dipole with an acceptable degree of accuracy. The VSWR for the measurement antenna was found to be less than 2:1.

Sample Calculations

Determining Spurious Emissions Levels


- Field Strength Level [dB μ V/m] = Analyzer Level [dBm] + 107 + AFCL [dB/m]
- AFCL [dB/m] = Antenna Factor [dB/m] + Cable Loss [dB]
- Margin [dB] = Field Strength Level [dB μ V/m] – Limit [dB μ V/m]

Radiated Band Edge Measurement Offset

- The amplitude offset shown in the radiated restricted band edge plots was calculated using the formula:
Offset (dB) = (Antenna Factor + Cable Loss + Attenuator) – Pre-amplifier Gain

FCC ID: C3K2085	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2311170118-09.C3K	Test Dates: 01/03/2024 - 03/18/2024	EUT Type: Portable Computing Device	Page 125 of 155

7.6.1 MIMO Radiated Spurious Emission Measurements




Plot 7-179. Radiated Spurious Plot below 1GHz MIMO (802.11a)


Mode	Antenna	UNII Band	Channel	Test Channel Freq. [MHz]	Restricted	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
802.11a	MIMO	2C	100	5500		95.14	Quasi-Peak	H	334	94	-91.55	15.98	31.43	43.52	-12.09

Table 7-30. Radiated Measurements MIMO


FCC ID: C3K2085	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2311170118-09.C3K	Test Dates: 01/03/2024 - 03/18/2024	EUT Type: Portable Computing Device	Page 126 of 155



Plot 7-180. Radiated Spurious Plot above 1GHz MIMO (802.11a – UNII Band 1 Ch. 40)




Plot 7-181. Radiated Spurious Plot above 1GHz MIMO (802.11a – UNII Band 2A Ch. 56)




Plot 7-182. Radiated Spurious Plot above 1GHz MIMO (802.11a – UNII Band 2C Ch. 120)


FCC ID: C3K2085	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2311170118-09.C3K	Test Dates: 01/03/2024 - 03/18/2024	EUT Type: Portable Computing Device	Page 127 of 155



Plot 7-183. Radiated Spurious Plot above 1GHz MIMO (802.11a – UNII Band 3 Ch. 157)




Plot 7-184. Radiated Spurious Plot above 1GHz MIMO (802.11a – UNII Band 4 Ch. 173)



Plot 7-185. Radiated Spurious Plot 18GHz – 26.5GHz MIMO (802.11a)

FCC ID: C3K2085	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2311170118-09.C3K	Test Dates: 01/03/2024 - 03/18/2024	EUT Type: Portable Computing Device	Page 128 of 155



Plot 7-186. Radiated Spurious Plot 26.5GHz – 40GHz MIMO (802.11a)

FCC ID: C3K2085	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2311170118-09.C3K	Test Dates: 01/03/2024 - 03/18/2024	EUT Type: Portable Computing Device	Page 129 of 155



MIMO Radiated Spurious Emission Measurements – UNII Band 1

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6Mbps
 Distance of Measurements: 1 & 3 Meters

Antenna	UNII Band	Channel	Test Channel Freq. [MHz]	Restricted	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Tumtable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]	
MIMO	1	36	5180		10360.00	Peak	H	-	-	-68.32	12.12	0.00	50.80	68.20	-17.40	
				*	15540.00	Average	H	125	264	-78.42	14.11	0.00	42.69	53.98	-11.29	
				*	15540.00	Peak	H	125	264	-67.35	14.11	0.00	53.76	73.98	-20.22	
				*	20720.00	Average	H	-	-	-64.22	3.27	-9.54	36.51	53.98	-17.47	
				*	20720.00	Peak	H	-	-	-53.94	3.27	-9.54	46.79	73.98	-27.19	
			25900.00	Peak	H	-	-	-54.51	4.35	-9.54	47.30	68.20	-20.90			
		40	5200		10400.00	Peak	H	-	-	-	-68.52	12.37	0.00	50.85	68.20	-17.35
				*	15600.00	Average	H	123	264	-78.69	14.22	0.00	42.53	53.98	-11.45	
				*	15600.00	Peak	H	123	264	-66.22	14.22	0.00	55.00	73.98	-18.98	
				*	20800.00	Average	H	-	-	-64.14	3.40	-9.54	36.72	53.98	-17.26	
				*	20800.00	Peak	H	-	-	-54.44	3.40	-9.54	46.42	73.98	-27.56	
			26000.00	Peak	H	-	-	-54.20	4.39	-9.54	47.64	68.20	-20.56			
		48	5240		10480.00	Peak	H	-	-	-	-69.08	13.08	0.00	51.00	68.20	-17.20
				*	15720.00	Average	H	113	163	-78.18	14.65	0.00	43.47	53.98	-10.51	
				*	15720.00	Peak	H	113	163	-65.71	14.65	0.00	55.94	73.98	-18.04	
					20960.00	Peak	H	-	-	-53.58	3.41	-9.54	47.30	68.20	-20.90	
					26200.00	Peak	H	-	-	-54.78	4.35	-9.54	47.03	68.20	-21.17	

Table 7-31. Radiated Measurements MIMO

FCC ID: C3K2085	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2311170118-09.C3K	Test Dates: 01/03/2024 - 03/18/2024	EUT Type: Portable Computing Device	Page 130 of 155



MIMO Radiated Spurious Emission Measurements – UNII Band 2A

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6Mbps
 Distance of Measurements: 1 & 3 Meters

Antenna	UNII Band	Channel	Test Channel Freq. [MHz]	Restricted	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Tumtable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]	
MIMO	2A	52	5260		10520.00	Peak	H	-	-	-68.05	12.95	0.00	51.90	68.20	-16.30	
				*	15780.00	Average	H	121	267	-78.91	14.23	0.00	42.32	53.98	-11.66	
				*	15780.00	Peak	H	121	267	-66.08	14.23	0.00	55.15	73.98	-18.83	
				*	21040.00	Average	H	-	-	-64.52	3.53	-9.54	36.47	53.98	-17.51	
				*	21040.00	Peak	H	-	-	-53.49	3.53	-9.54	47.50	73.98	-26.48	
					26300.00	Peak	H	-	-	-54.70	4.27	-9.54	47.03	68.20	-21.17	
		56	5280		10560.00	Peak	H	-	-	-	-68.56	12.97	0.00	51.41	68.20	-16.79
				*	15840.00	Average	H	129	262	-78.18	14.09	0.00	42.91	53.98	-11.07	
				*	15840.00	Peak	H	129	262	-66.14	14.09	0.00	54.95	73.98	-19.03	
				*	21120.00	Average	H	-	-	-64.23	3.66	-9.54	36.89	53.98	-17.09	
				*	21120.00	Peak	H	-	-	-53.83	3.66	-9.54	47.29	73.98	-26.69	
					26400.00	Peak	H	-	-	-54.73	4.21	-9.54	46.94	68.20	-21.26	
		64	5320	*	10640.00	Average	H	-	-	-	-79.95	12.51	0.00	39.56	53.98	-14.42
				*	10640.00	Peak	H	-	-	-	-68.23	12.51	0.00	51.28	73.98	-22.70
				*	15960.00	Average	H	122	163	-79.31	15.27	0.00	42.96	53.98	-11.02	
				*	15960.00	Peak	H	122	163	-66.68	15.27	0.00	55.59	73.98	-18.39	
				*	21280.00	Average	H	-	-	-64.32	3.75	-9.54	36.89	53.98	-17.09	
				*	21280.00	Peak	H	-	-	-53.48	3.75	-9.54	47.74	73.98	-26.24	
					26600.00	Peak	H	-	-	-54.37	4.20	-9.54	47.29	68.20	-20.91	

Table 7-32. Radiated Measurements MIMO

FCC ID: C3K2085	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2311170118-09.C3K	Test Dates: 01/03/2024 - 03/18/2024	EUT Type: Portable Computing Device	Page 131 of 155



MIMO Radiated Spurious Emission Measurements – UNII Band 2C

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6Mbps
 Distance of Measurements: 1 & 3 Meters

Antenna	UNII Band	Channel	Test Channel Freq. [MHz]	Restricted	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Tumtable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]	
MIMO	2C	100	5500	*	11000.00	Average	H	-	-	-79.05	12.66	0.00	40.61	53.98	-13.37	
				*	11000.00	Peak	H	-	-	-66.82	12.66	0.00	52.84	73.98	-21.14	
					16500.00	Peak	H	138	166	-58.64	15.81	0.00	64.17	68.20	-4.03	
					22000.00	Peak	H	-	-	-53.89	3.75	-9.54	47.32	68.20	-20.88	
					27500.00	Peak	H	-	-	-54.47	4.29	-9.54	47.28	68.20	-20.92	
		120	5600	*	11200.00	Average	H	-	-	-	-79.72	12.54	0.00	39.82	53.98	-14.16
				*	11200.00	Peak	H	-	-	-67.83	12.54	0.00	51.71	73.98	-22.27	
					16800.00	Peak	H	121	265	-61.57	16.25	0.00	61.68	68.20	-6.52	
				*	22400.00	Average	H	-	-	-64.51	3.72	-9.54	36.67	53.98	-17.31	
				*	22400.00	Peak	H	-	-	-54.43	3.72	-9.54	46.75	73.98	-27.23	
		144	5720		28000.00	Peak	H	-	-	-	-54.79	4.51	-9.54	47.18	68.20	-21.02
				*	11440.00	Average	H	-	-	-	-80.47	13.54	0.00	40.07	53.98	-13.91
				*	11440.00	Peak	H	-	-	-68.35	13.54	0.00	52.19	73.98	-21.79	
					17160.00	Peak	H	-	-	-67.10	16.79	0.00	56.69	68.20	-11.51	
				*	22880.00	Average	H	-	-	-64.58	3.87	-9.54	36.75	53.98	-17.23	
			22880.00	Peak	H	-	-	-53.31	3.87	-9.54	48.02	73.98	-25.96			
			28600.00	Peak	H	-	-	-	-56.12	5.03	-9.54	46.37	68.20	-21.83		

Table 7-33. Radiated Measurements MIMO

FCC ID: C3K2085	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2311170118-09.C3K	Test Dates: 01/03/2024 - 03/18/2024	EUT Type: Portable Computing Device	Page 132 of 155



MIMO Radiated Spurious Emission Measurements – UNII Band 3

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6Mbps
 Distance of Measurements: 1 & 3 Meters

Antenna	UNII Band	Channel	Test Channel Freq. [MHz]	Restricted	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Tumtable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]	
MIMO	3	149	5745	*	11490.00	Average	H	-	-	-80.00	13.10	0.00	40.10	53.98	-13.88	
				*	11490.00	Peak	H	-	-	-68.80	13.10	0.00	51.30	73.98	-22.68	
					17235.00	Peak	H	113	177	-68.08	16.91	0.00	55.83	68.20	-12.37	
				*	22980.00	Average	H	-	-	-64.62	3.75	-9.54	36.59	53.98	-17.39	
				*	22980.00	Peak	H	-	-	-53.52	3.75	-9.54	47.70	73.98	-26.28	
					28725.00	Peak	H	-	-	-55.63	5.10	-9.54	46.93	68.20	-21.27	
		157	5785	*	11570.00	Average	H	-	-	-79.83	12.96	0.00	40.13	53.98	-13.85	
				*	11570.00	Peak	H	-	-	-68.30	12.96	0.00	51.66	73.98	-22.32	
					17355.00	Peak	H	115	165	-68.19	17.83	0.00	56.64	68.20	-11.56	
					23140.00	Peak	H	-	-	-53.61	3.70	-9.54	47.55	68.20	-20.65	
					28925.00	Peak	H	-	-	-55.47	5.00	-9.54	46.99	68.20	-21.21	
		165	5825	*	11650.00	Average	H	-	-	-80.46	13.39	0.00	39.93	53.98	-14.05	
				*	11650.00	Peak	H	-	-	-68.71	13.39	0.00	51.68	73.98	-22.30	
					17475.00	Peak	H	131	203	-67.96	17.09	0.00	56.13	68.20	-12.07	
					23300.00	Peak	H	-	-	-53.47	3.73	-9.54	47.72	68.20	-20.48	
					29125.00	Peak	H	-	-	-55.61	5.04	-9.54	46.89	68.20	-21.31	

Table 7-34. Radiated Measurements MIMO

FCC ID: C3K2085	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2311170118-09.C3K	Test Dates: 01/03/2024 - 03/18/2024	EUT Type: Portable Computing Device	Page 133 of 155



MIMO Radiated Spurious Emission Measurements – UNII Band 4

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6Mbps
 Distance of Measurements: 1 & 3 Meters

Antenna	UNII Band	Channel	Test Channel Freq. [MHz]	Restricted	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Tumtable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
MIMO	4	169	5845	*	11690.00	Average	H	-	-	-80.42	13.59	0.00	40.17	53.98	-13.81
				*	11690.00	Peak	H	-	-	-68.72	13.59	0.00	51.87	73.98	-22.11
					17535.00	Peak	H	-	-	-68.28	17.44	0.00	56.16	68.20	-12.04
					23380.00	Peak	H	-	-	-53.23	3.63	-9.54	47.86	68.20	-20.34
					29225.00	Peak	H	-	-	-56.11	5.18	-9.54	46.53	68.20	-21.67
					35070.00	Peak	H	-	-	-55.61	7.59	-9.54	49.44	68.20	-18.76
		173	5865	*	11730.00	Average	H	-	-	-80.57	14.15	0.00	40.58	53.98	-13.40
				*	11730.00	Peak	H	-	-	-68.97	14.15	0.00	52.18	73.98	-21.80
					17595.00	Peak	H	-	-	-68.41	17.24	0.00	55.83	68.20	-12.37
					23460.00	Peak	H	-	-	-54.16	3.73	-9.54	47.03	68.20	-21.17
					29325.00	Peak	H	-	-	-56.07	5.43	-9.54	46.82	68.20	-21.38
					35190.00	Peak	H	-	-	-55.32	7.73	-9.54	49.88	68.20	-18.32
		177	5885	*	11770.00	Average	H	-	-	-80.35	13.95	0.00	40.60	53.98	-13.38
				*	11770.00	Peak	H	-	-	-68.42	13.95	0.00	52.53	73.98	-21.45
					17655.00	Peak	H	-	-	-68.53	16.96	0.00	55.43	68.20	-12.77
					23540.00	Peak	H	-	-	-54.91	3.78	-9.54	46.34	68.20	-21.86
					29425.00	Peak	H	-	-	-56.13	5.46	-9.54	46.79	68.20	-21.41
					35310.00	Peak	H	-	-	-54.40	7.92	-9.54	50.97	68.20	-17.23

Table 7-35. Radiated Measurements MIMO

FCC ID: C3K2085	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2311170118-09.C3K	Test Dates: 01/03/2024 - 03/18/2024	EUT Type: Portable Computing Device	Page 134 of 155



MIMO Radiated Spurious Emission Measurements

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6Mbps
 Distance of Measurements: 1 & 3 Meters


Mode	Antenna	UNII Band	Channel	Test Channel Freq. [MHz]	Restricted	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]	
802.11a	MIMO	1	40	5200		6240.00	Peak	V	109	222	-59.10	8.09	55.99	68.20	-12.21	
					*	7280.00	Average	V	117	120	-66.90	9.12	49.22	53.98	-4.76	
					*	7280.00	Peak	V	117	120	-57.24	9.12	58.88	73.98	-15.10	
		2A	56	5280		6336.00	Peak	V	114	220	-60.11	8.64	55.53	68.20	-12.67	
					*	7392.00	Average	V	114	125	-71.15	9.84	45.69	53.98	-8.29	
					*	7392.00	Peak	V	114	125	-61.19	9.84	55.65	73.98	-18.33	
		2C	100	5500		6600.00	Peak	V	115	125	-59.23	7.95	55.72	68.20	-12.48	
						6720.00	Peak	V	118	128	-58.05	7.98	56.93	68.20	-11.27	
			110	5600	*	7840.00	Average	V	109	223	-73.84	8.75	41.91	53.98	-12.07	
					*	7840.00	Peak	V	109	223	-62.82	8.75	52.93	73.98	-21.05	
			3	157	5785		6942.00	Peak	V	123	230	-62.84	8.16	52.32	68.20	-15.88
			4	173	5865		7038.00	Peak	V	116	216	-65.85	8.58	49.73	68.20	-18.47

Table 7-36. Radiated Measurements MIMO


FCC ID: C3K2085	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2311170118-09.C3K	Test Dates: 01/03/2024 - 03/18/2024	EUT Type: Portable Computing Device	Page 135 of 155

7.6.2 MIMO Radiated Band Edge Measurements (20MHz BW)

Worst Case Mode:	802.11be
Worst Case Transfer Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	5180MHz
Channel:	36




Plot 7-187. Radiated Lower Band Edge Plot MIMO (Average – UNII Band 1)




Plot 7-188. Radiated Lower Band Edge Plot MIMO (Peak – UNII Band 1)

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	5320MHz
Channel:	64



Plot 7-189. Radiated Upper Band Edge Plot MIMO (Average – UNII Band 2A)




Plot 7-190. Radiated Upper Band Edge Plot MIMO (Peak – UNII Band 2A)


FCC ID: C3K2085	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2311170118-09.C3K	Test Dates: 01/03/2024 - 03/18/2024	EUT Type: Portable Computing Device	Page 136 of 155



Worst Case Mode: 802.11ax
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5500MHz
 Channel: 100




Plot 7-191. Radiated Lower Band Edge Plot MIMO (Average – UNII Band 2C)



Plot 7-192. Radiated Lower Band Edge Plot MIMO (Peak – UNII Band 2C)

Worst Case Mode: 802.11be
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5825MHz
 Channel: 165




Plot 7-193. Radiated Upper Band Edge Plot MIMO (Peak – UNII Band 3)

FCC ID: C3K2085	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2311170118-09.C3K	Test Dates: 01/03/2024 - 03/18/2024	EUT Type: Portable Computing Device	Page 137 of 155




Worst Case Mode: 802.11ax
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5845MHz
 Channel: 169




Plot 7-194. Radiated Lower Band Edge Plot MIMO (Peak – UNII Band 4)

Worst Case Mode: 802.11ax
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5885MHz
 Channel: 177



Plot 7-195. Radiated Upper Band Edge Plot MIMO (Average – UNII Band 4)




Plot 7-196. Radiated Upper Band Edge Plot MIMO (Peak – UNII Band 4)


FCC ID: C3K2085	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2311170118-09.C3K	Test Dates: 01/03/2024 - 03/18/2024	EUT Type: Portable Computing Device	Page 138 of 155

7.6.3 MIMO Radiated Band Edge Measurements (40MHz BW)

Worst Case Mode:	802.11be
Worst Case Transfer Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	5190MHz
Channel:	38




Plot 7-197. Radiated Lower Band Edge Plot MIMO (Average – UNII Band 1)




Plot 7-198. Radiated Lower Band Edge Plot MIMO (Peak – UNII Band 1)

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	5310MHz
Channel:	62




Plot 7-199. Radiated Upper Band Edge Plot MIMO (Average – UNII Band 2A)




Plot 7-200. Radiated Upper Band Edge Plot MIMO (Peak – UNII Band 2A)

FCC ID: C3K2085	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2311170118-09.C3K	Test Dates: 01/03/2024 - 03/18/2024	EUT Type: Portable Computing Device	Page 139 of 155

Worst Case Mode: 802.11ax
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5510MHz
 Channel: 102




Plot 7-201. Radiated Lower Band Edge Plot MIMO (Average – UNII Band 2C)



Plot 7-202. Radiated Lower Band Edge Plot MIMO (Peak – UNII Band 2C)


Worst Case Mode: 802.11n
 Worst Case Transfer Rate: MCS8
 Distance of Measurements: 3 Meters
 Operating Frequency: 5795MHz
 Channel: 159



Plot 7-203. Radiated Upper Band Edge Plot MIMO (Peak – UNII Band 3)


FCC ID: C3K2085	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2311170118-09.C3K	Test Dates: 01/03/2024 - 03/18/2024	EUT Type: Portable Computing Device	Page 140 of 155

Worst Case Mode: 802.11ac
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5835MHz
 Channel: 167




Plot 7-204. Radiated Lower Band Edge Plot MIMO (Peak – UNII Band 4)

Worst Case Mode: 802.11ax
 Worst Case Transfer Rate: MCS8
 Distance of Measurements: 3 Meters
 Operating Frequency: 5875MHz
 Channel: 175



Plot 7-205. Radiated Upper Band Edge Plot MIMO (Average – UNII Band 4)




Plot 7-206. Radiated Upper Band Edge Plot MIMO (Peak – UNII Band 4)


FCC ID: C3K2085	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2311170118-09.C3K	Test Dates: 01/03/2024 - 03/18/2024	EUT Type: Portable Computing Device	Page 141 of 155

7.6.4 MIMO Radiated Band Edge Measurements (80MHz BW)

Worst Case Mode:	802.11ac
Worst Case Transfer Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	5210MHz
Channel:	42




Plot 7-207. Radiated Lower Band Edge Plot MIMO (Average – UNII Band 1)




Plot 7-208. Radiated Lower Band Edge Plot MIMO (Peak – UNII Band 1)

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	5290MHz
Channel:	58



Plot 7-209. Radiated Upper Band Edge Plot MIMO (Average – UNII Band 2A)



Plot 7-210. Radiated Upper Band Edge Plot MIMO (Peak – UNII Band 2A)

FCC ID: C3K2085	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2311170118-09.C3K	Test Dates: 01/03/2024 - 03/18/2024	EUT Type: Portable Computing Device	Page 142 of 155