



EMISSION TEST REPORT

Test report file No. : **01-IST-080/FB** Date of issue : July. 20, 2001.
Model / Type No. : L510B1
Kind of product : 15" LCD Monitor
Applicant : Daewoo Electronics Co., Ltd. Display Business Division
Manufacturer : Daewoo Electronics Co., Ltd. Display Business Division
Address : 543, Dangjung-Dong, Kunpo-City, Kyunggi-Do, Korea.

Test result according to the regulation(s)

Positive Negative

at page 3.

This test report with appendix consists of 14 pages.

It is not allowed to copy this report even partly without the allowance of the Test Laboratory.

This equipment derived from the basic model L510B (FCC ID: C5F7NFCML510B) that has been shown to be capable of continued compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.4-1992.

DIRECTORY

A) Documentation.		Page
Directory		<u>2</u>
Test regulations		<u>3</u>
Environmental Conditions		<u>3</u>
Test Conditions		<u>4 ~ 5</u>
Equipment under Test		<u>6</u>
Test Result		<u>7</u>
Test-setup (Figures)		<u>8</u>
Summary		<u>14</u>
B) Test Data.		
Conducted emissions (Mains)	: 450 kHz - 30 MHz	<u>9 ~ 11</u>
Radiated emissions	: 30 MHz – 1 GHz	<u>12 ~ 13</u>

C) Appendix

TEST REGULATIONS

The tests were performed according to the following regulations ;

- - FCC Part 15, Subpart B (Unintentional Radiators, Class B)

Information of Test Laboratory

IST EMC Lab.

San 21-8 Goan-Ri, Baekam-Myun, Yongin-Si, Kyunggi-Do, Korea

International - Tel : 82-31 - 333 - 4093. Fax : 82-31 - 333 - 4094.

Domestic - Tel : 031 - 333 - 4093. Fax : 031 - 333 - 4094.

ENVIRONMENTAL CONDITIONS

Temperature	<u>27</u>
Humidity	<u>48</u> %
Atmospheric pressure	<u>1000</u> mbar

TEST CONDITIONS

The measurement of the conducted emissions (Interference voltage) was performed in a shielded room.

Test location :

- Shielded room. No.1

 - Compact chamber 2

Used testing instruments :

<u>Name</u>	<u>Type</u>	<u>Manufacturer</u>	<u>Calibration. Date</u>	<u>Serial Number</u>
■ ESH 3	Test Receiver	Rohde & Schwarz	Jun. 11, 2001	861742/018
■ 3725/2	LISN	EMCO	Jul. 13, 2001	9102-1788
■ 3825/2	LISN	EMCO	Jul. 13, 2001	9103-1788
■ ESH 3-Z2	Pulse Limiter	Rohde & Schwarz	Jul. 13, 2001	357.8810.52

Test - accessories :

<u>Type</u>	<u>Manufacturer</u>
■ Aneroid Barometer	Sato
■ Hygrometer	Sato

Measurement Procedures :

Conducted emissions measurements were made in accordance with ANSI C-63.4-1992, "Method of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz". The measurement were performed over the frequency range of 0.45MHz to 30MHz using a 50Ω/ 50uH LISN as the input transducer to an EMI/Field Intensity Meter. The measurements were made with the detector set for "Peak" amplitude within an IF bandwidth of 10kHz or for "quasi-peak" within a bandwidth of 9kHz.

All used test-instruments as well as the test-accessories are calibrated regularly.

Test engineer :



B. K. Bae. / Research Engineer

IST EMC Lab.

The **measurement of the radiated emissions (Electric field)** in the frequency range from 30 MHz to 1GHz was performed in horizontal and vertical antenna polarization at a open-site which meet the site attenuation requirement of ANSI C63.4-1992 and a test distance of :

- - Open-site 1
- - 3 meters
- - Compact chamber
- - 10 meters

Used testing instruments :

<u>Name</u>	<u>Type</u>	<u>Manufacturer</u>	<u>Calibration. Date</u>	<u>Serial Number</u>
■ ESVP	Test Receiver	Rohde & Schwarz	Jun. 12, 2001	861744/004
■ VULB 9160	Antenna	Schwarzbeck	Jun. 04, 2001	3048

Test - accessories :

Type	Manufacturer
■ Aneroid Barometer	Sato
■ Hygrometer	Sato

Measurement procedures

Radiated measurements were in accordance with ANSI C63.4-1992 “Method of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz”. The measurements were performed over the frequency range of 30MHz to 1GHz using antenna as the input transducer to a EMI/Field Intensity Meter. The measurements were made with the detector set for “quasi-peak” within a bandwidth of 120kHz.

All used test-instruments as well as the test-accessories are calibrated regularly.

Test engineer :



B. K, Bae. / Research Engineer

IST EMC Lab.

EQUIPMENT UNDER TEST

Equipment Description

LCD Type	- 15.0" viewable, Amorphous TFT LCD
	- Dot pitch : 0.297mm
Resolution	- 1024 X 768, 75Hz
Scanning Frequency	- Horizontal: 30~62kHz, Vertical: 50~75Hz
Input Signal	- Video : RGB Analog (0.7Vp-p, 75 \bar{U})
	Sync : H/V Separate(TTL)
	- On : 28 W
Power Saving	Suspend/stand-by : 5 W
	- Off : 5W
Weight	- Net 4.6 Kg, Gross 6.1Kg
Active Display Area	- 304.1mm X 228.1mm
Dimension	- 487mm X 250mm X 465mm
Power Rating	- 100~240Vac, 50/60Hz (input)
	- Universal Power

Operation - mode of the E.U.T. :

The equipment under test was operated during the measurement under following conditions :

- Standby.
- Test program (H – Pattern) : Scrolling “H” characters under MS Windows98
- Test program (customer specific)

Configuration of the equipment under test :

Following peripheral devices and interface cables were connected during the measurement :

Equipment	Type	Brand	Serial No	FCC ID
PC	Brio BA600/550	HP	SG01603782	DoC
Keyboard	SK-2502C	HP	M000456678	DoC
Printer	A0302384	Northern Telecom	26633S60168	BS16XU2225C-L
Mouse1	M-S48a	HP	LZE01000039	JNZ201213
Mouse2	M-M28	Logitech	LCA53305547	DZL210365

- Unshielded AC power cable : 2.5m
- Shielded monitor's signal cables(Analog) : 1.5m

TEST RESULT

Conducted emissions : 450 kHz - 30 MHz

The requirements are.

KEPT NOT KEPT

Min. limit margin

6.8 dB at 0.599 MHz

Remarks : See test-graph to be attached at pages 9 ~ 11.

Radiated emissions (electric field) 30 MHz - 1000 MHz

The requirements are


KEPT NOT KEPT

Min. limit margin


5.7 dB at 60.3 MHz

Remarks : See test-data at page 12 ~ 13.

**Test Set-Up
(Type : L510B1)**



Picture 1 : Conducted emission 450kHz ~ 30MHz



Picture 2 : Radiated emission 30MHz ~ 1000MHz

Conducted Emission Test Data

Type : L510B1
 Manufacturer : Daewoo Electronics Co., Ltd.
 Operation mode : Scrolling "H" pattern display 1024 X 768, 75Hz
 Date : July 11, 2001

Highest Emissions relative to the limit


Frequency [MHz]	Reading [dB μ V]	Insertion loss [dB]	Phase (L1/N)	Result [dB μ V]	Limit [dB μ V]	Margin [dB]
0.599	40.4	0.8	L1	41.2	48.0	6.8
1.348	37.6	0.8		38.4	48.0	9.6
1.423	36.1	0.8		36.9	48.0	11.1
4.716	36.9	0.8		37.7	48.0	10.3
15.726	34.3	0.8		35.1	48.0	12.9
23.650	35.0	0.8		35.8	48.0	12.2
0.4520	36.5	0.8	N	37.3	48.0	10.7
0.602	38.0	0.8		39.6	48.0	8.4
1.875	33.3	0.8		34.1	48.0	13.9
5.313	35.0	0.8		35.8	48.0	12.2
15.726	35.4	0.8		36.2	48.0	11.8
22.459	31.3	0.8		32.1	48.0	15.9

Cable loss are less than 0.1 dB


*L1 : Live Line

**N : Neutral Line

*** Please refer to data graphs at page 10 ~ 11



MODEL : L51081
100Vac 60Hz Phase : LIVE




MODEL : L51001
120Vac 60Hz Phase : NEUTRAL

Radiation Test Data

Type : L510B1
 Manufacturer : Daewoo Electronics Co., Ltd.
 Operation mode : Scrolling "H" pattern display 1024 X 768, 75Hz
 Test distance : 3 m
 Antenna : VULB9160
 Date : July 12, 2001.

Freq. [MHz]	Reading [dBuV]	Antenna Factor [dB]	Cable Loss [dB]	Angle [deg]	Height [cm]	Polar [H/V]	Result [dBuV]	Limit [dBuV]	Margin [dB]
55.1	17.7	10.9	1.4	188	110	V	30.0	40.0	10.0
63.0	22.0	10.9	1.5	348	151	V	34.4	40.0	5.7
118.2	16.5	9.7	2.0	344	132	V	28.2	43.5	15.3
152.9	10.5	12.2	2.3	354	125	V	25.0	43.5	18.5
197.5	17.5	8.7	2.5	315	122	V	28.7	43.5	14.8
252.0	19.5	10.8	2.8	178	228	H	33.1	46.0	12.9
259.8	21.5	11.2	2.9	177	348	H	35.6	46.0	10.4
291.3	22.0	11.8	3.1	186	241	H	36.9	46.0	9.1
299.2	23.0	11.7	3.2	182	301	H	37.9	46.0	8.1
312.8	20.2	11.7	3.4	13	114	V	35.3	46.0	10.7
333.6	23.2	11.7	3.5	345	121	V	38.4	46.0	7.6
451.8	21.6	14.0	4.5	324	122	V	40.1	46.0	5.9
466.9	21.3	14.3	4.7	350	115	V	40.2	46.0	5.8
472.5	18.8	14.3	4.7	17	132	V	37.7	46.0	8.3
488.2	14.0	14.8	4.8	324	248	H	33.6	46.0	12.4
493.9	15.2	14.8	4.8	177	142	V	34.8	46.0	11.2
496.1	15.5	14.8	4.8	189	133	V	35.1	46.0	10.9
535.5	13.0	15.6	4.7	154	125	V	33.3	46.0	12.8
591.0	11.5	16.8	4.7	174	125	V	33.0	46.0	13.0
600.4	17.5	17.0	4.7	185	325	H	39.2	46.0	6.8

MEASUREMENT OF DISTURBANCE RADIATION



SUMMARY

GENERAL REMARKS :

The equipment is not modified anything, mechanical or circuit to improve EMI status during a measurement and complied the regulation “Part 15 subpart B Class B of CFR 47”

FINAL JUDGMENT :

The requirements according to the technical regulations are

- Kept
- Not kept

The equipment under test does


- Fulfill the general approval requirements mentioned on page 3.
- Not fulfill the general approval requirements mentioned on page 3.

Begin of testing : July 11, 2001

End of testing : July 18, 2001

Reviewed by :

Approved by :



**Joon H. Lee. EMC Manager
IST EMC Lab.**

G. Chung Chief of EMC Lab.