

# TEST REPORT

**Report Number. :** 14507330-E4V2

**Applicant :** SRAM LLC  
1000 W Fulton Market 4<sup>th</sup> Floor  
Chicago, IL 60607, United States

**Model :** 12930

**FCC ID :** C9O-RDMB2

**EUT Description :** Rear Derailleur with BLE, AIREA and ANT+ Radios

**Test Standard(s) :** FCC Part 1 Subpart I  
FCC Part 2 Subpart J

**Date Of Issue:**  
2022-11-10

**Prepared by:**  
UL Verification Services Inc.  
47173 Benicia Street  
Fremont, CA 94538 U.S.A.  
TEL: (510) 319-4000  
FAX: (510) 661-0888



Revision History

<u>Rev.</u>	<u>Issue Date</u>	<u>Revisions</u>	<u>Revised By</u>
V1	2022-11-02	Initial Issue	---
V2	2022-11-10	Updated Section 2	K.Kedida

---

## TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS .....	4
2. TEST METHODOLOGY .....	5
3. REFERENCES .....	5
4. FACILITIES AND ACCREDITATION .....	5
5. DEVICE UNDER TEST.....	5
6. MAXIMUM OUTPUT POWER .....	6
7. STANDALONE SAR TEST EXCLUSION CONSIDERATIONS .....	6
7.1. FCC.....	6

# 1. ATTESTATION OF TEST RESULTS

**COMPANY NAME:** SRAM LLC  
1000 W Fulton Market 4<sup>th</sup> Floor  
Chicago, IL 60607, United States

**EUT DESCRIPTION:** Rear Derailleur with BLE, AIREA and ANT+ Radios

**MODEL:** 12930

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
FCC PART 1 SUBPART I & PART 2 SUBPART J	Complies

UL Verification Services Inc. tested the above equipment in accordance with the requirements set forth in the above standards. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. All samples tested were in good operating condition throughout the entire test program. Measurement Uncertainties are published for informational purposes only and were not taken into account unless noted otherwise.

This document may not be altered or revised in any way unless done so by UL Verification Services Inc. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL Verification Services Inc. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by A2LA, NIST, any agency of the Federal Government, or any agency of the U.S. government.

Approved & Released For  
UL Verification Services Inc. By:



Dan Corona  
Operations Leader  
Consumer Technology Division  
UL Verification Services Inc.

Reviewed By:



Kiya Kedida  
Senior Project Engineer  
Consumer Technology Division  
UL Verification Services Inc.

---

## 2. TEST METHODOLOGY

This report contains data provided by the customer which can impact the validity of results. UL Verification Services Inc. is only responsible for the validity of results after the integration of the data provided by the customer.

All calculations were made in accordance with FCC KDB 447498 D01 v06, KDB 447498 D03 V01.

## 3. REFERENCES

All measurements were made as documented in test report UL Verification Services Inc. Document 14507330-E1 & 14507330-E2 for operation in the 2.4 GHz band and UL Verification Services Inc.

Output power, Duty cycle and Antenna gain data is excerpted from the applicable test reports or client declarations.

## 4. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 47173 and 47658 Kato Road, Fremont, California, USA.

UL Verification Services Inc. is accredited by A2LA, Certificate Number #0751.05, for all testing performed within the scope of this report.

## 5. DEVICE UNDER TEST

The EUT is an Rear Derailleur with BLE and AIREA Radios, BLE operating in the frequency range of 2402 to 2480MHz and AIREA operating in the frequency range of 2405 to 2475MHz .

## 6. MAXIMUM OUTPUT POWER

The maximum output power of the device is declared as the following:

BLE = Power: 7dBm; Antenna Gain: 0 dBi

AIREA = Power: 7dBm; Antenna Gain: 0 dBi

The antenna(s) gain and type, as provided by the manufacturer' are as follows:

The radio utilizes a trace on ceramic chip antenna.

## 7. STANDALONE SAR TEST EXCLUSION CONSIDERATIONS

### 7.1. FCC

SAR test exclusion in accordance with KDB 447498 D01.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ , for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where

- $f_{(\text{GHz})}$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

This test exclusion is applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.

**SAR Exclusion Calculation Table for Portable Devices (Separation distance  $< 50$ mm)**

Tx	Frequency (MHz)	Max Output power		Duty Cycle	Max Output Power with Duty factor correction (mW)	Separation distances (mm)	Calculated Threshold Value
		dBm	mW				
BLE	2402	7.00	5.00	100%	5.00	5	1.5
AIREA	2405	7.00	5.00	100%	5.00	5	1.6

### Conclusion:

The device operates with a maximum Duty Cycle of 100%. The Calculated Threshold with duty cycle applied is  $\leq 3$  for 1-g SAR and  $\leq 7$  for 10-g extremity SAR; therefore, this device qualifies for Standalone SAR test exclusion.

**END OF REPORT**