

Sub-part
2.983(e): TEST AND MEASUREMENT DATA

All tests and measurement data shown were performed in accordance with FCC Rules and Regulations, Volume II; Part 2, Sub-part J, Sections 2.981, 2.983, 2.985, 2.987, 2.989, 2.991, 2.993, 2.995, 2.997, 2.999 and the following individual Parts:

- ____ 21 - Domestic Public Fixed Radio Services
- 22 - Public Mobile Services
- ____ 22 Subpart H - Cellular Radiotelephone Service
- ____ 22.901(d) - Alternative technologies and auxiliary services
- ____ 23 - International Fixed Public Radiocommunication services
- ____ 24 - Personal Communications Services
- 74 Subpart H - Low Power Auxiliary Stations
- ____ 80 - Stations in the Maritime Services
- ____ 80 Subpart E - General Technical Standards
- ____ 80 Subpart F - Equipment Authorization for Compulsory Ships
- ____ 80 Subpart K - Private Coast Stations and Marine Utility Stations
- ____ 80 Subpart S - Compulsory Radiotelephone Installations for Small Passenger Boats
- ____ 80 Subpart T - Radiotelephone Installation Required for Vessels on the Great Lakes
- ____ 80 Subpart U - Radiotelephone Installations Required by the Bridge-to-Bridge Act
- ____ 80 Subpart V - Emergency Position Indicating Radiobeacons (EPIRB'S)
- ____ 80 Subpart W - Global Maritime Distress and Safety System (GMDSS)
- ____ 80 Subpart X - Voluntary Radio Installations
- ____ 87 - Aviation Services
- 90 - Private Land Mobile Radio Services
- ____ 94 - Private Operational-Fixed Microwave Service
- ____ 95 Subpart A - General Mobile Radio Service (GMRS)
- ____ 95 Subpart C - Radio Control (R/C) Radio Service
- ____ 95 Subpart D - Citizens Band (CB) Radio Service
- ____ 95 Subpart E - Family Radio Service
- ____ 95 Subpart F - Interactive Video and Data Service (IVDS)
- ____ 101 - Fixed Microwave Services

STANDARD TEST CONDITIONS
and
ENGINEERING PRACTICES

Except as noted herein, the following conditions and procedures were observed during the testing:

ROOM TEMPERATURE	= $25 \pm 5^{\circ}\text{C}$
ROOM HUMIDITY	= 20-50%
D.C. SUPPLY VOLTAGE, Vdc	= N/A
A.C. SUPPLY VOLTAGE, Vac	= 120
A.C. SUPPLY FREQUENCY, Hz	= 60

Prior to testing, the EUT was tuned up in accordance with the manufacturer's alignment procedures. All external gain controls were maintained at the position of maximum and/or optimum gain throughout the testing.

Measurement results, unless otherwise noted, are worst case measurements.

PAGE NO. 6. CASTEL0005

NAME OF TEST: Carrier Output Power (Conducted)

SPECIFICATION: FCC: 47 CFR 2.985(a)
IC: RSS-119, Section 6.2

GUIDE: TIA/EIA-603, Paragraph 2.2.1

TEST CONDITIONS: Standard Temperature and Humidity (S. T. & H.)

TEST EQUIPMENT: As per attached page

MEASUREMENT PROCEDURE

1. The EUT was connected to a resistive coaxial attenuator of normal load impedance, and the unmodulated output power was measured by means of an R. F. Power Meter.
2. Measurement accuracy is $\pm 3\%$.

MEASUREMENT RESULTS


<u>NOMINAL, MHZ</u>	<u>R.F. POWER OUTPUT, WATTS</u>
156	5 25

SUPERVISED BY:


MORTON FLOM, P. Eng.

TRANSMITTER POWER CONDUCTED MEASUREMENTS

TEST 1: R. F. POWER OUTPUT
TEST 2: FREQUENCY STABILITY



(1) COAXIAL ATTENUATOR

NARDA 766-10
SIERRA 661A-30
BIRD 8329 (30 dB)

X

(2) POWER METERS

HP 435A
HP 436A
HP 8901A POWER MODE

X
X

(3) FREQUENCY COUNTER

HP 5383A
HP 5334B
HP 8901A FREQUENCY MODE

X
X

PAGE NO.

8.

CASTEL0005

NAME OF TEST: Unwanted Emissions (Transmitter Conducted)

SPECIFICATION: FCC: 47 CFR 2.991
IC: RSS-119, Section 6.3

GUIDE: TIA/EIA-603, Paragraph 2.2.13

TEST CONDITIONS: S. T. & H.

TEST EQUIPMENT: As per attached page

MEASUREMENT PROCEDURE

1. The emissions were measured for the worst case as follows:

(a): within a band of frequencies defined by the carrier frequency plus and minus one channel.

(b): from the lowest frequency generated in the EUT and to at least the 10th harmonic of the carrier frequency, or 40 GHz, whichever is lower.

2. The magnitude of spurious emissions which are attenuated more than 20 dB below the permissible value need not be specified.

3. MEASUREMENT RESULTS: ATTACHED FOR WORST CASE

FREQUENCY OF CARRIER, MHz = 156

SPECTRUM SEARCHED, GHz = 0 to $10 \times f_c$

MAXIMUM RESPONSE, Hz = 2510

ALL OTHER EMISSIONS = ≥ 20 dB BELOW LIMIT


LIMIT, dBc: $-(43 + 10 \log P_0)$ = -50 (5 Watts)
-57 (25 Watts)

SUPERVISED BY:


MORTON FLOM, P. Eng.

TRANSMITTER SPURIOUS EMISSION

TEST A. OCCUPIED BANDWIDTH (IN-BAND SPURIOUS)
TEST B. OUT-OF-BAND SPURIOUS

(1) AUDIO OSCILLATOR/GENERATOR

HP 204D	—
HP 8903A	—
HP 3312A	x
	x

(2) COAXIAL ATTENUATOR

NARDA 766-10	—
SIERRA 661A-30	x
BIRD 8329 (30 dB)	x
	—

(3) FILTERS; NOTCH, HP, LP, BP

CIRQTEL FHT	—
EAGLE TNF-1	x
PHELPS DODGE PD-495-8	—
	—

(4) SPECTRUM ANALYZER

HP 8566B	—
HP 8563E	x
	—

(5) SCOPE

HP 1741A	—
HP 181T	—
TEK 935	—
HP 54502A	—
	—

PAGE NO.

10.1.

CASTEL0005

G87H006

TRANSMITTER SPURIOUS EMISSIONS (CONDUCTED)

POWER: LOW

FREQUENCY TUNED, MHz	FREQUENCY EMISSION, MHz	LEVEL, dBm	LEVEL, dBc	LEVEL, μW
156.000	312.297	-32.6	-69.5	1
156.000	468.042	-32.7	-69.6	1
156.000	623.834	-33.0	-69.9	1
156.000	779.632	-31.8	-68.7	1
156.000	936.091	-32.6	-69.5	1
156.000	1092.390	-32.0	-68.9	1
156.000	1247.857	-32.5	-69.4	1
156.000	1403.909	-32.5	-69.4	1
156.000	1560.079	-31.7	-68.6	1
156.000	1715.580	-30.8	-67.7	1
156.000	1872.327	-31.9	-68.8	1
156.000	2028.312	-32.5	-69.4	1
156.000	2183.637	-31.1	-68.0	1
156.000	2340.034	-30.5	-67.4	1

PAGE NO.

10.2.

CASTEL0005

G87H007

TRANSMITTER SPURIOUS EMISSIONS (CONDUCTED)

POWER: HIGH

FREQUENCY TUNED, MHz	FREQUENCY EMISSION, MHz	LEVEL, dBm	LEVEL, dBc	LEVEL, μW
156.000	312.317	-32.2	-76.1	1
156.000	468.336	-32.9	-76.8	1
156.000	624.498	-33.0	-76.9	1
156.000	779.568	-31.4	-75.3	1
156.000	936.453	-32.6	-76.5	1
156.000	1091.581	-32.6	-76.5	1
156.000	1247.708	-32.5	-76.4	1
156.000	1404.448	-32.0	-75.9	1
156.000	1559.881	-31.9	-75.8	1
156.000	1716.392	-31.0	-74.9	1
156.000	1871.738	-30.7	-74.6	1
156.000	2028.187	-31.4	-75.3	1
156.000	2183.917	-31.2	-75.1	1
156.000	2340.371	-30.0	-73.9	1

PAGE NO. 11.1. CASTEL0005

NAME OF TEST: Field Strength of Spurious Radiation

SPECIFICATION: FCC: 47 CFR 2.993(a)
IC: N/A

GUIDE: TIA/EIA-603, Section 2.2.12

TEST CONDITIONS: S. T. & H.

TEST EQUIPMENT: AS PER ATTACHED PAGE

MEASUREMENT PROCEDURE

1. A description of the measurement facilities was filed with the FCC and was found to be in compliance with the requirements of Section 15.38, by letter from the FCC dated March 3, 1997, FILE 31040/SIT. All pertinent changes will be reported to the Commission by up-date prior to March 2000.
2. At first, in order to locate all spurious frequencies and approximate amplitudes, and to determine proper equipment functioning, the test sample was set up at a distance of three meters from the test instrument. Valid spurious signals were determined by switching the power on and off.
3. In the field, the test sample was placed on a wooden turntable above ground at three (or thirty) meters away from the search antenna. The test sample was connected to an R.F. Wattmeter and a 50 ohm dummy load, and adjusted to its rated output. In order to obtain the maximum response at each spurious frequency, the turntable was rotated. Also, the Search Antennas were raised and lowered vertically, and all cables were oriented. Excess power lead was coiled near the power supply.
4. A signal generator, connected with a non-radiating cable to a vertically polarized half-wave antenna (for each frequency involved) was substituted for the transmitter. The Search Antenna was raised and lowered to obtain maximum indicated.
5. The signal generator output was adjusted until a signal level indication equal to that from the transmitter was obtained.
6. Steps 4 and 5 were repeated, using a horizontally polarized half-wave antenna. The higher of the two observations was noted.

PAGE NO.

11.2.

CASTEL0005

NAME OF TEST: Field Strength of Spurious Radiation

SPECIFICATION: FCC: 47 CFR 2.993(a)
IC: N/A

MEASUREMENT PROCEDURE (CONT.)

7. Power into the half-wave antenna was calculated from the characteristic impedance of the line, and the voltage output from the signal generator.
8. The level of each spurious radiation with reference to the transmitter power in dB, was calculated from:


$$\text{SPURIOUS LEVEL, dB} = 10 \log \frac{\text{Calculated Spurious Power}}{\text{Tx Power (Wattmeter)}} \quad [\text{from para. 7}]$$

9. The worst case for all channels is shown.

10. Measurement summary:

FREQUENCY OF CARRIER, MHz	= 156
SPECTRUM SEARCHED, GHz	= 0 to $10 \times F_C$
ALL OTHER EMISSIONS	= ≥ 20 dB BELOW LIMIT
LIMIT, dBc	= -57 (25 Watts) -50 (5 Watts)

11. Measurement results: ATTACHED FOR WORST CASE

RADIATED TEST SETUP

NOTES:

- (a) Search Antenna - Rotatable on boom.
- (b) Non-metallic boom.
- (c) Non-metallic mast.
- (d) Adjustable horizontally.
- (e) Equipment Under Test.
- (f) Turntable.
- (g) Boom adjustable in height.
- (h) External control cables routed horizontally at least one wavelength.
- (i) Rotatable.
- (j) Cables routed through hollow turntable center.
- (k) 30 cm or less.
- (l) External power source.
- (m) 10 cm diameter coil of excess cable.
- (n) 25 cm (V), 1 m-7 m (V, H).
- (o) 25 cm from bottom end of 'V', 1 m normally.
- (p) Calibrated Cable at least 10 m in length.
- (q) Amplifier (optional).
- (r) Spectrum Analyzer.

PAGE NO.

13.

CASTEL0005

TRANSMITTER SPURIOUS EMISSIONS (RADIATED FIELD STRENGTH)

ALL OTHER EMISSIONS $\approx \geq 20$ dB BELOW LIMIT

EMISSION, MHz/HARMONIC	SPURIOUS LEVEL BELOW		
	LO	CARRIER, dBc	Hi

2nd to 10th	<-65	<-70
-------------	------	------

SUPERVISED BY:


MORTON FLOM, P. Eng.

PAGE NO.

14.

CASTEL0005

NAME OF TEST: Emission Masks (Occupied Bandwidth)

SPECIFICATION: FCC: 47 CFR 2.989(c)(1)
IC: RSS-119, Section 6.4

GUIDE: TIA/EIA-603, Paragraph 2.2.11

TEST CONDITIONS: S. T. & H.

TEST EQUIPMENT: As per previous page

MEASUREMENT PROCEDURE


1. The EUT and test equipment were set up as shown on the following page, with the Spectrum Analyzer connected.
2. For EUTs supporting audio modulation, the audio signal generator was adjusted to the frequency of maximum response and with output level set for ± 2.5 kHz deviation (or 50% modulation). With level constant, the signal level was increased 16 dB.
3. For EUTs supporting digital modulation, the digital modulation mode was operated to its maximum extent.
4. The Occupied Bandwidth was measured with the Spectrum Analyzer controls set as shown on the test results.
5. MEASUREMENT RESULTS: ATTACHED

PAGE 15.1.

CASTEL0005

SPECTRUM ANALYZER PRESENTATION
TAIT ELECTRONICS, T836-26-0000 (TX)
1998-JUL-17, 11:14, FRI

POWER: LOW
MODULATION: NONE




PAGE 15.2.

CASTEL0005

SPECTRUM ANALYZER PRESENTATION
TAIT ELECTRONICS, T836-26-0000 (TX)
1998-JUL-17, 11:22, FRI


POWER: LOW
MODULATION: VOICE: 2500 Hz SINE WAVE
MASK: D, VHF/UHF 12.5kHz BW



PAGE 15.3.
SPECTRUM ANALYZER PRESENTATION
TAIT ELECTRONICS, T836-26-0000 (TX)
1998-JUL-17, 11:17, FRI

CASTEL0005

POWER: LOW
MODULATION: VOICE: 2500 Hz SINE WAVE
MASK: B, VHF/UHF 25kHz, w/LPF




PAGE 15.4.

CASTEL0005

SPECTRUM ANALYZER PRESENTATION
TAIT ELECTRONICS, T836-26-0000 (TX)
1998-JUL-17, 11:12, FRI

POWER: HIGH
MODULATION: NONE




PAGE 15.5.

CASTEL0005

SPECTRUM ANALYZER PRESENTATION
TAIT ELECTRONICS, T836-26-0000 (TX)
1998-JUL-17, 11:21, FRI

POWER: HIGH
MODULATION: VOICE: 2500 Hz SINE WAVE
MASK: D, VHF/UHF 12.5kHz BW




PAGE 15.6.

SPECTRUM ANALYZER PRESENTATION
TAIT ELECTRONICS, T836-26-0000 (TX)
1998-JUL-17, 11:17, FRI

CASTEL0005

POWER: HIGH
MODULATION: VOICE: 2500 Hz SINE WAVE
MASK: B, VHF/UHF 25kHz, w/LPF



© 1998 TAIT ELECTRONICS, INC. ALL RIGHTS RESERVED

PAGE NO. 16. CASTEL0005

NAME OF TEST: Transient Frequency Behavior

SPECIFICATION: FCC: 47 CFR 90.214
IC: RSS-119, Section 6.5

GUIDE: TIA/EIA-603, Paragraph 2.2.19

TEST CONDITIONS: S. T. & H.

TEST EQUIPMENT: As per attached page

MEASUREMENT PROCEDURE


1. The EUT was setup as shown on the attached page, following TIA/EIA-603 steps a, b, and c as a *guide*.
2. The transmitter was turned on.
3. Sufficient attenuation was provided so that the transmitter carrier level measured at the output of the combiner was 40 dB below the maximum input level of the test receiver. This level was recorded as step f.
4. The transmitter was turned off.
5. An RF signal generator (1) modulated with a 1 kHz tone at either 25, 12.5, or 6.25 kHz deviation, and set to the same frequency as the assigned transmitter frequency, (2) was adjusted to a level -20 dB below the level recorded for step f, as measured at the output of the combiner. This level was then fixed for the remainder of the test and is recorded at step h.
6. The oscilloscope was setup using TIA/EIA-603 steps j and k as a guide, and to either 10 ms/div (UHF) or 5 ms/div (VHF).
7. The 30 dB attenuator was removed, the transmitter was turned on, and the level of the carrier at the output of the combiner was recorded as step l.
8. The carrier on-time as referenced in TIA/EIA-603 steps m, n, and o was captured and plotted. The carrier off-time as referenced in TIA/EIA-603 steps p, q, r, and s was captured and plotted.

LEVELS MEASURED:

<u>step f</u> , dBm	= -17.5
<u>step h</u> , dBm	= -38.3
<u>step l</u> , dBm	= 12.0

SUPERVISED BY:


MORTON FLOM, P. Eng.

TRANSIENT FREQUENCY BEHAVIOR(1) ATTENUATOR

(NOTE: Removed after 1st step)
30 dB
20 dB
10 dB

KAY VARIABLE

(3) COMBINER

4 x 25 Ω COMBINER

(4) CRYSTAL DETECTOR

HP 8470B

(5) RF SIGNAL GENERATOR

HP 8656A
HP 8920A

(6) MODULATION ANALYZER

HP 8901A

(7) SCOPE


HP 54502A

PAGE 18.1.

CASTEL0005

OSCILLOSCOPE PRESENTATION
TAIT ELECTRONICS, T836-26-0000 (TX)
1998-JUL-17, 12:13, FRI

MODULATION: Ref Gen=12.5 kHz Deviation
REMARK: CARRIER ON TIME



Main	Timebase 10.0 ms/div	Delay/Pos 40.0000 ms	Reference Center	Mode Repetitive
Channel 1	Sensitivity 275 mV/div	Offset 0.00000 V	Probe 1.000 :1	Coupling dc (1M ohm)

Trigger mode : Edge
On Negative Edge Of Chan2
Trigger Level
Chan2 = -25.000 mV (noise reject ON)
Holdoff = 40.000 ns

PAGE 18.2.


OSCILLOSCOPE PRESENTATION

TAIT ELECTRONICS, T836-26-0000 (TX)

1998-JUL-17, 12:05, FRI

MODULATION: Ref Gen=12.5 kHz Deviation

REMARK: CARRIER OFF TIME



Main	Timebase 10.0 ms/div	Delay/Pos -30.0000 ms	Reference Center	Mode Repetitive
Channel 1	Sensitivity 275 mV/div	Offset 0.00000 V	Probe 1.000 : 1	Coupling dc (1M ohm)

Trigger mode : Edges
On Positive Edge Of Chan2
Trigger Level
Chan2 = -600.000 mV (noise reject ON)
Holdoff = 40.000 ns

PAGE 18.3.

CASTEL0005


OSCILLOSCOPE PRESENTATION

TAIT ELECTRONICS, T836-26-0000 (TX)

1998-JUL-17, 12:02, FRI

MODULATION: Ref Gen=25 kHz Deviation

REMARK: CARRIER ON TIME



Main	Timebase 10.0 ms/div	Delay/Pos 40.0000 ms	Reference Center	Mode Repetitive
Channel 1	Sensitivity 275 mV/div	Offset 0.00000 V	Probe 1.000 : 1	Coupling dc (1M ohm)

Trigger mode : Edge
On Negative Edge Of Chan2
Trigger Level
Chan2 = -25.000 mV (noise reject ON)
Holdoff = 40.000 ns

PAGE 18.4.


CASTEL0005

OSCILLOSCOPE PRESENTATION

TAIT ELECTRONICS, T836-26-0000 (TX)

1998-JUL-17, 12:03, FRI

MODULATION: Ref Gen=25 kHz Deviation
REMARK: CARRIER OFF TIME



Main	Timebase 10.0 ms/div	Delay/Pos -30.0000 ms	Reference Center	Mode Repetitive
Channel 1	Sensitivity 275 mV/div	Offset 0.00000 V	Probe 1.000 : 1	Coupling dc (1M ohm)

Trigger mode : Edge
On Positive Edge Of Chan2
Trigger Level
Chan2 = -600.000 mV (noise reject ON)
Holdoff = 40.000 ns

PAGE NO.

19.

CASTEL0005

NAME OF TEST: Audio Low Pass Filter (Voice Input)

SPECIFICATION: FCC: 47 CFR 2.987(a)
IC: RSS-119, Section 6.6

GUIDE: TIA/EIA-603, Paragraph 2.2.15

TEST CONDITIONS: S. T. & H.


TEST EQUIPMENT: As per attached page

MEASUREMENT PROCEDURE

1. The EUT and test equipment were set up such that the audio input was connected at the input to the modulation limiter, and the modulated stage.
2. The audio output was connected at the output to the modulated stage.
3. MEASUREMENT RESULTS: ATTACHED

TRANSMITTER TEST SET-UP

- TEST A. MODULATION CAPABILITY/DISTORTION
TEST B. AUDIO FREQUENCY RESPONSE
TEST C. HUM AND NOISE LEVEL
TEST D. RESPONSE OF LOW PASS FILTER
TEST E. MODULATION LIMITING

(1) AUDIO OSCILLATOR/GENERATOR

HP 204D	—
HP 8903A	—
HP 3312A	X
	X

(2) COAXIAL ATTENUATOR

NARDA 766-10	—
SIERRA 661A-30	X
BIRD 8329 (30 dB)	—
	—

(3) MODULATION ANALYZER

HP 8901A	X
	—

(4) AUDIO ANALYZER

HP 8903A	X
	—


(5) SCOPE

HP 1741A	—
HP 181T	—
TEK 935	—
	—

PAGE 21.

CASTEL0005

FREQUENCY RESPONSE OF AUDIO LOW PASS FILTER
TAIT ELECTRONICS, T836-26-0000 (TX)
17 JUL 1998, 10:25



PEAK AUDIO FREQUENCY, Hz: 2510

SUPERVISED BY:

MORTON FLOM, P. Eng.

PAGE NO. 22. CASTEL0005

NAME OF TEST: Audio Frequency Response

SPECIFICATION: FCC: 47 CFR 2.987(a)
IC: N/A

GUIDE: TIA/EIA-603, Section 2.2.6

TEST CONDITIONS: S. T. & H.


TEST EQUIPMENT: As per previous page

MEASUREMENT PROCEDURE

1. The EUT and test equipment were set up as shown on the following page.
2. The audio signal generator was connected to the audio input circuit/microphone of the EUT.
3. The audio signal input was adjusted to obtain 20% modulation at 1 kHz, and this point was taken as the 0 dB reference level.
4. With input levels held constant and below limiting at all frequencies, the audio signal generator was varied from 100 Hz to 50 kHz.
5. The response in dB relative to 1 kHz was then measured, using the HP 8901A Modulation Analyzer.
6. MEASUREMENT RESULTS: ATTACHED

PAGE 23.

TRANSMITTER AUDIO FREQUENCY RESPONSE
 TAIT ELECTRONICS, T836-26-0000 (TX)
 17 JUL 1998, 10:18



PEAK AUDIO FREQUENCY, Hz: 2510

TABLE VALUES:

FREQUENCY, LEVEL, Hz dB		FREQUENCY, LEVEL, Hz dB		FREQUENCY, LEVEL, Hz dB	
300	-10.2	30000	-30.6		
20000	-30.4	50000	-30.4		

MORTON FЛОM, P. Eng.

SUPERVISED BY:

PAGE NO. 24. CASTEL0005

NAME OF TEST: Modulation Limiting

SPECIFICATION: IC: RSS-119, Section 6.6
FCC: 47 CFR 2.987(b)

GUIDE: TIA/EIA-603, Paragraph 2.2.3

TEST CONDITIONS: S. T. & H.

TEST EQUIPMENT: As per attached page

MEASUREMENT PROCEDURE

1. The signal generator was connected to the input of the EUT as for "Frequency Response of the Modulating Circuit."
2. The modulation response was measured for each of three frequencies (one of which was the frequency of maximum response), and the input voltage was varied and was observed on an HP 8901A Modulation Analyzer.
3. The input level was varied from 30% modulation (± 1.5 kHz deviation) to at least 20 dB higher than the saturation point.
4. Measurements were performed for both negative and positive modulation and the respective results were recorded.
5. MEASUREMENT RESULTS: ATTACHED


PAGE 25.1.

CASTEL0005

MODULATION LIMITING

TAIT ELECTRONICS, T836-26-0000 (TX)

1998-JUL-17, 10:47



REFERENCE DEVIATION, kHz = 1.25

REFERENCE MODULATION, Hz = 1000

PEAKS = POSITIVE

AUDIO AMPLITUDE, mV = 33.43

SUPERVISED BY:

M. FLOM, P. Eng.


MORTON FLOM, P. Eng.

PAGE 25.2.

CASTEL0005

MODULATION LIMITING

TAIT ELECTRONICS, T836-26-0000 (TX)
1998-JUL-17, 10:47



REFERENCE DEVIATION, kHz = 1.25

REFERENCE MODULATION, Hz = 1000

PEAKS = NEGATIVE

AUDIO AMPLITUDE, mV = 33.43

SUPERVISED BY:

MORTON FLOM, P. Eng.


M. Morton F. Eng.

PAGE 25.3.

CASTEL0005

MODULATION LIMITING

TAIT ELECTRONICS, T836-26-0000 (TX)
1998-JUL-17, 10:39



REFERENCE DEVIATION, kHz = 2.5

REFERENCE MODULATION, Hz = 1000

PEAKS = POSITIVE

AUDIO AMPLITUDE, mV = 31.19


SUPERVISED BY:



MORTON FLOM, P. Eng.

PAGE 25.4.
MODULATION LIMITING
TAIT ELECTRONICS, T836-26-0000 (TX)
1998-JUL-17, 10:39

CASTEL0005



REFERENCE DEVIATION, kHz = 2.5

REFERENCE MODULATION, Hz = 1000

PEAKS = NEGATIVE

AUDIO AMPLITUDE, mV = 31.19

SUPERVISED BY:

M. Flom, P. Eng.

MORTON FLOM, P. Eng.

PAGE NO. 26. CASTEL0005

NAME OF TEST: Frequency Stability (Temperature Variation)

SPECIFICATION: FCC: 47 CFR 2.995(a)(1)
IC: RSS-119, Section 7.0

GUIDE: TIA/EIA-602, Section 2.2.2

TEST CONDITIONS: As indicated


TEST EQUIPMENT: As per attached page

MEASUREMENT PROCEDURE

1. The EUT and test equipment were set up as shown on the following page.
2. With all power removed, the temperature was decreased to -30°C and permitted to stabilize for three hours. Power was applied and the maximum change in frequency was noted within one minute.
3. With power OFF, the temperature was raised in 10°C steps. The sample was permitted to stabilize at each step for at least one-half hour. Power was applied and the maximum frequency change was noted within one minute.
4. The temperature tests were performed for the worst case.
5. MEASUREMENT RESULTS: ATTACHED

TRANSMITTER TEST SET-UP

- TEST A. OPERATIONAL STABILITY
 - TEST B. CARRIER FREQUENCY STABILITY
 - TEST C. OPERATIONAL PERFORMANCE STABILITY
 - TEST D. HUMIDITY
 - TEST E. VIBRATION
 - TEST F. ENVIRONMENTAL TEMPERATURE
 - TEST G. FREQUENCY STABILITY: TEMPERATURE VARIATION
 - TEST H. FREQUENCY STABILITY: VOLTAGE VARIATION
-

(1) TEMPERATURE, HUMIDITY, VIBRATION

TENNEY TEMPERATURE CHAMBER	<u>X</u>
WEBER HUMIDITY CHAMBER	<u> </u>
L.A.B. RVH 18-100	<u> </u>

(2) COAXIAL ATTENUATOR

NARDA 766-10	<u> </u>
SIERRA 661A-30	<u>X</u>
BIRD 8329 (30 dB)	<u>X</u>

(3) R.F. POWER

HP 435A POWER METER	<u> </u>
HP 436A POWER METER	<u>X</u>
HP 8901A POWER MODE	<u>X</u>


(4) FREQUENCY COUNTER

HP 5383A	<u> </u>
HP 5334B	<u>X</u>
HP 8901A	<u>X</u>

PAGE 28.

CASTEL0005

TRANSMITTER FREQUENCY STABILITY
TAIT ELECTRONICS, T836-26-0000 (TX)



FREQUENCY OF CARRIER, MHz = 156

LIMIT, ppm = ± 2.5

LIMIT, Hz = 390

SUPERVISED BY:


Morton Flom, P. Eng.

PAGE NO.

29.

CASTEL0005

NAME OF TEST: Frequency Stability (Voltage Variation)

SPECIFICATION: FCC: 47 CFR 2.995 (b)(1)
IC: RSS-119, Section 7.0

GUIDE: TIA/EIA-602, Section 2.2.2

TEST CONDITIONS: As indicated

TEST EQUIPMENT: As per attached page

MEASUREMENT PROCEDURE

1. The EUT was placed in a temperature chamber at $25 \pm 5^{\circ}\text{C}$ and connected as for "Frequency Stability – Temperature Variation" test.
2. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value measured at the input to the EUT.
3. The variation in frequency was measured for the worst case.

MEASUREMENT RESULTS

LIMIT, ppm	= 2.5
LIMIT, Hz	= 390

STV, %	Vac	CHANGE IN FREQUENCY, Hz	
85	102	156.000020	20
100	120	156.000000	0
115	138	155.999970	-30

SUPERVISED BY:


MORTON FLOM, P. Eng.

PAGE NO.

30.

CASTEL0005

NAME OF TEST:

Necessary Bandwidth and Emission Bandwidth

PARAGRAPH:

47 CFR 2.202(g)

MODULATION = 16K0F3E

NECESSARY BANDWIDTH CALCULATION:

MAXIMUM MODULATION (M), kHz	=	3
MAXIMUM DEVIATION (D), kHz	=	5
CONSTANT FACTOR (K)	=	1
NECESSARY BANDWIDTH (B _N), kHz	=	$(2 \times M) + (2 \times D \times K)$
	=	16.0

MODULATION = 11K0F3E

NECESSARY BANDWIDTH CALCULATION:

MAXIMUM MODULATION (M), kHz	=	3
MAXIMUM DEVIATION (D), kHz	=	2.5
CONSTANT FACTOR (K)	=	1
NECESSARY BANDWIDTH (B _N), kHz	=	$(2 \times M) + (2 \times D \times K)$
	=	11.0

SUPERVISED BY:


MORTON FLOM, P. Eng.

TESTIMONIAL
AND
STATEMENT OF CERTIFICATION

CASTEL0005

THIS IS TO CERTIFY:

1. THAT the application was prepared either by, or under the direct supervision of, the undersigned.
2. THAT the technical data supplied with the application was taken under my direction and supervision.
3. THAT the data was obtained on representative units, randomly selected.
4. THAT, to the best of my knowledge and belief, the facts set forth in the application and accompanying technical data are true and correct.

CERTIFYING ENGINEER:


MORTON FLOM, P. Eng.

STATEMENT OF QUALIFICATIONS

EDUCATION:

1. B. ENG. in ENGINEERING PHYSICS, 1949, McGill University, Montreal, Canada.
2. Post Graduate Studies, McGill University & Sir George Williams University, Montreal.

PROFESSIONAL AFFILIATIONS:

1. ARIZONA SOCIETY OF PROFESSIONAL ENGINEERS (NSPE), #026 031 821.
2. ORDER OF ENGINEERS (QUEBEC) 1949. #4534.
3. ASSOCIATION OF PROFESSIONAL ENGINEERS, GEOPHYSICISTS & GEOLOGISTS OF ALBERTA #5916.
4. REGISTERED ENGINEERING CONSULTANT - GOVERNMENT OF CANADA, DEPARTMENT OF COMMUNICATIONS. Radio Equipment Approvals.
5. IEEE, Lifetime Member No. 0417204 (member since 1947).

EXPERIENCE:

1. Research/Development/Senior Project Engineer, R.C.A. LIMITED (4 years).
2. Owner/Chief Engineer of Electronics. Design/Manufacturing & Cable TV Companies (10 years).
3. CONSULTING ENGINEER (over 25 years).



MORTON FLOM, P. Eng.

TEST INSTRUMENTATION LIST

<u>All equipment calibrated within last 90 days</u>	<u>ELECTRONIC COUNTER</u> HP 5383A; HP 5334B	<u>PHANTOM</u> M.F.A. Labs Left and Right human head	<u>TEST SET</u> Semi-Automatic: HP 8953A; HP 8954A Interface: Computer / Controller; P.S. Programmer; HP 59501A; RF Communications: HP 8920A
<u>ADAPTER</u> HP X281 (Coaxial waveguide); HP S281; HP 85659 (Quasi peak)	<u>FILTER</u> Ciratech FHT/7-50-57/50-1A/1B (HP); Jerrold TLB-1; THB-1, Piezo 5064; Eagle TNF-1 Series, Krohn-Hite 3202; Phelps-Dodge #PD-495-8; Newtöne #PD6000 Line Protector; 870-890 MHz (Lab Design); 900 MHz (Lab Design); Solar High-Pass s/n 882029	<u>PLOTTER</u> HP 7470; HP 7475A	<u>TRANSFORMERS</u> Audio Isolation: Solar 6220-1A; Impedance: HP 11694A; Isolation: Solar 7032-1; Matching: Solar 7033-1
<u>AMPLIFIER</u> Pre-amp. HP 10885A (2-1300 MHz); HP 8447D, HP 8447E, HP 8449A		<u>POWER METER</u> AF GR 1840A; HP 435A with 8481A & 8482H Power Sensors; HP 436A; HP 8901A	<u>TRANSMISSION & NOISE MEASURING SET</u> HP 3555B
<u>ANTENNA</u> See end		<u>POWER SUPPLY</u> HP 6286A; Heathkit 1P 2711; 1P 5220; Honda EM400 (portable gas gen.); HP 6012	<u>VIBRATION CHAMBER</u> Unholtz-Dickie T 500; Unholtz-Dickie T 4000
<u>ATTENUATOR</u> Kay 432D; Power, Sierra 661A-30; Narda 76610; Narda 4779-3, -6, -10 dB	<u>FREQ. DEV. METER</u> HP 8901A	<u>PRINTER</u> Brother HL-8; Brother HL-10V; HP DeskJet 640C	<u>VOLTMETER</u> HP 410C; HP 3478A
<u>AUDIO OSCILLATOR</u> HP 204D; AIEC DTC-1; Motorola S-1333B; HP 3312A; HP 8903A	<u>FREQ. DOUBLER</u> HP 11721A	<u>R. F. PRESELECTOR</u> HP 85685A	<u>WATTMETER</u> Bird 43, Sierra 174A-2
<u>BATTERY</u> Sears Diehard, Stock #4341	<u>FREQUENCY METER</u> HP 537A; HP 536A	<u>GENERATOR</u> Solar 6550-1 (power sweep); HP 8640B, GAW 1012, HP 8656A (signal); Solar 8282-1 (spike)	<u>ANTENNAS</u> <u>30 - 50 Hz</u> Emco 7603 M-Field; Emco 7604 M-Field <u>20 - 200 MHz</u> Aprel Biconical Model AAB20200 <u>20 - 300 MHz</u> Emco Biconical H-Field <u>25 - 1000 MHz</u> Singer DM-105A; Emco 3121C <u>200 - 1000 MHz</u> Aprel Log Periodic, Model ALP 2001 <u>10 kHz - 30 MHz</u> Emco 3107B, E-Field; Emco 3101B/1, Rod E-Field <u>10 kHz - 32 MHz</u> Singer 94593-1 (Loop) <u>150 kHz - 32 MHz</u> Singer 92197-1 (41") <u>150 kHz - 32 MHz</u> Singer 93049-1 (9') <u>1 - 10 GHz</u> Singer 90794-A Discone <u>1 - 18 GHz</u> Horn: Aprel Model AAH-118 <u>18 - 40 GHz</u> Emco 3116, Horn <u>40 - 60 GHz</u> Horn: HP 11970U, HP 11971U, HP 11975A (Lo Drive Amplifier) <u>50 - 75 GHz</u> Mixer, HP 11970V, HP 11971V <u>75 - 110 GHz</u> Mixer, HP 11970W
<u>CAMERA</u> Oscilloscope, Tektronix C5A; Polaroid Impulse AF; Kodak DC-50	<u>HUMIDITY CHAMBER</u> Embeam Co FW30; Bowser 0	<u>RADIATION METER</u> Narda 8717 w/8010 Amp, 80218 and 8760 probes	
<u>CAPACITOR</u> Feed-Thru, 10 μ F, Solar 6512-106R; Solar 7525-1	<u>LIMITER, R.F.</u> HP 11867A; HP 11693A; HP 10509A	<u>RESISTOR, PRECISION</u> Solar 7144-1.0, 7144-10.0; Solar 8525-1	
<u>CLOSE FIELD PROBE</u> HP 11940A, 11941A, HP 11945A	<u>LISN</u> Singer 91221-1; Ailtech 94641-1 (50 μ H)	<u>SCALE</u> Weigh-Tronix 3632T-50	
<u>COMPUTER</u> HP 332; HP Vectra 486/25VL; Various PC COmpatables	<u>LOAD, POWER</u> Telewave TLW-25; Bird 8329	<u>SCANNER</u> HP 9190A Scanjet	
<u>CONVERTOR, Down</u> HP 117 108	<u>MILLIAMMETER</u> HP 4288	<u>SCREEN ROOM</u> Lindgren 22-2/2-0	
<u>COUPLER</u> Narda 1080, Waveguide; HP S750E (Cross guide); Waveline 274/40; Solar 7415-3; Solar 7835-891 & -896	<u>MIXER</u> HP 10514A; Mini-Circuits TAK-1H	<u>SIGNAL LEVEL METER</u> Jerrold 704B	
<u>CURRENT PROBE</u> Solar 6741-1	<u>OPEN FIELD SITE</u> As filed with FCC & IC and kept up-dated.	<u>SIGNAL SAMPLER</u> R. F. Bird 4273-030, 4275-030	
<u>DETECTOR</u> HP 8470B	<u>TURNTABLES:</u> Up to 2000# capacity	<u>SINAD/VOLTMETER</u> Helper Sinadder	
<u>DIGITAL MULTIMETER</u> HP 3476A w/H.F. Probe; Fluke 8030A-01; HP 3478A	<u>GROUND SCREEN:</u> Complies with docket 80-284	<u>SPECTRUM ANALYZER</u> HP 8558B, 8557; HP 8563E; HP 853A; HP 8566B/8568B	
<u>DISTORTION ANALYZER</u> HP 334A; HP 8903A	<u>ANTENNA MAST:</u> Complies as above	<u>TEMPERATURE CHAMBER</u> Tenney, Jr	
	<u>OSCILLOSCOPE</u> HP 1741A; HP 181T; Tektronix T935; HP 54502A	<u>TEMPERATURE PROBE</u> Fluke 80T-150C	
		<u>TERMINATION</u> Narda 320B Waveguide, Waveline #281	