

KTL Test Report: 0R02733

Applicant: Tait Electronics Ltd.
558 Wairakei Road
Burnside
Christchurch, New Zealand

**Equipment Under Test:
(E.U.T.)** VHF Paging Transmitter
T836-26-1010 Standard
T836-26-1012 Externally Referenced

FCC ID: CASTEL0047

In Accordance With: **FCC Part 22**
FCC Part 90

Tested By: KTL Ottawa Inc.
3325 River Road, R.R. 5
Ottawa, Ontario K1V 1H2

Authorized By:

G. Westwell, Technologist

Date:

Total Number of Pages: 24

*EQUIPMENT: VHF Paging Transmitter, T836-26-1010 Standard
And T836-26-1012 Externally Referenced
FCC ID: CASTEL0047*

Table of Contents

Section 1.	Summary of Test Results.....	3
Section 2.	General Equipment Specification	5
Section 3.	RF Power Output	6
Section 4.	Occupied Bandwidth.....	7
Section 5.	Spurious Emissions at Antenna Terminals.....	11
Section 6.	Field Strength of Spurious Emissions	12
Section 7.	Frequency Stability	13
Section 8.	Transient Frequency Behaviour	14
Section 9.	Test Equipment List	19
Annex A	Test Diagrams	A1

*EQUIPMENT: VHF Paging Transmitter, T836-26-1010 Standard
And T836-26-1012 Externally Referenced
FCC ID: CASTEL0047*

Section 1. Summary of Test Results

General

All measurements are traceable to national standards.

These tests were conducted on a sample of the equipment for the purpose of demonstrating compliance with FCC Part 22 and FCC Part 90.



New Submission



Production Unit



Class II Permissive Change



Pre-Production Unit



Equipment Code

THIS TEST REPORT RELATES ONLY TO THE ITEM(S) TESTED.

THE FOLLOWING DEVIATIONS FROM, ADDITIONS TO, OR EXCLUSIONS FROM THE TEST SPECIFICATIONS HAVE BEEN MADE.

See " Summary of Test Data".



NVLAP LAB CODE: 100351-0

TESTED BY: _____ DATE: _____
Russell Grant, Wireless Group Manager

KTL Ottawa Inc. authorizes the above named company to reproduce this report provided it is reproduced in its entirety and for use by the company's employees only.

Any use which a third party makes of this report, or any reliance on or decisions to be made based on it, are the responsibility of such third parties. KTL Ottawa Inc. accepts no responsibility for damages, if any, suffered by any third party as a result of decisions made or actions based on this report.

This report applies only to the items tested.

*EQUIPMENT: VHF Paging Transmitter, T836-26-1010 Standard
And T836-26-1012 Externally Referenced
FCC ID: CASTEL0047*

Summary Of Test Data

Name Of Test	Para. No.	Result
RF Power Output	2.1046	Complies
Audio Frequency Response	2.1047	Not Applicable
Audio Low-Pass Filter Response	2.1047	Not Applicable
Modulation Limiting	2.1047	Not Applicable
Occupied Bandwidth	2.1049	Complies
Spurious Emissions at Antenna Terminals	2.1051	Complies
Field Strength of Spurious Emissions	2.1053	Complies
Frequency Stability	2.1055	Complies
Transient Frequency Behavior	—	Complies

Footnotes For N/A's:

Test Conditions:

Indoor Temperature: 23 °C
 Humidity: 50 %

Outdoor Temperature: 25 °C
 Humidity: 65 %

*EQUIPMENT: VHF Paging Transmitter, T836-26-1010 Standard
And T836-26-1012 Externally Referenced
FCC ID: CASTEL0047*

Section 3. RF Power Output

Para. No.: 2.1046

Test Performed By: Russell Grant	Date of Test: August 10, 2000
---	--------------------------------------

Minimum Standard: ± 1 dB

Test Results: Complies. The RF power output is within 0.7 dB of the manufacturer's rating.

Measurement Data:

Measured (W)	Rated (W)
29.5	25.0

*EQUIPMENT: VHF Paging Transmitter, T836-26-1010 Standard
And T836-26-1012 Externally Referenced
FCC ID: CASTEL0047*

Section 4. Occupied Bandwidth

Para. No.: 2.1049

Test Performed By: Russell Grant	Date of Test: August 10, 2000
---	--------------------------------------


Minimum Standard: Para. No.'s 90.210(c)
90.210(d)
22.359

Test Results: Complies.


Measurement Data: See attached graphs.

EQUIPMENT: VHF Paging Transmitter, T836-26-1010 Standard
And T836-26-1012 Externally Referenced
FCC ID: CASTEL0047


Modulated 1200 bps POCSAG 4.5 kHz Deviation



*EQUIPMENT: VHF Paging Transmitter, T836-26-1010 Standard
And T836-26-1012 Externally Referenced
FCC ID: CASTEL0047*



*EQUIPMENT: VHF Paging Transmitter, T836-26-1010 Standard
And T836-26-1012 Externally Referenced
FCC ID: CASTEL0047*



*EQUIPMENT: VHF Paging Transmitter, T836-26-1010 Standard
And T836-26-1012 Externally Referenced
FCC ID: CASTEL0047*

Section 5. Spurious Emissions at Antenna Terminals

Para. No.: 2.1051

Test Performed By: Russell Grant	Date of Test: August 10, 2000
---	--------------------------------------

Minimum Standard: Para. No.'s 90.210 (c)(d)
22.359 (b)(1)

Test Results: Complies.

No emissions were detected within 20dB of the specification limit. The spectrum was searched up to the 10th harmonic of the fundamental frequency of operation.

Measurement Data: See attached graphs.

*EQUIPMENT: VHF Paging Transmitter, T836-26-1010 Standard
And T836-26-1012 Externally Referenced
FCC ID: CASTEL0047*

Section 6. Field Strength of Spurious Emissions

Para. No.: 2.1053

Test Performed By: Russell Grant	Date of Test: August 10, 2000
---	--------------------------------------

Minimum Standard: Para. No.'s 90.210 (c), (d)
22.359 (b)(1)

Test Results: Complies. No emissions were detected within 20dB of the specification limit. The spectrum was searched up to the 10th harmonics of the fundamental frequency of operation.

Measurement Data: See attached tables.

*EQUIPMENT: VHF Paging Transmitter, T836-26-1010 Standard
 And T836-26-1012 Externally Referenced
 FCC ID: CASTEL0047*

Section 7. Frequency Stability

Para. No.: 2.1055

Test Performed By: Russell Grant	Date of Test: August 10, 2000
---	--------------------------------------

Minimum Standard: Para. No.'s 22.355
 90.213

Test Results: Complies. The maximum frequency drift is 61 Hz.
 This is 0.379 ppm standard and 1 Hz, 0.00621 ppm external.

Measurement Data: Standard Test Voltage (STV): 120 VAC
 Test Frequency: 161.000 MHz

Test Condition	Frequency (MHz)	Frequency Drift (Hz)
-30	161.000 027	27
-20	161.000 054	54
-10	161.000 040	40
0	161.000 018	18
+10	161.999 993	7
+20	161.000 039	39
+30	161.999 982	18
+40	161.999 981	19
+50	161.000 061	61

There was no change in the frequency due to $\pm 15\%$ variation of standard test voltage.

The maximum frequency drift using external reference is 1 Hz.

*EQUIPMENT: VHF Paging Transmitter, T836-26-1010 Standard
And T836-26-1012 Externally Referenced
FCC ID: CASTEL0047*

Section 8. Transient Frequency Behaviour

Test Performed By: Russell Grant	Date of Test: August 10, 2000
---	--------------------------------------


Minimum Standard: Para. No. 90.214

Test Results: Complies.

Measurement Data: See attached graphs.


*EQUIPMENT: VHF Paging Transmitter, T836-26-1010 Standard
And T836-26-1012 Externally Referenced
FCC ID: CASTEL0047*

Wideband ± 25 kHz




*EQUIPMENT: VHF Paging Transmitter, T836-26-1010 Standard
And T836-26-1012 Externally Referenced
FCC ID: CASTEL0047*

Wideband ± 25 kHz




*EQUIPMENT: VHF Paging Transmitter, T836-26-1010 Standard
And T836-26-1012 Externally Referenced
FCC ID: CASTEL0047*

Narrowband ± 12.5 kHz



EQUIPMENT: VHF Paging Transmitter, T836-26-1010 Standard
And T836-26-1012 Externally Referenced
FCC ID: CASTEL0047

Narrowband ± 12.5 kHz



*EQUIPMENT: VHF Paging Transmitter, T836-26-1010 Standard
 And T836-26-1012 Externally Referenced
 FCC ID: CASTEL0047*

Section 9. Test Equipment List

CAL CYCLE	EQUIPMENT	MANUFACTURER	MODEL	SERIAL	LAST CAL.	NEXT CAL.
1 Year	Spectrum Analyzer	Hewlett Packard	8565E	FA000981	June 16/00	June 16/01
1 Year	Climate Chamber	Thermotron	SM-16C	15649-S	COU	COU
1 Year	Attenuator	Narda	768-10	9709	Oct. 8/99	Oct. 8/00
1 Year	Attenuator	Narda	769-20	4153	Oct. 1/99	Oct. 1/00
1 Year	Attenuator	Narda	776B-20	FA001400	Oct. 15/99	Oct. 15/00
2 Year	Insertion Unit	Rohde & Schwarz	URV5-Z4	FA000905	Oct. 6/99	Oct. 6/01
2 Year	Power Sensor	Rohde & Schwarz	URV5-Z5	FA000419	Oct. 6/99	Oct. 6/01
1 Year	Horn Antenna	EMCO #2	3115	4336	Nov. 11/99	Nov. 11/00
1 Year	Dipole Antenna Set	EMCO #2	3121C	FA001349	June 27/00	June 27/01
1Year	Frequency Counter	Hewlett Packard	HP5350A	2444A00135	May 7/00	Nov. 7/00


NA: Not Applicable
 NCR: No Cal Required
 COU: CAL On Use

*EQUIPMENT: VHF Paging Transmitter, T836-26-1010 Standard
And T836-26-1012 Externally Referenced
FCC ID: CASTEL0047*


Annex A
Test Diagrams

*EQUIPMENT: VHF Paging Transmitter, T836-26-1010 Standard
And T836-26-1012 Externally Referenced
FCC ID: CASTEL0047*

Para. No. 2.1046 - R.F. Power Output




Para. No. 2.1047 - Audio Frequency Response




*EQUIPMENT: VHF Paging Transmitter, T836-26-1010 Standard
And T836-26-1012 Externally Referenced
FCC ID: CASTEL0047*

Para. No. 2.1047 - Modulation Limiting




Para. No. 2.1049 - Occupied Bandwidth




*EQUIPMENT: VHF Paging Transmitter, T836-26-1010 Standard
And T836-26-1012 Externally Referenced
FCC ID: CASTEL0047*


Para. No. 2.1051 - Spurious Emissions at Antenna Terminals



Para. No. 2.1053 - Field Strength of Spurious Radiation




Para. No. 2.1055 - Frequency Stability



*EQUIPMENT: VHF Paging Transmitter, T836-26-1010 Standard
And T836-26-1012 Externally Referenced
FCC ID: CASTEL0047*

Para. No. 90.214 - Transient Frequency Behaviour



Voice

This measurement was made using measurement procedure TIA/EIA Land Mobile FM or PM Communications Equipment Measurement and Performance Standards TIA/EIA-603 February 1993 Telecommunications Industry Association (American National Standard ANSI/TIA/EIA-603-1992 Approved: October 27, 1992) Para. no. 2.2 Methods of Measurement for Transmitters Para. no. 2.2.19 Transient Frequency Behaviour (page no. 83).

Data

This measurement was made using measurement procedure TIA/EIA Digital C4FM/CQPSK Transceiver Measurement Methods TSB102.CAAA Para. no. 2.2.17 Transient Frequency Behaviour (page no. 74).