

REPORT NUMBER 1612

December 2000

RADIO PERFORMANCE MEASUREMENTS

ON THE T2020-343-F04 MOBILE TRANSCEIVER
(12.5 kHz Channel Spacing & 25.0 kHz Channel Spacing)

FCC ID: CASTEL 0052

SERIAL # 17042576

In accordance with

FCC 47 CFR Parts 22 and 90

PREPARED BY: Sivachanthiran _____
Test Technician

CHECKED & APPROVED BY: S.A. Crompton _____
Laboratory Manager

TELTEST LABORATORIES

Tait Electronics Limited

PO Box 1645

558 Wairakei Road

Christchurch 5

New Zealand

Phone: +64 3 3583399

Fax: +64 3 3580432

TABLE OF CONTENTS

TEST	PAGE
TRANSMITTER OUTPUT POWER (CONDUCTED)	3
AUDIO FREQUENCY FILTER	4
TRANSMITTER AUDIO FREQUENCY RESPONSE	5
MODULATION LIMITING	7
MODULATION LIMITING (STEADY STATE and INSTANTANEOUS)	10
OCCUPIED BANDWIDTH	13
SPURIOUS EMISSIONS (CONDUCTED)	18
SPURIOUS EMISSIONS (RADIATED)	23
TRANSMITTER FREQUENCY STABILITY (TEMPERATURE)	28
TRANSMITTER FREQUENCY STABILITY (VOLTAGE)	30
TRANSIENT FREQUENCY BEHAVIOR	31
LIST OF TEST EQUIPMENT	40

NAME OF TEST: TRANSMITTER OUTPUT POWER (CONDUCTED)

TEST CONDITIONS: Ambient Temperature 20 °C
 Relative Humidity 60 %
 Standard Voltage 13.8 V DC

SPECIFICATION: FCC 47 CFR 2.1046 (a)

GUIDE: TIA/EIA-603 2.2.1

MEASUREMENT PROCEDURE:

- The Equipment Under Test (EUT) was set up as shown on the following diagram.
- The coaxial attenuator used has an impedance of 50Ω.
- The unmodulated output power was measured with an RF Power Meter.

MEASUREMENT RESULTS

Manufacturer’s Rated Output Power: Switchable 5 W and 25 W


Frequency 158.1025 MHz	25 W nominal	5 W nominal
Power (W)	28	5.13
Variation from nom (%)	12	2.6
Measurement Uncertainty	+ 0.63 , - 0.68 dB	

LIMIT CLAUSE: FCC 47 CFR 90.205

Radio Type: Mobile Frequency Band: 150 MHz ~ 174 MHz

(n) “The output power shall not exceed by more than 20% the manufacturer’s rated output power for the particular transmitter.”

TEST SETUP: (See page 40 for test equipment information.)



NAME OF TEST: AUDIO FREQUENCY FILTER RESPONSE

TEST CONDITIONS: Ambient Temperature ~ °C
Relative Humidity ~ %
Standard Voltage ~ V DC

SPECIFICATION: FCC 47 CFR 2.1047 (a)

GUIDE: TIA/EIA-603 2.2.15

MEASUREMENT PROCEDURE:

This test was not carried out as the EUT meets the emission limitations specified in §90.210.

MEASUREMENT RESULTS:

See Occupied Bandwidth tests on page 13.

LIMIT CLAUSE: FCC 47 CFR 90.211 (a)

(a) “ Transmitters utilizing analog emissions that are equipped with an audio low-pass filter must meet the emission limitations specified in § 90.210....”

TEST SETUP USED: (See page 13 - Occupied Bandwidth)

NAME OF TEST: TRANSMITTER AUDIO FREQUENCY RESPONSE
PRE-EMPHASIS

TEST CONDITIONS: Ambient Temperature 19 °C
Relative Humidity 70 %
Standard Voltage 13.8 V DC

SPECIFICATION: FCC 47 CFR 2.1047 (a)

GUIDE: TIA/EIA-603 2.2.6


MEASUREMENT PROCEDURE:

- The Equipment Under Test (EUT) was set up as shown on the following diagram.
- An audio input tone of 1000 Hz was applied with the level set to obtain 20% max deviation. This was used as the 0dB reference point.
- The AF was varied while the deviation level was held constant.
- The response in dB relative to 1000 Hz was measured.

MEASUREMENT RESULTS: See the plot on the following page.



LIMIT CLAUSE: TIA/EIA-603 2.2.6

TEST SETUP: See page 40 for test equipment information.



NAME OF TEST: TRANSMITTER AUDIO FREQUENCY RESPONSE
PRE-EMPHASIS

SPECIFICATION: FCC 47 CFR 2.1047 (a)



NAME OF TEST: TRANSMITTER MODULATION LIMITING

TEST CONDITIONS: Ambient Temperature 19 °C
 Relative Humidity 70 %
 Standard Voltage 13.8 V DC

SPECIFICATION: FCC 47 CFR 2.1047 (b)

GUIDE: TIA/EIA-603 2.2.3


MEASUREMENT PROCEDURE:

- The Equipment Under Test (EUT) was set up as shown on the following diagram.
- The modulation response was measured at three audio frequencies while varying the input level.
- Measurements were made for both positive and negative deviation.

MEASUREMENT RESULTS: See the plots on the following page.



LIMIT CLAUSE: FCC 47 CFR 90.211 (a) 2.1047 (b)

TEST SETUP: See page 31 for test equipment information.





NAME OF TEST: TRANSMITTER MODULATION LIMITING

SPECIFICATION: FCC CFR 2.1047 (b)



NAME OF TEST: TRANSMITTER MODULATION LIMITING

SPECIFICATION: FCC CFR 2.1047 (b)



NAME OF TEST: TRANSMITTER MODULATION LIMITING
STEADY STATE AND INSTANTANEOUS

TEST CONDITIONS: Ambient Temperature 19 °C
Relative Humidity 70 %
Standard Voltage 13.8 V DC

SPECIFICATION: FCC 47 CFR 2.1047 (b)

GUIDE: TIA/EIA-603 2.2.3


MEASUREMENT PROCEDURE:

- The Equipment Under Test (EUT) was set up as shown on the following diagram.
- The modulation response was measured with a level stepped 20 dB above the level required to obtain 60% deviation at 1000 Hz AF.
- Measurements were made for both positive and negative deviation.

MEASUREMENT RESULTS: See the plots on the following page.



LIMIT CLAUSE: FCC CFR 90.211 (a) 2.1047 (b)

TEST SETUP: See page 31 for test equipment information.





NAME OF TEST: TRANSMITTER MODULATION LIMITING
STEADY STATE AND INSTANTANEOUS

SPECIFICATION: FCC CFR 2.1047 (b)



NAME OF TEST: TRANSMITTER MODULATION LIMITING
STEADY STATE AND INSTANTANEOUS

SPECIFICATION: FCC CFR 2.1047 (b)



NAME OF TEST: OCCUPIED BANDWIDTH

TEST CONDITIONS: Ambient Temperature 20 °C
 Relative Humidity 60 %
 Standard Voltage 13.8 V DC

SPECIFICATION: FCC 47 CFR 2.1049 (c) (1)

GUIDE: TIA/EIA-603 2.2.11


MEASUREMENT PROCEDURE:

- The Equipment Under Test (EUT) was set up as shown on the following diagram.
- The EUT was modulated by a 2500 Hz tone at an input level 16 dB above a level that produced 50% deviation. The input level was established at the frequency of maximum response of the audio modulating circuit.
- The Occupied Bandwidth was measured on the Spectrum Analyser with the controls set as shown on the following plots.

MEASUREMENT RESULTS: See the plots on the following pages.

LIMIT CLAUSE: FCC 47 CFR 90.210

TEST SETUP: See page 31 for test equipment information.




NAME OF TEST: OCCUPIED BANDWIDTH

SPECIFICATION: FCC CFR 2.1049 (c) (1)


MASK "D"

Power: 25 W UNMODULATED 158.1025 MHz , 12.5 KHz Channel pacing



Tarf 1612 25w, 12.5 C.Spacing, Unmodulated MASK "D"

Power: 25 W MODULATED 158.1025 MHz , 12.5 KHz Channel pacing




Tarf 1612, 25W , 12.5 KHz C.Spacing , Modulated MASK "D"

NAME OF TEST: OCCUPIED BANDWIDTH

SPECIFICATION: FCC CFR 2.1049 (c) (1)


MASK "D"

Power: 5 W UNMODULATED 158.1025 MHz , 12.5 KHz Channel pacing



Tarf 1612 5W, 12.5 KHz C.Spacing , Unmodulated MASK "D"

Power: 5 W MODULATED 158.1025 MHz , 12.5 KHz Channel pacing




Tarf 1612, 5W, 12.5 KHz C.Spacing , Modulated MASK "D"

NAME OF TEST: OCCUPIED BANDWIDTH

SPECIFICATION: FCC CFR 2.1049 (c) (1)


MASK "B"

Power: 25 W UNMODULATED 158.1025 MHz , 25 KHz Channel pacing



Tarf 1612, 25W , 25 KHz C.Spacing , Unmodulated MASK "B"

Power: 25 W MODULATED 158.1025 MHz , 25 KHz Channel pacing




Tarf 1612, 25W , 25KHz C.Spacing , Modulated , MASK "B"

NAME OF TEST: OCCUPIED BANDWIDTH

SPECIFICATION: FCC CFR 2.1049 (c) (1)


MASK "B"

Power: 5 W UNMODULATED 158.1025 MHz , 25 KHz Channel pacing



Tarf 1612 , 5W , 25 KHz C.Spacing , Unmodulated MASK "B"

Power: 5 W MODULATED 158.1025 MHz , 25 KHz Channel pacing



Tarf 1612 , 5W , 25KHz C.Spacing , Modulated MASK "B"

NAME OF TEST: SPURIOUS EMISSIONS CONDUCTED

TEST CONDITIONS: Ambient Temperature 19 °C
 Relative Humidity 65 %
 Standard Voltage 13.8 V DC

SPECIFICATION: FCC 47 CFR 2.1051

GUIDE: TIA/EIA-603 2.2.13


MEASUREMENT PROCEDURE:

- The Equipment Under test was set up as shown in the following diagram.
- The frequency range examined was from the lowest frequency generated within the EUT, to a frequency higher than the 10th Harmonic: 100 kHz to Fc-BW
 Fc + BW to 2 GHz
- Spurious emissions which were attenuated more than 20 dB below the limit were not recorded.

MEASUREMENT RESULTS: See the tables on the following tables.

LIMIT CLAUSE: FCC 47 CFR 90.210

TEST SETUP: See page 31 for test equipment information.



NAME OF TEST: SPURIOUS EMISSIONS (CONDUCTED)
 SPECIFICATION: FCC CFR 2.1051

158.1025 MHz @ 25W, 12.5 KHz Channel Spacing		Emission Mask “ D ”
Emission Freq MHz	Level dBm	Level dBc
No emissions were detected at a level greater than 20 dB below the limit.		

LIMITS:

Carrier Output Power P Watts	Emission Mask “D” $50 + 10\log_{10}(P_{\text{Watts}})$	
25 W	63.98 dBc	-20 dBm
5 W	56.99 dBc	-20 dBm

NAME OF TEST: SPURIOUS EMISSIONS (CONDUCTED)
 SPECIFICATION: FCC CFR 2.1051

158.1025 MHz @ 5W, 12.5 KHz Channel Spacing		Emission Mask “ D “
Emission Freq MHz	Level dBm	Level dBc
No emissions were detected at a level greater than 20 dB below the limit.		

LIMITS:

Carrier Output Power P Watts	Emission Mask “D” $50 + 10\log_{10}(P_{Watts})$	
25 W	63.98 dBc	-20 dBm
5 W	56.99 dBc	-20 dBm

NAME OF TEST: SPURIOUS EMISSIONS (CONDUCTED)
 SPECIFICATION: FCC CFR 2.1051

158.1025 MHz @ 25W, 25 KHz Channel Spacing		Emission Mask “ B “
Emission Freq MHz	Level dBm	Level dBc
No emissions were detected at a level greater than 20 dB below the limit.		

LIMITS:

Carrier Output Power P Watts	Emission Mask “B” $43 + 10\log_{10}(P_{\text{Watts}})$	
25 W	57.0 dBc	-13 dBm
5 W	50.0 dBc	-13 dBm

NAME OF TEST: SPURIOUS EMISSIONS (CONDUCTED)
 SPECIFICATION: FCC CFR 2.1051

158.1025 MHz @ 5W, 25 KHz Channel Spacing		Emission Mask “ B “
Emission Freq MHz	Level dBm	Level dBc
No emissions were detected at a level greater than 20 dB below the limit.		

LIMITS:

Carrier Output Power P Watts	Emission Mask “B” $43 + 10\log_{10}(P_{Watts})$	
25 W	57.0 dBc	-13 dBm
5 W	50.0 dBc	-13 dBm

NAME OF TEST: SPURIOUS EMISSIONS RADIATED

TEST CONDITIONS: Ambient Temperature 20 °C
 Relative Humidity 75 %
 Standard Voltage 13.8 V DC

SPECIFICATION: FCC 47 CFR 2.1053 (a)

GUIDE: TIA/EIA-603 2.2.12


MEASUREMENT PROCEDURE:

- The Equipment Under test was set up as shown in the following diagram.
- The EUT was placed on a wooden turntable at a distance of three metres from the test antenna. The output terminal was connected to an RF dummy load.
- The frequency range examined was from the lowest frequency generated within the EUT, to a frequency higher than the 10th Harmonic: 100 kHz to Fc-BW
 Fc + BW to 2 GHz
- The turntable was rotated through 360° to obtain the maximum response of each spurious emission. Valid emissions were determined by switching the EUT on and off.
- The EUT was replaced by a signal generator and substitution antenna to make measurements by the substitution method.

MEASUREMENT RESULTS: See the tables on the following pages.

LIMIT CLAUSE: FCC CFR 90.210

TEST SETUP: See page 31 for test equipment information



NAME OF TEST: SPURIOUS EMISSIONS (RADIATED)

SPECIFICATION: FCC CFR 2.1053 (a)

158.1025 MHz @ 25W, 12.5 KHz Channel Spacing		Emission Mask “ D “
Emission Freq MHz	Level dBm	Level dBc
No emissions were detected at a level greater than 20 dB below the limit.		

LIMITS:

Carrier Output Power P Watts	Emission Mask “D” $50 + 10\log_{10}(P_{Watts})$	
25 W	63.98 dBc	-20 dBm
5 W	56.99 dBc	-20 dBm

NAME OF TEST: SPURIOUS EMISSIONS (RADIATED)

SPECIFICATION: FCC CFR 2.1053 (a)

158.1025 MHz @ 5W, 12.5 KHz Channel Spacing		Emission Mask “ D “
Emission Freq MHz	Level dBm	Level dBc
No emissions were detected at a level greater than 20 dB below the limit.		

LIMITS:

Carrier Output Power P Watts	Emission Mask “D” $50 + 10\log_{10}(P_{\text{Watts}})$	
25 W	63.98 dBc	-20 dBm
5 W	56.99 dBc	-20 dBm

NAME OF TEST: SPURIOUS EMISSIONS (RADIATED)

SPECIFICATION: FCC CFR 2.1053 (a)

158.1025 MHz @ 25W, 25 KHz Channel Spacing		Emission Mask “ B “
Emission Freq MHz	Level dBm	Level dBc
No emissions were detected at a level greater than 20 dB below the limit.		

LIMITS:

Carrier Output Power P Watts	Emission Mask “B” $43 + 10\log_{10}(P_{\text{Watts}})$	
25 W	57.0 dBc	-13 dBm
5 W	50.0 dBc	-13 dBm

NAME OF TEST: SPURIOUS EMISSIONS (RADIATED)

SPECIFICATION: FCC CFR 2.1053 (a)

158.1025 MHz @ 5W, 25 KHz Channel Spacing		Emission Mask “ B “
Emission Freq MHz	Level dBm	Level dBc
No emissions were detected at a level greater than 20 dB below the limit.		

LIMITS:

Carrier Output Power P Watts	Emission Mask “B” $43 + 10\log_{10}(P_{\text{watts}})$	
25 W	57.0 dBc	-13 dBm
5 W	50.0 dBc	-13 dBm

NAME OF TEST: TRANSMITTER FREQUENCY STABILITY (TEMPERATURE)

TEST CONDITIONS: Ambient Temperature 18 °C
 Relative Humidity 65 %
 Standard Voltage 13.8 V DC

SPECIFICATION: FCC 47 CFR 2.1055 (a)

GUIDE: TIA/EIA-603 2.2.2

MEASUREMENT PROCEDURE:


- The Equipment Under test was set up as shown in the following diagram.
- The EUT was tested for frequency error from -30 °C to +50 °C in 10 °C increments.
- The frequency error was recorded in parts per million (ppm).

MEASUREMENT RESULTS: See the plot on the following page.

LIMIT CLAUSE: FCC CFR 90.213



Frequency Range	Frequency Error (ppm)
150 MHz to 174 MHz	± 5.0

TEST SETUP: See page 31 for test equipment information.



NAME OF TEST: TRANSMITTER FREQUENCY STABILITY (TEMPERATURE)

SPECIFICATION: FCC CFR 2.1055 (a) (1)



NAME OF TEST: TRANSMITTER FREQUENCY STABILITY (VOLTAGE)

TEST CONDITIONS: Ambient Temperature 20 °C
 Relative Humidity 60 %
 Standard Voltage 13.8 V DC

SPECIFICATION: FCC 47 CFR 2.1055 (d) (2)

GUIDE: TIA/EIA-603 2.2.2

MEASUREMENT PROCEDURE:

- The Equipment Under test was set up as shown in the following diagram.
- The EUT was tested for frequency error at a nominal battery voltage of 13.8V and $V_{nom} \pm 15\%$. (11.7V and 15.9V).
- The frequency error was recorded in parts per million (ppm).


MEASUREMENT RESULTS:

Channel Spacing (KHz)	Frequency Error (ppm) @158.1025 MHz		
	11.7V DC	13.8 V DC	15.9 V DC
12.5	-0.06	-0.08	-0.09
25.0	0.55	0.54	0.52

LIMIT CLAUSE: FCC 47 CFR 90.213

Frequency Range	Frequency Error (ppm)
150 MHz to 174 MHz	± 5.0

TEST SETUP: See page 31 for test equipment information.



NAME OF TEST: TRANSIENT FREQUENCY BEHAVIOR

TEST CONDITIONS: Ambient temperature 21 °C
 Relative humidity 60 %
 Standard Voltage 13.8 VDC

SPECIFICATION: FCC 47 CFR 90.214

GUIDE: TIA/EIA-603 2.2.19

MEASUREMENT PROCEDURE:

1. The Equipment Under Test (EUT) was set up as shown on the following diagram.
2. Measurements and plots were made following the TIA/EIA procedure.


MEASUREMENT RESULTS:

See the tables and plots on the following pages.

LIMIT CLAUSE: FCC 47 CFR 90.214

See the tables on the following pages.

TEST SETUP: See page 40 for test equipment information.



NAME OF TEST: TRANSIENT FREQUENCY BEHAVIOR

SPECIFICATION: FCC 47 CFR 90.214

12.5KHz CHANNEL SPACING

FREQUENCY	158.1025 MHz @ 25W Tx	
TRANSIENT RESPONSE PERIOD	CARRIER PEAK VARIATION FROM NOMINAL	
	KEY ON (KHz)	KEY OFF (KHz)
t1	1.25	N/A
t2	0.19	N/A
t3	N/A	0.625
t2~t3	0.19	
ERROR LIMIT (t2~t3) @ 5 PPM (KHz)	0.79	

Confirm that during periods t1 and t3 the frequency difference does not exceed the value of one channel separation.	YES	NO
	✓	
Confirm that during the period t2 the frequency difference does not exceed half a channel separation.	YES	NO
	✓	
Confirm that during the period t2 to t3 the frequency difference does not exceed the frequency error limit	YES	NO
	✓	


LIMIT: 12.5KHz CHANNEL SPACING

TRANSIENT PERIODS	MAXIMUM FREQUENCY DIFFERENCE (KHz)	FREQUENCY RANGE 150-174 MHz
t1 (mS)	±12.5	5 mS
t2 (mS)	±6.25	20 mS
t3 (mS)	±12.5	5 mS

NAME OF TEST: TRANSIENT FREQUENCY BEHAVIOR


SPECIFICATION: FCC 47 CFR 90.214

12.5KHz CHANNEL SPACING 25 W KEY-ON



t 10mS/Div

12.5KHz CHANNEL SPACING 25 W KEY-OFF



t10mS/Div

NAME OF TEST: TRANSIENT FREQUENCY BEHAVIOR

SPECIFICATION: FCC 47 CFR 90.214

12.5KHz CHANNEL SPACING

FREQUENCY	158.1025 MHz @ 5W Tx	
TRANSIENT RESPONSE PERIOD	CARRIER PEAK VARIATION FROM NOMINAL	
	KEY ON (KHz)	KEY OFF (KHz)
t1	1.31	N/A
t2	0.29	N/A
t3	N/A	0.69
t2~t3	0.29	
ERROR LIMIT (t2~t3) @ 5 PPM (KHz)	0.79	

Confirm that during periods t1 and t3 the frequency difference does not exceed the value of one channel separation.	YES	NO
	✓	
Confirm that during the period t2 the frequency difference does not exceed half a channel separation.	YES	NO
	✓	
Confirm that during the period t2 to t3 the frequency difference does not exceed the frequency error limit	YES	NO
	✓	


LIMIT: 12.5KHz CHANNEL SPACING

TRANSIENT PERIODS	MAXIMUM FREQUENCY DIFFERENCE (KHz)	FREQUENCY RANGE 150-174 MHz
t1 (mS)	±12.5	5 mS
t2 (mS)	±6.25	20 mS
t3 (mS)	±12.5	5 mS

NAME OF TEST: TRANSIENT FREQUENCY BEHAVIOR


SPECIFICATION: FCC 47 CFR 90.214

12.5KHz CHANNEL SPACING 5W KEY-ON



t 10mS/Div

12.5KHz CHANNEL SPACING 5W KEY-OFF



t 10mS/Div

NAME OF TEST: TRANSIENT FREQUENCY BEHAVIOR

SPECIFICATION: FCC 47 CFR 90.214

25KHz CHANNEL SPACING

FREQUENCY	158.1025MHz @ 25 W Tx	
TRANSIENT RESPONSE PERIOD	CARRIER PEAK VARIATION FROM NOMINAL	
	KEY ON (KHz)	KEY OFF (KHz)
t1	1.85	N/A
t2	0.40	N/A
t3	N/A	4.26
t2~t3	0.40	
ERROR LIMIT (t2~t3) @ 5PPM (KHz)	0.79	

Confirm that during periods t1 and t3 the frequency difference does not exceed the value of one channel separation.	YES	NO
	✓	
Confirm that during the period t2 the frequency difference does not exceed half a channel separation.	YES	NO
	✓	
Confirm that during the period t2 to t3 the frequency difference does not exceed the frequency error limit	YES	NO
	✓	


LIMIT: 25KHz CHANNEL SPACING

TRANSIENT PERIODS	MAXIMUM FREQUENCY DIFFERENCE (KHz)	FREQUENCY RANGE 150-174 MHz
t1 (mS)	±25	5 mS
t2 (mS)	±12.5	20 mS
t3 (mS)	±25	5 mS

NAME OF TEST: TRANSIENT FREQUENCY BEHAVIOR


SPECIFICATION: FCC 47 CFR 90.214

25KHz CHANNEL SPACING 25 W KEY-ON



t 10mS/Div

25KHz CHANNEL SPACING 25 W KEY-OFF



t 10mS/Div

NAME OF TEST: TRANSIENT FREQUENCY BEHAVIOR

SPECIFICATION: FCC 47 CFR 90.214

25KHz CHANNEL SPACING

FREQUENCY	158.1025MHz @ 5 W Tx	
TRANSIENT RESPONSE PERIOD	CARRIER PEAK VARIATION FROM NOMINAL	
	KEY ON (KHz)	KEY OFF (KHz)
t1	2.37	N/A
t2	0.39	N/A
t3	N/A	2.11
t2~t3	0.39	
ERROR LIMIT (t2~t3) @ 5PPM (KHz)	0.79	

Confirm that during periods t1 and t3 the frequency difference does not exceed the value of one channel separation.	YES	NO
	✓	
Confirm that during the period t2 the frequency difference does not exceed half a channel separation.	YES	NO
	✓	
Confirm that during the period t2 to t3 the frequency difference does not exceed the frequency error limit	YES	NO
	✓	


LIMIT: 25KHz CHANNEL SPACING

TRANSIENT PERIODS	MAXIMUM FREQUENCY DIFFERENCE (KHz)	FREQUENCY RANGE 150-174 MHz
t1 (mS)	±25	5 mS
t2 (mS)	±12.5	20 mS
t3 (mS)	±25	5 mS

NAME OF TEST: TRANSIENT FREQUENCY BEHAVIOR


SPECIFICATION: FCC 47 CFR 90.214

25KHz CHANNEL SPACING 5W KEY-ON



t 10mS/Div

25KHz CHANNEL SPACING 5W KEY-OFF



t 10mS/Div

TEST EQUIPMENT LIST

To facilitate inclusion on each page, the test equipment used is identified (numbered) and listed against the related test in the report.

No	Equipment Type	Model number	Serial Number	Tait ID:
01	Signal Generator	HP 8642B (Opt 001)	2512A00176	E3064
02	Signal Generator	HP8648A	3430U00344	E3579
03	Signal Generator	HP8656A	2142A02103	E3063
04	Signal Generator	HP8648C	3443U00543	E3558
05	Signal Generator	SMY01 1062.5502.11	841736/019	E3553
10	Spectrum Analyser	HP8596E (Opt 140)	3346A00213	E3427
11	Modulation Analyser	HP8901B (Opt 002)	2441A00393	E3073
12	Modulation Analyser	FMA 0852.8500.52	842541/001	E3554
13	Audio Analyser	HP8903A	2308A02597	E3074
14	Power Head	HP11722A	2320A00688	E3307
15	Power Meter	NRVS 1020.1809.02	841954/005	E3555
16	Power Sensor	URV5-Z4 395.1619.55	841.498/003	E3557
20	Power Supply	HP6032A	2441A-0041	E3075
21	Power Supply	NGSM32/10 192.0810.31	Fnr 434	E3556
22	Oscilloscope	Tektronics TDS 340	B013611	E3585
23	Universal Counter	Goldstar FC-2015U	600801	E3550
24	Environmental Chamber	Contherm Spatial Cal	E3397	E3397
24	Environmental Chamber	Contherm Temp Control	E3397	E3397
25	Portable Hygrometer (ASL)	Rotronic A1	2070300/38	N/A
25	Whirling Hygrometer	Casella 3156 / 82	TA004	TA004
30	Directional Coupler	HP778D-012	1144 07392	E3292
31	4 Port Combiner (CAST)	DVU4, W 201.4018.03	300729/47	E3623
32	4 Port Combiner	DVU4, W 201.4018.03	300971/28	E3572
33	3 Port Combiner	Weinschel 1506A, 1W	LD858	E3672
34	Mixer Spurious Emission	Tait (3.2G ≤ Rfx ≤ 4.0G)	E3661	E3661
35	Mixer Transient ACP	Minicircuits ZAD-11	77031	E3394

TEST EQUIPMENT LIST (Cont.)

No	Equipment Type	Model number	Serial Number	Tait ID:	
36	Voltmeter	HP3478A	2545A25838	E1559	
37	Variac	Yamabishi S-260-5	TX-533	E1737	
38	RX and TX, RF Paths	Tait CAST Interface	E3067	E3067	
40	Reference Dipoles	Emco 3121C-DB1	9510-1164	E3559	
41	Antenna	Biconical	9307-1680	E3033	
42	Reference Horn Antenna	Emco DRG 3115	9512-4638	E3560	
43	Horn Antenna	Emco DRG 3115	2084	E3076	
44	Corner 175-420 MHz	Ailtech DM 105A-T2	J1417-103	E3031	
45	Corner 400-1000 MHz	Ailtech DM 105A-T3	J1418-108	E3036	
46	S-LINE TEM CELL	1089.9296.02	338232/003	E3636	
50	Amplifier AR 1M-1000M	25W1000A	20444	E3637	
51	Amplifier AR 10K-250M	25A250	16373	E3570	
52	Amplifier +21.7 dB	Tait ZFL-1000LN	E3660	E3360	
53	RF Filter 21.4M (CAST)	Tait NDK 21G-6DT	E3069	E3069	
54	RF Filter 21.4M (ACP)	Tait NDK 21G-6DT	RA-7'	E3249	
55	Filter Notch	Tait	N/A	?	
56	Filter High Pass	Tait	Mhz	N/A	?
57	Filter Low Pass	Tait	Mhz	N/A	?
60	RF Attenuator 250W	Weinschel 45-30-34	JW663	E3386	
61	RF Attenuator 150W	Weinschel 40-20-33	CJ404	E3387	
62	RF Attenuator 150W	Weinschel 57-10-34	LB590	E3674	
63	RF Attenuator 150W	Weinschel 40-06-34	KV457	E3561	
64	RF Attenuator 50W	Weinschel 24-10-34	AL0401	E3388	
65	RF Attenuator 50W	Weinschel 24-20-44	AW1266	E3562	

TEST EQUIPMENT LIST (Cont.)

No	Equipment Type	Model number	Serial Number	Tait ID:
66	RF Attenuator 25W	Weinschel 33-20-33	BD5871	E3673
67	RF Attenuator 150W(CAST)	Weinschel 40-20-33	CJ405	3366/82
70	RF Load 150W	Byrd 8166	524	E3625
71	RF Load 50 W	Weinschel F1426	BF0487	E3675
72	RF Load 50 W	Weinschel F1426	AE2490	E3624
73	RF Termination 20W	Deltec	118.001	E3626
74	RF Termination W	MCL NTRM-50	951215	E3574
75	RF Termination W	MCL NTRM-50	954214	E3575
76	RF Termination W	MCL NTRM-50	954214	E3576
80	20 M Coax Cable	RG214/U 50 (Ext Cal)	CBL01	E3659
81	2 M Coax Cable	RG213/U 50 (Ext Cal)	CBL02	E3658
82	3 M Coax Cable (BLUE)	Suhner Sucoflex 104A	25033 / 4A	E3694
83	1 M Coax Cable (BLUE)	Suhner Sucoflex 104A	25006 / 4A	E3693
84	1 M Coax Cable (BLUE)	Suhner Sucoflex 104A	25005 / 4A	E3692
85	1 M Coax Cable (BLUE)	Suhner Sucoflex 104A	25004 / 4A	E3691
86	1 M Coax Cable (BLUE)	Suhner Sucoflex 104A	25003 / 4A	E3690
87	Audio Analyser	HP8903B	2818A04275	E3710
88	Spectrum Analyser	HP8562E	3821A00799	E3715
89	Field Strength Meter	Holaday HI-422	95661	E3630
90	Power Supply	HP6012B	2524A00616	E3712
91	20 M Coax Cable	RG214/U 50 (Ext Cal)	3404	24/08/99
92	LISN	EMCO 3825/2	9204-1961	E3040