



849 NW STATE ROAD 45
NEWBERRY, FL 32669 USA
PH: 888.472.2424 OR
352.472.5500
FAX: 352.472.2030
EMAIL: INFO@TIMCOENGR.COM
[HTTP://WWW.TIMCOENGR.COM](http://WWW.TIMCOENGR.COM)

RF Exposure Evaluation Report

APPLICANT	TAIT LIMITED
	535 Wairakei Road P.O. Box 1645 Christchurch 8140 New Zealand
FCC ID	CASTMBC0A
MODEL NUMBER	TMBC0A
PRODUCT DESCRIPTION	25W MOBILE TRANSCEIVER
STANDARD APPLIED	CFR 47 Part 2.1091
PREPARED BY	Franklin Rose

We, TIMCO ENGINEERING, INC. would like to declare that the device has been evaluated in accordance with 47 CFR Part 2.1091 and meets the requirements.

The attached report shall not be reproduced except in full without the written approval of TIMCO ENGINEERING, INC.

GENERAL REMARKS

Attestations

This equipment has been evaluated in accordance with the standards identified in this report. To the best of my knowledge and belief, these evaluations were performed using the procedures described in this report.

I attest that the necessary evaluations were made, under my supervision, at:

Timco Engineering Inc.
849 NW State Road 45
Newberry, FL 32669



Authorized Signatory Name:

Franklin Rose, Engineering Project Manager

Date: 1/19/2018

RF Exposure Requirements

General information

Device type: 25W MOBILE TRANSCEIVER

Antenna

The manufacturer does not specify an antenna, but a typical antenna has a gain of 0 dBi.

Configuration	Antenna p/n	Type	Max. Gain (dBi)
Fixed mounted	Any	External mounted	5.15

MPE Calculation:

The minimum separation distance is calculated as follows:

$$E(V/m) = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power density: } P_d(mW/cm^2) = \frac{E^2}{3770}$$

The limit for general uncontrolled exposure environment is shown in FCC rule Part 1.1310, Table 1.

**Minimum Separation Distance for Mobile or Fixed Devices
General Population/Uncontrolled Exposure**

Insert values in yellow highlighted boxes to determine Minimum Separation Distance

Max Power	25.3 W	<i>equals</i>	Max Power	25300	mW
Duty Cycle	50 %	<i>equals</i>	Duty Factor	0.5	numeric
Antenna Gain	5.15 dBi	<i>equals</i>	Gain numeric	3.273407	numeric
Coax Loss	0 dB		Gain - Coax Loss	3.273407	numeric
Power Density	0.2 mW/cm ²				
Frequency	220 MHz				

Enter power Density from the chart to the right

Rule Part 1.1310, Table 1 (B)

Frequency range MHz	Power den mW/cm ²	Enter this value mW/cm ²
0.3-1.34	100	100
1.34-30	180/f ²	0.0
30-300	0.2	0.2
300-1,500	f/1500	0.1
1,500-100,000	1	1

f = frequency in MHz

Minimum Separation Distance	128 cm	1.28 m
------------------------------------	---------------	---------------

Minimum Separation in Inches 50.49632 Inches