

# LABORATORY TEST REPORT

## RADIO PERFORMANCE MEASUREMENTS

for the

TMBHKB Mobile Transceiver

Tested in accordance with:

FCC 47 CFR Parts 22 and 90

RSS-119 Issue 12

RSS-Gen Issue 5

Report Revision: 1  
Issue Date: 5 June 2018

PREPARED BY: L. M. White

  
Test Technician

CHECKED & APPROVED BY: M. C. James

  
Laboratory Technical Manager



FCC REGISTRATION: 838288  
IC LISTING REGISTRATION: SITE# 737A-1

All tests reported herein have been performed in accordance with the laboratory's scope of accreditation.

This document must not be reproduced except in full, without the written permission of the Compliance Laboratory Manager

## TABLE OF CONTENTS

REVISION .....	3
INTRODUCTION .....	4
STATEMENT OF COMPLIANCE .....	5
MODULATION TYPES, NECESSARY BANDWIDTH & EMISSION DESIGNATORS	6
TEST RESULTS.....	8
TRANSMITTER OUTPUT POWER (CONDUCTED) .....	8
TRANSMITTER AUDIO FREQUENCY RESPONSE - PRE-EMPHASIS.....	10
TRANSMITTER MODULATION LIMITING .....	14
TRANSMITTER OCCUPIED BANDWIDTH AND SPECTRUM MASKS .....	18
TRANSMITTER SPURIOUS EMISSIONS (CONDUCTED).....	55
TRANSMITTER SPURIOUS EMISSIONS (RADIATED).....	71
TRANSIENT FREQUENCY BEHAVIOR.....	76
TRANSMITTER FREQUENCY STABILITY - TEMPERATURE .....	89
TRANSMITTER FREQUENCY STABILITY - VOLTAGE .....	91
RECEIVER SPURIOUS EMISSIONS (CONDUCTED) .....	92
TEST EQUIPMENT LIST.....	94
ANNEX A – TEST SETUP DETAILS.....	96

## REVISION

Date	Revision	Comments
5 June 2018	1	Initial test report

## INTRODUCTION

Type approval testing of the TMBHKB, 40 Watt, Mobile transceiver in order to demonstrate compliance with FCC 47 Parts 22 & 90, and RSS-119 Issue 12 & RSS-Gen Issue 5. This radio supports analogue, digital FFSK, Digital Mobile Radio (DMR), APCO P25 phase-1 and APCO P25 phase-2 modulations.

### REPORT PREPARED FOR

Tait Ltd  
245 Wooldridge Road  
Harewood  
Christchurch 8051  
New Zealand

### DESCRIPTION OF SAMPLE

Manufacturer: Tait Limited  
Equipment: Mobile Transceiver  
Type: TMBHKB  
Product Code: T02-00012-RBAA  
Serial Number(s): 20554861  
Frequency range: 378 → 470 MHz  
Transmit Power: 40 W

Modulation		Channel Spacing	Speech Channels	Symbol Rate (symbols/sec)	Data Rate (bps)
Analogue FM		12.5 kHz	1	-	-
FFSK	Fast Frequency Shift Keying	12.5 kHz	-	1200	1200
		12.5 kHz	-	2400	2400
Digital Mobile Radio (DMR)	4 Level FSK (2 slot TDMA) (ETSI TS102 361-1)	12.5 kHz	2	4800	9600
APCO P25 Phase 1	C4FM (TIA 102)	12.5 kHz	1	4800	9600
APCO P25 Phase 2	H-CPM (2 slot TDMA) (TIA 102)	12.5 kHz	2	6000	12000

### HARDWARE & SOFTWARE

Quantity: 1

	Analogue, FFSK and DMR tests	P25 tests
Hardware ID	TMBB24-HK00_0002	TMBB24-HK00_0002
Boot Code	QMB2B_S00_3.04.01.0003	QMB2B_S00_3.04.01.0003
DSP	QMB2A_E00_2.18.02.0041	QMB2A_A02_2.12.07.0045
Radio Application	QMB2F_E00_2.18.02.0041	QMB2F_A00_2.12.07.0045
Firmware Package	QI93M_E00_2.18.02.0041	QI94M_A02_2.12.07.0045
FPGA Image	QMB2G_S00_1.12.04.0001	QMB2G_S00_1.12.04.0001

### TEST CONDITIONS

All testing was performed between 8 → 16 May 2018, and under the following conditions:

Ambient temperature: 15°C → 30°C  
Relative Humidity: 20% → 75%  
Standard Test Voltage: 13.8 V<sub>DC</sub>

## STATEMENT OF COMPLIANCE

We, TELTEST LABORATORIES of 558 Wairakei Road, Christchurch, New Zealand, declare under our sole responsibility that the product:

Equipment: Mobile Transceiver  
Type: TMBHKB  
Product Code: T02-00012-RBAA  
Serial Number(s): 20554861  
Quantity: 1

to which this declaration relates, is in conformity with the following standards:

FCC 47 CFR Parts 22 and 90

RSS-119 Issue 12 & RSS-Gen Issue 5

**Signature:** 

M. C. James  
Laboratory Technical Manager

**Date:** 5 July 2018

## MODULATION TYPES, NECESSARY BANDWIDTH & EMISSION DESIGNATORS

### MODULATION TYPES:

F3E	Analogue Frequency Modulation (FM)	
F2D	FFSK	1200 bps and 2400 bps
FXW	DMR Digital Voice	9600 bps
FXD	DMR Digital Data	9600 bps
F1E, F7E	P25 phase 1 Digital Voice	9600 bps
F1D, F7D	P25 phase 1 Digital Data	9600 bps
F1W	P25 phase 2 Digital Voice / Data	12000 bps

CHANNEL SPACING: 12.5 kHz

### EMISSION DESIGNATORS:

	12.5 kHz
Analog FM	11K0F3E
FFSK Data 1200 bps	6K60F2D
FFSK Data 2400 bps	7K80F2D
Digital Voice DMR	7K60FXW
Digital Data DMR	7K60FXD
Digital Voice P25 phase 1	8K10F1E
Digital Data P25 phase 1	8K10F1D
Digital Voice P25 phase 2	8K10F1W
Digital Data P25 phase 2	8K10F1W

### CALCULATIONS

Equation:  $B_n = 2M + 2Dk$

(M is highest modulating frequency; D is peak allowable deviation; k is a constant of 1 for FM)

#### Analogue Voice 12.5 kHz Bandwidth

Necessary bandwidth

M = 3.0 kHz

D = 2.5 kHz

$$B_n = (2 \times 3.0) + (2 \times 2.5) \times 1$$

$$= 11.0 \text{ kHz}$$

Emission Designator

**11K0F3E**

F3E represents an FM voice transmission

#### Fast Frequency Shift Keying (FFSK – 1200 bps) 12.5 kHz Bandwidth

Necessary bandwidth

M = 1.8 kHz

D = 1.5 kHz (60% of peak deviation)

$$B_n = (2 \times 1.8) + (2 \times 1.5) \times 1$$

$$= 6.6 \text{ kHz}$$

Emission Designator

**6K60F2D**

F2D represents a FM data transmission with the use of a modulating sub carrier

#### Fast Frequency Shift Keying (FFSK – 2400 bps) 12.5 kHz Bandwidth

Necessary bandwidth

M = 2.4 kHz

D = 1.5 kHz (60% of peak deviation)

$$B_n = (2 \times 2.4) + (2 \times 1.5) \times 1$$

$$= 7.8 \text{ kHz}$$

Emission Designator

**7K80F2D**

F2D represents a FM data transmission with the use of a modulating sub carrier

## Emission Designators – Continued

### Digital Voice 12.5 kHz Bandwidth DMR

99% bandwidth  
= 7.6 kHz

Emission Designator  
**7K60FXW**

FXW represents a FM Time Division Multiple Access (TDMA) combination of data and telephony

### Digital Data 12.5 kHz Bandwidth DMR

99% bandwidth  
= 7.6 kHz

Emission Designator  
**7K60FXD**

FXD represents FM Time Division Multiple Access (TDMA) data only

### Digital Voice 12.5 kHz Bandwidth P25 phase 1

99% bandwidth  
= 8.1 kHz

Emission Designator  
**8K10F1E**

F1E represents a digital FM voice transmission

### Digital Data 12.5 kHz Bandwidth P25 phase 1

99% bandwidth  
= 8.1 kHz

Emission Designator  
**8K10F1D**

F1D represents an digital FM data transmission

### Digital Voice 12.5 kHz Bandwidth P25 phase 2

99% bandwidth  
= 8.1 kHz

Emission Designator  
**8K10F1W**

F1W represents a single FM telephony channel

### Digital Data 12.5 kHz Bandwidth P25 phase 2

99% bandwidth  
= 8.1 kHz

Emission Designator  
**8K10F1W**

F1W represents digital FM data transmission

## TEST RESULTS

### TRANSMITTER OUTPUT POWER (CONDUCTED)

SPECIFICATION: FCC 47 CFR 2.1046  
RSS-119 5.4

GUIDE: TIA/EIA-603D 2.2.1

#### MEASUREMENT PROCEDURE:

1. Refer Annex A for Equipment set up.
2. The coaxial attenuator has an impedance of 50 Ohms.
3. The unmodulated output power was measured with an RF Power meter.

#### MEASUREMENT RESULTS:

Manufacturer's Rated Output Power:

Switchable: 40 W and 10 W

Nominal 40 W	Measured	Variation (%)	Variation (dB)
406.2 MHz	42.4	6.0	0.3
418.05 MHz	42.6	6.4	0.3
429.9 MHz	40.6	1.4	0.1
450.1 MHz	39.6	-0.9	0.0
459.9 MHz	43.0	7.5	0.3
469.9 MHz	41.2	2.9	0.1
Measurement Uncertainty		± 0.6 dB	



Transmitter Output Power (Conducted) - continued

Nominal 10 W	Measured	Variation (%)	Variation (dB)
406.2 MHz	11.0	9.9	0.4
418.05 MHz	10.8	8.0	0.3
429.9 MHz	10.4	4.4	0.2
450.1 MHz	10.2	2.0	0.1
459.9 MHz	10.5	4.8	0.2
469.9 MHz	10.5	5.0	0.2
Measurement Uncertainty		± 0.6 dB	

LIMIT CLAUSES:

FCC 47 CFR 90.205 (s)

The output power shall not exceed by more than 20%... the manufacturer's rated output power for the particular transmitter specifically listed on the authorization.

RSS-119 5.4

The output power shall be within ±1.0 dB of the manufacturer's rated power.

## TRANSMITTER AUDIO FREQUENCY RESPONSE - PRE-EMPHASIS

SPECIFICATION: FCC 47 CFR 2.1047 (a)

GUIDE: TIA/EIA-603D 2.2.6

### MEASUREMENT PROCEDURE:

1. Refer Annex A for Equipment set up.
2. An audio input tone of 1000 Hz was applied with the level set to obtain 20% of maximum deviation. This was used as the 0 dB reference point.
3. The AF was varied while the audio level was held constant.
4. The response in dB relative to 1000 Hz was measured.

### MEASUREMENT RESULTS:

See the plots on the following pages for 12.5 kHz channel spacing tested at 40 W transmit power.


LIMIT CLAUSE: TIA/EIA-603D 3.2.6

MEASUREMENT UNCERTAINTY:  $\pm 1.5 \%$

### Transmitter Audio Frequency Response – Pre-emphasis


SPECIFICATION: FCC CFR 2.1047 (a)

Tx FREQUENCY: 406.2 MHz 12.5 kHz Channel Spacing



SPECIFICATION: FCC CFR 2.1047 (a)

Tx FREQUENCY: 418.05 MHz 12.5 kHz Channel Spacing




### Transmitter Audio Frequency Response – Pre-emphasis

SPECIFICATION: FCC CFR 2.1047 (a)

Tx FREQUENCY: 429.9 MHz


12.5 kHz Channel Spacing



SPECIFICATION: FCC CFR 2.1047 (a)

Tx FREQUENCY: 450.1 MHz

12.5 kHz Channel Spacing




### Transmitter Audio Frequency Response – Pre-emphasis

SPECIFICATION: FCC CFR 2.1047 (a)

Tx FREQUENCY: 459.9 MHz


12.5 kHz Channel Spacing



SPECIFICATION: FCC CFR 2.1047 (a)

Tx FREQUENCY: 469.9 MHz

12.5 kHz Channel Spacing



## TRANSMITTER MODULATION LIMITING

SPECIFICATION: FCC 47 CFR 2.1047 (b)

GUIDE: TIA/EIA-603D 2.2.3

### MEASUREMENT PROCEDURE:

1. Refer Annex A for Equipment set up.
2. The modulation response was measured at three audio frequencies while varying the input level.
3. Measurements were made for both Positive and Negative Deviation.

### MEASUREMENT RESULTS:

See the plots on the following pages for 12.5 kHz channel spacing.

LIMIT CLAUSE: TIA/EIA-603D 1.3.4.4


MEASUREMENT UNCERTAINTY:  $\pm 1.5 \%$

### Transmitter Modulation Limiting

SPECIFICATION: FCC CFR 2.1047 (b)

Tx FREQUENCY: 406.2 MHz


12.5 kHz Channel Spacing



SPECIFICATION: FCC CFR 2.1047 (b)

Tx FREQUENCY: 418.05 MHz

12.5 kHz Channel Spacing




### Transmitter Modulation Limiting

SPECIFICATION: FCC CFR 2.1047 (b)

Tx FREQUENCY: 429.9 MHz


12.5 kHz Channel Spacing



SPECIFICATION: FCC CFR 2.1047 (b)

Tx FREQUENCY: 450.1 MHz

12.5 kHz Channel Spacing






### Transmitter Modulation Limiting

SPECIFICATION: FCC CFR 2.1047 (b)

Tx FREQUENCY: 459.9 MHz


12.5 kHz Channel Spacing



SPECIFICATION: FCC CFR 2.1047 (b)

Tx FREQUENCY: 469.9 MHz

12.5 kHz Channel Spacing



## TRANSMITTER OCCUPIED BANDWIDTH AND SPECTRUM MASKS

SPECIFICATION: FCC 47 CFR 2.1049 (c) RSS-119 5.5

GUIDE: TIA/EIA-603D 2.2.11 (Analog)  
TIA-102.CAAA-C 2.2.5 (Digital)

### MEASUREMENT PROCEDURE:

1. Refer Annex A for Equipment Set up.
2. For analog measurements: The EUT was modulated by a 2500 Hz tone at an input level 16 dB above a level that produced 50% deviation. The input level was established at the frequency of maximum response of the audio modulating circuit.  
For Data measurements: The EUT was modulated with an internally generated pseudo random bit sequence at the appropriate Baud rates.
3. The Occupied Bandwidth was measured on the Spectrum Analyser, with bandwidth settings as follows.

Emission Mask D – Resolution Bandwidth = 100 Hz, Video Bandwidth = 1 kHz

### MEASUREMENT RESULTS:

See the plots on the following pages for 12.5 kHz channel spacing.

MEASUREMENT UNCERTAINTY 95%  $\pm 0.65\text{dB}$

LIMIT CLAUSE: FCC 47 CFR 90.210 RSS-119 5.5

### EMISSION MASKS

Emission Mask D 12.5 kHz Channel Spacing Analog, FFSK, Digital Voice/data

### DATA SPEED


Digital Voice/Data 12.5 kHz Channel Spacing 9600 bps & 12000 bps  
FFSK 12.5 kHz Channel Spacing 1200 bps & 2400 bps

### Occupied Bandwidth and Spectrum Masks

ANALOG VOICE


SPECIFICATION: FCC CFR 2.1049 (c) RSS-119 5.5

Tx FREQUENCY: 406.2 MHz 40 W 12.5 kHz Channel Spacing



**Analogue Modulation 406.2000MHz Mask D 40W**  
**RBW=100Hz, VBW=1000Hz, Detector Mode=Peak**  
**Result=Pass**

Tx FREQUENCY: 406.2 MHz 10 W 12.5 kHz Channel Spacing




**Analogue Modulation 406.2000MHz Mask D 10W**  
**RBW=100Hz, VBW=1000Hz, Detector Mode=Peak**  
**Result=Pass**

### Occupied Bandwidth and Spectrum Masks

ANALOG VOICE


SPECIFICATION: FCC CFR 2.1049 (c) RSS-119 5.5

Tx FREQUENCY: 418.05 MHz 40 W 12.5 kHz Channel Spacing



**Analogue Modulation 418.0500MHz Mask D 40W**  
**RBW=100Hz, VBW=1000Hz, Detector Mode=Peak**  
**Result=Pass**

Tx FREQUENCY: 418.05 MHz 10 W 12.5 kHz Channel Spacing




**Analogue Modulation 418.0500MHz Mask D 10W**  
**RBW=100Hz, VBW=1000Hz, Detector Mode=Peak**  
**Result=Pass**

### Occupied Bandwidth and Spectrum Masks

ANALOG VOICE


SPECIFICATION: FCC CFR 2.1049 (c) RSS-119 5.5

Tx FREQUENCY: 429.9 MHz 40 W 12.5 kHz Channel Spacing



**Analogue Modulation 429.9000MHz Mask D 40W**  
**RBW=100Hz, VBW=1000Hz, Detector Mode=Peak**  
**Result=Pass**

Tx FREQUENCY: 429.9 MHz 10 W 12.5 kHz Channel Spacing




**Analogue Modulation 429.9000MHz Mask D 10W**  
**RBW=100Hz, VBW=1000Hz, Detector Mode=Peak**  
**Result=Pass**

### Occupied Bandwidth and Spectrum Masks

ANALOG VOICE


SPECIFICATION: FCC CFR 2.1049 (c) RSS-119 5.5

Tx FREQUENCY: 450.1 MHz 40 W 12.5 kHz Channel Spacing



**Analogue Modulation 450.1000MHz Mask D 40W**  
**RBW=100Hz, VBW=1000Hz, Detector Mode=Peak**  
**Result=Pass**

Tx FREQUENCY: 450.1 MHz 10 W 12.5 kHz Channel Spacing




**Analogue Modulation 450.1000MHz Mask D 10W**  
**RBW=100Hz, VBW=1000Hz, Detector Mode=Peak**  
**Result=Pass**

### Occupied Bandwidth and Spectrum Masks

ANALOG VOICE


SPECIFICATION: FCC CFR 2.1049 (c) RSS-119 5.5

Tx FREQUENCY: 459.9 MHz 40 W 12.5 kHz Channel Spacing



**Analogue Modulation 459.9000MHz Mask D 40W**  
**RBW=100Hz, VBW=1000Hz, Detector Mode=Peak**  
**Result=Pass**

Tx FREQUENCY: 459.9 MHz 10 W 12.5 kHz Channel Spacing




**Analogue Modulation 459.9000MHz Mask D 10W**  
**RBW=100Hz, VBW=1000Hz, Detector Mode=Peak**  
**Result=Pass**

### Occupied Bandwidth and Spectrum Masks

ANALOG VOICE


SPECIFICATION: FCC CFR 2.1049 (c) RSS-119 5.5

Tx FREQUENCY: 469.9 MHz 40 W 12.5 kHz Channel Spacing



**Analogue Modulation 469.9000MHz Mask D 40W**  
**RBW=100Hz, VBW=1000Hz, Detector Mode=Peak**  
**Result=Pass**

Tx FREQUENCY: 469.9 MHz 10 W 12.5 kHz Channel Spacing



**Analogue Modulation 469.9000MHz Mask D 10W**  
**RBW=100Hz, VBW=1000Hz, Detector Mode=Peak**  
**Result=Pass**




### Occupied Bandwidth and Spectrum Masks


FFSK 1200 bps

SPECIFICATION: FCC CFR 2.1049 (c) RSS-119 5.5

Tx FREQUENCY: 406.2 MHz 40 W 12.5 kHz Channel Spacing



Tx FREQUENCY: 406.2 MHz 10 W 12.5 kHz Channel Spacing




### Occupied Bandwidth and Spectrum Masks


FFSK 1200 bps

SPECIFICATION: FCC CFR 2.1049 (c) RSS-119 5.5

Tx FREQUENCY: 418.05 MHz 40 W 12.5 kHz Channel Spacing



Tx FREQUENCY: 418.05 MHz 10 W 12.5 kHz Channel Spacing




### Occupied Bandwidth and Spectrum Masks


FFSK 1200 bps

SPECIFICATION: FCC CFR 2.1049 (c) RSS-119 5.5

Tx FREQUENCY: 429.9 MHz 40 W 12.5 kHz Channel Spacing



Tx FREQUENCY: 429.9 MHz 10 W 12.5 kHz Channel Spacing




### Occupied Bandwidth and Spectrum Masks


FFSK 1200 bps

SPECIFICATION: FCC CFR 2.1049 (c) RSS-119 5.5

Tx FREQUENCY: 450.1 MHz 40 W 12.5 kHz Channel Spacing



Tx FREQUENCY: 450.1 MHz 10 W 12.5 kHz Channel Spacing




### Occupied Bandwidth and Spectrum Masks


FFSK 1200 bps

SPECIFICATION: FCC CFR 2.1049 (c) RSS-119 5.5

Tx FREQUENCY: 459.9 MHz 40 W 12.5 kHz Channel Spacing



Tx FREQUENCY: 459.9 MHz 10 W 12.5 kHz Channel Spacing




### Occupied Bandwidth and Spectrum Masks


FFSK 1200 bps

SPECIFICATION: FCC CFR 2.1049 (c) RSS-119 5.5

Tx FREQUENCY: 469.9 MHz 40 W 12.5 kHz Channel Spacing



Tx FREQUENCY: 469.9 MHz 10 W 12.5 kHz Channel Spacing




### Occupied Bandwidth and Spectrum Masks


FFSK 2400 bps

SPECIFICATION: FCC CFR 2.1049 (c) RSS-119 5.5

Tx FREQUENCY: 406.2 MHz 40 W 12.5 kHz Channel Spacing



Tx FREQUENCY: 406.2 MHz 10 W 12.5 kHz Channel Spacing




### Occupied Bandwidth and Spectrum Masks


FFSK 2400 bps

SPECIFICATION: FCC CFR 2.1049 (c) RSS-119 5.5

Tx FREQUENCY: 418.05 MHz 40 W 12.5 kHz Channel Spacing



Tx FREQUENCY: 418.05 MHz 10 W 12.5 kHz Channel Spacing






### Occupied Bandwidth and Spectrum Masks


FFSK 2400 bps

SPECIFICATION: FCC CFR 2.1049 (c) RSS-119 5.5

Tx FREQUENCY: 429.9 MHz 40 W 12.5 kHz Channel Spacing



Tx FREQUENCY: 429.9 MHz 10 W 12.5 kHz Channel Spacing




### Occupied Bandwidth and Spectrum Masks


FFSK 2400 bps

SPECIFICATION: FCC CFR 2.1049 (c) RSS-119 5.5

Tx FREQUENCY: 450.1 MHz 40 W 12.5 kHz Channel Spacing



Tx FREQUENCY: 450.1 MHz 10 W 12.5 kHz Channel Spacing




### Occupied Bandwidth and Spectrum Masks


FFSK 2400 bps

SPECIFICATION: FCC CFR 2.1049 (c) RSS-119 5.5

Tx FREQUENCY: 459.9 MHz 40 W 12.5 kHz Channel Spacing



Tx FREQUENCY: 459.9 MHz 10 W 12.5 kHz Channel Spacing




### Occupied Bandwidth and Spectrum Masks


FFSK 2400 bps

SPECIFICATION: FCC CFR 2.1049 (c) RSS-119 5.5

Tx FREQUENCY: 469.9 MHz 40 W 12.5 kHz Channel Spacing



Tx FREQUENCY: 469.9 MHz 10 W 12.5 kHz Channel Spacing




### Occupied Bandwidth and Spectrum Masks

DMR


SPECIFICATION: FCC CFR 2.1049 (c) RSS-119 5.5

Tx FREQUENCY: 406.2 MHz 40 W 12.5 kHz Channel Spacing



**DMR 406.2000MHz Mask D 40W**  
**RBW=100Hz, VBW=1000Hz, Detector Mode=Peak**  
**Result=Pass**

Tx FREQUENCY: 406.2 MHz 10 W 12.5 kHz Channel Spacing




**DMR 406.2000MHz Mask D 10W**  
**RBW=100Hz, VBW=1000Hz, Detector Mode=Peak**  
**Result=Pass**

### Occupied Bandwidth and Spectrum Masks

DMR


SPECIFICATION: FCC CFR 2.1049 (c) RSS-119 5.5

Tx FREQUENCY: 418.05 MHz 40 W 12.5 kHz Channel Spacing



**DMR 418.0500MHz Mask D 40W**  
**RBW=100Hz, VBW=1000Hz, Detector Mode=Peak**  
**Result=Pass**

Tx FREQUENCY: 418.05 MHz 10 W 12.5 kHz Channel Spacing




**DMR 418.0500MHz Mask D 10W**  
**RBW=100Hz, VBW=1000Hz, Detector Mode=Peak**  
**Result=Pass**

### Occupied Bandwidth and Spectrum Masks

DMR


SPECIFICATION: FCC CFR 2.1049 (c) RSS-119 5.5

Tx FREQUENCY: 429.9 MHz 40 W 12.5 kHz Channel Spacing



**DMR 429.9000MHz Mask D 40W**  
**RBW=100Hz, VBW=1000Hz, Detector Mode=Peak**  
**Result=Pass**

Tx FREQUENCY: 429.9 MHz 10 W 12.5 kHz Channel Spacing




**DMR 429.9000MHz Mask D 10W**  
**RBW=100Hz, VBW=1000Hz, Detector Mode=Peak**  
**Result=Pass**

### Occupied Bandwidth and Spectrum Masks


DMR

SPECIFICATION: FCC CFR 2.1049 (c) RSS-119 5.5

Tx FREQUENCY: 450.1 MHz 40 W 12.5 kHz Channel Spacing



Tx FREQUENCY: 450.1 MHz 10 W 12.5 kHz Channel Spacing






### Occupied Bandwidth and Spectrum Masks

DMR


SPECIFICATION: FCC CFR 2.1049 (c) RSS-119 5.5

Tx FREQUENCY: 459.9 MHz 40 W 12.5 kHz Channel Spacing



**DMR 459.9000MHz Mask D 40W**  
**RBW=100Hz, VBW=1000Hz, Detector Mode=Peak**  
**Result=Pass**

Tx FREQUENCY: 459.9 MHz 10 W 12.5 kHz Channel Spacing




**DMR 459.9000MHz Mask D 10W**  
**RBW=100Hz, VBW=1000Hz, Detector Mode=Peak**  
**Result=Pass**

### Occupied Bandwidth and Spectrum Masks

DMR


SPECIFICATION: FCC CFR 2.1049 (c) RSS-119 5.5

Tx FREQUENCY: 469.9 MHz 40 W 12.5 kHz Channel Spacing



**DMR 469.9000MHz Mask D 40W**  
**RBW=100Hz, VBW=1000Hz, Detector Mode=Peak**  
**Result=Pass**

Tx FREQUENCY: 469.9 MHz 10 W 12.5 kHz Channel Spacing




**DMR 469.9000MHz Mask D 10W**  
**RBW=100Hz, VBW=1000Hz, Detector Mode=Peak**  
**Result=Pass**

### Occupied Bandwidth and Spectrum Masks


APCO P25 phase I C4FM

SPECIFICATION: FCC CFR 2.1049 (c) RSS-119 5.5

Tx FREQUENCY: 406.2 MHz 40 W 12.5 kHz Channel Spacing



Tx FREQUENCY: 406.2 MHz 10 W 12.5 kHz Channel Spacing




### Occupied Bandwidth and Spectrum Masks


APCO P25 phase I C4FM

SPECIFICATION: FCC CFR 2.1049 (c) RSS-119 5.5

Tx FREQUENCY: 418.05 MHz 40 W 12.5 kHz Channel Spacing



Tx FREQUENCY: 418.05 MHz 10 W 12.5 kHz Channel Spacing




### Occupied Bandwidth and Spectrum Masks


APCO P25 phase I C4FM

SPECIFICATION: FCC CFR 2.1049 (c) RSS-119 5.5

Tx FREQUENCY: 429.9 MHz 40 W 12.5 kHz Channel Spacing



Tx FREQUENCY: 429.9 MHz 10 W 12.5 kHz Channel Spacing




### Occupied Bandwidth and Spectrum Masks


APCO P25 phase I C4FM

SPECIFICATION: FCC CFR 2.1049 (c) RSS-119 5.5

Tx FREQUENCY: 450.1 MHz 40 W 12.5 kHz Channel Spacing



Tx FREQUENCY: 450.1 MHz 10 W 12.5 kHz Channel Spacing




### Occupied Bandwidth and Spectrum Masks


APCO P25 phase I C4FM

SPECIFICATION: FCC CFR 2.1049 (c) RSS-119 5.5

Tx FREQUENCY: 459.9 MHz 40 W 12.5 kHz Channel Spacing



Tx FREQUENCY: 459.9 MHz 10 W 12.5 kHz Channel Spacing




### Occupied Bandwidth and Spectrum Masks


APCO P25 phase I C4FM

SPECIFICATION: FCC CFR 2.1049 (c) RSS-119 5.5

Tx FREQUENCY: 469.9 MHz 40 W 12.5 kHz Channel Spacing



Tx FREQUENCY: 469.9 MHz 10 W 12.5 kHz Channel Spacing






### Occupied Bandwidth and Spectrum Masks

APCO P25 phase II H-CPM


SPECIFICATION: FCC CFR 2.1049 (c) RSS-119 5.5

Tx FREQUENCY: 406.2 MHz 40 W 12.5 kHz Channel Spacing



**P25II H-CPM 406.2000MHz Mask D 40W**  
**RBW=100Hz, VBW=1000Hz, Detector Mode=Peak**  
**Result=Pass**

Tx FREQUENCY: 406.2 MHz 10 W 12.5 kHz Channel Spacing




**P25II H-CPM 406.2000MHz Mask D 10W**  
**RBW=100Hz, VBW=1000Hz, Detector Mode=Peak**  
**Result=Pass**

### Occupied Bandwidth and Spectrum Masks


APCO P25 phase II H-CPM

SPECIFICATION: FCC CFR 2.1049 (c) RSS-119 5.5

Tx FREQUENCY: 418.05 MHz 40 W 12.5 kHz Channel Spacing



Tx FREQUENCY: 418.05 MHz 10 W 12.5 kHz Channel Spacing




### Occupied Bandwidth and Spectrum Masks


APCO P25 phase II H-CPM

SPECIFICATION: FCC CFR 2.1049 (c) RSS-119 5.5

Tx FREQUENCY: 429.9 MHz 40 W 12.5 kHz Channel Spacing



Tx FREQUENCY: 429.9 MHz 10 W 12.5 kHz Channel Spacing




### Occupied Bandwidth and Spectrum Masks


APCO P25 phase II H-CPM

SPECIFICATION: FCC CFR 2.1049 (c) RSS-119 5.5

Tx FREQUENCY: 450.1 MHz 40 W 12.5 kHz Channel Spacing



Tx FREQUENCY: 450.1 MHz 10 W 12.5 kHz Channel Spacing




### Occupied Bandwidth and Spectrum Masks


APCO P25 phase II H-CPM

SPECIFICATION: FCC CFR 2.1049 (c) RSS-119 5.5

Tx FREQUENCY: 459.9 MHz 40 W 12.5 kHz Channel Spacing



Tx FREQUENCY: 459.9 MHz 10 W 12.5 kHz Channel Spacing




### Occupied Bandwidth and Spectrum Masks


APCO P25 phase II H-CPM

SPECIFICATION: FCC CFR 2.1049 (c) RSS-119 5.5

Tx FREQUENCY: 469.9 MHz 40 W 12.5 kHz Channel Spacing



Tx FREQUENCY: 469.9 MHz 10 W 12.5 kHz Channel Spacing



## TRANSMITTER SPURIOUS EMISSIONS (CONDUCTED)

SPECIFICATIONS: FCC 47 CFR 2.1051

RSS-119 5.8

GUIDE: TIA/EIA-603D 2.2.13

### MEASUREMENT PROCEDURE:

1. Refer Annex A for equipment set up.
2. The frequency range examined was from the lowest frequency generated within the EUT, to a frequency higher than the 10<sup>th</sup> Harmonic: 100 kHz to Fc-BW  
Fc+ BW to 10Fc GHz
3. A Pre-scan is performed with a resolution bandwidth of 1 kHz, and a video bandwidth of 3 kHz. If any emissions are found to be within 20 dB of the limit a second measurement is made with the carrier modulated, and a resolution bandwidth of 10 kHz, and a video bandwidth of 30 kHz.

Spurious emissions which were attenuated by more than 20 dB below the limit were not recorded.

A photograph of the test set-up is included below.


### MEASUREMENT RESULTS:

See the tables and plots on the following pages for 12.5 kHz channel spacing.

LIMIT CLAUSES: FCC 47 CFR 90.210

RSS-119 5.8

Photo: Conducted Emissions Test Setup



Spurious Emissions (Tx Conducted)

SPECIFICATION: FCC CFR 2.1051

RSS-119 5.8

12.5 kHz Channel Spacing

378.1 MHz @ 40 W

Emission Mask D

Emission Frequency (MHz)	Level (dBm)	Level (dBc)
~	~	~

12.5 kHz Channel Spacing


378.1 MHz @ 10 W

Emission Mask D

Emission Frequency (MHz)	Level (dBm)	Level (dBc)
49.1520	-35.4	-75.4
Measurement Uncertainty:	≤12.75 GHz ± 3.0 dB	
No other emissions were detected at a level greater than 20 dB below the limit.		



Spurious Emissions (Tx Conducted)  
378.1 MHz 40 watts plots



Spurious Emissions (Tx Conducted)

SPECIFICATION: FCC CFR 2.1051

RSS-119 5.8

12.5 kHz Channel Spacing

406.2 MHz @ 40 W

Emission Mask D

Emission Frequency (MHz)	Level (dBm)	Level (dBc)
~	~	~


12.5 kHz Channel Spacing

406.2 MHz @ 10 W

Emission Mask D

Emission Frequency (MHz)	Level (dBm)	Level (dBc)
~	~	~
Measurement Uncertainty:	≤12.75 GHz ± 3.0 dB	
No emissions were detected at a level greater than 20 dB below the limit.		

Spurious Emissions (Tx Conducted)  
406.2 MHz 40 watts plots



Spurious Emissions (Tx Conducted)

SPECIFICATION: FCC CFR 2.1051

RSS-119 5.8

12.5 kHz Channel Spacing

418.05 MHz @ 40 W

Emission Mask D

Emission Frequency (MHz)	Level (dBm)	Level (dBc)
~	~	~


12.5 kHz Channel Spacing

418.05 MHz @ 10 W

Emission Mask D

Emission Frequency (MHz)	Level (dBm)	Level (dBc)
~	~	~
Measurement Uncertainty:	≤12.75 GHz ± 3.0 dB	
No emissions were detected at a level greater than 20 dB below the limit.		

Spurious Emissions (Tx Conducted)  
418.05 MHz 40 watts plots



Spurious Emissions (Tx Conducted)

SPECIFICATION: FCC CFR 2.1051

RSS-119 5.8

12.5 kHz Channel Spacing

429.9 MHz @ 40 W

Emission Mask D

Emission Frequency (MHz)	Level (dBm)	Level (dBc)
~	~	~


12.5 kHz Channel Spacing

429.9 MHz @ 10 W

Emission Mask D

Emission Frequency (MHz)	Level (dBm)	Level (dBc)
442.3681	-39.4	-79.4
Measurement Uncertainty:	$\leq 12.75$ GHz $\pm 3.0$ dB	
No other emissions were detected at a level greater than 20 dB below the limit.		

Spurious Emissions (Tx Conducted)  
429.9 MHz 40 watts plots



Spurious Emissions (Tx Conducted)

SPECIFICATION: FCC CFR 2.1051

RSS-119 5.8

12.5 kHz Channel Spacing                      450.1 MHz @ 40 W                      Emission Mask D


Emission Frequency (MHz)	Level (dBm)	Level (dBc)
442.3681	-37.4	-83.4

12.5 kHz Channel Spacing                      450.1 MHz @ 10 W                      Emission Mask D

Emission Frequency (MHz)	Level (dBm)	Level (dBc)
442.3681	-38.2	-78.2
Measurement Uncertainty:	≤12.75 GHz    ± 3.0 dB	
No other emissions were detected at a level greater than 20 dB below the limit.		



Spurious Emissions (Tx Conducted)  
450.1 MHz 40 watts plots



Spurious Emissions (Tx Conducted)

SPECIFICATION: FCC CFR 2.1051

RSS-119 5.8


12.5 kHz Channel Spacing                      459.9 MHz @ 40 W                      Emission Mask D

Emission Frequency (MHz)	Level (dBm)	Level (dBc)
477.4320	-33.9	-79.9

12.5 kHz Channel Spacing                      459.9 MHz @ 10 W                      Emission Mask D

Emission Frequency (MHz)	Level (dBm)	Level (dBc)
477.4320	-39.4	-79.4
Measurement Uncertainty:	≤12.75 GHz    ± 3.0 dB	
No other emissions were detected at a level greater than 20 dB below the limit.		

Spurious Emissions (Tx Conducted)  
459.9 MHz 40 watts plots



Spurious Emissions (Tx Conducted)

SPECIFICATION: FCC CFR 2.1051

RSS-119 5.8

12.5 kHz Channel Spacing

469.9 MHz @ 40 W

Emission Mask D

Emission Frequency (MHz)	Level (dBm)	Level (dBc)
442.3681	-39.3	-85.3
497.4320	-35.4	-81.4


12.5 kHz Channel Spacing

469.9 MHz @ 10 W

Emission Mask D

Emission Frequency (MHz)	Level (dBm)	Level (dBc)
~	~	~
Measurement Uncertainty:	$\leq 12.75$ GHz $\pm 3.0$ dB	
No other emissions were detected at a level greater than 20 dB below the limit.		

Spurious Emissions (Tx Conducted)  
469.9 MHz 40 watts plots



Spurious Emissions (Tx Conducted)

SPECIFICATION: FCC CFR 2.1051 RSS-119 5.8  
LIMITS: FCC 47 CFR 90.210 RSS-119 5.8

Carrier Output Power	Emission Mask D 12.5 kHz Channel Spacing $50 + 10 \text{ Log}_{10} (P_{\text{Watts}})$	
	40 W	-20 dBm
10 W	-20 dBm	-60 dBc

## TRANSMITTER SPURIOUS EMISSIONS (RADIATED)

SPECIFICATION: FCC 47 CFR 2.1053

GUIDE: TIA/EIA-603D 2.2.12

### MEASUREMENT PROCEDURE:

#### Initial Scan:

1. The EUT is placed in the S-Line TEM cell and emissions are measured from 30 MHz to 800 MHz. Any emission within 20 dB of the limit is then re-tested on the OATS.
2. The EUT is placed in the reverberation chamber and emissions are measured from 800 MHz to the upper frequency required. Any emission within 20 dB of the limit is then re-tested on the OATS.
3. The harmonics emissions up to the 6<sup>th</sup> harmonic of the fundamental frequency are measured on the OATS

#### OATS Measurement:

1. The EUT is placed on a wooden turntable at a distance of three metres from the test antenna. The output terminal is connected to an RF dummy load.
2. The test antenna is raised from 1 m to 4 m to obtain a maximum reading; the turntable is then rotated through 360° to obtain the maximum response of each spurious emission. Valid emissions are determined by switching the EUT on and off.
3. The EUT is then replaced by a signal generator and substitution antenna to make measurements by the substitution method.

### MEASUREMENT RESULTS:

See the tables on the following pages

LIMIT CLAUSE: FCC 47 CFR 90.210

Spurious Emissions (Tx Radiated) - Continued

SPECIFICATION: FCC CFR 2.1053

12.5 kHz Channel Spacing                      378.1 MHz @ 40 W                      Emission Mask D

Emission Frequency (MHz)	Level (dBm)	Level (dBc)
756.2	-38.47	-84.47

12.5 kHz Channel Spacing                      378.1 MHz @ 10 W                      Emission Mask D

Emission Frequency (MHz)	Level (dBm)	Level (dBc)
~	~	~
Measurement Uncertainty	± 4.6 dB	
No other emissions were detected at a level greater than 20 dB below the limit.		

12.5 kHz Channel Spacing                      406.2 MHz @ 40 W                      Emission Mask D

Emission Frequency (MHz)	Level (dBm)	Level (dBc)
812.398	-27.04	-73.04

12.5 kHz Channel Spacing                      406.2 MHz @ 10 W                      Emission Mask D

Emission Frequency (MHz)	Level (dBm)	Level (dBc)
812.398	-29.95	-69.95
Measurement Uncertainty	± 4.6 dB	
No other emissions were detected at a level greater than 20 dB below the limit.		

12.5 kHz Channel Spacing                      418.05 MHz @ 40 W                      Emission Mask D

Emission Frequency (MHz)	Level (dBm)	Level (dBc)
836.101	-27.01	-73.01

12.5 kHz Channel Spacing                      418.05 MHz @ 10 W                      Emission Mask D

Emission Frequency (MHz)	Level (dBm)	Level (dBc)
836.101	-29.26	-69.26
Measurement Uncertainty	± 4.6 dB	
No other emissions were detected at a level greater than 20 dB below the limit.		



Spurious Emissions (Tx Radiated) - Continued

12.5 kHz Channel Spacing                      429.9 MHz @ 40 W                      Emission Mask D

Emission Frequency (MHz)	Level (dBm)	Level (dBc)
859.798	-29.30	-75.30

12.5 kHz Channel Spacing                      429.9 MHz @ 10 W                      Emission Mask D

Emission Frequency (MHz)	Level (dBm)	Level (dBc)
859.798	-32.13	-72.13
Measurement Uncertainty	± 4.6 dB	
No other emissions were detected at a level greater than 20 dB below the limit.		

12.5 kHz Channel Spacing                      450.1 MHz @ 40 W                      Emission Mask D

Emission Frequency (MHz)	Level (dBm)	Level (dBc)
~	~	~

12.5 kHz Channel Spacing                      450.1 MHz @ 10 W                      Emission Mask D

Emission Frequency (MHz)	Level (dBm)	Level (dBc)
~	~	~
Measurement Uncertainty	± 4.6 dB	
No emissions were detected at a level greater than 20 dB below the limit.		

12.5 kHz Channel Spacing                      459.9 MHz @ 40 W                      Emission Mask D

Emission Frequency (MHz)	Level (dBm)	Level (dBc)
~	~	~

12.5 kHz Channel Spacing                      459.9 MHz @ 10 W                      Emission Mask D

Emission Frequency (MHz)	Level (dBm)	Level (dBc)
~	~	~
Measurement Uncertainty	± 4.6 dB	
No emissions were detected at a level greater than 20 dB below the limit.		

Spurious Emissions (Tx Radiated) - Continued

12.5 kHz Channel Spacing                      469.9 MHz @ 40 W                      Emission Mask D

Emission Frequency (MHz)	Level (dBm)	Level (dBc)
~	~	~

12.5 kHz Channel Spacing                      469.9 MHz @ 10 W                      Emission Mask D

Emission Frequency (MHz)	Level (dBm)	Level (dBc)
~	~	~
Measurement Uncertainty	± 4.6 dB	
No emissions were detected at a level greater than 20 dB below the limit.		

LIMITS:                      FCC CFR 2.1053

Carrier Output Power	Emission Mask D 12.5 kHz Channel Spacing 50 + 10 Log <sub>10</sub> (P <sub>Watts</sub> )	
40 W	-20 dBm	-66 dBc
10 W	-20 dBm	-60 dBc

Spurious Emissions (Tx Radiated) - Continued

Open Area Test Site Results:

12.5 kHz Channel Spacing

429.9 MHz @ 40 W


Emission Mask D

Harmonics Emission Frequency (MHz)	Level (dBm)	Level (dBc)
859.798	-29.30	-75.30
1289.7	-45.55	-91.55
1719.6	-45.71	-91.71
2149.5	-60.56	-106.56
2579.4	-59.28	-105.28
3009.3	-60.42	-106.42
Measurement Uncertainty	± 4.6 dB	

Sample Calculation	Measurement					Result	
	Reference	Substitution					
Emission Frequency (MHz)	Reference Level (dBm)	Sig-gen Level	Cable and Attenuator Gain	Antenna Gain (dBd)	Path and Boresight corrections	dBm	nW
859.798	-61.33	-12.05	-16.83	-0.35	-0.08	-29.30	1174.22
		A	B	C	D	E	

Result (E) = A+B+C+D

Photo: OATS Setup



## TRANSIENT FREQUENCY BEHAVIOR

SPECIFICATION: FCC 47 CFR 90.214 RSS-119 5.9

GUIDE: TIA/EIA-603D 2.2.19

### MEASUREMENT PROCEDURE:

1. Refer Annex A for equipment set up.
2. Measurements and plots were made following the TIA/EIA procedure.

### MEASUREMENT RESULTS:

See the tables and plots on the following pages for 12.5 kHz channel spacing.

LIMIT CLAUSES: FCC 47 CFR 90.214 RSS-119 5.9

### Transient Frequency Behaviour

SPECIFICATION: FCC 47 CFR 90.214

RSS-119 5.9

Tx FREQUENCY: 406.2 MHz 40 W

12.5 kHz Channel Spacing

406.2 MHz @ 40 W Tx

TRANSIENT RESPONSE PERIOD	CARRIER PEAK VARIATION FROM NORMAL	
	Key ON (kHz)	Key OFF (kHz)
t1	-0.5	N/A
t2	-0.6	N/A
t3	N/A	-0.5

Confirm that during periods t1 and t3 the frequency difference does not exceed the value of one channel separation.	YES	NO
	<input type="checkbox"/>	<input type="checkbox"/>
Confirm that during the period t2 the frequency difference does not exceed half a channel separation.	YES	NO
	<input type="checkbox"/>	<input type="checkbox"/>
Confirm that during the period t2 to t3 the frequency difference does not exceed the frequency error limit.	YES	NO
	<input type="checkbox"/>	<input type="checkbox"/>

Measurement Uncertainty: Frequency  $\pm$  130 Hz; Time  $\pm$  0.2%

LIMIT: FCC 47 CFR 90.214

TRANSIENT PERIODS	FREQUENCY RANGE	
	150 MHz – 174 MHz	421 MHz – 512 MHz
t1 (ms)	5 ms	10 ms
t2 (ms)	20 ms	25 ms
t3 (ms)	5 ms	10 ms

LIMIT: RSS-119 5.9

Transient Frequency Behaviour for Equipment Designed to Operate on 12.5 kHz Channels			
TRANSIENT PERIODS	Maximum Frequency Difference	FREQUENCY RANGE	
		138 – 174 MHz	406.1 – 470 MHz
t1 (ms)	$\pm$ 12.5 kHz	5 ms	10 ms
t2 (ms)	$\pm$ 6.25 kHz	20 ms	25 ms
t3 (ms)	$\pm$ 12.5 kHz	5 ms	10 ms

Note: RSS-119 5.9 - If the transmitter carrier output power rating is 6 Watts or less, the frequency difference during the time periods t1 and t3 may exceed the maximum frequency difference for these time periods.

### Transient Frequency Behaviour



SPECIFICATION: FCC 47 CFR 90.214

RSS-119 5.9

Tx FREQUENCY: 406.2 MHz

40 W

12.5 kHz Channel Spacing



### Transient Frequency Behaviour

SPECIFICATION: FCC 47 CFR 90.214

Tx FREQUENCY: 418.05 MHz                      40 W                      12.5 kHz Channel Spacing

418.05 MHz @ 40 W Tx

TRANSIENT RESPONSE PERIOD	CARRIER PEAK VARIATION FROM NORMAL	
	Key ON (kHz)	Key OFF (kHz)
t1	-0.6	N/A
t2	-0.8	N/A
t3	N/A	-0.6

Confirm that during periods t1 and t3 the frequency difference does not exceed the value of one channel separation.	YES	NO
	<input type="checkbox"/>	<input type="checkbox"/>
Confirm that during the period t2 the frequency difference does not exceed half a channel separation.	YES	NO
	<input type="checkbox"/>	<input type="checkbox"/>
Confirm that during the period t2 to t3 the frequency difference does not exceed the frequency error limit.	YES	NO
	<input type="checkbox"/>	<input type="checkbox"/>

Measurement Uncertainty: Frequency  $\pm$  130 Hz; Time  $\pm$  0.2%

LIMIT: FCC 47 CFR 90.214

TRANSIENT PERIODS	FREQUENCY RANGE	
	150 MHz – 174 MHz	421 MHz – 512 MHz
t1 (ms)	5 ms	10 ms
t2 (ms)	20 ms	25 ms
t3 (ms)	5 ms	10 ms

LIMIT: RSS-119 5.9



Transient Frequency Behaviour for Equipment Designed to Operate on 12.5 kHz Channels			
TRANSIENT PERIODS	Maximum Frequency Difference	FREQUENCY RANGE	
		138 – 174 MHz	406.1 – 470 MHz
t1 (ms)	$\pm$ 12.5 kHz	5 ms	10 ms
t2 (ms)	$\pm$ 6.25 kHz	20 ms	25 ms
t3 (ms)	$\pm$ 12.5 kHz	5 ms	10 ms

Note: RSS-119 5.9 - If the transmitter carrier output power rating is 6 Watts or less, the frequency difference during the time periods t1 and t3 may exceed the maximum frequency difference for these time periods,

### Transient Frequency Behavior

SPECIFICATION: FCC 47 CFR 90.214

Tx FREQUENCY: 418.05 MHz      40 W      12.5 kHz Channel Spacing





### Transient Frequency Behaviour

SPECIFICATION: FCC 47 CFR 90.214

RSS-119 5.9

Tx FREQUENCY: 429.9 MHz 40 W

12.5 kHz Channel Spacing

429.9 MHz @ 40 W Tx

TRANSIENT RESPONSE PERIOD	CARRIER PEAK VARIATION FROM NORMAL	
	Key ON (kHz)	Key OFF (kHz)
t1	-0.6	N/A
t2	-0.6	N/A
t3	N/A	-0.7

Confirm that during periods t1 and t3 the frequency difference does not exceed the value of one channel separation.	YES	NO
	<input type="checkbox"/>	<input type="checkbox"/>
Confirm that during the period t2 the frequency difference does not exceed half a channel separation.	YES	NO
	<input type="checkbox"/>	<input type="checkbox"/>
Confirm that during the period t2 to t3 the frequency difference does not exceed the frequency error limit.	YES	NO
	<input type="checkbox"/>	<input type="checkbox"/>

Measurement Uncertainty: Frequency  $\pm$  130 Hz; Time  $\pm$  0.2%

LIMIT: FCC 47 CFR 90.214

TRANSIENT PERIODS	FREQUENCY RANGE	
	150 MHz – 174 MHz	421 MHz – 512 MHz
t1 (ms)	5 ms	10 ms
t2 (ms)	20 ms	25 ms
t3 (ms)	5 ms	10 ms

LIMIT: RSS-119 5.9

Transient Frequency Behaviour for Equipment Designed to Operate on 12.5 kHz Channels			
TRANSIENT PERIODS	Maximum Frequency Difference	FREQUENCY RANGE	
		138 – 174 MHz	406.1 – 470 MHz
t1 (ms)	$\pm$ 12.5 kHz	5 ms	10 ms
t2 (ms)	$\pm$ 6.25 kHz	20 ms	25 ms
t3 (ms)	$\pm$ 12.5 kHz	5 ms	10 ms



Note: RSS-119 5.9 - If the transmitter carrier output power rating is 6 Watts or less, the frequency difference during the time periods t1 and t3 may exceed the maximum frequency difference for these time periods.

### Transient Frequency Behaviour

SPECIFICATION: FCC 47 CFR 90.214

RSS-119 5.9

Tx FREQUENCY: 429.9 MHz      40 W      12.5 kHz Channel Spacing



### Transient Frequency Behaviour

SPECIFICATION: FCC 47 CFR 90.214

RSS-119 5.9

Tx FREQUENCY: 450.1 MHz

40 W

12.5 kHz Channel Spacing

450.1 MHz @ 40 W Tx

TRANSIENT RESPONSE PERIOD	CARRIER PEAK VARIATION FROM NORMAL	
	Key ON (kHz)	Key OFF (kHz)
t1	1.2	N/A
t2	-0.7	N/A
t3	N/A	-0.5

Confirm that during periods t1 and t3 the frequency difference does not exceed the value of one channel separation.	YES	NO
	<input type="checkbox"/>	<input type="checkbox"/>
Confirm that during the period t2 the frequency difference does not exceed half a channel separation.	YES	NO
	<input type="checkbox"/>	<input type="checkbox"/>
Confirm that during the period t2 to t3 the frequency difference does not exceed the frequency error limit.	YES	NO
	<input type="checkbox"/>	<input type="checkbox"/>

Measurement Uncertainty: Frequency  $\pm$  130 Hz; Time  $\pm$  0.2%

LIMIT: FCC 47 CFR 90.214

TRANSIENT PERIODS	FREQUENCY RANGE	
	150 MHz – 174 MHz	421 MHz – 512 MHz
t1 (ms)	5 ms	10 ms
t2 (ms)	20 ms	25 ms
t3 (ms)	5 ms	10 ms

LIMIT: RSS-119 5.9

Transient Frequency Behaviour for Equipment Designed to Operate on 12.5 kHz Channels			
TRANSIENT PERIODS	Maximum Frequency Difference	FREQUENCY RANGE	
		138 – 174 MHz	406.1 – 470 MHz
t1 (ms)	$\pm$ 12.5 kHz	5 ms	10 ms
t2 (ms)	$\pm$ 6.25 kHz	20 ms	25 ms
t3 (ms)	$\pm$ 12.5 kHz	5 ms	10 ms



Note: RSS-119 5.9 - If the transmitter carrier output power rating is 6 Watts or less, the frequency difference during the time periods t1 and t3 may exceed the maximum frequency difference for these time periods.

### Transient Frequency Behaviour

SPECIFICATION: FCC 47 CFR 90.214

RSS-119 5.9

Tx FREQUENCY: 450.1 MHz 40 W 12.5 kHz Channel Spacing



### Transient Frequency Behaviour

SPECIFICATION: FCC 47 CFR 90.214

RSS-119 5.9

Tx FREQUENCY: 459.9 MHz

40 W

12.5 kHz Channel Spacing

459.9 MHz @ 40 W Tx

TRANSIENT RESPONSE PERIOD	CARRIER PEAK VARIATION FROM NORMAL	
	Key ON (kHz)	Key OFF (kHz)
t1	0.6	N/A
t2	-0.7	N/A
t3	N/A	-0.7

Confirm that during periods t1 and t3 the frequency difference does not exceed the value of one channel separation.	YES	NO
	<input type="checkbox"/>	<input type="checkbox"/>
Confirm that during the period t2 the frequency difference does not exceed half a channel separation.	YES	NO
	<input type="checkbox"/>	<input type="checkbox"/>
Confirm that during the period t2 to t3 the frequency difference does not exceed the frequency error limit.	YES	NO
	<input type="checkbox"/>	<input type="checkbox"/>

Measurement Uncertainty: Frequency  $\pm$  130 Hz; Time  $\pm$  0.2%

LIMIT: FCC 47 CFR 90.214

TRANSIENT PERIODS	FREQUENCY RANGE	
	150 MHz – 174 MHz	421 MHz – 512 MHz
t1 (ms)	5 ms	10 ms
t2 (ms)	20 ms	25 ms
t3 (ms)	5 ms	10 ms

LIMIT: RSS-119 5.9

Transient Frequency Behaviour for Equipment Designed to Operate on 12.5 kHz Channels			
TRANSIENT PERIODS	Maximum Frequency Difference	FREQUENCY RANGE	
		138 – 174 MHz	406.1 – 470 MHz
t1 (ms)	$\pm$ 12.5 kHz	5 ms	10 ms
t2 (ms)	$\pm$ 6.25 kHz	20 ms	25 ms
t3 (ms)	$\pm$ 12.5 kHz	5 ms	10 ms



Note: RSS-119 5.9 - If the transmitter carrier output power rating is 6 Watts or less, the frequency difference during the time periods t1 and t3 may exceed the maximum frequency difference for these time periods.

### Transient Frequency Behaviour

SPECIFICATION: FCC 47 CFR 90.214

RSS-119 5.9

Tx FREQUENCY: 459.9 MHz 40 W 12.5 kHz Channel Spacing



### Transient Frequency Behaviour

SPECIFICATION: FCC 47 CFR 90.214

RSS-119 5.9

Tx FREQUENCY: 469.9 MHz

40 W

12.5 kHz Channel Spacing

469.9 MHz @ 40 W Tx

TRANSIENT RESPONSE PERIOD	CARRIER PEAK VARIATION FROM NORMAL	
	Key ON (kHz)	Key OFF (kHz)
t1	-0.8	N/A
t2	-0.9	N/A
t3	N/A	-0.5

Confirm that during periods t1 and t3 the frequency difference does not exceed the value of one channel separation.	YES	NO
	<input type="checkbox"/>	<input type="checkbox"/>
Confirm that during the period t2 the frequency difference does not exceed half a channel separation.	YES	NO
	<input type="checkbox"/>	<input type="checkbox"/>
Confirm that during the period t2 to t3 the frequency difference does not exceed the frequency error limit.	YES	NO
	<input type="checkbox"/>	<input type="checkbox"/>

Measurement Uncertainty: Frequency  $\pm$  130 Hz; Time  $\pm$  0.2%

LIMIT: FCC 47 CFR 90.214

TRANSIENT PERIODS	FREQUENCY RANGE	
	150 MHz – 174 MHz	421 MHz – 512 MHz
t1 (ms)	5 ms	10 ms
t2 (ms)	20 ms	25 ms
t3 (ms)	5 ms	10 ms

LIMIT: RSS-119 5.9

Transient Frequency Behaviour for Equipment Designed to Operate on 12.5 kHz Channels			
TRANSIENT PERIODS	Maximum Frequency Difference	FREQUENCY RANGE	
		138 – 174 MHz	406.1 – 470 MHz
t1 (ms)	$\pm$ 12.5 kHz	5 ms	10 ms
t2 (ms)	$\pm$ 6.25 kHz	20 ms	25 ms
t3 (ms)	$\pm$ 12.5 kHz	5 ms	10 ms



Note: RSS-119 5.9 - If the transmitter carrier output power rating is 6 Watts or less, the frequency difference during the time periods t1 and t3 may exceed the maximum frequency difference for these time periods.

### Transient Frequency Behaviour

SPECIFICATION: FCC 47 CFR 90.214

RSS-119 5.9

Tx FREQUENCY: 469.9 MHz 40 W 12.5 kHz Channel Spacing





TRANSMITTER FREQUENCY STABILITY - TEMPERATURE

SPECIFICATION: FCC 47 CFR 2.1055 (a) (1)

RSS-119 5.3

GUIDE: TIA/EIA-603D 2.2.2

MEASUREMENT PROCEDURE:

1. Refer Annex A for equipment set up.
2. The EUT was tested for frequency error from -30° C to +50° C in 10° C increments
3. The frequency error was recorded in parts per million (ppm).

MEASUREMENT RESULTS:

See the plots on the following pages for 12.5 kHz channel spacing.







Temperature (°C)	Error (ppm)					
	406.2 MHz	418.05 MHz	429.9 MHz	450.1 MHz	459.9 MHz	469.9 MHz
-30	-0.09	-0.08	-0.07	-0.07	-0.08	-0.09
-20	-0.07	-0.07	-0.06	-0.05	-0.03	-0.01
-10	0.00	0.00	0.00	-0.02	-0.03	-0.04
0	-0.06	-0.06	-0.07	-0.09	-0.10	-0.10
10	-0.07	-0.07	-0.06	-0.06	-0.05	-0.05
20	0.00	0.00	0.00	0.00	-0.01	-0.01
30	-0.05	-0.05	-0.06	-0.07	-0.08	-0.08
40	-0.10	-0.10	-0.10	-0.10	-0.10	-0.09
50	-0.04	-0.04	-0.03	-0.03	-0.02	-0.01
Measurement Uncertainty				± 7 x 10 <sup>-8</sup>		

LIMIT: FCC 47 CFR 90.213

RSS-119 5.3

Channel Spacing (kHz)	Frequency Error (ppm)					
	406.2 MHz	418.05 MHz	429.9 MHz	450.1 MHz	459.9 MHz	469.9 MHz
12.5	2.0	2.0	2.5	2.5	2.5	2.5

### Transmitter Frequency Stability – Temperature



TRANSMITTER FREQUENCY STABILITY - VOLTAGE

SPECIFICATION: FCC 47 CFR 2.1055 (d) (1)

RSS-119 5.3

GUIDE: TIA/EIA-603D 2.2.2

MEASUREMENT PROCEDURE:

1. Refer Annex A for equipment set up.
2. The EUT was tested for frequency error at an input voltage to the radio of 85% to 115%.
3. The frequency error was recorded in parts per million (ppm).

MEASUREMENT RESULTS:

	FREQUENCY ERROR (ppm) for 12.5 kHz		
	13.8 V <sub>DC</sub>	11.7 V <sub>DC</sub>	15.9 V <sub>DC</sub>
406.2 MHz	-0.10	-0.10	-0.10
418.05 MHz	-0.01	-0.01	-0.02
429.9 MHz	0.00	-0.01	-0.01
450.1 MHz	-0.05	-0.05	-0.06
459.9 MHz	-0.02	-0.05	-0.07
469.9 MHz	-0.01	-0.01	-0.02
Measurement Uncertainty	± 7 x 10 <sup>-8</sup>		

LIMIT CLAUSES: FCC 47 CFR 90.213

RSS-119 5.3

Channel Spacing (kHz)	Frequency Error (ppm)					
12.5	406.2 MHz	418.05 MHz	429.9 MHz	450.1 MHz	459.9 MHz	469.9 MHz
	2.0	2.0	2.5	2.5	2.5	2.5

## RECEIVER SPURIOUS EMISSIONS (CONDUCTED)

SPECIFICATION: RSS-119 5.11

GUIDE: TIA/EIA-603D 2.1.2

### MEASUREMENT PROCEDURE:

1. Refer Annex A for Equipment set up diagram.
2. The frequency range examined was from 30 MHz to 3 times highest tunable frequency.
3. Spurious emissions which were attenuated more than 20 dB below the limit were not recorded.

378.1 MHz Receive		
Emission Frequency (MHz)	Level (nW)	Level (dBm)
~	~	~
Measurement Uncertainty	≤12.75 GHz ± 3.0 dB	
No emissions were detected within 20 dB of Limit.		

406.2 MHz Receive		
Emission Frequency (MHz)	Level (nW)	Level (dBm)
~	~	~
Measurement Uncertainty	≤12.75 GHz ± 3.0 dB	
No emissions were detected within 20 dB of Limit.		

418.05 MHz Receive		
Emission Frequency (MHz)	Level (nW)	Level (dBm)
~	~	~
Measurement Uncertainty	≤12.75 GHz ± 3.0 dB	
No emissions were detected within 20 dB of Limit.		

429.9 MHz Receive		
Emission Frequency (MHz)	Level (nW)	Level (dBm)
~	~	~
Measurement Uncertainty	≤12.75 GHz ± 3.0 dB	
No emissions were detected within 20 dB of Limit.		

Receiver Spurious Emissions (Conducted) – Continued

450.1 MHz Receive		
Emission Frequency (MHz)	Level (nW)	Level (dBm)
~	~	~
Measurement Uncertainty	≤12.75 GHz ± 3.0 dB	
No emissions were detected within 20 dB of Limit.		

459.9 MHz Receive		
Emission Frequency (MHz)	Level (nW)	Level (dBm)
~	~	~
Measurement Uncertainty	≤12.75 GHz ± 3.0 dB	
No emissions were detected within 20 dB of Limit.		

469.9 MHz Receive		
Emission Frequency (MHz)	Level (nW)	Level (dBm)
~	~	~
Measurement Uncertainty	≤12.75 GHz ± 3.0 dB	
No emissions were detected within 20 dB of Limit.		

LIMIT CLAUSE: RSS-Gen 6(b)

LIMIT	30 → 1000 MHz	2 nW	- 57 dBm
	> 1000 MHz	5 nW	- 53 dBm

## TEST EQUIPMENT LIST


Equipment Type	Information	Manufacturer	Model No	Serial No#	Tait ID	Cal Due
Antenna	Reference Dipoles	Emco	3121C DB1	9510-1164	E3559	14-Apr-19
Antenna	18GHz DRG	Emco	DRG3115	9512-4638	E3560	15-May-20
Antenna	18GHz DRG	Emco	DRG3115	2084	E3076	
Antenna	Log Periodic	Schwarzbeck	VUSLP	9111-219	E4617	
Antenna	Reverb - 1-18GHz DRG	Schwarzbeck	BBHA 9120 D	9120D-885	E4857	
Antenna	Reverb - 1-18GHz DRG	Schwarzbeck	BBHA 9120 D	9120D-884	E4858	
Audio Analyser	TREVA1	Hewlett Packard	HP8903A	2437A04625	E4986	28-Sep-18
Coax Cable	2m Black	Suhner	RG214HF/Nm/ Nm/2000	TeltestBlack2	E4623	20-Dec-18
Coax Cable	2m Black	Suhner	RG214HF/Nm/ Nm/2000	TeltestBlack3	E4624	20-Dec-18
Coax Cable	2m Black	Suhner	RG214HF/Nm/ Nm/2000	TeltestBlack4	E4653	21-Dec-18
Coax Cable	OATS Turntable Cable 1	Intelcom	RG214	OATS1	E4621	1-Jan-19
Coax Cable	OATS Tower Cable	Intelcom	RG214	OATS2	E4622	1-Jan-19
Coax Cable	2m Black	Suhner	RG214HF/Nm/ Nm/2000	TeltestBlack5	E4850	20-Dec-18
Coax Cable	2m Black	Suhner	RG214HF/Nm/ Nm/2000	TeltestBlack6	E4849	20-Dec-18
Coax Cable	Reverb - 4.5m Multiflex 141	TeltestBlue6	MF 141	TeltestBlue6	E4843	20-Dec-18
Coax Cable	Reverb - 2m Multiflex 141	TeltestBlue5	MF 141	TeltestBlue5	E4844	20-Dec-18
Coax Cable	Reverb - 2m Multiflex 141	TeltestBlue4	MF 141	TeltestBlue4	E4845	20-Dec-18
Coax Cable	Reverb - 1m Multiflex 141	TeltestBlue2	MF 141	TeltestBlue2	E4847	20-Dec-18
Coax Cable	Reverb - 1m Multiflex 141	TeltestBlue1	MF 141	TeltestBlue1	E4848	20-Dec-18
Coax Cable	OATS Turntable Cable 2	Intelcom	RG215	OATS3	E4995	1-Jan-19
Coax Cable	2m Black	Suhner	RG214HF/Nm/ Nm/2000	TeltestBlack7	E5004	1-Jan-19
Environ. Chamber	Chest	Contherm	Chest	E3397	E3397	1-Aug-18
Modulation Analyser	TREVA1	Hewlett Packard	HP8901B (Opt 002)	2441A00393	E3073	3-Oct-18
Modulation Analyser	Includes Audio Analyser	Rohde & Schwarz	FMA0852.8500.52	842541/001	E3554	8-Mar-19
Multimeter		Fluke	77	35069359	E3237	26-Sep-18
OATS	NSA	Tait				9-Jul-18
OATS	Antenna Tower	Electrometrics	EM-4720-2	112	E4447	
OATS	Controller	Electrometrics	EM-4700	119	E4445	
OATS	Turntable	Electrometrics	EM-4704A	105	E4446	
OATS	FCC Listing Registration			837095		
Oscilloscope	100 MHz Digital	Tektronics	TDS340	BO13611	E3585	28-Sep-19
Power Meter	TREVA1 Power Head for HP8901	Hewlett Packard	HP11722A	3111A05573	E7054	30-Sep-18
Power Supply		Rohde & Schwarz	NGS M32/10 192.0810.31	Fnr 434	E3556	24-Apr-19
Power Supply	60V/50A/1000W	Hewlett Packard	HP6012B	2524A00616	E3712	30-Sep-19
Power Supply	60V/25A	Agilent	N5767A	3111A05573	E4979	10-Oct-18
Power Supply	40V/38A	Agilent	N5766A	US09E4663L	E4719	26-Sep-19
RF Amplifier	+21.7 dB 1GHz	Tait	ZFL-1000LN	E3660	E3360	17-Apr-19
RF Amplifier	Pre-amplifier	Agilent	87405C	MY47010688	E4941	9-Oct-18
RF Attenuator	30dB 350W	Weinschel	67-30-33	BR0531	E4280	20-Dec-18

TELTEST Laboratories  
Tait Ltd  
Report Number 3901

RF Attenuator	10dB 50W	Weinschel	24-10-34	AZ0401	E3388	20-Dec-18
RF Attenuator	20dB 25W	Weinschel	33-20-33	BD5871	E3673	20-Dec-18
RF Attenuator	TREVA1 3dB	Weinschel	Model 1	BL9958	E4081	20-Dec-18
RF Attenuator	TREVA 1 20dB 150W	Weinschel	40-20-23	MF817	E4082	20-Dec-18
RF Chamber	S-LINE TEM CELL	Rohde & Schwarz	1089.9296.02	338232/003	E3636	
RF Chamber	Reverb - Stirrer controller for reverb chamber	Teseq	Stirrer Controller	29765.1	E4854	
RF Chamber	Reverb - 0.5 - 18GHz Reverberation Chamber	Teseq	RVC XS	29765	E4855	
RF Combiner	TREVA1	Minicircuits	ZFSC-4-1	-	E4083	
RF Load	50W	Weinschel	F1426	BF0487	E3675	20-Dec-18
Signal Generator	Analog 1GHz	Hewlett Packard	HP8648A	3430U00344	E3579	25-Sep-18
Signal Generator	Analog 4GHz	Agilent	E4422B	GB40050320	E3788	28-Sep-18
Signal Generator	TREVA1 Analog 3.2GHz	Agilent	E8663D	MY50420224	E4908	20-Oct-18
Spectrum Analyser	26.5GHz	Agilent	PXA N9030A	MY49432161	E4907	18-Oct-18
Spectrum Analyser	13.2GHz	Agilent	E4445A	MY42510072	E4139	15-Oct-18
Temp & Humidity Datalogger		Hobo	U21-011	10134276	E4981	22-Apr-19
Testware	Conducted Emissions		March 2019	-	-	
Testware	Frequency Vs Temperature		April 2021	-	-	
Testware	Occupied Bandwidth		5/10/2012	-	-	
Testware	Radiated Emissions		September 2015	-	-	
Testware	Reverb Emissions		March 2020	-	-	
Testware	Sideband Spectrum		February 2017	-	-	
Testware	S-Line Radiated Emissions		May 2016	-	-	
Testware	TREVA		April 2018	-	-	
TREVA 1		Teltest	-	1	-	19-Oct-18

\* NOTE: Items without calibration dates are calibrated immediately before use, or set using calibrated instruments.

## ANNEX A – TEST SETUP DETAILS



All other testing is performed using the Teltest Radio **EVA**luation system (TREVA), which is configured as shown below. The Spectrum Analyser is connected to the EUT via the attenuator network for Conducted Emissions testing, and Occupied Bandwidth.

