Summary FCC ID: CASTPDH5A / IC: 737A-TPDH5A

A) 3 antenna disclosed	B) 2 batt. disclosed	C) 10 body-mount disclosed	D) 10 audio access. disclosed	E) keypad / disp
1) Helical TPA-AN-013, 400-470 MHz 2) Whip TPA-AN-011, 400-470 MHz	1) 7.4V 1880mAh Low Capacity Li-ion 2) 7.4V 2400mAh High Capacity Li-ion	0) none 1) A Battery Clip 14mm 2) B Nylon Case + Battery Clip 14mm 3) C Nylon Case Belt Loop 7mm 4) D Nylon Case + D-Stud Spring Clip 31mm 5) E Nylon Case + D-Stud Belt Loop 42mm 6) F Leather Case + Battery Clip 14mm 7) G Leather Case Spring Clip 17mm 8) H Leather Case + D-Stud Spring Clip 31mm 9) I Leather Case + D-Stud Belt Loop 42mm 10) J Leather Case Belt Loop 10mm	0) none 1) Speaker-Microphone CFAA 2) Speaker-Microphone DMAA 3) Speaker-Microphone BFAA 4) Headset-Microphone EFAA 5) Headset-Microphone DEAA 6) Earphone-Microphone CBAA 7) Earphone-Microphone BAAA	1) 16-Key 2) 4-Key

	I	II	III	IV	V	VI	VII	VIII	IX	X	XI	XII	XIII
Page	Body or Face	A) ant.	B) batt.	C) b-w	D) audio	E) kypd	Front or Back	F1 406.2	F2 422.125	F3 438.05	F4 453.975	F5 469.9	Plot No.
18	F	2	2	0	0	1	F			1.97			1
18	F	1	2	0	0	1	F			1.97			3
18	F	1	1	0	0	1	F			2.03			4
18	F	1	1	0	0	2	F			2.045			5
19	B	2	1	1	3	1	B			2.96			6
19	B	2	1	2	3	1	B			3.1			7
19	B	2	1	3	3	1	B			2.77			8
19	B	2	1	4	3	1	B			2.015			9
19	B	2	1	5	3	1	B			0.905			10
19	B	2	1	6	3	1	B			3.125			11
19	B	2	1	7	3	1	B			2.345			12
19	B	2	1	8	3	1	B			1.755			13
19	B	2	1	9	3	1	B			0.81			14
19	B	2	1	10	3	1	B			2.26			15
19	B	2	2	6	3	1	B			2.54			16
19	B	2	1	6	4	1	B			3.095			17
19	B	2	1	6	5	1	B			**3.26**			18
19	B	2	1	6	5	2	B			3.055			19
20	B	1	1	1	3	1	B			2.62			22
20	B	1	1	2	3	1	B			2.735			23
20	B	1	1	3	3	1	B			2.69			24
20	B	1	1	4	3	1	B			1.93			25
20	B	1	1	5	3	1	B			0.925			26
20	B	1	1	6	3	1	B			2.73			27
20	B	1	1	7	3	1	B			2.07			28
20	B	1	1	8	3	1	B			1.705			29
20	B	1	1	9	3	1	B			0.795			30
20	B	1	1	10	3	1	B			1.985			31

FCC ONLINE TABLE OF FREQUENCY ALLOCATIONS, Revised on April 16, 2013

MHz	FCC Rule Part(s)
406.1-410	**90**
410-420	**90, 95I**
420-450	**90, 95I, 97**
450-454	**74D, 74H, 90, 95I**
454-455	22, 80, 95I
455-456	74D, 74H, 95I
456-460	**22, 80, 90, 95I**
460-462.5375	**90**
462.5375-462.7375	95
462.7375-467.5375	**80, 90**
467.5375-467.7375	80, 95
467.7375-470	**80, 90**
470-512	**22, 73, 74G, 74H, 90**