

APPENDIX B Plots Of The SAR Measurements

Plots of the measured SAR distributions inside the phantom are given in this Appendix for all tested configurations. The spatial peak SAR values were assessed with the procedure described in this report.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M140227 450 MHz Body Worn Antenna Whip FCC.da52:0

DUT Name: Tait PTT Transceiver, Type: TPDH7A, Serial: 25543015

Configuration: Body Battery Clip 16 Key 24-03-14

Communication System: 0 - CW (0); Communication System Band: Tait 481 MHz FCC; Frequency: 450.1 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=450$ MHz; $\sigma = 0.94$ S/m; $\epsilon_r = 56.4$; $\rho = 1000.0$ g/cm³
 Phantom section: Flat Section

DASY Configuration:


Probe: ET3DV6 - SN1380; ConvF: (7.49,7.49,7.49); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Body Battery Clip 16 Key 24-03-14/Channel 1 Test/Area Scan (81x221x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 8.510 W/kg


Body Battery Clip 16 Key 24-03-14/Channel 1 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 63.410 V/m; **Power Drift = 0.06 dB**

Averaged SAR: SAR(1g) = 8.090 W/kg; SAR(10g) = 5.770 W/kg

Maximum value of SAR (interpolated) = 11.200 W/kg



SAR Measurement Plot 1



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M140227 450 MHz Body Worn Antenna Whip FCC.da52:0

DUT Name: Tait PTT Transceiver, Type: TPDH7A, Serial: 25543015

Configuration: Body Battery Clip 16 Key 24-03-14

Communication System: 0 - CW (0); Communication System Band: Tait 481 MHz FCC; Frequency: 465.5 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=465.5$ MHz; $\sigma = 0.94$ S/m; $\epsilon_r = 56.1$; $\rho = 1000.0\text{g/cm}^3$
 Phantom section: Flat Section

DASY Configuration:


Probe: ET3DV6 - SN1380; ConvF: (7.49,7.49,7.49); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Body Battery Clip 16 Key 24-03-14/Channel 2 Test/Area Scan (81x221x1): Interpolated grid: $dx=1.5$ mm, $dy=1.5$ mm; Maximum value of SAR (interpolated) = 8.910 W/kg

Body Battery Clip 16 Key 24-03-14/Channel 2 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: $dx=1.6$ mm, $dy=1.6$ mm, $dz=1.0$ mm; Reference Value = 66.822 V/m; **Power Drift = -0.18 dB**

Averaged SAR: SAR(1g) = 8.740 W/kg; SAR(10g) = 6.170 W/kg

Maximum value of SAR (interpolated) = 12.300 W/kg




0 dB = 8.91 W/kg = 9.50 dBW/kg

SAR Measurement Plot 2



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M140227 450 MHz Body Worn Antenna Whip FCC.da52:0

DUT Name: Tait PTT Transceiver, Type: TPDH7A, Serial: 25543015

Configuration: Body Battery Clip 16 Key 24-03-14

Communication System: 0 - CW (0); Communication System Band: Tait 481 MHz FCC; Frequency: 481.0 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=481$ MHz; $\sigma = 0.95$ S/m; $\epsilon_r = 55.8$; $\rho = 1000.0$ g/cm³
 Phantom section: Flat Section

DASY Configuration:


Probe: ET3DV6 - SN1380; ConvF: (7.49,7.49,7.49); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Body Battery Clip 16 Key 24-03-14/Channel 3 Test/Area Scan (81x221x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 10.400 W/kg

Body Battery Clip 16 Key 24-03-14/Channel 3 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 69.984 V/m; **Power Drift = -0.14 dB**

Averaged SAR: SAR(1g) = 10.100 W/kg; SAR(10g) = 7.110 W/kg

Maximum value of SAR (interpolated) = 14.400 W/kg




0 dB = 10.4 W/kg = 10.17 dBW/kg

SAR Measurement Plot 3



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M140227 450 MHz Body Worn Antenna Whip FCC.da52:0

DUT Name: Tait PTT Transceiver, Type: TPDH7A, Serial: 25543015

Configuration: Body Battery Clip 16 Key 24-03-14

Communication System: 0 - CW (0); Communication System Band: Tait 481 MHz FCC; Frequency: 496.5 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=496.5$ MHz; $\sigma = 0.96$ S/m; $\epsilon_r = 55.4$; $\rho = 1000.0\text{g/cm}^3$
 Phantom section: Flat Section

DASY Configuration:


Probe: ET3DV6 - SN1380; ConvF: (7.49,7.49,7.49); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Body Battery Clip 16 Key 24-03-14/Channel 4 Test/Area Scan (81x221x1): Interpolated grid: $dx=1.5$ mm, $dy=1.5$ mm; Maximum value of SAR (interpolated) = 9.920 W/kg

Body Battery Clip 16 Key 24-03-14/Channel 4 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: $dx=1.6$ mm, $dy=1.6$ mm, $dz=1.0$ mm; Reference Value = 68.620 V/m; **Power Drift = -0.19 dB**

Averaged SAR: SAR(1g) = 9.440 W/kg; SAR(10g) = 6.540 W/kg

Maximum value of SAR (interpolated) = 13.600 W/kg




0 dB = 9.92 W/kg = 9.97 dBW/kg

SAR Measurement Plot 4



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M140227 450 MHz Body Worn Antenna Whip FCC.da52:0

DUT Name: Tait PTT Transceiver, Type: TPDH7A, Serial: 25543015

Configuration: Body Battery Clip 16 Key 24-03-14

Communication System: 0 - CW (0); Communication System Band: Tait 481 MHz FCC; Frequency: 511.9 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=512$ MHz; $\sigma = 0.96$ S/m; $\epsilon_r = 55.2$; $\rho = 1000.0$ g/cm³
 Phantom section: Flat Section

DASY Configuration:


Probe: ET3DV6 - SN1380; ConvF: (7.49,7.49,7.49); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Body Battery Clip 16 Key 24-03-14/Channel 5 Test/Area Scan (81x221x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 6.260 W/kg


Body Battery Clip 16 Key 24-03-14/Channel 5 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 52.856 V/m; **Power Drift = -0.20 dB**

Averaged SAR: SAR(1g) = 6.100 W/kg; SAR(10g) = 4.220 W/kg

Maximum value of SAR (interpolated) = 8.870 W/kg



SAR Measurement Plot 5



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M140227 450 MHz Body Worn Antenna Whip FCC.da52:1

DUT Name: Tait PTT Transceiver, Type: TPDH7A, Serial: 25543015

Configuration: Body Nylon Case Battery Clip 16 Key 24-03-14

Communication System: 0 - CW (0); Communication System Band: Tait 481 MHz FCC; Frequency: 450.1 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=450$ MHz; $\sigma = 0.94$ S/m; $\epsilon_r = 56.4$; $\rho = 1000.0\text{g/cm}^3$
 Phantom section: Flat Section


DASY Configuration:

Probe: ET3DV6 - SN1380; ConvF: (7.49,7.49,7.49); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)


Body Nylon Case Battery Clip 16 Key 24-03-14/Channel 1 Test/Area Scan (81x221x1): Interpolated grid: $dx=1.5$ mm, $dy=1.5$ mm; Maximum value of SAR (interpolated) = 9.480 W/kg

Body Nylon Case Battery Clip 16 Key 24-03-14/Channel 1 Test/Zoom Scan (26x26x36)/Cube 0: Interpolated grid: $dx=1.6$ mm, $dy=1.6$ mm, $dz=1.0$ mm; Reference Value = 71.869 V/m; **Power Drift = - 0.19 dB**

Averaged SAR: SAR(1g) = 9.340 W/kg; SAR(10g) = 6.630 W/kg
 Maximum value of SAR (interpolated) = 13.000 W/kg



SAR Measurement Plot 6



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M140227 450 MHz Body Worn Antenna Whip FCC.da52:1

DUT Name: Tait PTT Transceiver, Type: TPDH7A, Serial: 25543015

Configuration: Body Nylon Case Battery Clip 16 Key 24-03-14

Communication System: 0 - CW (0); Communication System Band: Tait 481 MHz FCC; Frequency: 465.5 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=465.5$ MHz; $\sigma = 0.94$ S/m; $\epsilon_r = 56.1$; $\rho = 1000.0\text{g/cm}^3$
 Phantom section: Flat Section


DASY Configuration:

Probe: ET3DV6 - SN1380; ConvF: (7.49,7.49,7.49); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)


Body Nylon Case Battery Clip 16 Key 24-03-14/Channel 2 Test/Area Scan (81x221x1): Interpolated grid: $dx=1.5$ mm, $dy=1.5$ mm; Maximum value of SAR (interpolated) = 9.170 W/kg

Body Nylon Case Battery Clip 16 Key 24-03-14/Channel 2 Test/Zoom Scan (26x26x36)/Cube 0: Interpolated grid: $dx=1.6$ mm, $dy=1.6$ mm, $dz=1.0$ mm; Reference Value = 77.247 V/m; **Power Drift = - 0.09 dB**

Averaged SAR: SAR(1g) = 9.180 W/kg; SAR(10g) = 6.490 W/kg
 Maximum value of SAR (interpolated) = 12.900 W/kg



SAR Measurement Plot 7



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M140227 450 MHz Body Worn Antenna Whip FCC.da52:1

DUT Name: Tait PTT Transceiver, Type: TPDH7A, Serial: 25543015

Configuration: Body Nylon Case Battery Clip 16 Key 24-03-14

Communication System: 0 - CW (0); Communication System Band: Tait 481 MHz FCC; Frequency: 481.0 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=481$ MHz; $\sigma = 0.95$ S/m; $\epsilon_r = 55.8$; $\rho = 1000.0$ g/cm³
 Phantom section: Flat Section


DASY Configuration:

Probe: ET3DV6 - SN1380; ConvF: (7.49,7.49,7.49); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)


Body Nylon Case Battery Clip 16 Key 24-03-14/Channel 3 Test/Area Scan (81x221x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 11.300 W/kg

Body Nylon Case Battery Clip 16 Key 24-03-14/Channel 3 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 91.031 V/m; **Power Drift = - 0.18 dB**

Averaged SAR: SAR(1g) = 10.900 W/kg; SAR(10g) = 7.710 W/kg
 Maximum value of SAR (interpolated) = 15.500 W/kg



SAR Measurement Plot 8



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M140227 450 MHz Body Worn Antenna Whip FCC.da52:1

DUT Name: Tait PTT Transceiver, Type: TPDH7A, Serial: 25543015

Configuration: Body Nylon Case Battery Clip 16 Key 24-03-14

Communication System: 0 - CW (0); Communication System Band: Tait 481 MHz FCC; Frequency: 496.5 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=496.5$ MHz; $\sigma = 0.96$ S/m; $\epsilon_r = 55.4$; $\rho = 1000.0$ g/cm³
 Phantom section: Flat Section


DASY Configuration:

Probe: ET3DV6 - SN1380; ConvF: (7.49,7.49,7.49); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)


Body Nylon Case Battery Clip 16 Key 24-03-14/Channel 4 Test/Area Scan (81x221x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 10.300 W/kg

Body Nylon Case Battery Clip 16 Key 24-03-14/Channel 4 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 79.017 V/m; **Power Drift = - 0.14 dB**

Averaged SAR: SAR(1g) = 10.300 W/kg; SAR(10g) = 7.190 W/kg
 Maximum value of SAR (interpolated) = 14.700 W/kg



SAR Measurement Plot 9



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M140227 450 MHz Body Worn Antenna Whip FCC.da52:1

DUT Name: Tait PTT Transceiver, Type: TPDH7A, Serial: 25543015

Configuration: Body Nylon Case Battery Clip 16 Key 24-03-14

Communication System: 0 - CW (0); Communication System Band: Tait 481 MHz FCC; Frequency: 511.9 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=512$ MHz; $\sigma = 0.96$ S/m; $\epsilon_r = 55.2$; $\rho = 1000.0$ g/cm³
 Phantom section: Flat Section


DASY Configuration:

Probe: ET3DV6 - SN1380; ConvF: (7.49,7.49,7.49); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)


Body Nylon Case Battery Clip 16 Key 24-03-14/Channel 5 Test/Area Scan (81x221x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 8.110 W/kg

Body Nylon Case Battery Clip 16 Key 24-03-14/Channel 5 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 66.859 V/m; **Power Drift = - 0.18 dB**

Averaged SAR: SAR(1g) = 7.960 W/kg; SAR(10g) = 5.570 W/kg
 Maximum value of SAR (interpolated) = 11.400 W/kg



SAR Measurement Plot 10



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M140227 450 MHz Body Worn Antenna Whip FCC.da52:2

DUT Name: Tait PTT Transceiver, Type: TPDH7A, Serial: 25543015

Configuration: Body Nylon Case Belt Loop 16 Key 25-03-14

Communication System: 0 - CW (0); Communication System Band: Tait 481 MHz FCC; Frequency: 450.1 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=450$ MHz; $\sigma = 0.91$ S/m; $\epsilon_r = 55.7$; $\rho = 1000.0$ g/cm³
 Phantom section: Flat Section

DASY Configuration:

Probe: ET3DV6 - SN1380; ConvF: (7.49,7.49,7.49); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)


Body Nylon Case Belt Loop 16 Key 25-03-14/Channel 1 Test/Area Scan (81x221x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 8.420 W/kg

Body Nylon Case Belt Loop 16 Key 25-03-14/Channel 1 Test/Zoom Scan (26x26x36)/Cube 0:


Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 66.752 V/m; **Power Drift = - 0.19 dB**

Averaged SAR: SAR(1g) = 8.370 W/kg; SAR(10g) = 5.990 W/kg

Maximum value of SAR (interpolated) = 11.200 W/kg



SAR Measurement Plot 11



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M140227 450 MHz Body Worn Antenna Whip FCC.da52:2

DUT Name: Tait PTT Transceiver, Type: TPDH7A, Serial: 25543015

Configuration: Body Nylon Case Belt Loop 16 Key 25-03-14

Communication System: 0 - CW (0); Communication System Band: Tait 481 MHz FCC; Frequency: 465.5 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=465.5$ MHz; $\sigma = 0.92$ S/m; $\epsilon_r = 55.5$; $\rho = 1000.0\text{g/cm}^3$
 Phantom section: Flat Section


DASY Configuration:

Probe: ET3DV6 - SN1380; ConvF: (7.49,7.49,7.49); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)


Body Nylon Case Belt Loop 16 Key 25-03-14/Channel 2 Test/Area Scan (81x221x1): Interpolated grid: $dx=1.5$ mm, $dy=1.5$ mm; Maximum value of SAR (interpolated) = 10.100 W/kg

Body Nylon Case Belt Loop 16 Key 25-03-14/Channel 2 Test/Zoom Scan (26x26x36)/Cube 0: Interpolated grid: $dx=1.6$ mm, $dy=1.6$ mm, $dz=1.0$ mm; Reference Value = 71.942 V/m; **Power Drift = - 0.12 dB**

Averaged SAR: SAR(1g) = 10.200 W/kg; SAR(10g) = 7.220 W/kg
 Maximum value of SAR (interpolated) = 14.000 W/kg



SAR Measurement Plot 12



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M140227 450 MHz Body Worn Antenna Whip FCC.da52:2

DUT Name: Tait PTT Transceiver, Type: TPDH7A, Serial: 25543015

Configuration: Body Nylon Case Belt Loop 16 Key 25-03-14

Communication System: 0 - CW (0); Communication System Band: Tait 481 MHz FCC; Frequency: 481.0 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=481$ MHz; $\sigma = 0.93$ S/m; $\epsilon_r = 55.2$; $\rho = 1000.0\text{g/cm}^3$
 Phantom section: Flat Section


DASY Configuration:

Probe: ET3DV6 - SN1380; ConvF: (7.49,7.49,7.49); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)


Body Nylon Case Belt Loop 16 Key 25-03-14/Channel 3 Test/Area Scan (81x221x1): Interpolated grid: $dx=1.5$ mm, $dy=1.5$ mm; Maximum value of SAR (interpolated) = 11.500 W/kg

Body Nylon Case Belt Loop 16 Key 25-03-14/Channel 3 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: $dx=1.6$ mm, $dy=1.6$ mm, $dz=1.0$ mm; Reference Value = 84.126 V/m; **Power Drift = - 0.09 dB**

Averaged SAR: SAR(1g) = 11.300 W/kg; SAR(10g) = 8.010 W/kg
 Maximum value of SAR (interpolated) = 15.800 W/kg



SAR Measurement Plot 13



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M140227 450 MHz Body Worn Antenna Whip FCC.da52:2

DUT Name: Tait PTT Transceiver, Type: TPDH7A, Serial: 25543015

Configuration: Body Nylon Case Belt Loop 16 Key 25-03-14

Communication System: 0 - CW (0); Communication System Band: Tait 481 MHz FCC; Frequency: 496.5 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=496.5$ MHz; $\sigma = 0.94$ S/m; $\epsilon_r = 54.9$; $\rho = 1000.0$ g/cm³
 Phantom section: Flat Section


DASY Configuration:

Probe: ET3DV6 - SN1380; ConvF: (7.49,7.49,7.49); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)


Body Nylon Case Belt Loop 16 Key 25-03-14/Channel 4 Test/Area Scan (81x221x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 10.700 W/kg

Body Nylon Case Belt Loop 16 Key 25-03-14/Channel 4 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 73.194 V/m; **Power Drift = - 0.00 dB**

Averaged SAR: SAR(1g) = 10.300 W/kg; SAR(10g) = 7.410 W/kg
 Maximum value of SAR (interpolated) = 14.300 W/kg



SAR Measurement Plot 14



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M140227 450 MHz Body Worn Antenna Whip FCC.da52:2

DUT Name: Tait PTT Transceiver, Type: TPDH7A, Serial: 25543015

Configuration: Body Nylon Case Belt Loop 16 Key 25-03-14

Communication System: 0 - CW (0); Communication System Band: Tait 481 MHz FCC; Frequency: 511.9 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=512$ MHz; $\sigma = 0.95$ S/m; $\epsilon_r = 54.6$; $\rho = 1000.0$ g/cm³
 Phantom section: Flat Section


DASY Configuration:

Probe: ET3DV6 - SN1380; ConvF: (7.49,7.49,7.49); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)


Body Nylon Case Belt Loop 16 Key 25-03-14/Channel 5 Test/Area Scan (81x221x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 7.950 W/kg

Body Nylon Case Belt Loop 16 Key 25-03-14/Channel 5 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 57.160 V/m; **Power Drift = - 0.17 dB**

Averaged SAR: SAR(1g) = 7.520 W/kg; SAR(10g) = 5.410 W/kg
 Maximum value of SAR (interpolated) = 10.300 W/kg



SAR Measurement Plot 15



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M140227 450 MHz Body Worn Antenna Whip FCC.da52:3

DUT Name: Tait PTT Transceiver, Type: TPDH7A, Serial: 25543015

Configuration: Body Nylon Case Belt Loop 16 Key 03-06-14

Communication System: 0 - CW (0); Communication System Band: Tait 481 MHz FCC; Frequency: 459.9 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=460$ MHz; $\sigma = 0.97$ S/m; $\epsilon_r = 57.6$; $\rho = 1000.0$ g/cm³
 Phantom section: Flat Section


DASY Configuration:

Probe: ET3DV6 - SN1380; ConvF: (7.49,7.49,7.49); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection)
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)


Body Nylon Case Belt Loop 16 Key 03-06-14/Channel 6 Test/Area Scan (81x221x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 11.900 W/kg

Body Nylon Case Belt Loop 16 Key 03-06-14/Channel 6 Test/Zoom Scan (26x26x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 74.140 V/m; **Power Drift = - 0.10 dB**

Averaged SAR: SAR(1g) = 10.900 W/kg; SAR(10g) = 7.750 W/kg
 Maximum value of SAR (interpolated) = 16.100 W/kg



SAR Measurement Plot 16



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M140227 450 MHz Body Worn Antenna Whip FCC.da52:3

DUT Name: Tait PTT Transceiver, Type: TPDH7A, Serial: 25543015

Configuration: Body Nylon Case Belt Loop 16 Key 03-06-14

Communication System: 0 - CW (0); Communication System Band: Tait 481 MHz FCC; Frequency: 469.9 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=470$ MHz; $\sigma = 0.98$ S/m; $\epsilon_r = 57.4$; $\rho = 1000.0$ g/cm³
 Phantom section: Flat Section


DASY Configuration:

Probe: ET3DV6 - SN1380; ConvF: (7.49,7.49,7.49); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)


Body Nylon Case Belt Loop 16 Key 03-06-14/Channel 7 Test/Area Scan (81x221x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 11.000 W/kg

Body Nylon Case Belt Loop 16 Key 03-06-14/Channel 7 Test/Zoom Scan (26x26x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 78.826 V/m; **Power Drift = - 0.04 dB**

Averaged SAR: SAR(1g) = 10.400 W/kg; SAR(10g) = 7.460 W/kg
 Maximum value of SAR (interpolated) = 15.300 W/kg



SAR Measurement Plot 17



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M140227 450 MHz Body Worn Antenna Whip FCC.da52:4

DUT Name: Tait PTT Transceiver, Type: TPDH7A, Serial: 25543015

Configuration: Body Nylon Case D-Stud Spring Clip 16 Key 25-03-14

Communication System: 0 - CW (0); Communication System Band: Tait 481 MHz FCC; Frequency: 481.0 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=481$ MHz; $\sigma = 0.93$ S/m; $\epsilon_r = 55.2$; $\rho = 1000.0$ g/cm³
 Phantom section: Flat Section

DASY Configuration:

Probe: ET3DV6 - SN1380; ConvF: (7.49,7.49,7.49); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Body Nylon Case D-Stud Spring Clip 16 Key 25-03-14/Channel 3 Test/Area Scan (81x221x1):


Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 7.910 W/kg

Body Nylon Case D-Stud Spring Clip 16 Key 25-03-14/Channel 3 Test/Zoom Scan (21x21x36)/Cube

0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 58.272 V/m; **Power Drift = -0.21 dB**

Averaged SAR: SAR(1g) = 7.930 W/kg; SAR(10g) = 5.270 W/kg

Maximum value of SAR (interpolated) = 12.700 W/kg




SAR Measurement Plot 18



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M140227 450 MHz Body Worn Antenna Whip FCC.da52:5

DUT Name: Tait PTT Transceiver, Type: TPDH7A, Serial: 25543015

Configuration: Body Nylon Case D-Stud Belt Loop 16 Key 25-03-14

Communication System: 0 - CW (0); Communication System Band: Tait 481 MHz FCC; Frequency: 481.0 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=481$ MHz; $\sigma = 0.93$ S/m; $\epsilon_r = 55.2$; $\rho = 1000.0\text{g/cm}^3$
 Phantom section: Flat Section

DASY Configuration:

Probe: ET3DV6 - SN1380; ConvF: (7.49,7.49,7.49); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Body Nylon Case D-Stud Belt Loop 16 Key 25-03-14/Channel 3 Test/Area Scan (81x221x1):


Interpolated grid: $dx=1.5$ mm, $dy=1.5$ mm; Maximum value of SAR (interpolated) = 4.480 W/kg

Body Nylon Case D-Stud Belt Loop 16 Key 25-03-14/Channel 3 Test/Zoom Scan (21x21x36)/Cube


0: Interpolated grid: $dx=1.6$ mm, $dy=1.6$ mm, $dz=1.0$ mm; Reference Value = 45.129 V/m; **Power Drift = -0.12 dB**

Averaged SAR: SAR(1g) = 4.370 W/kg; SAR(10g) = 3.230 W/kg

Maximum value of SAR (interpolated) = 5.730 W/kg



SAR Measurement Plot 19



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M140227 450 MHz Body Worn Antenna Whip FCC.da52:6

DUT Name: Tait PTT Transceiver, Type: TPDH7A, Serial: 25543015

Configuration: Body Soft Leather Case Battery Clip 16 Key 25-03-14

Communication System: 0 - CW (0); Communication System Band: Tait 481 MHz FCC; Frequency: 450.1 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=450$ MHz; $\sigma = 0.91$ S/m; $\epsilon_r = 55.7$; $\rho = 1000.0\text{g/cm}^3$
 Phantom section: Flat Section

DASY Configuration:


Probe: ET3DV6 - SN1380; ConvF: (7.49,7.49,7.49); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Body Soft Leather Case Battery Clip 16 Key 25-03-14/Channel 1 Test/Area Scan (81x221x1):


Interpolated grid: $dx=1.5$ mm, $dy=1.5$ mm; Maximum value of SAR (interpolated) = 9.990 W/kg

Body Soft Leather Case Battery Clip 16 Key 25-03-14/Channel 1 Test/Zoom Scan (26x31x36)/Cube 0:

Interpolated grid: $dx=1.6$ mm, $dy=1.6$ mm, $dz=1.0$ mm; Reference Value = 70.057 V/m; **Power Drift = 0.01 dB**
Averaged SAR: SAR(1g) = 9.810 W/kg; SAR(10g) = 7.030 W/kg
 Maximum value of SAR (interpolated) = 13.100 W/kg



SAR Measurement Plot 20



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M140227 450 MHz Body Worn Antenna Whip FCC.da52:6

DUT Name: Tait PTT Transceiver, Type: TPDH7A, Serial: 25543015

Configuration: Body Soft Leather Case Battery Clip 16 Key 25-03-14

Communication System: 0 - CW (0); Communication System Band: Tait 481 MHz FCC; Frequency: 465.5 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=465.5$ MHz; $\sigma = 0.92$ S/m; $\epsilon_r = 55.5$; $\rho = 1000.0\text{g/cm}^3$
 Phantom section: Flat Section

DASY Configuration:

Probe: ET3DV6 - SN1380; ConvF: (7.49,7.49,7.49); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Body Soft Leather Case Battery Clip 16 Key 25-03-14/Channel 2 Test/Area Scan (81x221x1):


Interpolated grid: $dx=1.5$ mm, $dy=1.5$ mm; Maximum value of SAR (interpolated) = 9.380 W/kg

Body Soft Leather Case Battery Clip 16 Key 25-03-14/Channel 2 Test/Zoom Scan (26x31x36)/Cube

0: Interpolated grid: $dx=1.6$ mm, $dy=1.6$ mm, $dz=1.0$ mm; Reference Value = 69.094 V/m; **Power Drift = -0.19 dB**

Averaged SAR: SAR(1g) = 9.070 W/kg; SAR(10g) = 6.480 W/kg

Maximum value of SAR (interpolated) = 12.200 W/kg




SAR Measurement Plot 21



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M140227 450 MHz Body Worn Antenna Whip FCC.da52:6

DUT Name: Tait PTT Transceiver, Type: TPDH7A, Serial: 25543015

Configuration: Body Soft Leather Case Battery Clip 16 Key 25-03-14

Communication System: 0 - CW (0); Communication System Band: Tait 481 MHz FCC; Frequency: 481.0 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=481$ MHz; $\sigma = 0.93$ S/m; $\epsilon_r = 55.2$; $\rho = 1000.0\text{g/cm}^3$
 Phantom section: Flat Section

DASY Configuration:

Probe: ET3DV6 - SN1380; ConvF: (7.49,7.49,7.49); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Body Soft Leather Case Battery Clip 16 Key 25-03-14/Channel 3 Test/Area Scan (81x221x1):


Interpolated grid: $dx=1.5$ mm, $dy=1.5$ mm; Maximum value of SAR (interpolated) = 10.200 W/kg

Body Soft Leather Case Battery Clip 16 Key 25-03-14/Channel 3 Test/Zoom Scan (21x21x36)/Cube


0: Interpolated grid: $dx=1.6$ mm, $dy=1.6$ mm, $dz=1.0$ mm; Reference Value = 82.102 V/m; **Power Drift = -0.18 dB**

Averaged SAR: SAR(1g) = 9.770 W/kg; SAR(10g) = 6.960 W/kg

Maximum value of SAR (interpolated) = 13.400 W/kg



SAR Measurement Plot 22



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M140227 450 MHz Body Worn Antenna Whip FCC.da52:6

DUT Name: Tait PTT Transceiver, Type: TPDH7A, Serial: 25543015

Configuration: Body Soft Leather Case Battery Clip 16 Key 25-03-14

Communication System: 0 - CW (0); Communication System Band: Tait 481 MHz FCC; Frequency: 496.5 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=496.5$ MHz; $\sigma = 0.94$ S/m; $\epsilon_r = 54.9$; $\rho = 1000.0$ g/cm³
 Phantom section: Flat Section

DASY Configuration:

Probe: ET3DV6 - SN1380; ConvF: (7.49,7.49,7.49); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Body Soft Leather Case Battery Clip 16 Key 25-03-14/Channel 4 Test/Area Scan (81x221x1):


Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 11.000 W/kg

Body Soft Leather Case Battery Clip 16 Key 25-03-14/Channel 4 Test/Zoom Scan (21x21x36)/Cube


0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 75.405 V/m; **Power Drift = -0.19 dB**

Averaged SAR: SAR(1g) = 10.200 W/kg; SAR(10g) = 7.230 W/kg

Maximum value of SAR (interpolated) = 14.300 W/kg



SAR Measurement Plot 23



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M140227 450 MHz Body Worn Antenna Whip FCC.da52:6

DUT Name: Tait PTT Transceiver, Type: TPDH7A, Serial: 25543015

Configuration: Body Soft Leather Case Battery Clip 16 Key 25-03-14

Communication System: 0 - CW (0); Communication System Band: Tait 481 MHz FCC; Frequency: 511.9 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=512$ MHz; $\sigma = 0.95$ S/m; $\epsilon_r = 54.6$; $\rho = 1000.0$ g/cm³
 Phantom section: Flat Section

DASY Configuration:

Probe: ET3DV6 - SN1380; ConvF: (7.49,7.49,7.49); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)


Body Soft Leather Case Battery Clip 16 Key 25-03-14/Channel 5 Test/Area Scan (81x221x1):

Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 8.240 W/kg


Body Soft Leather Case Battery Clip 16 Key 25-03-14/Channel 5 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 69.753 V/m; **Power Drift = -0.18 dB**

Averaged SAR: SAR(1g) = 7.800 W/kg; SAR(10g) = 5.480 W/kg

Maximum value of SAR (interpolated) = 11.000 W/kg



SAR Measurement Plot 24



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M140227 450 MHz Body Worn Antenna Whip FCC.da52:7

DUT Name: Tait PTT Transceiver, Type: TPDH7A, Serial: 25543015

Configuration: Body Leather Case Spring Clip 16 Key 26-03-14

Communication System: 0 - CW (0); Communication System Band: Tait 481 MHz FCC; Frequency: 450.1 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=450$ MHz; $\sigma = 0.91$ S/m; $\epsilon_r = 55.7$; $\rho = 1000.0\text{g/cm}^3$
 Phantom section: Flat Section

DASY Configuration:


Probe: ET3DV6 - SN1380; ConvF: (7.49,7.49,7.49); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Body Leather Case Spring Clip 16 Key 26-03-14/Channel 1 Test/Area Scan (81x221x1): Interpolated grid: $dx=1.5$ mm, $dy=1.5$ mm; Maximum value of SAR (interpolated) = 8.280 W/kg


Body Leather Case Spring Clip 16 Key 26-03-14/Channel 1 Test/Zoom Scan (26x31x36)/Cube 0: Interpolated grid: $dx=1.6$ mm, $dy=1.6$ mm, $dz=1.0$ mm; Reference Value = 56.584 V/m; **Power Drift = -0.08 dB**

Averaged SAR: SAR(1g) = 8.870 W/kg; SAR(10g) = 5.820 W/kg

Maximum value of SAR (interpolated) = 14.100 W/kg



SAR Measurement Plot 25



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M140227 450 MHz Body Worn Antenna Whip FCC.da52:7

DUT Name: Tait PTT Transceiver, Type: TPDH7A, Serial: 25543015

Configuration: Body Leather Case Spring Clip 16 Key 26-03-14

Communication System: 0 - CW (0); Communication System Band: Tait 481 MHz FCC; Frequency: 465.5 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=465.5$ MHz; $\sigma = 0.92$ S/m; $\epsilon_r = 55.5$; $\rho = 1000.0\text{g/cm}^3$
 Phantom section: Flat Section

DASY Configuration:


Probe: ET3DV6 - SN1380; ConvF: (7.49,7.49,7.49); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Body Leather Case Spring Clip 16 Key 26-03-14/Channel 2 Test/Area Scan (81x221x1): Interpolated grid: $dx=1.5$ mm, $dy=1.5$ mm; Maximum value of SAR (interpolated) = 8.540 W/kg


Body Leather Case Spring Clip 16 Key 26-03-14/Channel 2 Test/Zoom Scan (26x31x36)/Cube 0: Interpolated grid: $dx=1.6$ mm, $dy=1.6$ mm, $dz=1.0$ mm; Reference Value = 59.866 V/m; **Power Drift = - 0.18 dB**

Averaged SAR: SAR(1g) = 8.600 W/kg; SAR(10g) = 5.670 W/kg

Maximum value of SAR (interpolated) = 13.400 W/kg



SAR Measurement Plot 26



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M140227 450 MHz Body Worn Antenna Whip FCC.da52:7

DUT Name: Tait PTT Transceiver, Type: TPDH7A, Serial: 25543015

Configuration: Body Leather Case Spring Clip 16 Key 26-03-14

Communication System: 0 - CW (0); Communication System Band: Tait 481 MHz FCC; Frequency: 481.0 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=481$ MHz; $\sigma = 0.93$ S/m; $\epsilon_r = 55.2$; $\rho = 1000.0\text{g/cm}^3$
 Phantom section: Flat Section

DASY Configuration:


Probe: ET3DV6 - SN1380; ConvF: (7.49,7.49,7.49); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Body Leather Case Spring Clip 16 Key 26-03-14/Channel 3 Test/Area Scan (81x221x1): Interpolated grid: $dx=1.5$ mm, $dy=1.5$ mm; Maximum value of SAR (interpolated) = 8.700 W/kg


Body Leather Case Spring Clip 16 Key 26-03-14/Channel 3 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: $dx=1.6$ mm, $dy=1.6$ mm, $dz=1.0$ mm; Reference Value = 62.672 V/m; **Power Drift = -0.15 dB**

Averaged SAR: SAR(1g) = 8.870 W/kg; SAR(10g) = 5.860 W/kg

Maximum value of SAR (interpolated) = 14.500 W/kg



SAR Measurement Plot 27



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M140227 450 MHz Body Worn Antenna Whip FCC.da52:7

DUT Name: Tait PTT Transceiver, Type: TPDH7A, Serial: 25543015

Configuration: Body Leather Case Spring Clip 16 Key 26-03-14

Communication System: 0 - CW (0); Communication System Band: Tait 481 MHz FCC; Frequency: 496.5 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=496.5$ MHz; $\sigma = 0.94$ S/m; $\epsilon_r = 54.9$; $\rho = 1000.0\text{g/cm}^3$
 Phantom section: Flat Section

DASY Configuration:


Probe: ET3DV6 - SN1380; ConvF: (7.49,7.49,7.49); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Body Leather Case Spring Clip 16 Key 26-03-14/Channel 4 Test/Area Scan (81x221x1): Interpolated grid: $dx=1.5$ mm, $dy=1.5$ mm; Maximum value of SAR (interpolated) = 11.000 W/kg


Body Leather Case Spring Clip 16 Key 26-03-14/Channel 4 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: $dx=1.6$ mm, $dy=1.6$ mm, $dz=1.0$ mm; Reference Value = 64.172 V/m; **Power Drift = -0.21 dB**

Averaged SAR: SAR(1g) = 10.300 W/kg; SAR(10g) = 6.660 W/kg

Maximum value of SAR (interpolated) = 16.700 W/kg



SAR Measurement Plot 28



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M140227 450 MHz Body Worn Antenna Whip FCC.da52:7

DUT Name: Tait PTT Transceiver, Type: TPDH7A, Serial: 25543015

Configuration: Body Leather Case Spring Clip 16 Key 26-03-14

Communication System: 0 - CW (0); Communication System Band: Tait 481 MHz FCC; Frequency: 511.9 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=512$ MHz; $\sigma = 0.95$ S/m; $\epsilon_r = 54.6$; $\rho = 1000.0$ g/cm³
 Phantom section: Flat Section

DASY Configuration:


Probe: ET3DV6 - SN1380; ConvF: (7.49,7.49,7.49); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Body Leather Case Spring Clip 16 Key 26-03-14/Channel 5 Test/Area Scan (81x221x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 8.130 W/kg


Body Leather Case Spring Clip 16 Key 26-03-14/Channel 5 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 48.750 V/m; **Power Drift = - 0.10 dB**

Averaged SAR: SAR(1g) = 7.630 W/kg; SAR(10g) = 4.910 W/kg

Maximum value of SAR (interpolated) = 12.600 W/kg



SAR Measurement Plot 29



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M140227 450 MHz Body Worn Antenna Whip FCC.da52:8

DUT Name: Tait PTT Transceiver, Type: TPDH7A, Serial: 25543015

Configuration: Body Leather Case D-Stud Spring Clip 16 Key 26-03-14

Communication System: 0 - CW (0); Communication System Band: Tait 481 MHz FCC; Frequency: 481.0 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=481$ MHz; $\sigma = 0.93$ S/m; $\epsilon_r = 55.2$; $\rho = 1000.0$ g/cm³
 Phantom section: Flat Section

DASY Configuration:

Probe: ET3DV6 - SN1380; ConvF: (7.49,7.49,7.49); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Body Leather Case D-Stud Spring Clip 16 Key 26-03-14/Channel 3 Test/Area Scan (81x221x1):


Interpolated grid: $dx=1.5$ mm, $dy=1.5$ mm; Maximum value of SAR (interpolated) = 6.210 W/kg

Body Leather Case D-Stud Spring Clip 16 Key 26-03-14/Channel 3 Test/Zoom Scan

(21x21x36)/Cube 0: Interpolated grid: $dx=1.6$ mm, $dy=1.6$ mm, $dz=1.0$ mm; Reference Value = 48.131 V/m; **Power Drift = -0.15 dB**

Averaged SAR: SAR(1g) = 6.390 W/kg; SAR(10g) = 4.290 W/kg

Maximum value of SAR (interpolated) = 9.810 W/kg




SAR Measurement Plot 30



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M140227 450 MHz Body Worn Antenna Whip FCC.da52:9

DUT Name: Tait PTT Transceiver, Type: TPDH7A, Serial: 25543015

Configuration: Body Leather Case D-Stud Belt Loop 16 Key 26-03-14

Communication System: 0 - CW (0); Communication System Band: Tait 481 MHz FCC; Frequency: 481.0 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=481$ MHz; $\sigma = 0.93$ S/m; $\epsilon_r = 55.2$; $\rho = 1000.0$ g/cm³
 Phantom section: Flat Section

DASY Configuration:

Probe: ET3DV6 - SN1380; ConvF: (7.49,7.49,7.49); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Body Leather Case D-Stud Belt Loop 16 Key 26-03-14/Channel 3 Test/Area Scan (81x221x1):


Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 3.400 W/kg

Body Leather Case D-Stud Belt Loop 16 Key 26-03-14/Channel 3 Test/Zoom Scan (21x21x36)/Cube

0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 36.479 V/m; **Power Drift = -0.07 dB**

Averaged SAR: SAR(1g) = 3.360 W/kg; SAR(10g) = 2.490 W/kg

Maximum value of SAR (interpolated) = 4.390 W/kg




SAR Measurement Plot 31



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M140227 450 MHz Body Worn Antenna Whip FCC.da52:10

DUT Name: Tait PTT Transceiver, Type: TPDH7A, Serial: 25543015

Configuration: Body Leather Case Belt Loop 16 Key 26-03-14

Communication System: 0 - CW (0); Communication System Band: Tait 481 MHz FCC; Frequency: 465.5 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=465.5$ MHz; $\sigma = 0.92$ S/m; $\epsilon_r = 55.5$; $\rho = 1000.0$ g/cm³
 Phantom section: Flat Section


DASY Configuration:

Probe: ET3DV6 - SN1380; ConvF: (7.49,7.49,7.49); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)


Body Leather Case Belt Loop 16 Key 26-03-14/Channel 2 Test/Area Scan (81x221x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 7.980 W/kg

Body Leather Case Belt Loop 16 Key 26-03-14/Channel 2 Test/Zoom Scan (26x31x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 58.790 V/m; **Power Drift = - 0.13 dB**

Averaged SAR: SAR(1g) = 7.720 W/kg; SAR(10g) = 5.590 W/kg
 Maximum value of SAR (interpolated) = 10.300 W/kg



SAR Measurement Plot 32



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M140227 450 MHz Body Worn Antenna Whip FCC.da52:10

DUT Name: Tait PTT Transceiver, Type: TPDH7A, Serial: 25543015

Configuration: Body Leather Case Belt Loop 16 Key 26-03-14

Communication System: 0 - CW (0); Communication System Band: Tait 481 MHz FCC; Frequency: 481.0 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=481$ MHz; $\sigma = 0.93$ S/m; $\epsilon_r = 55.2$; $\rho = 1000.0$ g/cm³
 Phantom section: Flat Section


DASY Configuration:

Probe: ET3DV6 - SN1380; ConvF: (7.49,7.49,7.49); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)


Body Leather Case Belt Loop 16 Key 26-03-14/Channel 3 Test/Area Scan (81x221x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 8.720 W/kg

Body Leather Case Belt Loop 16 Key 26-03-14/Channel 3 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 62.317 V/m; **Power Drift = - 0.21 dB**

Averaged SAR: SAR(1g) = 8.590 W/kg; SAR(10g) = 6.230 W/kg
 Maximum value of SAR (interpolated) = 11.500 W/kg



SAR Measurement Plot 33



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M140227 450 MHz Body Worn Antenna Whip FCC.da52:10

DUT Name: Tait PTT Transceiver, Type: TPDH7A, Serial: 25543015

Configuration: Body Leather Case Belt Loop 16 Key 26-03-14

Communication System: 0 - CW (0); Communication System Band: Tait 481 MHz FCC; Frequency: 496.5 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=496.5$ MHz; $\sigma = 0.94$ S/m; $\epsilon_r = 54.9$; $\rho = 1000.0\text{g/cm}^3$
 Phantom section: Flat Section

DASY Configuration:


Probe: ET3DV6 - SN1380; ConvF: (7.49,7.49,7.49); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Body Leather Case Belt Loop 16 Key 26-03-14/Channel 4 Test/Area Scan (81x221x1): Interpolated grid: $dx=1.5$ mm, $dy=1.5$ mm; Maximum value of SAR (interpolated) = 8.910 W/kg


Body Leather Case Belt Loop 16 Key 26-03-14/Channel 4 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: $dx=1.6$ mm, $dy=1.6$ mm, $dz=1.0$ mm; Reference Value = 61.937 V/m; **Power Drift = - 0.17 dB**

Averaged SAR: SAR(1g) = 8.470 W/kg; SAR(10g) = 6.100 W/kg

Maximum value of SAR (interpolated) = 11.500 W/kg



SAR Measurement Plot 34



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M140227 450 MHz Body Worn Antenna Whip FCC.da52:10

DUT Name: Tait PTT Transceiver, Type: TPDH7A, Serial: 25543015

Configuration: Body Leather Case Belt Loop 16 Key 26-03-14

Communication System: 0 - CW (0); Communication System Band: Tait 481 MHz FCC; Frequency: 511.9 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=512$ MHz; $\sigma = 0.95$ S/m; $\epsilon_r = 54.6$; $\rho = 1000.0$ g/cm³
 Phantom section: Flat Section


DASY Configuration:

Probe: ET3DV6 - SN1380; ConvF: (7.49,7.49,7.49); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)


Body Leather Case Belt Loop 16 Key 26-03-14/Channel 5 Test/Area Scan (81x221x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 6.000 W/kg

Body Leather Case Belt Loop 16 Key 26-03-14/Channel 5 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 52.814 V/m; **Power Drift = - 0.18 dB**

Averaged SAR: SAR(1g) = 5.720 W/kg; SAR(10g) = 4.120 W/kg
 Maximum value of SAR (interpolated) = 7.850 W/kg



SAR Measurement Plot 35



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M140227 450 MHz Body Worn Antenna Whip FCC.da52:11

DUT Name: Tait PTT Transceiver, Type: TPDH7A, Serial: 25543015

Configuration: Body Nylon Case Belt Loop Extended Battery 16 Key 25-03-14

Communication System: 0 - CW (0); Communication System Band: Tait 481 MHz FCC; Frequency: 481.0 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=481$ MHz; $\sigma = 0.93$ S/m; $\epsilon_r = 55.2$; $\rho = 1000.0\text{g/cm}^3$
 Phantom section: Flat Section

DASY Configuration:

Probe: ET3DV6 - SN1380; ConvF: (7.49,7.49,7.49); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)


Body Nylon Case Belt Loop Extended Battery 16 Key 25-03-14/Channel 3 Test/Area Scan (81x221x1):

Interpolated grid: $dx=1.5$ mm, $dy=1.5$ mm; Maximum value of SAR (interpolated) = 9.380 W/kg


Body Nylon Case Belt Loop Extended Battery 16 Key 25-03-14/Channel 3 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: $dx=1.6$ mm, $dy=1.6$ mm, $dz=1.0$ mm; Reference Value = 71.721 V/m; **Power Drift = -0.19 dB**

Averaged SAR: SAR(1g) = 9.260 W/kg; SAR(10g) = 6.680 W/kg

Maximum value of SAR (interpolated) = 12.500 W/kg



SAR Measurement Plot 36



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M140227 450 MHz Body Worn Antenna Whip FCC.da52:12

DUT Name: Tait PTT Transceiver, Type: TPDH7A, Serial: 25543015


Configuration: Body Nylon Case Belt Loop Audio Accessory FAAA 16 Key 26-03-14

Communication System: 0 - CW (0); Communication System Band: Tait 481 MHz FCC; Frequency: 481.0 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=481$ MHz; $\sigma = 0.93$ S/m; $\epsilon_r = 55.2$; $\rho = 1000.0\text{g/cm}^3$
 Phantom section: Flat Section


DASY Configuration:

Probe: ET3DV6 - SN1380; ConvF: (7.49,7.49,7.49); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Body Nylon Case Belt Loop Audio Accessory FAAA 16 Key 26-03-14/Channel 3 Test/Area Scan (81x221x1): Interpolated grid: $dx=1.5$ mm, $dy=1.5$ mm; Maximum value of SAR (interpolated) = 11.100 W/kg
Body Nylon Case Belt Loop Audio Accessory FAAA 16 Key 26-03-14/Channel 3 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: $dx=1.6$ mm, $dy=1.6$ mm, $dz=1.0$ mm; Reference Value = 84.404 V/m; **Power Drift = -0.14 dB**
Averaged SAR: SAR(1g) = 10.900 W/kg; SAR(10g) = 7.840 W/kg
 Maximum value of SAR (interpolated) = 15.000 W/kg



SAR Measurement Plot 37



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M140227 450 MHz Body Worn Antenna Whip FCC.da52:13

DUT Name: Tait PTT Transceiver, Type: TPDH7A, Serial: 25543015

Configuration: Body Nylon Case Belt Loop Audio Accessory FEAA 16 Key 26-03-14

Communication System: 0 - CW (0); Communication System Band: Tait 481 MHz FCC; Frequency: 481.0 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=481$ MHz; $\sigma = 0.93$ S/m; $\epsilon_r = 55.2$; $\rho = 1000.0$ g/cm³
 Phantom section: Flat Section

DASY Configuration:

Probe: ET3DV6 - SN1380; ConvF: (7.49,7.49,7.49); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Body Nylon Case Belt Loop Audio Accessory FEAA 16 Key 26-03-14/Channel 3 Test/Area Scan


(81x221x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 9.710 W/kg

Body Nylon Case Belt Loop Audio Accessory FEAA 16 Key 26-03-14/Channel 3 Test/Zoom Scan


(26x26x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 74.264 V/m; **Power Drift = -0.07 dB**

Averaged SAR: SAR(1g) = 9.610 W/kg; SAR(10g) = 6.930 W/kg

Maximum value of SAR (interpolated) = 13.100 W/kg



SAR Measurement Plot 38



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M140227 450 MHz Body Worn Antenna Whip FCC.da52:14

DUT Name: Tait PTT Transceiver, Type: TPDH7A, Serial: 25543020

Configuration: Body Nylon Case Belt Loop 4-key Variant 31-03-14

Communication System: 0 - CW (0); Communication System Band: Tait 481 MHz FCC; Frequency: 450.1 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=450$ MHz; $\sigma = 0.93$ S/m; $\epsilon_r = 55.9$; $\rho = 1000.0\text{g/cm}^3$
 Phantom section: Flat Section

DASY Configuration:


Probe: ET3DV6 - SN1380; ConvF: (7.49,7.49,7.49); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Body Nylon Case Belt Loop 4-key Variant 31-03-14/Channel 1 Test/Area Scan (81x221x1): Interpolated grid: $dx=1.5$ mm, $dy=1.5$ mm; Maximum value of SAR (interpolated) = 11.000 W/kg


Body Nylon Case Belt Loop 4-key Variant 31-03-14/Channel 1 Test/Zoom Scan (26x26x36)/Cube 0: Interpolated grid: $dx=1.6$ mm, $dy=1.6$ mm, $dz=1.0$ mm; Reference Value = 72.788 V/m; **Power Drift = -0.21 dB**

Averaged SAR: SAR(1g) = 10.900 W/kg; SAR(10g) = 7.750 W/kg

Maximum value of SAR (interpolated) = 15.100 W/kg



SAR Measurement Plot 39



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M140227 450 MHz Body Worn Antenna Whip FCC.da52:15

DUT Name: Tait PTT Transceiver, Type: TPDH7A, Serial: 25543015

Configuration: Body Nylon Case Belt Loop 16-key Variability 31-03-14

Communication System: 0 - CW (0); Communication System Band: Tait 481 MHz FCC; Frequency: 481.0 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=481$ MHz; $\sigma = 0.95$ S/m; $\epsilon_r = 55.5$; $\rho = 1000.0\text{g/cm}^3$
 Phantom section: Flat Section

DASY Configuration:

Probe: ET3DV6 - SN1380; ConvF: (7.49,7.49,7.49); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Body Nylon Case Belt Loop 16-key Variability 31-03-14/Channel 3 Test/Area Scan (81x221x1):


Interpolated grid: $dx=1.5$ mm, $dy=1.5$ mm; Maximum value of SAR (interpolated) = 12.300 W/kg

Body Nylon Case Belt Loop 16-key Variability 31-03-14/Channel 3 Test/Zoom Scan


(26x31x36)/Cube 0: Interpolated grid: $dx=1.6$ mm, $dy=1.6$ mm, $dz=1.0$ mm; Reference Value = 76.142 V/m; **Power Drift = -0.08 dB**

Averaged SAR: SAR(1g) = 10.900 W/kg; SAR(10g) = 7.720 W/kg

Maximum value of SAR (interpolated) = 15.600 W/kg



SAR Measurement Plot 40



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M140227 450 MHz Body Worn Antenna Whip FCC.da52:16

DUT Name: Dipole 450 MHz, Type: D450V3, Serial: 1074

Configuration: System Check 24-03-14

Communication System: 0 - CW 450 MHz; Communication System Band: 450 MHz; Frequency: 450.0 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=450$ MHz; $\sigma = 0.94$ S/m; $\epsilon_r = 56.4$; $\rho = 1000.0$ g/cm³
 Phantom section: Flat Section

DASY Configuration:


Probe: ET3DV6 - SN1380; ConvF: (7.49,7.49,7.49); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection)
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

System Check 24-03-14/Channel 1Test/Area Scan (51x121x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm;
 Maximum value of SAR (interpolated) = 1.950 W/kg


System Check 24-03-14/Channel 1Test/Zoom Scan (31x31x36)/Cube 0: Interpolated grid: dx=1.0 mm, dy=1.0 mm, dz=1.0 mm; Reference Value = 47.657 V/m; **Power Drift = -0.02 dB**

Averaged SAR: SAR(1g) = 1.890 W/kg; SAR(10g) = 1.190 W/kg

Maximum value of SAR (interpolated) = 3.250 W/kg



SAR Measurement Plot 41



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M140227 450 MHz Body Worn Antenna Whip FCC.da52:17

DUT Name: Dipole 450 MHz, Type: D450V3, Serial: 1074

Configuration: System Check 25-03-14

Communication System: 0 - CW 450 MHz; Communication System Band: 450 MHz; Frequency: 450.0 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=450$ MHz; $\sigma = 0.91$ S/m; $\epsilon_r = 55.7$; $\rho = 1000.0$ g/cm³
 Phantom section: Flat Section

DASY Configuration:


Probe: ET3DV6 - SN1380; ConvF: (7.49,7.49,7.49); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection)
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

System Check 25-03-14/Channel 1Test/Area Scan (51x121x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm;
 Maximum value of SAR (interpolated) = 1.960 W/kg

System Check 25-03-14/Channel 1Test/Zoom Scan (31x31x36)/Cube 0: Interpolated grid: dx=1.0 mm, dy=1.0 mm, dz=1.0 mm; Reference Value = 47.585 V/m; **Power Drift = -0.02 dB**

Averaged SAR: SAR(1g) = 1.860 W/kg; SAR(10g) = 1.180 W/kg

Maximum value of SAR (interpolated) = 3.200 W/kg




0 dB = 1.96 W/kg = 2.92 dBW/kg

SAR Measurement Plot 42



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M140227 450 MHz Body Worn Antenna Whip FCC.da52:18

DUT Name: Dipole 450 MHz, Type: D450V3, Serial: 1074

Configuration: System Check 26-03-14

Communication System: 0 - CW 450 MHz; Communication System Band: 450 MHz; Frequency: 450.0 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=450$ MHz; $\sigma = 0.92$ S/m; $\epsilon_r = 55.5$; $\rho = 1000.0$ g/cm³
 Phantom section: Flat Section

DASY Configuration:


Probe: ET3DV6 - SN1380; ConvF: (7.49,7.49,7.49); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection)
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

System Check 26-03-14/Channel 1Test/Area Scan (51x121x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm;
 Maximum value of SAR (interpolated) = 1.930 W/kg

System Check 26-03-14/Channel 1Test/Zoom Scan (31x31x36)/Cube 0: Interpolated grid: dx=1.0 mm, dy=1.0 mm, dz=1.0 mm; Reference Value = 47.514 V/m; **Power Drift = -0.03 dB**

Averaged SAR: SAR(1g) = 1.850 W/kg; SAR(10g) = 1.170 W/kg

Maximum value of SAR (interpolated) = 3.130 W/kg




0 dB = 1.93 W/kg = 2.86 dBW/kg

SAR Measurement Plot 43



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M140227 450 MHz Body Worn Antenna Whip FCC.da52:19

DUT Name: Dipole 450 MHz, Type: D450V3, Serial: 1074

Configuration: System Check 03-06-14

Communication System: 0 - CW 450 MHz; Communication System Band: 450 MHz; Frequency: 450.0 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=450$ MHz; $\sigma = 0.96$ S/m; $\epsilon_r = 57.7$; $\rho = 1000.0$ g/cm³
 Phantom section: Flat Section

DASY Configuration:


Probe: ET3DV6 - SN1380; ConvF: (7.49,7.49,7.49); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection)
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

System Check 03-06-14/Channel 1Test/Area Scan (51x121x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm;
 Maximum value of SAR (interpolated) = 1.880 W/kg

System Check 03-06-14/Channel 1Test/Zoom Scan (31x31x36)/Cube 0: Interpolated grid: dx=1.0 mm, dy=1.0 mm, dz=1.0 mm; Reference Value = 45.759 V/m; **Power Drift = -0.01 dB**

Averaged SAR: SAR(1g) = 1.830 W/kg; SAR(10g) = 1.150 W/kg

Maximum value of SAR (interpolated) = 3.130 W/kg




0 dB = 1.88 W/kg = 2.74 dBW/kg

SAR Measurement Plot 44



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M140227 450 MHz Body Worn Antenna Helical FCC.da52:0

DUT Name: Tait PTT Transceiver, Type: TPDH7A, Serial: 25543015

Configuration: Body Battery Clip 16 Key 27-03-14

Communication System: 0 - CW (0); Communication System Band: Tait 481 MHz FCC; Frequency: 450.1 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=450$ MHz; $\sigma = 0.90$ S/m; $\epsilon_r = 55.6$; $\rho = 1000.0\text{g/cm}^3$
 Phantom section: Flat Section

DASY Configuration:


Probe: ET3DV6 - SN1380; ConvF: (7.49,7.49,7.49); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Body Battery Clip 16 Key 27-03-14/Channel 1 Test/Area Scan (81x221x1): Interpolated grid: $dx=1.5$ mm, $dy=1.5$ mm; Maximum value of SAR (interpolated) = 10.200 W/kg

Body Battery Clip 16 Key 27-03-14/Channel 1 Test/Zoom Scan (26x31x36)/Cube 0: Interpolated grid: $dx=1.6$ mm, $dy=1.6$ mm, $dz=1.0$ mm; Reference Value = 72.961 V/m; **Power Drift = -0.03 dB**

Averaged SAR: SAR(1g) = 9.860 W/kg; SAR(10g) = 7.000 W/kg

Maximum value of SAR (interpolated) = 13.200 W/kg




SAR Measurement Plot 45



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M140227 450 MHz Body Worn Antenna Helical FCC.da52:0

DUT Name: Tait PTT Transceiver, Type: TPDH7A, Serial: 25543015

Configuration: Body Battery Clip 16 Key 27-03-14

Communication System: 0 - CW (0); Communication System Band: Tait 481 MHz FCC; Frequency: 465.5 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=465.5$ MHz; $\sigma = 0.91$ S/m; $\epsilon_r = 55.4$; $\rho = 1000.0\text{g/cm}^3$
 Phantom section: Flat Section

DASY Configuration:


Probe: ET3DV6 - SN1380; ConvF: (7.49,7.49,7.49); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Body Battery Clip 16 Key 27-03-14/Channel 2 Test/Area Scan (81x221x1): Interpolated grid: $dx=1.5$ mm, $dy=1.5$ mm; Maximum value of SAR (interpolated) = 8.870 W/kg

Body Battery Clip 16 Key 27-03-14/Channel 2 Test/Zoom Scan (26x31x36)/Cube 0: Interpolated grid: $dx=1.6$ mm, $dy=1.6$ mm, $dz=1.0$ mm; Reference Value = 68.203 V/m; **Power Drift = -0.14 dB**

Averaged SAR: SAR(1g) = 8.630 W/kg; SAR(10g) = 6.120 W/kg

Maximum value of SAR (interpolated) = 11.700 W/kg




0 dB = 8.87 W/kg = 9.48 dBW/kg

SAR Measurement Plot 46



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M140227 450 MHz Body Worn Antenna Helical FCC.da52:0

DUT Name: Tait PTT Transceiver, Type: TPDH7A, Serial: 25543015

Configuration: Body Battery Clip 16 Key 27-03-14

Communication System: 0 - CW (0); Communication System Band: Tait 481 MHz FCC; Frequency: 481.0 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=481$ MHz; $\sigma = 0.92$ S/m; $\epsilon_r = 55.1$; $\rho = 1000.0$ g/cm³
 Phantom section: Flat Section

DASY Configuration:


Probe: ET3DV6 - SN1380; ConvF: (7.49,7.49,7.49); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Body Battery Clip 16 Key 27-03-14/Channel 3 Test/Area Scan (81x221x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 9.930 W/kg

Body Battery Clip 16 Key 27-03-14/Channel 3 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 80.504 V/m; **Power Drift = -0.18 dB**

Averaged SAR: SAR(1g) = 9.290 W/kg; SAR(10g) = 6.570 W/kg

Maximum value of SAR (interpolated) = 12.800 W/kg




0 dB = 9.93 W/kg = 9.97 dBW/kg

SAR Measurement Plot 47



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M140227 450 MHz Body Worn Antenna Helical FCC.da52:0

DUT Name: Tait PTT Transceiver, Type: TPDH7A, Serial: 25543015

Configuration: Body Battery Clip 16 Key 27-03-14

Communication System: 0 - CW (0); Communication System Band: Tait 481 MHz FCC; Frequency: 496.5 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=496.5$ MHz; $\sigma = 0.94$ S/m; $\epsilon_r = 54.8$; $\rho = 1000.0\text{g/cm}^3$
 Phantom section: Flat Section

DASY Configuration:


Probe: ET3DV6 - SN1380; ConvF: (7.49,7.49,7.49); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Body Battery Clip 16 Key 27-03-14/Channel 4 Test/Area Scan (81x221x1): Interpolated grid: $dx=1.5$ mm, $dy=1.5$ mm; Maximum value of SAR (interpolated) = 6.460 W/kg

Body Battery Clip 16 Key 27-03-14/Channel 4 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: $dx=1.6$ mm, $dy=1.6$ mm, $dz=1.0$ mm; Reference Value = 55.078 V/m; **Power Drift = -0.02 dB**

Averaged SAR: SAR(1g) = 6.090 W/kg; SAR(10g) = 4.270 W/kg

Maximum value of SAR (interpolated) = 8.540 W/kg




0 dB = 6.46 W/kg = 8.10 dBW/kg

SAR Measurement Plot 48



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M140227 450 MHz Body Worn Antenna Helical FCC.da52:1

DUT Name: Tait PTT Transceiver, Type: TPDH7A, Serial: 25543015

Configuration: Body Nylon Case Battery Clip 16 Key 27-03-14

Communication System: 0 - CW (0); Communication System Band: Tait 481 MHz FCC; Frequency: 450.1 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=450$ MHz; $\sigma = 0.90$ S/m; $\epsilon_r = 55.6$; $\rho = 1000.0\text{g/cm}^3$
 Phantom section: Flat Section

DASY Configuration:


Probe: ET3DV6 - SN1380; ConvF: (7.49,7.49,7.49); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Body Nylon Case Battery Clip 16 Key 27-03-14/Channel 1 Test/Area Scan (81x221x1): Interpolated grid: $dx=1.5$ mm, $dy=1.5$ mm; Maximum value of SAR (interpolated) = 10.500 W/kg


Body Nylon Case Battery Clip 16 Key 27-03-14/Channel 1 Test/Zoom Scan (26x31x36)/Cube 0: Interpolated grid: $dx=1.6$ mm, $dy=1.6$ mm, $dz=1.0$ mm; Reference Value = 76.716 V/m; **Power Drift = 0.01 dB**

Averaged SAR: SAR(1g) = 10.200 W/kg; SAR(10g) = 7.310 W/kg

Maximum value of SAR (interpolated) = 13.600 W/kg



SAR Measurement Plot 49



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M140227 450 MHz Body Worn Antenna Helical FCC.da52:1

DUT Name: Tait PTT Transceiver, Type: TPDH7A, Serial: 25543015

Configuration: Body Nylon Case Battery Clip 16 Key 27-03-14

Communication System: 0 - CW (0); Communication System Band: Tait 481 MHz FCC; Frequency: 465.5 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=465.5$ MHz; $\sigma = 0.91$ S/m; $\epsilon_r = 55.4$; $\rho = 1000.0\text{g/cm}^3$
 Phantom section: Flat Section


DASY Configuration:

Probe: ET3DV6 - SN1380; ConvF: (7.49,7.49,7.49); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)


Body Nylon Case Battery Clip 16 Key 27-03-14/Channel 2 Test/Area Scan (81x221x1): Interpolated grid: $dx=1.5$ mm, $dy=1.5$ mm; Maximum value of SAR (interpolated) = 9.300 W/kg

Body Nylon Case Battery Clip 16 Key 27-03-14/Channel 2 Test/Zoom Scan (26x31x36)/Cube 0: Interpolated grid: $dx=1.6$ mm, $dy=1.6$ mm, $dz=1.0$ mm; Reference Value = 64.391 V/m; **Power Drift = - 0.15 dB**

Averaged SAR: SAR(1g) = 9.110 W/kg; SAR(10g) = 6.490 W/kg
 Maximum value of SAR (interpolated) = 12.300 W/kg



SAR Measurement Plot 50



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M140227 450 MHz Body Worn Antenna Helical FCC.da52:1

DUT Name: Tait PTT Transceiver, Type: TPDH7A, Serial: 25543015

Configuration: Body Nylon Case Battery Clip 16 Key 27-03-14

Communication System: 0 - CW (0); Communication System Band: Tait 481 MHz FCC; Frequency: 481.0 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=481$ MHz; $\sigma = 0.92$ S/m; $\epsilon_r = 55.1$; $\rho = 1000.0$ g/cm³
 Phantom section: Flat Section


DASY Configuration:

Probe: ET3DV6 - SN1380; ConvF: (7.49,7.49,7.49); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)


Body Nylon Case Battery Clip 16 Key 27-03-14/Channel 3 Test/Area Scan (81x221x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 10.300 W/kg

Body Nylon Case Battery Clip 16 Key 27-03-14/Channel 3 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 83.415 V/m; **Power Drift = - 0.10 dB**

Averaged SAR: SAR(1g) = 9.670 W/kg; SAR(10g) = 6.810 W/kg
 Maximum value of SAR (interpolated) = 13.400 W/kg



SAR Measurement Plot 51



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M140227 450 MHz Body Worn Antenna Helical FCC.da52:1

DUT Name: Tait PTT Transceiver, Type: TPDH7A, Serial: 25543015

Configuration: Body Nylon Case Battery Clip 16 Key 27-03-14

Communication System: 0 - CW (0); Communication System Band: Tait 481 MHz FCC; Frequency: 496.5 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=496.5$ MHz; $\sigma = 0.94$ S/m; $\epsilon_r = 54.8$; $\rho = 1000.0\text{g/cm}^3$
 Phantom section: Flat Section


DASY Configuration:

Probe: ET3DV6 - SN1380; ConvF: (7.49,7.49,7.49); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)


Body Nylon Case Battery Clip 16 Key 27-03-14/Channel 4 Test/Area Scan (81x221x1): Interpolated grid: $dx=1.5$ mm, $dy=1.5$ mm; Maximum value of SAR (interpolated) = 6.370 W/kg

Body Nylon Case Battery Clip 16 Key 27-03-14/Channel 4 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: $dx=1.6$ mm, $dy=1.6$ mm, $dz=1.0$ mm; Reference Value = 58.736 V/m; **Power Drift = - 0.12 dB**

Averaged SAR: SAR(1g) = 5.900 W/kg; SAR(10g) = 4.150 W/kg
 Maximum value of SAR (interpolated) = 8.290 W/kg



SAR Measurement Plot 52



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M140227 450 MHz Body Worn Antenna Helical FCC.da52:2

DUT Name: Tait PTT Transceiver, Type: TPDH7A, Serial: 25543015

Configuration: Body Nylon Case Belt Loop 16 Key 27-03-14

Communication System: 0 - CW (0); Communication System Band: Tait 481 MHz FCC; Frequency: 450.1 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=450$ MHz; $\sigma = 0.90$ S/m; $\epsilon_r = 55.6$; $\rho = 1000.0$ g/cm³
 Phantom section: Flat Section


DASY Configuration:

Probe: ET3DV6 - SN1380; ConvF: (7.49,7.49,7.49); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)


Body Nylon Case Belt Loop 16 Key 27-03-14/Channel 1 Test/Area Scan (81x221x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 11.300 W/kg

Body Nylon Case Belt Loop 16 Key 27-03-14/Channel 1 Test/Zoom Scan (26x31x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 76.983 V/m; **Power Drift = - 0.02 dB**

Averaged SAR: SAR(1g) = 11.300 W/kg; SAR(10g) = 7.940 W/kg
 Maximum value of SAR (interpolated) = 15.400 W/kg



SAR Measurement Plot 53



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M140227 450 MHz Body Worn Antenna Helical FCC.da52:2

DUT Name: Tait PTT Transceiver, Type: TPDH7A, Serial: 25543015

Configuration: Body Nylon Case Belt Loop 16 Key 27-03-14

Communication System: 0 - CW (0); Communication System Band: Tait 481 MHz FCC; Frequency: 465.5 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=465.5$ MHz; $\sigma = 0.91$ S/m; $\epsilon_r = 55.4$; $\rho = 1000.0$ g/cm³
 Phantom section: Flat Section


DASY Configuration:

Probe: ET3DV6 - SN1380; ConvF: (7.49,7.49,7.49); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)


Body Nylon Case Belt Loop 16 Key 27-03-14/Channel 2 Test/Area Scan (81x221x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 9.780 W/kg

Body Nylon Case Belt Loop 16 Key 27-03-14/Channel 2 Test/Zoom Scan (26x31x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 79.384 V/m; **Power Drift = - 0.16 dB**

Averaged SAR: SAR(1g) = 9.880 W/kg; SAR(10g) = 6.950 W/kg
 Maximum value of SAR (interpolated) = 13.500 W/kg



SAR Measurement Plot 54



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M140227 450 MHz Body Worn Antenna Helical FCC.da52:2

DUT Name: Tait PTT Transceiver, Type: TPDH7A, Serial: 25543015

Configuration: Body Nylon Case Belt Loop 16 Key 27-03-14

Communication System: 0 - CW (0); Communication System Band: Tait 481 MHz FCC; Frequency: 481.0 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=481$ MHz; $\sigma = 0.92$ S/m; $\epsilon_r = 55.1$; $\rho = 1000.0$ g/cm³
 Phantom section: Flat Section


DASY Configuration:

Probe: ET3DV6 - SN1380; ConvF: (7.49,7.49,7.49); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)


Body Nylon Case Belt Loop 16 Key 27-03-14/Channel 3 Test/Area Scan (81x221x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 9.380 W/kg

Body Nylon Case Belt Loop 16 Key 27-03-14/Channel 3 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 75.814 V/m; **Power Drift = - 0.17 dB**

Averaged SAR: SAR(1g) = 9.000 W/kg; SAR(10g) = 6.360 W/kg
 Maximum value of SAR (interpolated) = 12.400 W/kg



SAR Measurement Plot 55



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M140227 450 MHz Body Worn Antenna Helical FCC.da52:2

DUT Name: Tait PTT Transceiver, Type: TPDH7A, Serial: 25543015

Configuration: Body Nylon Case Belt Loop 16 Key 27-03-14

Communication System: 0 - CW (0); Communication System Band: Tait 481 MHz FCC; Frequency: 496.5 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=496.5$ MHz; $\sigma = 0.94$ S/m; $\epsilon_r = 54.8$; $\rho = 1000.0\text{g/cm}^3$
 Phantom section: Flat Section


DASY Configuration:

Probe: ET3DV6 - SN1380; ConvF: (7.49,7.49,7.49); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)


Body Nylon Case Belt Loop 16 Key 27-03-14/Channel 4 Test/Area Scan (81x221x1): Interpolated grid: $dx=1.5$ mm, $dy=1.5$ mm; Maximum value of SAR (interpolated) = 6.260 W/kg

Body Nylon Case Belt Loop 16 Key 27-03-14/Channel 4 Test/Zoom Scan (26x26x36)/Cube 0: Interpolated grid: $dx=1.6$ mm, $dy=1.6$ mm, $dz=1.0$ mm; Reference Value = 58.054 V/m; **Power Drift = - 0.16 dB**

Averaged SAR: SAR(1g) = 5.800 W/kg; SAR(10g) = 4.160 W/kg
 Maximum value of SAR (interpolated) = 8.080 W/kg



SAR Measurement Plot 56



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M140227 450 MHz Body Worn Antenna Helical FCC.da52:3

DUT Name: Tait PTT Transceiver, Type: TPDH7A, Serial: 25543015

Configuration: Body Nylon Case Belt Loop 16 Key 03-06-14

Communication System: 0 - CW (0); Communication System Band: Tait 481 MHz FCC; Frequency: 459.9 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=460$ MHz; $\sigma = 0.97$ S/m; $\epsilon_r = 57.6$; $\rho = 1000.0$ g/cm³
 Phantom section: Flat Section


DASY Configuration:

Probe: ET3DV6 - SN1380; ConvF: (7.49,7.49,7.49); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection)
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)


Body Nylon Case Belt Loop 16 Key 03-06-14/Channel 6 Test/Area Scan (81x221x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 10.000 W/kg

Body Nylon Case Belt Loop 16 Key 03-06-14/Channel 6 Test/Zoom Scan (26x31x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 80.057 V/m; **Power Drift = 0.12 dB**

Averaged SAR: SAR(1g) = 9.370 W/kg; SAR(10g) = 6.690 W/kg
 Maximum value of SAR (interpolated) = 13.800 W/kg



SAR Measurement Plot 57



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M140227 450 MHz Body Worn Antenna Helical FCC.da52:3

DUT Name: Tait PTT Transceiver, Type: TPDH7A, Serial: 25543015

Configuration: Body Nylon Case Belt Loop 16 Key 03-06-14

Communication System: 0 - CW (0); Communication System Band: Tait 481 MHz FCC; Frequency: 469.9 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=470$ MHz; $\sigma = 0.98$ S/m; $\epsilon_r = 57.4$; $\rho = 1000.0$ g/cm³
 Phantom section: Flat Section


DASY Configuration:

Probe: ET3DV6 - SN1380; ConvF: (7.49,7.49,7.49); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)


Body Nylon Case Belt Loop 16 Key 03-06-14/Channel 7 Test/Area Scan (81x221x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 12.000 W/kg

Body Nylon Case Belt Loop 16 Key 03-06-14/Channel 7 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 84.700 V/m; **Power Drift = - 0.01 dB**

Averaged SAR: SAR(1g) = 11.100 W/kg; SAR(10g) = 7.800 W/kg
 Maximum value of SAR (interpolated) = 16.700 W/kg



SAR Measurement Plot 58



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M140227 450 MHz Body Worn Antenna Helical FCC.da52:4

DUT Name: Tait PTT Transceiver, Type: TPDH7A, Serial: 25543015

Configuration: Body Nylon Case D-Stud Spring Clip 16 Key 28-03-14

Communication System: 0 - CW (0); Communication System Band: Tait 481 MHz FCC; Frequency: 481.0 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=481$ MHz; $\sigma = 0.95$ S/m; $\epsilon_r = 55.0$; $\rho = 1000.0$ g/cm³
 Phantom section: Flat Section

DASY Configuration:

Probe: ET3DV6 - SN1380; ConvF: (7.49,7.49,7.49); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Body Nylon Case D-Stud Spring Clip 16 Key 28-03-14/Channel 3 Test/Area Scan (81x221x1):


Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 7.610 W/kg

Body Nylon Case D-Stud Spring Clip 16 Key 28-03-14/Channel 3 Test/Zoom Scan (21x21x36)/Cube

0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 63.020 V/m; **Power Drift = -0.19 dB**

Averaged SAR: SAR(1g) = 7.000 W/kg; SAR(10g) = 4.670 W/kg

Maximum value of SAR (interpolated) = 11.100 W/kg




SAR Measurement Plot 59



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M140227 450 MHz Body Worn Antenna Helical FCC.da52:5

DUT Name: Tait PTT Transceiver, Type: TPDH7A, Serial: 25543015

Configuration: Body Nylon Case D-Stud Belt Loop 16 Key 28-03-14

Communication System: 0 - CW (0); Communication System Band: Tait 481 MHz FCC; Frequency: 481.0 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=481$ MHz; $\sigma = 0.95$ S/m; $\epsilon_r = 55.0$; $\rho = 1000.0$ g/cm³
 Phantom section: Flat Section

DASY Configuration:

Probe: ET3DV6 - SN1380; ConvF: (7.49,7.49,7.49); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Body Nylon Case D-Stud Belt Loop 16 Key 28-03-14/Channel 3 Test/Area Scan (81x221x1):


Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 3.780 W/kg

Body Nylon Case D-Stud Belt Loop 16 Key 28-03-14/Channel 3 Test/Zoom Scan (21x21x36)/Cube

0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 47.268 V/m; **Power Drift = -0.08 dB**

Averaged SAR: SAR(1g) = 3.560 W/kg; SAR(10g) = 2.630 W/kg

Maximum value of SAR (interpolated) = 4.750 W/kg




SAR Measurement Plot 60



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M140227 450 MHz Body Worn Antenna Helical FCC.da52:6

DUT Name: Tait PTT Transceiver, Type: TPDH7A, Serial: 25543015

Configuration: Body Soft Leather Case Battery Clip 16 Key 28-03-14

Communication System: 0 - CW (0); Communication System Band: Tait 481 MHz FCC; Frequency: 450.1 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=450$ MHz; $\sigma = 0.92$ S/m; $\epsilon_r = 55.4$; $\rho = 1000.0\text{g/cm}^3$
 Phantom section: Flat Section

DASY Configuration:

Probe: ET3DV6 - SN1380; ConvF: (7.49,7.49,7.49); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Body Soft Leather Case Battery Clip 16 Key 28-03-14/Channel 1 Test/Area Scan (81x221x1):


Interpolated grid: $dx=1.5$ mm, $dy=1.5$ mm; Maximum value of SAR (interpolated) = 10.800 W/kg

Body Soft Leather Case Battery Clip 16 Key 28-03-14/Channel 1 Test/Zoom Scan (26x31x36)/Cube

0: Interpolated grid: $dx=1.6$ mm, $dy=1.6$ mm, $dz=1.0$ mm; Reference Value = 78.545 V/m; **Power Drift = -0.18 dB**

Averaged SAR: SAR(1g) = 10.300 W/kg; SAR(10g) = 7.390 W/kg

Maximum value of SAR (interpolated) = 13.900 W/kg




SAR Measurement Plot 61



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M140227 450 MHz Body Worn Antenna Helical FCC.da52:6

DUT Name: Tait PTT Transceiver, Type: TPDH7A, Serial: 25543015

Configuration: Body Soft Leather Case Battery Clip 16 Key 28-03-14

Communication System: 0 - CW (0); Communication System Band: Tait 481 MHz FCC; Frequency: 465.5 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=465.5$ MHz; $\sigma = 0.94$ S/m; $\epsilon_r = 55.3$; $\rho = 1000.0\text{g/cm}^3$
 Phantom section: Flat Section

DASY Configuration:

Probe: ET3DV6 - SN1380; ConvF: (7.49,7.49,7.49); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)


Body Soft Leather Case Battery Clip 16 Key 28-03-14/Channel 2 Test/Area Scan (81x221x1):

Interpolated grid: $dx=1.5$ mm, $dy=1.5$ mm; Maximum value of SAR (interpolated) = 9.660 W/kg

Body Soft Leather Case Battery Clip 16 Key 28-03-14/Channel 2 Test/Zoom Scan (26x31x36)/Cube 0: Interpolated grid: $dx=1.6$ mm, $dy=1.6$ mm, $dz=1.0$ mm; Reference Value = 63.441 V/m; **Power Drift = -0.16 dB**

Averaged SAR: SAR(1g) = 9.370 W/kg; SAR(10g) = 6.680 W/kg

Maximum value of SAR (interpolated) = 12.900 W/kg




SAR Measurement Plot 62



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M140227 450 MHz Body Worn Antenna Helical FCC.da52:6

DUT Name: Tait PTT Transceiver, Type: TPDH7A, Serial: 25543015

Configuration: Body Soft Leather Case Battery Clip 16 Key 28-03-14

Communication System: 0 - CW (0); Communication System Band: Tait 481 MHz FCC; Frequency: 481.0 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=481$ MHz; $\sigma = 0.95$ S/m; $\epsilon_r = 55.0$; $\rho = 1000.0\text{g/cm}^3$
 Phantom section: Flat Section

DASY Configuration:

Probe: ET3DV6 - SN1380; ConvF: (7.49,7.49,7.49); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)


Body Soft Leather Case Battery Clip 16 Key 28-03-14/Channel 3 Test/Area Scan (81x221x1):

Interpolated grid: $dx=1.5$ mm, $dy=1.5$ mm; Maximum value of SAR (interpolated) = 9.840 W/kg

Body Soft Leather Case Battery Clip 16 Key 28-03-14/Channel 3 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: $dx=1.6$ mm, $dy=1.6$ mm, $dz=1.0$ mm; Reference Value = 68.281 V/m; **Power Drift = 0.05 dB**

Averaged SAR: SAR(1g) = 9.310 W/kg; SAR(10g) = 6.580 W/kg

Maximum value of SAR (interpolated) = 13.100 W/kg




SAR Measurement Plot 63



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M140227 450 MHz Body Worn Antenna Helical FCC.da52:6

DUT Name: Tait PTT Transceiver, Type: TPDH7A, Serial: 25543015

Configuration: Body Soft Leather Case Battery Clip 16 Key 28-03-14

Communication System: 0 - CW (0); Communication System Band: Tait 481 MHz FCC; Frequency: 496.5 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=496.5$ MHz; $\sigma = 0.96$ S/m; $\epsilon_r = 54.7$; $\rho = 1000.0\text{g/cm}^3$
 Phantom section: Flat Section

DASY Configuration:

Probe: ET3DV6 - SN1380; ConvF: (7.49,7.49,7.49); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Body Soft Leather Case Battery Clip 16 Key 28-03-14/Channel 4 Test/Area Scan (81x221x1):


Interpolated grid: $dx=1.5$ mm, $dy=1.5$ mm; Maximum value of SAR (interpolated) = 6.550 W/kg

Body Soft Leather Case Battery Clip 16 Key 28-03-14/Channel 4 Test/Zoom Scan (26x26x36)/Cube

0: Interpolated grid: $dx=1.6$ mm, $dy=1.6$ mm, $dz=1.0$ mm; Reference Value = 57.208 V/m; **Power Drift = -0.12 dB**

Averaged SAR: SAR(1g) = 6.050 W/kg; SAR(10g) = 4.250 W/kg

Maximum value of SAR (interpolated) = 8.700 W/kg




SAR Measurement Plot 64



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M140227 450 MHz Body Worn Antenna Helical FCC.da52:7

DUT Name: Tait PTT Transceiver, Type: TPDH7A, Serial: 25543015

Configuration: Body Leather Case Spring Clip 16 Key 28-03-14

Communication System: 0 - CW (0); Communication System Band: Tait 481 MHz FCC; Frequency: 450.1 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=450$ MHz; $\sigma = 0.92$ S/m; $\epsilon_r = 55.4$; $\rho = 1000.0$ g/cm³
 Phantom section: Flat Section

DASY Configuration:


Probe: ET3DV6 - SN1380; ConvF: (7.49,7.49,7.49); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Body Leather Case Spring Clip 16 Key 28-03-14/Channel 1 Test/Area Scan (81x221x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 10.400 W/kg


Body Leather Case Spring Clip 16 Key 28-03-14/Channel 1 Test/Zoom Scan (26x31x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 66.256 V/m; **Power Drift = -0.02 dB**

Averaged SAR: SAR(1g) = 9.430 W/kg; SAR(10g) = 6.160 W/kg

Maximum value of SAR (interpolated) = 15.100 W/kg



SAR Measurement Plot 65



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M140227 450 MHz Body Worn Antenna Helical FCC.da52:7

DUT Name: Tait PTT Transceiver, Type: TPDH7A, Serial: 25543015

Configuration: Body Leather Case Spring Clip 16 Key 28-03-14

Communication System: 0 - CW (0); Communication System Band: Tait 481 MHz FCC; Frequency: 465.5 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=465.5$ MHz; $\sigma = 0.94$ S/m; $\epsilon_r = 55.3$; $\rho = 1000.0\text{g/cm}^3$
 Phantom section: Flat Section

DASY Configuration:


Probe: ET3DV6 - SN1380; ConvF: (7.49,7.49,7.49); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Body Leather Case Spring Clip 16 Key 28-03-14/Channel 2 Test/Area Scan (81x221x1): Interpolated grid: $dx=1.5$ mm, $dy=1.5$ mm; Maximum value of SAR (interpolated) = 8.580 W/kg


Body Leather Case Spring Clip 16 Key 28-03-14/Channel 2 Test/Zoom Scan (26x31x36)/Cube 0: Interpolated grid: $dx=1.6$ mm, $dy=1.6$ mm, $dz=1.0$ mm; Reference Value = 51.801 V/m; **Power Drift = -0.16 dB**

Averaged SAR: SAR(1g) = 8.340 W/kg; SAR(10g) = 5.470 W/kg

Maximum value of SAR (interpolated) = 13.500 W/kg



SAR Measurement Plot 66



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M140227 450 MHz Body Worn Antenna Helical FCC.da52:7

DUT Name: Tait PTT Transceiver, Type: TPDH7A, Serial: 25543015

Configuration: Body Leather Case Spring Clip 16 Key 28-03-14

Communication System: 0 - CW (0); Communication System Band: Tait 481 MHz FCC; Frequency: 481.0 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=481$ MHz; $\sigma = 0.95$ S/m; $\epsilon_r = 55.0$; $\rho = 1000.0\text{g/cm}^3$
 Phantom section: Flat Section

DASY Configuration:


Probe: ET3DV6 - SN1380; ConvF: (7.49,7.49,7.49); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Body Leather Case Spring Clip 16 Key 28-03-14/Channel 3 Test/Area Scan (81x221x1): Interpolated grid: $dx=1.5$ mm, $dy=1.5$ mm; Maximum value of SAR (interpolated) = 9.550 W/kg


Body Leather Case Spring Clip 16 Key 28-03-14/Channel 3 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: $dx=1.6$ mm, $dy=1.6$ mm, $dz=1.0$ mm; Reference Value = 60.728 V/m; **Power Drift = -0.08 dB**

Averaged SAR: SAR(1g) = 9.160 W/kg; SAR(10g) = 5.960 W/kg

Maximum value of SAR (interpolated) = 14.800 W/kg



SAR Measurement Plot 67



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M140227 450 MHz Body Worn Antenna Helical FCC.da52:7

DUT Name: Tait PTT Transceiver, Type: TPDH7A, Serial: 25543015

Configuration: Body Leather Case Spring Clip 16 Key 28-03-14

Communication System: 0 - CW (0); Communication System Band: Tait 481 MHz FCC; Frequency: 496.5 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=496.5$ MHz; $\sigma = 0.96$ S/m; $\epsilon_r = 54.7$; $\rho = 1000.0\text{g/cm}^3$
 Phantom section: Flat Section

DASY Configuration:


Probe: ET3DV6 - SN1380; ConvF: (7.49,7.49,7.49); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Body Leather Case Spring Clip 16 Key 28-03-14/Channel 4 Test/Area Scan (81x221x1): Interpolated grid: $dx=1.5$ mm, $dy=1.5$ mm; Maximum value of SAR (interpolated) = 5.820 W/kg

Body Leather Case Spring Clip 16 Key 28-03-14/Channel 4 Test/Zoom Scan (26x26x36)/Cube 0: Interpolated grid: $dx=1.6$ mm, $dy=1.6$ mm, $dz=1.0$ mm; Reference Value = 48.950 V/m; **Power Drift = -0.17 dB**

Averaged SAR: SAR(1g) = 5.750 W/kg; SAR(10g) = 3.720 W/kg

Maximum value of SAR (interpolated) = 9.500 W/kg




SAR Measurement Plot 68



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M140227 450 MHz Body Worn Antenna Helical FCC.da52:8

DUT Name: Tait PTT Transceiver, Type: TPDH7A, Serial: 25543015

Configuration: Body Leather Case D-Stud Spring Clip 16 Key 28-03-14

Communication System: 0 - CW (0); Communication System Band: Tait 481 MHz FCC; Frequency: 481.0 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=481$ MHz; $\sigma = 0.95$ S/m; $\epsilon_r = 55.0$; $\rho = 1000.0\text{g/cm}^3$
 Phantom section: Flat Section

DASY Configuration:

Probe: ET3DV6 - SN1380; ConvF: (7.49,7.49,7.49); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Body Leather Case D-Stud Spring Clip 16 Key 28-03-14/Channel 3 Test/Area Scan (81x221x1):


Interpolated grid: $dx=1.5$ mm, $dy=1.5$ mm; Maximum value of SAR (interpolated) = 5.840 W/kg

Body Leather Case D-Stud Spring Clip 16 Key 28-03-14/Channel 3 Test/Zoom Scan

(21x21x36)/Cube 0: Interpolated grid: $dx=1.6$ mm, $dy=1.6$ mm, $dz=1.0$ mm; Reference Value = 45.969 V/m; **Power Drift = 0.02 dB**

Averaged SAR: SAR(1g) = 5.630 W/kg; SAR(10g) = 3.720 W/kg

Maximum value of SAR (interpolated) = 9.060 W/kg




SAR Measurement Plot 69



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M140227 450 MHz Body Worn Antenna Helical FCC.da52:9

DUT Name: Tait PTT Transceiver, Type: TPDH7A, Serial: 25543015

Configuration: Body Leather Case D-Stud Belt Loop 16 Key 28-03-14

Communication System: 0 - CW (0); Communication System Band: Tait 481 MHz FCC; Frequency: 481.0 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=481$ MHz; $\sigma = 0.95$ S/m; $\epsilon_r = 55.0$; $\rho = 1000.0$ g/cm³
 Phantom section: Flat Section

DASY Configuration:

Probe: ET3DV6 - SN1380; ConvF: (7.49,7.49,7.49); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Body Leather Case D-Stud Belt Loop 16 Key 28-03-14/Channel 3 Test/Area Scan (81x221x1):


Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 3.040 W/kg

Body Leather Case D-Stud Belt Loop 16 Key 28-03-14/Channel 3 Test/Zoom Scan (21x21x36)/Cube

0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 34.412 V/m; **Power Drift = -0.00 dB**

Averaged SAR: SAR(1g) = 2.910 W/kg; SAR(10g) = 2.160 W/kg

Maximum value of SAR (interpolated) = 3.880 W/kg




SAR Measurement Plot 70



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M140227 450 MHz Body Worn Antenna Helical FCC.da52:10

DUT Name: Tait PTT Transceiver, Type: TPDH7A, Serial: 25543015

Configuration: Body Leather Case Belt Loop 16 Key 28-03-14

Communication System: 0 - CW (0); Communication System Band: Tait 481 MHz FCC; Frequency: 481.0 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=481$ MHz; $\sigma = 0.95$ S/m; $\epsilon_r = 55.0$; $\rho = 1000.0$ g/cm³
 Phantom section: Flat Section


DASY Configuration:

Probe: ET3DV6 - SN1380; ConvF: (7.49,7.49,7.49); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)


Body Leather Case Belt Loop 16 Key 28-03-14/Channel 3 Test/Area Scan (81x221x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 6.860 W/kg

Body Leather Case Belt Loop 16 Key 28-03-14/Channel 3 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 60.291 V/m; **Power Drift = 0.03 dB**

Averaged SAR: SAR(1g) = 6.680 W/kg; SAR(10g) = 4.850 W/kg
 Maximum value of SAR (interpolated) = 9.060 W/kg



SAR Measurement Plot 71



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M140227 450 MHz Body Worn Antenna Helical FCC.da52:11

DUT Name: Tait PTT Transceiver, Type: TPDH7A, Serial: 25543015

Configuration: Body Nylon Case Belt Loop Extended Battery 16 Key 31-03-14

Communication System: 0 - CW (0); Communication System Band: Tait 481 MHz FCC; Frequency: 450.1 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=450$ MHz; $\sigma = 0.93$ S/m; $\epsilon_r = 55.9$; $\rho = 1000.0$ g/cm³
 Phantom section: Flat Section

DASY Configuration:

Probe: ET3DV6 - SN1380; ConvF: (7.49,7.49,7.49); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Body Nylon Case Belt Loop Extended Battery 16 Key 31-03-14/Channel 1 Test/Area Scan (81x221x1):


Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 9.210 W/kg

Body Nylon Case Belt Loop Extended Battery 16 Key 31-03-14/Channel 1 Test/Zoom Scan

(26x31x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 71.952 V/m; **Power Drift = -0.07 dB**

Averaged SAR: SAR(1g) = 9.090 W/kg; SAR(10g) = 6.610 W/kg

Maximum value of SAR (interpolated) = 12.200 W/kg




SAR Measurement Plot 72



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M140227 450 MHz Body Worn Antenna Helical FCC.da52:12

DUT Name: Tait PTT Transceiver, Type: TPDH7A, Serial: 25543015

Configuration: Body Nylon Case Belt Loop FAAA Audio Accessory 16 Key 31-03-14

Communication System: 0 - CW (0); Communication System Band: Tait 481 MHz FCC; Frequency: 450.1 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=450$ MHz; $\sigma = 0.93$ S/m; $\epsilon_r = 55.9$; $\rho = 1000.0$ g/cm³
 Phantom section: Flat Section

DASY Configuration:

Probe: ET3DV6 - SN1380; ConvF: (7.49,7.49,7.49); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Body Nylon Case Belt Loop FAAA Audio Accessory 16 Key 31-03-14/Channel 1 Test/Area Scan


(81x221x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 9.480 W/kg

Body Nylon Case Belt Loop FAAA Audio Accessory 16 Key 31-03-14/Channel 1 Test/Zoom Scan


(21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 66.532 V/m; **Power Drift = -0.14 dB**

Averaged SAR: SAR(1g) = 9.410 W/kg; SAR(10g) = 6.770 W/kg

Maximum value of SAR (interpolated) = 12.800 W/kg



SAR Measurement Plot 73



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M140227 450 MHz Body Worn Antenna Helical FCC.da52:13

DUT Name: Tait PTT Transceiver, Type: TPDH7A, Serial: 25543015


Configuration: Body Nylon Case Belt Loop FEAA Audio Accessory 16 Key 31-03-14

Communication System: 0 - CW (0); Communication System Band: Tait 481 MHz FCC; Frequency: 450.1 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=450$ MHz; $\sigma = 0.93$ S/m; $\epsilon_r = 55.9$; $\rho = 1000.0$ g/cm³
 Phantom section: Flat Section


DASY Configuration:

Probe: ET3DV6 - SN1380; ConvF: (7.49,7.49,7.49); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Body Nylon Case Belt Loop FEAA Audio Accessory 16 Key 31-03-14/Channel 1 Test/Area Scan (81x221x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 10.800 W/kg
Body Nylon Case Belt Loop FEAA Audio Accessory 16 Key 31-03-14/Channel 1 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 74.635 V/m; **Power Drift = -0.15 dB**
Averaged SAR: SAR(1g) = 11.000 W/kg; SAR(10g) = 7.780 W/kg
 Maximum value of SAR (interpolated) = 15.100 W/kg



SAR Measurement Plot 74



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M140227 450 MHz Body Worn Antenna Helical FCC.da52:14

DUT Name: Tait PTT Transceiver, Type: TPDH7A, Serial: 25543015

Configuration: Body Nylon Case Belt Loop 4 Key 31-03-14

Communication System: 0 - CW (0); Communication System Band: Tait 481 MHz FCC; Frequency: 450.1 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=450$ MHz; $\sigma = 0.93$ S/m; $\epsilon_r = 55.9$; $\rho = 1000.0$ g/cm³
 Phantom section: Flat Section


DASY Configuration:

Probe: ET3DV6 - SN1380; ConvF: (7.49,7.49,7.49); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)


Body Nylon Case Belt Loop 4 Key 31-03-14/Channel 1 Test/Area Scan (81x221x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 10.700 W/kg

Body Nylon Case Belt Loop 4 Key 31-03-14/Channel 1 Test/Zoom Scan (36x31x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 77.617 V/m; **Power Drift = 0.03 dB**

Averaged SAR: SAR(1g) = 10.300 W/kg; SAR(10g) = 7.250 W/kg
 Maximum value of SAR (interpolated) = 14.300 W/kg



SAR Measurement Plot 75



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M140227 450 MHz Body Worn Antenna Helical FCC.da52:15

DUT Name: Tait PTT Transceiver, Type: TPDH7A, Serial: 25543015

Configuration: Body Nylon Case Belt Loop 16-key Variability 31-03-14

Communication System: 0 - CW (0); Communication System Band: Tait 481 MHz FCC; Frequency: 450.1 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=450$ MHz; $\sigma = 0.93$ S/m; $\epsilon_r = 55.9$; $\rho = 1000.0$ g/cm³
 Phantom section: Flat Section

DASY Configuration:

Probe: ET3DV6 - SN1380; ConvF: (7.49,7.49,7.49); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Body Nylon Case Belt Loop 16-key Variability 31-03-14/Channel 1 Test/Area Scan (81x221x1):


Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 11.900 W/kg

Body Nylon Case Belt Loop 16-key Variability 31-03-14/Channel 1 Test/Zoom Scan

(26x31x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 79.362 V/m; **Power Drift = -0.08 dB**

Averaged SAR: SAR(1g) = 11.800 W/kg; SAR(10g) = 8.200 W/kg

Maximum value of SAR (interpolated) = 16.800 W/kg




SAR Measurement Plot 76



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M140227 450 MHz Body Worn Antenna Helical FCC.da52:16

DUT Name: Dipole 450 MHz, Type: D450V3, Serial: 1074

Configuration: System Check 27-03-14

Communication System: 0 - CW 450 MHz; Communication System Band: 450 MHz;; Frequency: 450.0 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=450$ MHz; $\sigma = 0.90$ S/m; $\epsilon_r = 55.6$; $\rho = 1000.0\text{g/cm}^3$
 Phantom section: Flat Section

DASY Configuration:


Probe: ET3DV6 - SN1380; ConvF: (7.49,7.49,7.49); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection)
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

System Check 27-03-14/Channel 1Test/Area Scan (51x121x1): Interpolated grid: $dx=1.5$ mm, $dy=1.5$ mm;
 Maximum value of SAR (interpolated) = 1.920 W/kg

System Check 27-03-14/Channel 1Test/Zoom Scan (31x31x36)/Cube 0: Interpolated grid: $dx=1.0$ mm, $dy=1.0$ mm, $dz=1.0$ mm; Reference Value = 46.992 V/m; **Power Drift = 0.20 dB**

Averaged SAR: SAR(1g) = 1.850 W/kg; SAR(10g) = 1.170 W/kg

Maximum value of SAR (interpolated) = 3.210 W/kg




0 dB = 1.92 W/kg = 2.83 dBW/kg

SAR Measurement Plot 77



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M140227 450 MHz Body Worn Antenna Helical FCC.da52:17

DUT Name: Dipole 450 MHz, Type: D450V3, Serial: 1074

Configuration: System Check 28-03-14

Communication System: 0 - CW 450 MHz; Communication System Band: 450 MHz; Frequency: 450.0 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=450$ MHz; $\sigma = 0.92$ S/m; $\epsilon_r = 55.4$; $\rho = 1000.0$ g/cm³
 Phantom section: Flat Section

DASY Configuration:


Probe: ET3DV6 - SN1380; ConvF: (7.49,7.49,7.49); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection)
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

System Check 28-03-14/Channel 1Test/Area Scan (51x121x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm;
 Maximum value of SAR (interpolated) = 1.970 W/kg

System Check 28-03-14/Channel 1Test/Zoom Scan (31x31x36)/Cube 0: Interpolated grid: dx=1.0 mm, dy=1.0 mm, dz=1.0 mm; Reference Value = 48.224 V/m; **Power Drift = -0.01 dB**

Averaged SAR: SAR(1g) = 1.920 W/kg; SAR(10g) = 1.210 W/kg

Maximum value of SAR (interpolated) = 3.310 W/kg




0 dB = 1.97 W/kg = 2.94 dBW/kg

SAR Measurement Plot 78



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M140227 450 MHz Body Worn Antenna Helical FCC.da52:18

DUT Name: Dipole 450 MHz, Type: D450V3, Serial: 1074

Configuration: System Check 31-03-14

Communication System: 0 - CW 450 MHz; Communication System Band: 450 MHz; Frequency: 450.0 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=450$ MHz; $\sigma = 0.93$ S/m; $\epsilon_r = 55.9$; $\rho = 1000.0$ g/cm³
 Phantom section: Flat Section

DASY Configuration:


Probe: ET3DV6 - SN1380; ConvF: (7.49,7.49,7.49); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection)
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

System Check 31-03-14/Channel 1Test/Area Scan (51x121x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm;
 Maximum value of SAR (interpolated) = 1.980 W/kg

System Check 31-03-14/Channel 1Test/Zoom Scan (31x31x36)/Cube 0: Interpolated grid: dx=1.0 mm, dy=1.0 mm, dz=1.0 mm; Reference Value = 48.186 V/m; **Power Drift = -0.04 dB**

Averaged SAR: SAR(1g) = 1.900 W/kg; SAR(10g) = 1.200 W/kg

Maximum value of SAR (interpolated) = 3.270 W/kg




SAR Measurement Plot 79



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M140227 450 MHz Face Frontal Antenna Whip.da52:0

DUT Name: Tait PTT Transceiver, Type: TPDH7A, Serial: 25543015

Configuration: Head Face Frontal 16 Key 01-04-14

Communication System: 0 - CW (0); Communication System Band: Tait 485 MHz; Frequency: 450.0 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=450$ MHz; $\sigma = 0.84$ S/m; $\epsilon_r = 42.8$; $\rho = 1.0\text{g/cm}^3$
 Phantom section: Flat Section

DASY Configuration:


Probe: ET3DV6 - SN1380; ConvF: (7.31,7.31,7.31); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection)
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.7(1137); SEMCAD X Version 14.6.10 (7164)

Head Face Frontal 16 Key 01-04-14/Channel 1 Test/Area Scan (81x221x1): Interpolated grid: $dx=1.5$ mm, $dy=1.5$ mm; Maximum value of SAR (interpolated) = 5.750 W/kg

Head Face Frontal 16 Key 01-04-14/Channel 1 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: $dx=1.6$ mm, $dy=1.6$ mm, $dz=1.0$ mm; Reference Value = 55.230 V/m; Power Drift = -0.08 dB

Averaged SAR: SAR(1g) = 5.660 W/kg; SAR(10g) = 4.250 W/kg

Maximum value of SAR (interpolated) = 6.880 W/kg




0 dB = 5.75 W/kg = 7.60 dBW/kg

SAR Measurement Plot 80



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M140227 450 MHz Face Frontal Antenna Whip.da52:0

DUT Name: Tait PTT Transceiver, Type: TPDH7A, Serial: 25543015

Configuration: Head Face Frontal 16 Key 01-04-14

Communication System: 0 - CW (0); Communication System Band: Tait 485 MHz; Frequency: 467.5 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=450$ MHz; $\sigma = 0.86$ S/m; $\epsilon_r = 42.4$; $\rho = 1000.0$ g/cm³
 Phantom section: Flat Section

DASY Configuration:


Probe: ET3DV6 - SN1380; ConvF: (7.31,7.31,7.31); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection)
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.7(1137); SEMCAD X Version 14.6.10 (7164)

Head Face Frontal 16 Key 01-04-14/Channel 2 Test/Area Scan (81x221x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 6.320 W/kg

Head Face Frontal 16 Key 01-04-14/Channel 2 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 62.051 V/m; **Power Drift = -0.13 dB**

Averaged SAR: SAR(1g) = 6.230 W/kg; SAR(10g) = 4.680 W/kg

Maximum value of SAR (interpolated) = 7.710 W/kg




0 dB = 5.75 W/kg = 7.60 dBW/kg

SAR Measurement Plot 81



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M140227 450 MHz Face Frontal Antenna Whip.da52:0

DUT Name: Tait PTT Transceiver, Type: TPDH7A, Serial: 25543015

Configuration: Head Face Frontal 16 Key 01-04-14

Communication System: 0 - CW (0); Communication System Band: Tait 485 MHz; Frequency: 485.0 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=467.5$ MHz; $\sigma = 0.87$ S/m; $\epsilon_r = 42.0$; $\rho = 1000.0\text{g/cm}^3$
 Phantom section: Flat Section

DASY Configuration:


Probe: ET3DV6 - SN1380; ConvF: (7.31,7.31,7.31); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection)
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.7(1137); SEMCAD X Version 14.6.10 (7164)

Head Face Frontal 16 Key 01-04-14/Channel 3 Test/Area Scan (81x221x1): Interpolated grid: $dx=1.5$ mm, $dy=1.5$ mm; Maximum value of SAR (interpolated) = 6.440 W/kg

Head Face Frontal 16 Key 01-04-14/Channel 3 Test/Zoom Scan (26x26x36)/Cube 0: Interpolated grid: $dx=1.6$ mm, $dy=1.6$ mm, $dz=1.0$ mm; Reference Value = 59.003 V/m; **Power Drift = -0.12 dB**

Averaged SAR: SAR(1g) = 6.220 W/kg; SAR(10g) = 4.680 W/kg

Maximum value of SAR (interpolated) = 7.800 W/kg




0 dB = 6.32 W/kg = 8.01 dBW/kg

SAR Measurement Plot 82



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M140227 450 MHz Face Frontal Antenna Whip.da52:0

DUT Name: Tait PTT Transceiver, Type: TPDH7A, Serial: 25543015

Configuration: Head Face Frontal 16 Key 01-04-14

Communication System: 0 - CW (0); Communication System Band: Tait 485 MHz; Frequency: 502.5 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=485$ MHz; $\sigma = 0.88$ S/m; $\epsilon_r = 41.6$; $\rho = 1000.0$ g/cm³
 Phantom section: Flat Section

DASY Configuration:


Probe: ET3DV6 - SN1380; ConvF: (7.31,7.31,7.31); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection)
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.7(1137); SEMCAD X Version 14.6.10 (7164)

Head Face Frontal 16 Key 01-04-14/Channel 4 Test/Area Scan (81x221x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 3.860 W/kg

Head Face Frontal 16 Key 01-04-14/Channel 4 Test/Zoom Scan (26x26x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 46.437 V/m; **Power Drift = -0.20 dB**

Averaged SAR: SAR(1g) = 3.740 W/kg; SAR(10g) = 2.810 W/kg

Maximum value of SAR (interpolated) = 4.780 W/kg




0 dB = 6.44 W/kg = 8.09 dBW/kg

SAR Measurement Plot 83



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M140227 450 MHz Face Frontal Antenna Whip.da52:0

DUT Name: Tait PTT Transceiver, Type: TPDH7A, Serial: 25543015

Configuration: Head Face Frontal 16 Key 01-04-14

Communication System: 0 - CW (0); Communication System Band: Tait 481 MHz FCC; Frequency: 511.9 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=502.5$ MHz; $\sigma = 0.89$ S/m; $\epsilon_r = 41.5$; $\rho = 1000.0$ g/cm³
 Phantom section: Flat Section

DASY Configuration:


Probe: ET3DV6 - SN1380; ConvF: (7.31,7.31,7.31); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection)
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.7(1137); SEMCAD X Version 14.6.10 (7164)

Head Face Frontal 16 Key 01-04-14/Channel 5 Test/Area Scan (81x221x1): Interpolated grid: dx=1.5 mm, dy=1.5 mm; Maximum value of SAR (interpolated) = 3.730 W/kg

Head Face Frontal 16 Key 01-04-14/Channel 5 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: dx=1.6 mm, dy=1.6 mm, dz=1.0 mm; Reference Value = 46.959 V/m; **Power Drift = -0.12 dB**

Averaged SAR: SAR(1g) = 3.590 W/kg; SAR(10g) = 2.710 W/kg

Maximum value of SAR (interpolated) = 4.560 W/kg




0 dB = 3.86 W/kg = 5.87 dBW/kg

SAR Measurement Plot 84



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M140227 450 MHz Face Frontal Antenna Whip.da52:1

DUT Name: Tait PTT Transceiver, Type: TPDH7A, Serial: 25543015

Configuration: Head Face Frontal 4 Key 01-04-14

Communication System: 0 - CW (0); Communication System Band: Tait 485 MHz; Frequency: 467.5 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=467.5$ MHz; $\sigma = 0.86$ S/m; $\epsilon_r = 42.4$; $\rho = 1.0\text{g/cm}^3$
 Phantom section: Flat Section

DASY Configuration:


Probe: ET3DV6 - SN1380; ConvF: (7.31,7.31,7.31); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection)
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.7(1137); SEMCAD X Version 14.6.10 (7164)

Head Face Frontal 4 Key 01-04-14/Channel 2 Test/Area Scan (81x221x1): Interpolated grid: $dx=1.5$ mm, $dy=1.5$ mm; Maximum value of SAR (interpolated) = 6.020 W/kg


Head Face Frontal 4 Key 01-04-14/Channel 2 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: $dx=1.6$ mm, $dy=1.6$ mm, $dz=1.0$ mm; Reference Value = 56.824 V/m; **Power Drift = -0.19 dB**

Averaged SAR: SAR(1g) = 5.960 W/kg; SAR(10g) = 4.480 W/kg

Maximum value of SAR (interpolated) = 7.360 W/kg



SAR Measurement Plot 85



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M140227 450 MHz Face Frontal Antenna Whip.da52:2

DUT Name: Tait PTT Transceiver, Type: TPDH7A, Serial: 25543015

Configuration: Head Face Frontal Low Capacity Battery 16 Key 01-04-14

Communication System: 0 - CW (0); Communication System Band: Tait 485 MHz; Frequency: 467.5 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=467.5$ MHz; $\sigma = 0.86$ S/m; $\epsilon_r = 42.4$; $\rho = 1.0\text{g/cm}^3$
 Phantom section: Flat Section

DASY Configuration:

Probe: ET3DV6 - SN1380; ConvF: (7.31,7.31,7.31); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection)
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.7(1137); SEMCAD X Version 14.6.10 (7164)

Head Face Frontal Low Capacity Battery 16 Key 01-04-14/Channel 2 Test/Area Scan (81x221x1):


Interpolated grid: $dx=1.5$ mm, $dy=1.5$ mm; Maximum value of SAR (interpolated) = 5.720 W/kg

Head Face Frontal Low Capacity Battery 16 Key 01-04-14/Channel 2 Test/Zoom Scan

(21x21x36)/Cube 0: Interpolated grid: $dx=1.6$ mm, $dy=1.6$ mm, $dz=1.0$ mm; Reference Value = 58.352 V/m; **Power Drift = -0.20 dB**

Averaged SAR: SAR(1g) = 5.630 W/kg; SAR(10g) = 4.240 W/kg

Maximum value of SAR (interpolated) = 6.900 W/kg




SAR Measurement Plot 86



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M140227 450 MHz Face Frontal Antenna Whip.da52:3

DUT Name: Dipole 450 MHz, Type: D450V3, Serial: 1074

Configuration: System Check 01-04-14

Communication System: 0 - CW 450 MHz; Communication System Band: **450MHz**; Frequency: 450.0 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=450$ MHz; $\sigma = 0.84$ S/m; $\epsilon_r = 42.8$; $\rho = 1.0g/cm^3$
 Phantom section: Flat Section

DASY Configuration:


Probe: ET3DV6 - SN1380; ConvF: (7.31,7.31,7.31); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection)
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.7(1137); SEMCAD X Version 14.6.10 (7164)

System Check 01-04-14/Channel 1Test/Area Scan (51x121x1): Interpolated grid: $dx=1.5$ mm, $dy=1.5$ mm;
 Maximum value of SAR (interpolated) = 1.990 W/kg

System Check 01-04-14/Channel 1Test/Zoom Scan (31x31x36)/Cube 0: Interpolated grid: $dx=1.0$ mm, $dy=1.0$ mm, $dz=1.0$ mm; Reference Value = 51.395 V/m; **Power Drift = -0.08 dB**

Averaged SAR: SAR(1g) = 1.880 W/kg; SAR(10g) = 1.190 W/kg

Maximum value of SAR (interpolated) = 3.090 W/kg




0 dB = 1.99 W/kg = 2.99 dBW/kg

SAR Measurement Plot 87



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M140227 450 MHz Face Frontal Antenna Helical.da52:0

DUT Name: Tait PTT Transceiver, Type: TPDH7A, Serial: 25543015

Configuration: Head Face Frontal 16 Key 01-04-14

Communication System: 0 - CW (0); Communication System Band: Tait 485 MHz; Frequency: 485.0 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=485$ MHz; $\sigma = 0.87$ S/m; $\epsilon_r = 42.0$; $\rho = 1.0g/cm^3$
 Phantom section: Flat Section

DASY Configuration:


Probe: ET3DV6 - SN1380; ConvF: (7.31,7.31,7.31); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.7(1137); SEMCAD X Version 14.6.10 (7164)

Head Face Frontal 16 Key 01-04-14/Channel 3 Test/Area Scan (81x181x1): Interpolated grid: $dx=1.5$ mm, $dy=1.5$ mm; Maximum value of SAR (interpolated) = 6.920 W/kg

Head Face Frontal 16 Key 01-04-14/Channel 3 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: $dx=1.6$ mm, $dy=1.6$ mm, $dz=1.0$ mm; Reference Value = 64.746 V/m; **Power Drift = -0.19 dB**

Averaged SAR: SAR(1g) = 6.670 W/kg; SAR(10g) = 5.020 W/kg

Maximum value of SAR (interpolated) = 8.330 W/kg




0 dB = 6.92 W/kg = 8.40 dBW/kg

SAR Measurement Plot 88



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M140227 450 MHz Face Frontal Antenna Helical.da52:1

DUT Name: Tait PTT Transceiver, Type: TPDH7A, Serial: 25543015

Configuration: Head Face Frontal Low Capacity Battery 16 Key 01-04-14

Communication System: 0 - CW (0); Communication System Band: Tait 485 MHz; Frequency: 485.0 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=485$ MHz; $\sigma = 0.87$ S/m; $\epsilon_r = 42.0$; $\rho = 1.0\text{g/cm}^3$
 Phantom section: Flat Section

DASY Configuration:

Probe: ET3DV6 - SN1380; ConvF: (7.31,7.31,7.31); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.7(1137); SEMCAD X Version 14.6.10 (7164)

Head Face Frontal Low Capacity Battery 16 Key 01-04-14/Channel 3 Test/Area Scan (81x181x1):


Interpolated grid: $dx=1.5$ mm, $dy=1.5$ mm; Maximum value of SAR (interpolated) = 6.170 W/kg

Head Face Frontal Low Capacity Battery 16 Key 01-04-14/Channel 3 Test/Zoom Scan

(21x21x36)/Cube 0: Interpolated grid: $dx=1.6$ mm, $dy=1.6$ mm, $dz=1.0$ mm; Reference Value = 64.398 V/m; **Power Drift = -0.20 dB**

Averaged SAR: SAR(1g) = 5.930 W/kg; SAR(10g) = 4.470 W/kg

Maximum value of SAR (interpolated) = 7.410 W/kg




SAR Measurement Plot 89



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech Test File: M140227 450 MHz Face Frontal Antenna Helical.da52:2

DUT Name: Tait PTT Transceiver, Type: TPDH7A, Serial: 25543015

Configuration: Head Face Frontal 4 Key 01-04-14

Communication System: 0 - CW (0); Communication System Band: Tait 485 MHz; Frequency: 485.0 MHz, Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=485$ MHz; $\sigma = 0.87$ S/m; $\epsilon_r = 42.0$; $\rho = 1.0\text{g/cm}^3$
 Phantom section: Flat Section

DASY Configuration:


Probe: ET3DV6 - SN1380; ConvF: (7.31,7.31,7.31); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection (Locations From Previous Scan Used))
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.7(1137); SEMCAD X Version 14.6.10 (7164)

Head Face Frontal 4 Key 01-04-14/Channel 3 Test/Area Scan (81x181x1): Interpolated grid: $dx=1.5$ mm, $dy=1.5$ mm; Maximum value of SAR (interpolated) = 6.690 W/kg

Head Face Frontal 4 Key 01-04-14/Channel 3 Test/Zoom Scan (21x21x36)/Cube 0: Interpolated grid: $dx=1.6$ mm, $dy=1.6$ mm, $dz=1.0$ mm; Reference Value = 65.057 V/m; **Power Drift = -0.19 dB**

Averaged SAR: SAR(1g) = 6.490 W/kg; SAR(10g) = 4.880 W/kg

Maximum value of SAR (interpolated) = 8.130 W/kg




0 dB = 6.69 W/kg = 8.25 dBW/kg

SAR Measurement Plot 90



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.