

FCC Test Report

FCC ID : Z64-2564N

Equipment : CC2564 Bluetooth HCI Module

Model No. : CC2564MODN

Brand Name : Texas Instruments

Applicant : Texas Instruments Inc

Address : 12500 TI Blvd, Dallas USA 75243

Standard : 47 CFR FCC Part 15.247

Received Date : Dec. 04, 2013

Tested Date : Dec. 12, 2013 ~ Feb. 27, 2014

We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Approved & Reviewed by:

Gary Chang / Manager

lac MRA



Page: 1 of 47

Report No.: FR3D0402AD Report Version: Rev. 01



Table of Contents

1	GENERAL DESCRIPTION	5
1.1	Information	5
1.2	Local Support Equipment List	7
1.3	Test Setup Chart	7
1.4	The Equipment List	8
1.5	Test Standards	g
1.6	Measurement Uncertainty	10
2	TEST CONFIGURATION	11
2.1	Testing Condition	11
2.2	The Worst Test Modes and Channel Details	11
3	TRANSMITTER TEST RESULTS	12
3.1	Conducted Emissions	12
3.2	Unwanted Emissions into Restricted Frequency Bands	15
3.3	Emissions in non-restricted frequency bands	31
3.4	Conducted Output Power	36
3.5	Number of Hopping Frequency	38
3.6	20dB and Occupied Bandwidth	40
3.7	Channel Separation	42
3.8	Number of Dwell Time	44
4	TEST LABORATORY INFORMATION	47



Release Record

Report No.	Version	Description	Issued Date
FR3D0402AD	Rev. 01	Initial issue	Mar. 26, 2014

Report No.: FR3D0402AD Page: 3 of 47



Summary of Test Results

FCC Rules	Test Items	Measured	Result
15.207	Conducted Emissions	[dBuV]: 0.302MHz 39.91 (Margin 10.28dB) - AV	Pass
15.247(d) 15.209	Radiated Emissions	[dBuV/m at 3m]: 2483.50MHz 43.89 (Margin 10.11dB) - AV	Pass
15.247(d)	Band Edge	Meet the requirement of limit	Pass
15.247(b)(1)	Conducted Output Power	Power [dBm]: BR: 11.18 EDR: 12.89	Pass
15.247(a)(1)(iii)	Number of Hopping Channels	Meet the requirement of limit	Pass
15.247(a)(1)	Hopping Channel Separation	Meet the requirement of limit	Pass
15.247(a)(1)(iii)	Dwell Time	Meet the requirement of limit	Pass
15.203	Antenna Requirement	Meet the requirement of limit	Pass

Report No.: FR3D0402AD Page: 4 of 47



1 General Description

1.1 Information

1.1.1 Specification of the Equipment under Test (EUT)

RF General Information							
Frequency Range (MHz) Bluetooth Ch. Frequency Channel Number Data Rate							
2400-2483.5	BR V2.1	2402-2480	0-78 [79]	1 Mbps			
2400-2483.5	EDR V2.1	2402-2480	0-78 [79]	2 Mbps			
2400-2483.5	EDR V2.1	2402-2480	0-78 [79]	3 Mbps			

Note 1: RF output power specifies that Maximum Peak Conducted Output Power.

Note 2: Bluetooth BR uses a GFSK.

Note 3: Bluetooth EDR uses a combination of $\pi/4$ -DQPSK and 8DPSK.

1.1.2 Antenna Details

Ant. No.	Туре	Gain (dBi)	Brand	Model
1	Chip antenna	-1.38	MAG.LAYERS	LTA-5320-2G4S3-A1

1.1.3 EUT Operational Condition

Type of Power Supply 3.3Vdc from host

1.1.4 Accessories

N/A

Report No.: FR3D0402AD Page: 5 of 47



1.1.5 Channel List

Frequency band (MHz)				2400~2483.5			
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2422	40	2442	60	2462
1	2403	21	2423	41	2443	61	2463
2	2404	22	2424	42	2444	62	2464
3	2405	23	2425	43	2445	63	2465
4	2406	24	2426	44	2446	64	2466
5	2407	25	2427	45	2447	65	2467
6	2408	26	2428	46	2448	66	2468
7	2409	27	2429	47	2449	67	2469
8	2410	28	2430	48	2450	68	2470
9	2411	29	2431	49	2451	69	2471
10	2412	30	2432	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461		

1.1.6 Test Tool

Test Tool	HCI Tester V3.0.0.24

1.1.7 Power Setting

Modulation Mode	Test Frequency (MHz)				
Wodulation Wode	2402	2441	2480		
GFSK/1Mbps	255,63	255,63	255,63		
8DPSK/3Mbps	255,63	255,63	255,63		


Report No.: FR3D0402AD Page: 6 of 47



1.2 Local Support Equipment List

	Support Equipment List							
No.	Equipment	Brand	Model	S/N	FCC ID	Signal cable / Length (m)		
1	Notebook	DELL	E5420		DoC	RS232, 3m non-shielded		
2	Fixture	Ampak	GT966X_EVB_IO BOARD_V00					
3	Adapter for fixture	LINKSYS	KSAFB0500100W 1US					

1.3 Test Setup Chart



Report No.: FR3D0402AD Page: 7 of 47



1.4 The Equipment List

Test Item	Conducted Emission	Conducted Emission						
Test Site	Conduction room 1 / (C	Conduction room 1 / (CO01-WS)						
Tested date	Dec. 18, 2013	Dec. 18, 2013						
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until			
EMC Receiver	R&S	ESCS 30	100169	Oct. 15, 2013	Oct. 14, 2014			
LISN	SCHWARZBECK MESS-ELEKTRONIK	Schwarzbeck 8127	8127-667	Nov. 23, 2013	Nov. 22, 2014			
LISN (Support Unit)	SCHWARZBECK MESS-ELEKTRONIK	Schwarzbeck 8127	8127-666	Dec. 04, 2013	Dec. 03, 2014			
RF Cable-CON	Woken	CFD200-NL	CFD200-NL-001	Apr. 24, 2013	Apr. 23, 2014			
50 ohm terminal (Support Unit)	NA 50 04 Apr. 22, 2013 Apr. 21, 2014							
Note: Calibration Interval of instruments listed above is one year.								

Test Item	RF Conducted	RF Conducted							
Test Site	(TH01-WS)	TH01-WS)							
Tested date	Dec. 12 ~ 24, 2013	Dec. 12 ~ 24, 2013							
Instrument	Manufacturer	Manufacturer Model No. Serial No. Calibration Date Calibration Until							
Spectrum Analyzer	R&S	FSV 40	101499	Jan. 28, 2013	Jan. 27, 2014				
Power Meter	Anritsu	ML2495A	1241002	Oct. 24, 2013	Oct. 23, 2014				
Power Sensor	Anritsu	MA2411B	1207366	Oct. 24, 2013	Oct. 23, 2014				
Note: Calibration Interval of instruments listed above is one year.									

Test Item	RF Conducted				
Test Site	(TH01-WS)				
Tested date	Feb. 26, 2014				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
Spectrum Analyzer	R&S	FSV40	101063	Feb. 17, 2014	Feb. 16, 2015
Power Meter	Anritsu	ML2495A	1241002	Oct. 24, 2013	Oct. 23, 2014
Power Sensor	Anritsu	MA2411B	1207366	Oct. 24, 2013	Oct. 23, 2014
Note: Calibration Inter	val of instruments listed	above is one year.			

Report No.: FR3D0402AD Page: 8 of 47



Test Item	Radiated Emission						
Test Site	966 chamber 2 / (03C	H02-WS)					
Tested date	Feb. 11 ~ Feb. 22, 201	14					
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until		
Spectrum Analyzer	R&S	FSV40	101499	Feb. 08, 2014	Feb. 07, 2015		
Receiver	R&S	ESR3	101657	Jan. 18, 2014	Jan. 17, 2015		
Bilog Antenna	SCHWARZBECK	VULB9168	VULB9168-524	Jan. 08, 2014	Jan. 07, 2015		
Horn Antenna 1G-18G	SCHWARZBECK	BBHA 9120D	BBHA 9120 D 1095	Jan. 07, 2014	Jan. 06, 2015		
Horn Antenna 18G-40G	SCHWARZBECK	BBHA 9170	BBHA 9170517	Dec. 27, 2013	Dec. 26, 2014		
Amplifier	Burgeon	BPA-530	100218	Dec. 09, 2013	Dec. 08, 2014		
Amplifier	Agilent	83017A	MY39501309	Dec. 09, 2013	Dec. 08, 2014		
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16140/4	Dec. 17, 2013	Dec. 16, 2014		
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16018/4	Dec. 17, 2013	Dec. 16, 2014		
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16015/4	Dec. 17, 2013	Dec. 16, 2014		
RF Cable-R03m	Woken	CFD400NL-LW	CFD400NL-003	Dec. 17, 2013	Dec. 16, 2014		
RF Cable-R10m	Woken	CFD400NL-LW	CFD400NL-004	Dec. 17, 2013	Dec. 16, 2014		
control	EM Electronics	EM1000	060608	N/A	N/A		
Note: Calibration Inter-	val of instruments listed	above is one year.					

Loop Antenna	R&S	HFH2-Z2	100330	Nov. 15, 2012	Nov. 14, 2014
Amplifier	EM	EM18G40G	060572	Jun. 20, 2013	Jun. 19, 2015
Note: Calibration Interv	al of instruments listed	d above is two year.			

1.5 Test Standards

According to the specification of EUT, the EUT must comply with following standards and KDB documents.

47 CFR FCC Part 15.247 FCC Public notice DA 00-705 ANSI C63.10-2009

Note: The EUT has been tested and complied with FCC part 15B requirement. FCC Part 15B test results are issued to another report.

Report No.: FR3D0402AD Page: 9 of 47



1.6 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2)

Measurement Uncertainty	
Parameters	Uncertainty
Bandwidth	±35.286 Hz
Conducted power	±0.536 dB
Frequency error	±35.286 Hz
Temperature	±0.3 °C
Conducted emission	±2.946 dB
AC conducted emission	±2.43 dB
Radiated emission	±2.49 dB

Report No.: FR3D0402AD Page: 10 of 47



2 Test Configuration

2.1 Testing Condition

Test Item	Test Site	Ambient Condition	Tested By
AC Conduction	CO01-WS	21°C / 60%	Skys Huang
Radiated Emissions	03CH02-WS	18°C / 66%	Aska Huang
RF Conducted	TH01-WS	21°C / 61%	Felix Sung

FCC site registration No.: 657002IC site registration No.: 10807A-2

2.2 The Worst Test Modes and Channel Details

Test item	Mode	Test Frequency (MHz)	Data Rate (Mbps)	Test Configuration
Conducted Emissions	8DPSK	2441	3Mbps	-
Radiated Emissions ≤ 1GHz	8DPSK	2441	3Mbps	-
Radiated Emissions > 1GHz	GFSK 8DPSK	2402, 2441, 2480 2402, 2441, 2480	1Mbps 3Mbps	-
Conducted Output Power	GFSK 8DPSK	2402, 2441, 2480 2402, 2441, 2480	1Mbps 3Mbps	-
Number of Hopping Channels	GFSK 8DPSK	2402~2480 2402~2480	1Mbps 3Mbps	-
Hopping Channel Separation	GFSK 8DPSK	2402, 2441, 2480 2402, 2441, 2480	1Mbps 3Mbps	-
Dwell Time	GFSK 8DPSK	2402 2402	1Mbps 3Mbps	-

NOTE:

Report No.: FR3D0402AD Page: 11 of 47

The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement -X, Y, and Z-plane. The Z-plane results were found as the worst case and were shown in this report.



3 Transmitter Test Results

3.1 Conducted Emissions


3.1.1 Limit of Conducted Emissions

	Conducted Emissions Limit	
Frequency Emission (MHz)	Quasi-Peak	Average
0.15-0.5	66 - 56 *	56 - 46 *
0.5-5	56	46
5-30	60	50
Note 1: * Decreases with the logarith	m of the frequency.	,

3.1.2 Test Procedures

- 1. The device is placed on a test table, raised 80 cm above the reference ground plane. The vertical conducting plane is located 40 cm to the rear of the device.
- 2. The device is connected to line impedance stabilization network (LISN) and other accessories are connected to other LISN. Measured levels of AC power line conducted emission are across the 50 Ω LISN port.
- 3. AC conducted emission measurements is made over frequency range from 150 kHz to 30 MHz.
- 4. This measurement was performed with AC 120V / 60Hz.

3.1.3 Test Setup




Note: 1. Support units were connected to second LISN.

Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

Report No.: FR3D0402AD Page: 12 of 47




Test Result of Conducted Emissions 3.1.4



2: Over Limit (dB) = Level (dBuV) - Limit Line (dBuV)

Report No.: FR3D0402AD Page: 13 of 47





Report No.: FR3D0402AD Page: 14 of 47



3.2 Unwanted Emissions into Restricted Frequency Bands

3.2.1 Limit of Unwanted Emissions into Restricted Frequency Bands

	Restricted Band	Emissions Limit	
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

Note 1:

Qusai-Peak value is measured for frequency below 1GHz except for 9–90 kHz, 110–490 kHz frequency band. Peak and average value are measured for frequency above 1GHz. The limit on average radio frequency emission is as above table. The limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit

Measurements may be performed at a distance other than what is specified provided. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor as below, Frequency at or above 30 MHz: 20 dB/decade Frequency below 30 MHz: 40 dB/decade.

3.2.2 Test Procedures

- Measurement is made at a semi-anechoic chamber that incorporates a turntable allowing a EUT rotation of 360°. A continuously-rotating, remotely-controlled turntable is installed at the test site to support the EUT and facilitate determination of the direction of maximum radiation for each EUT emission frequency. The EUT is placed at a height of 0.8 m test table above the ground plane.
- 2. Measurement is made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna is varied in height (1m ~ 4m) above the reference ground plane to obtain the maximum signal strength. Distance between EUT and antenna is 3 m.
- 3. This investigation is performed with the EUT rotated 360°, the antenna height scanned between 1 m and 4 m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations.

Note:

3.

- 1. 120kHz measurement bandwidth of test receiver and Quasi-peak detector is for radiated emission below 1GHz.
- 2. RBW=1MHz, VBW=3MHz and Peak detector is for peak measured value of radiated emission above 1GHz.

Radiated emission above 1GHz / Average value for harmonics

The average value is: Average = Peak value + 20log(Duty cycle) Where the duty factor is calculated from following formula for DH5 packet type which has worst duty factor:


20log (Duty cycle) = 20log
$$\frac{1s / 1600 * 5}{100 \text{ ms}}$$
 = -30.1dB

4. Radiated emission above 1GHz / Average value for other emissions RBW=1MHz, VBW=1/T and Peak detector

Report No.: FR3D0402AD Page: 15 of 47



3.2.3 Test Setup




Page: 16 of 47

Report No.: FR3D0402AD



3.2.4 Transmitter Radiated Unwanted Emissions (Below 1GHz)



Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Report No.: FR3D0402AD Page: 17 of 47



Modulation				8DP	SK			Test Fre	q. (MHz)		2441		
Polarization				Verti	cal					"			
				•									
	90	Leve	l (dBu	V/m)									
	80												
	70												
	60												
	00										FCC	CLAS	S-B
	50												
	40												
	•												
	30	1 2		3	4	5	6						
	20			1									
	10												
	10												
	0	30	100.	20	0. 30	00.		500. 60		. 800.	90	0.	1000
								iency (MHz)					
			Fi	req. [n Limi	t Margi		Factor	Remark		NT.	Turn
				MHz	level dBuV/m	40.47	/ dD	readin _{ dBuV	g dB			igh 	Table
			'	אחוי	ubuv/m	ubuv,	/m ub	ubuv	ub		CI	m	deg
	1		_	40.67	25.30	40.0	-14.70	41.64	-16.34	Peak	_		
	2		(65.89	21.85	40.0	0 -18.15	39.71	-17.86	Peak			
	3			42.52	21.33		ð -22 . 17			Peak			
	4			14.30	21.97		0 -21.53		-18.79	Peak			
	5			57.86			21.68		-14.30	Peak			
•	5		38	86.96	22.59	46.0	0 -23.41	36.07	-13.48	Peak			

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor, cable loss and amplifier gain


Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Report No.: FR3D0402AD Page: 18 of 47



3.2.5 Transmitter Radiated Unwanted Emissions (Above 1GHz) for GFSK



Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) - Limit (dBuV/m).

Report No.: FR3D0402AD Page: 19 of 47



Modulation	GFS	K			Test Fre	eq. (MHz)		2402				
Polarization	Vertical											
Leve	el (dBuV/m)											
117	a (abaviii)											
110												
90												
30												
70								FCC CLAS	SS-B			
70				6								
50	2 4			- 1			FCC	CLASS-B (A	AVG)			
50												
20												
30	3											
40												
10												
1000	4000.	6000. 80	00. 100). 14000. ency (MHz)		00. 20000.	22000.	25000			
	F [122.			Factor	Remark	ANT	Turn			
	rreq. i	mission level	LIMIT	nangti	readin		Kelliark	High	Table			
	MHz	dBuV/m	dBuV/n	ı dB	dBuV	dB		cm	deg			
									_			
1 2	2363.00 2363.00	37.98 50.43		-16.02 -23.57	39.99 52.44		Average Peak					
3	4804.00				19.03		Average					
4	4804.00	55.24	74.00	-18.76	49.13		Peak					
5	12010.00						Average					
6	12010.00	56.61	74.00	-17.39	42.31	14.30	Peak					


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR3D0402AD Page: 20 of 47

Report Version: Rev. 01





Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR3D0402AD Page: 21 of 47




Modulation		(GFS	K				T	est	Fred	լ. (MI	Hz)		2	2441	
Polarization		Vertical														
1	17 Lev	el (dBuV/ı	m)													
1	10				_				_			_				+-
	90			-	+			-	-		+	-		+		+-
															FCC CLA	SS-B
	70															
			2		4			6						FCC (CLASS-B	(AVG)
	50		Ť											-		,,,,,
	30				•											
	10															\perp
	0															
	100	0 400	00. (5000.	800	0. 100		2000. Teque			6000.	180	00. 20	0000.	22000.	25000
		Fre	a. F	missi	on l	limit		-		-	Fact	or	Ren	nark	ANT	Tur
			-	leve				8		ding					High	Tab
		MH	z	dBuV/	m o	dBuV/	m di	3	dBu	ı۷	dB	3			cm	deg
1		4882	00	23.9		54.00	30	08	17.	65		27	Δ.,,	erage		
2		4882		54.0		74.00			47.			27	Pea	_		
3		7323				54.00			14.		11.			erage		
4				56.6					44.		11.		Pea	k		
5		12205							11.		14.			erage		
6		12205	.00	56.0	4	/4.00	-1/	.96	41.	.83	14.	21	Pea	iK		

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR3D0402AD Page: 22 of 47






Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR3D0402AD Page: 23 of 47





Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)


*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR3D0402AD Page: 24 of 47



3.2.6 Transmitter Radiated Unwanted Emissions (Above 1GHz) for 8DPSK



Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) - Limit (dBuV/m).

Report No.: FR3D0402AD Page: 25 of 47



Modulation			8DF	SK			Test Fre	q. (MHz)		2402	
Polarization			Vert	ical							
	117 ^L	evel (dBuV/m)		1						
	110	+									
	90										
	70									FCC CLAS	S-B
	′′										
	L	2	4			6			FCC	CLASS-B (A	VG)
	50	\dashv t									
		- 1									
	30	-				5					
	10										
	ັ1	000	4000.	6000. 80	00. 100		00. 14000. Iency (MHz)	16000. 180	000. 20000.	22000.	25000
			Frea.	Emission	Limit	Margi	n SA	Factor	Remark	ANT	Turn
			2	level		6-	reading			High	Table
			MHz	dBuV/m	dBuV/	m dB	dBuV	dB		cm	deg
1			2363.00					-2.01	Averag	e	
2			2363.00	51.55 27.15		-22.45		-2.01 6.11	Peak		
2			4004.00	27.13	34.00	-20.00	21.04	0.11	Averag	e	

6.11

14.30

14.30

Peak

Peak

Average

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

4804.00 57.25 74.00 -16.75

12010.00 24.40 54.00 -29.60 10.10 12010.00 54.50 74.00 -19.50 40.20

*Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR3D0402AD Page: 26 of 47

Report Version: Rev. 01



Modulation	8DP	8DPSK				Test Freq. (MHz)			2441		
Polarization	Horiz	zontal		•			•				
117 Lev	el (dBuV/m)										
110											
90—											
30											
								FCC CLAS	S-B		
70											
	2	4		6			FCC	CLASS-B (A	VG)		
50											
30	1	- 3									
10											
0											
~100	00 4000.	6000. 80	00. 100		. 14000. 1 ncy (MHz)	6000. 1800	00. 20000.	22000.	25000		
	Freg. F	mission	limit	Margin	SA	Factor	Remark	ANT	Turn		
		level	222	1101 6211	reading		ricinal it	High	Table		
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg		
1	4882.00	27.77		-26.23	21.50	6.27	Average				
2	4882.00		74.00		51.60	6.27	Peak				
3 4	7323.00 7323.00			-28.87 -18.77	13.14 43.24	11.99 11.99	Average Peak				
-	1323.00	33.23	74.00	-10.//	43.24	11.99	reak				

14.21

Average

Peak

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

12205.00 25.83 54.00 -28.17 11.62

12205.00 55.93 74.00 -18.07 41.72

*Factor includes antenna factor, cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR3D0402AD Page: 27 of 47

Report Version: Rev. 01



Modulation	8DI	PSK				Tes	t Fre	q. (MH	z)		24	41		
Polarization		Vertical												
117	Level (dBuV/m)												
110														+-
90														-
												F	CC CLAS	SS-B
70														
		2	!	4			6					FCC CI	ASS-B (A	AVG)
50													,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	
30				3			_							
							Ĭ							
10														
0														
٠,	1000	4000.	6000.	8000	. 100			4000. (MHz)	16000.	18000	. 200	00. 22	2000.	25000
		Freq.	Emissi	on I	imit		_	SA	Facto	r	Rema	rk	ANT	Turn
			leve			8		ading		•	rteille		High	Tabl
		MHz	dBuV/	m d	BuV/	m dB	0	BuV	dB				cm	deg
4		4002 00	27.6		4 00	-26.1		1.61	6.2	_	A			
1 2		4882.00				-26.1		1.71	6.2		Aver Peak	_		
3		7323.00				-25.8		6.17	11.9		Aver			
4		7323.00		6 7	4.00	-15.7	4 4	6.27	11.9	9	Peak	_		
5		12205.00						0.89	14.2		Aver	•		
6	1	12205.00	55.2	9 7	4.00	-18.8	0 4	0.99	14.2	21	Peak			


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR3D0402AD Page: 28 of 47

Report Version: Rev. 01





Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR3D0402AD Page: 29 of 47



Modulation		8DI	8DPSK			Te	Test Freq. (MHz)				480			
Polarization	Ver	Vertical												
117	Level	(dBuV/m)												
110														
90														
70				_								F	CC CLAS	S-B
70		_ 4												
	\vdash	2	<u> </u>									FCC CL	ASS-B (A	WG)
50		1												
				6										
30		- 3		5										
10														
0														
	1000	4000.	6000.	8000	. 100			14000. :y (MHz)		000. 180	00. 200	000. 22	2000.	25000
		Freq.	Emissi	on I	imit	Marg	in	SΔ	F	actor	Rema	ark	ANT	Turn
			leve			· iai B		eadin		uc co.	· · · ·		High	Tabl
		MHz	dBuV/	m d	BuV/	m dB		dBuV	_	dB			cm	deg
4		2492.50		<u> </u>	4 00	42.0		42.02	_	1 03	Δ			
1 2		2483.56 2483.56				-12.0 -18.6		43.92 57.29		-1.93 -1.93	Peal	rage		
3		4960.00				-25.8		21.70		6.43		rage		
4		4960.00						51.80		6.43	Peal	_		
5		7440.00						16.62		12.08		rage		
6		7440.00	38.8	0 7	4 00	-35 2	a	26.72		12.08	Peal	, -		

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR3D0402AD Page: 30 of 47

Report Version: Rev. 01



3.3 Emissions in non-restricted frequency bands

3.3.1 Emissions in non-restricted frequency bands limit

Peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz

3.3.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.3.3 Test Procedures


Reference level measurement

- 1. Set RBW=100kHz, VBW = 300kHz, Detector = Peak, Sweep time = Auto
- 2. Trace = max hold, Allow Trace to fully stabilize
- 3. Use the peak marker function to determine the maximum PSD level

Emission level measurement

- 1. Set RBW=100kHz, VBW = 300kHz, Detector = Peak, Sweep time = Auto
- 2. Trace = max hold, Allow Trace to fully stabilize
- 3. Scan Frequency range is up to 25GHz
- 4. Use the peak marker function to determine the maximum amplitude level

3.3.4 Test Setup




Report No.: FR3D0402AD Page: 31 of 47




3.3.5 Test Result of Emissions in non-restricted frequency bands

GFSK



Report No.: FR3D0402AD Page: 32 of 47






Report No.: FR3D0402AD Page: 33 of 47




8DPSK



Report No.: FR3D0402AD Page: 34 of 47





Report No.: FR3D0402AD Page: 35 of 47



3.4 Conducted Output Power

3.4.1 Limit of Unwanted Emissions into Non-Restricted Frequency Bands

1 Watt For frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band.
0.125 Watt For all other frequency hopping systems in the 2400–2483.5 MHz band.
0.125 Watt For Frequency hopping systems operating in the 2400–2483.5 MHz band have hopping channel carrier frequencies that are separated by two-thirds of the 20 dB bandwidth of the hopping channel.

3.4.2 Test Procedures

- 1. A wideband power meter is used for power measurement. Bandwidth of power senor and meter is 50MHz
- 2 If duty cycle of test signal is not 100 %, trigger and gating function of power meter will be enabled to capture transmission burst for measuring output power

3.4.3 Test Setup



Report No.: FR3D0402AD Page: 36 of 47



3.4.4 Test Result of Conducted Output Power

Modulation Mode	Freq. (MHz)	Output Power (mW)	Output Power (dBm)	Limit (mW)
GFSK	2402	13.03	11.15	125
GFSK	2441	13.12	11.18	125
GFSK	2480	12.88	11.10	125
8DPSK	2402	19.23	12.84	125
8DPSK	2441	19.45	12.89	125
8DPSK	2480	18.88	12.76	125

Modulation Mode	Freq. (MHz)	AV Output Power (mW)	AV Output Power (dBm)
GFSK	2402	12.88	11.10
GFSK	2441	12.97	11.13
GFSK	2480	12.71	11.04
8DPSK	2402	10.81	10.34
8DPSK	2441	10.86	10.36
8DPSK	2480	10.47	10.20

Note: Average power is for reference only

Report No.: FR3D0402AD Page: 37 of 47



3.5 Number of Hopping Frequency


3.5.1 Limit of Number of Hopping Frequency

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels.

3.5.2 Test Procedures

- 1. Set RBW = 100kHz, VBW = 300kHz, Sweep time = Auto, Detector = Peak Trace max hold.
- 2 Allow trace to stabilize.


3.5.3 Test Setup



Report No.: FR3D0402AD Page: 38 of 47



3.5.4 Test Result of Number of Hopping Frequency



Report No.: FR3D0402AD Page: 39 of 47




3.6 20dB and Occupied Bandwidth

3.6.1 Test Procedures

- 1. Set RBW=30kHz, VBW=100kHz, Sweep time = Auto, Detector=Peak Trace max hold
- 2 Allow trace to stabilize
- 3 Use N dB function of spectrum analyzer to measuring 20 dB bandwidth
- 4. Use Occupied bandwidth function of spectrum analyzer to measuring 99% occupied bandwidth

3.6.2 Test Setup




Report No.: FR3D0402AD Page: 40 of 47



3.6.3 Test result of 20dB and Occupied Bandwidth

Modulation Mode	Freq. (MHz)	20dB Bandwidth (MHz)	Occupied Bandwidth (MHz)
GFSK	2402	0.948	0.847
GFSK	2441	0.952	0.881
GFSK	2480	0.948	0.864
8DPSK	2402	1.361	1.224
8DPSK	2441	1.361	1.224
8DPSK	2480	1.361	1.224



Report No.: FR3D0402AD Page: 41 of 47



3.7 Channel Separation


3.7.1 Limit of Channel Separation

- Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.
- Frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.

3.7.2 Test Procedures

- 1. Set RBW=100kHz, VBW=300kHz, Sweep time = Auto, Detector=Peak Trace max hold
- 2 Allow trace to stabilize
- 3 Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The EUT shall show compliance with the appropriate regulatory limit

3.7.3 Test Setup




Report No.: FR3D0402AD Page: 42 of 47



3.7.4 Test result of Channel Separation

Modulation Mode	Freq. (MHz)	Channel Separation (MHz)	20dB Bandwidth (MHz)	Minimum Limit (MHz)
GFSK	2402	1.000	0.948	0.632
GFSK	2441	1.000	0.952	0.635
GFSK	2480	1.000	0.948	0.632
8DPSK	2402	1.000	1.361	0.907
8DPSK	2441	1.000	1.361	0.907
8DPSK	2480	1.000	1.361	0.907



Report No.: FR3D0402AD Page: 43 of 47



3.8 Number of Dwell Time


3.8.1 Limit of Dwell time

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

3.8.2 Test Procedures

- Set RBW=100kHz,VBW=300kHz,Sweep time = 500us(DH1),2ms(DH3),4ms(DH5), Detector=Peak, Span=0Hz,Trace max hold
- 2 Enable gating and trigger function of spectrum analyzer to measure burst on time.
- 3. The DH1 packet can cover a single time slot. A maximum length packet has duration of 1 time slots. The hopping rate is 1600 hops/second so the maximum dwell time is 1/1600 seconds, or 0.625ms. DH1 Packet permit maximum 1600 / 79 /2 = 10.12 hops per second in each channel (1 time slot RX, 1 time slot TX). So, the dwell time is the time duration of the pulse times 10.12 x 31.6 = 320 within 31.6 seconds.
- 4. The DH3 packet can cover up to 3 time slots. A maximum length packet has duration of 3 time slots. The hopping rate is 1600 hops/second so the maximum dwell time is 3/1600 seconds, or 1.875ms. DH3 Packet permit maximum 1600 / 79 / 4 = 5.06 hops per second in each channel (3 time slots RX, 1 time slot TX). So, the dwell time is the time duration of the pulse times 5.06 x 31.6 = 160 within 31.6 seconds.
- 5. The DH5 packet can cover up to 5 time slots. Operate DH5 at maximum dwell time and maximum duty cycle. A maximum length packet has duration of 5 time slots. The hopping rate is 1600 hops/second so the maximum dwell time is 5/1600 seconds, or 3.125ms. DH5 Packet permit maximum 1600/ 79 / 6 = 3.37 hops per second in each channel (5 time slots RX, 1 time slot TX). So, the dwell time is the time duration of the pulse times 3.37 x 31.6 = 106.6 within 31.6 seconds

3.8.3 Test Setup




Report No.: FR3D0402AD Page: 44 of 47




3.8.4 Test Result of Dwell Time

Modulation Mode	Freq. (MHz)	No. of Pulse in a 31.6 (79Hopping*0.4)	Length of Pulse Time (msec)	Result (msec)	Limit (msec)
GFSK-DH1	2480	320	0.43768	0.140	400
GFSK-DH3	2480	160	1.70145	0.272	400
GFSK-DH5	2480	106.6	2.96377	0.316	400
8DPSK-DH1	2480	320	0.44058	0.141	400
8DPSK-DH3	2480	160	1.70290	0.272	400
8DPSK-DH5	2480	106.6	2.96377	0.316	400



Report No.: FR3D0402AD Page: 45 of 47





Report No.: FR3D0402AD

Page: 46 of 47



4 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corp, it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan Hsiang. Location map can be found on our website http://www.icertifi.com.tw.

Linkou Kwei Shan

Tel: 886-2-2601-1640 Tel: 886-3-271-8666

No. 30-2, Ding Fwu Tsuen, Lin Kou District, New Taipei
City, Taiwan, R.O.C.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan
Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.

If you have any suggestion, please feel free to contact us as below information

Tel: 886-3-271-8666 Fax: 886-3-318-0155

Email: ICC_Service@icertifi.com.tw

==END==

Report No.: FR3D0402AD Page: 47 of 47