

## Standalone SAR test exclusion considerations

RF feature	Mode	Transmitting Frequency(MHz)	Test separation distance (mm)	ANT Gain (dBi)	Max. power with tune-up tolerance (dBm) <sup>Note 1</sup>	Max. power with tune-up tolerance (mW)	Power thresholds	SAR test exclusion thresholds
Bluetooth LE	1 Mbps	2 480.00	5.0	-5.70	-1.00	0.794 3	0.25	3.00

Note1. Please refer to the operation description for Max tune-up power.

### KDB 447498 D01 clause 4.3.1 Step 1) SAR test exclusion thresholds for 100MHz to 6GHz at test separation distances ≤ 50 mm

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1g SAR and  $\leq 7.5$  for 10g extremity SAR

#### Sample Calculation

$$= [ ( 0.7943\text{mW} / 5\text{mm} ) ] \times [ \sqrt{2.48\text{GHz}} ] = 0.25$$

Note. The calculation result was rounded to two decimal place for comparison.

**Conclusion :** SAR evaluation for general population exposure conditions by measurement or numerical simulation is not required