

RF Exposure

Reference: CFR 47 FCC Part 1.1310
RSS-102. Issue 5

Description: All transmitters in the device have the possibility of transmitting simultaneously. The worst-case exposure for each transmitter was used to calculate the percentage of the allowable limit that each transmitter contributed. All of the percentages were then added together to verify that at the specified operating distance, they were below the allowable limit.

All measurements were peak or RMS power readings taken from test reports from accredited test labs. Antenna gains were taken from the manufacturer’s specifications.

Limits: Maximum exposure limits from CFR 47, FCC Part 1.1310:

Table 1 - Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

RF Exposure

Occupational/Controlled	0
General Population/uncontrolled	1

Transmitter	Frequency	Antenna Gain	Power	Power Density	Limit	Power density/Limit	Highest	Total	Type
	MHz	numerical	mW	mW/cm ²	mW/cm ²				
1	908.4	1	0.58	0.00012	0.6056	0.0002			PK/EIRP
1	916	1	0.65	0.00013	0.6107	0.0002	1	0.02%	PK/EIRP
2	1710.7	3.98	251.18	0.19898	1.0000	0.1990			PK/EIRP
2	777	4.94	251.18	0.24698	0.5180	0.4768	1	47.68%	PK/EIRP
							TOTAL	47.70%	

Distance	20	cm
----------	----	----

PASS?	YES
-------	-----

Note: where antenna gain = 1, the power measurements were taken from a field strength measurement converted to EIRP

RF Exposure

IC / ISED

Using RSS-102, Issue 5, Section 2.5.2

RF exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is greater than 20 cm, except when the device operates as follows:

- below 20 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 1 W (adjusted for tune-up tolerance);
- at or above 20 MHz and below 48 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $4.49/f^{0.5}$ W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 48 MHz and below 300 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 0.6 W (adjusted for tune-up tolerance);
- at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $1.31 \times 10^{-2} f^{(0.6834)}$ W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 5 W (adjusted for tune-up tolerance). In these cases, the information contained in the RF exposure

RF Exposure

Transmitter	Frequency	Antenna Gain	Power	EIRP	Limit	Highest	Total	Type
	MHz	numerical	mW	W	W			
1	908.4	1	0.58	0.0006	1.377076			PK/EIRP
1	916	1	0.65	0.0007	1.384939	1	0.05%	PK/EIRP
2	1710.7	1.70	251.18	0.4270	2.122376			PK/EIRP
2	777	1.70	251.18	0.4270	1.237613	1	34.50%	PK/EIRP
TOTAL							39.50%	

RESULT = PASS

*EIRP was measured for transmitters with integral antenna.

**Conducted values come from IC:5131A-ME910C1NV

Antenna gain used was 2.3 dBi for transmitter 2 as declared by the manufacturer