

Amended
FCC/ISED Test Report

Prepared for: Digital Monitoring Products

Address: 2500 North Partnership Blvd.
Springfield, MO 6582

Product: 1168

Test Report No: R20190311-21A

Approved by:



Nic S. Johnson, NCE

Technical Manager

iNARTE Certified EMC Engineer #EMC-003337-NE

DATE: 23 July 2019

Total Pages: 50

The Nebraska Center for Excellence in Electronics (NCEE) authorizes the above named company to reproduce this report provided it is reproduced in its entirety for use by the company's employees only. Any use that a third party makes of this report, or any reliance on or decisions made based on it, are the responsibility of such third parties. NCEE accepts no responsibility for damages, if any, suffered by any third party as a result of decisions made or actions based on this report. This report applies only to the items tested.



Report Number:	R20190311-21	Rev	A
Prepared for:	Digital Monitoring Product		

REVISION PAGE


Rev. No.	Date	Description
0	28 May 2019	Original – NJohnson Prepared by KVepuri/CJacobson
A	23 July 2019	Modified Section 2.1 to state the device also acts as a receiver. Measured receive mode emissions and added note (i) to Section 3.2 Includes NCEE Labs report R20190311-21 and its amendment in full. -NJ



Report Number:	R20190311-21	Rev	0
Prepared for:	Digital Monitoring Product		

CONTENTS

Revision Page	2
1.0 Summary of test results.....	4
2.0 EUT Description	5
2.1 Equipment under test	5
2.2 Description of test modes	6
2.3 Description of support units.....	6
3.0 Laboratory description.....	7
3.1 Laboratory description.....	7
3.2 Test personnel.....	7
3.3 Test equipment.....	8
4.0 Detailed results.....	9
4.1 Duty Cycle	9
4.2 Radiated emissions.....	11
4.3 Peak Output Power	20
4.4 Bandwidth.....	24
4.5 Bandedges	32
4.6 Carrier frequency seperation, number of hopping channels, time of occupancy	42
Appendix A: Sample Calculation	47
Appendix B – Measurement Uncertainty	49
REPORT END.....	50

	Report Number:	R20190311-21	Rev	0
	Prepared for:	Digital Monitoring Product		

1.0 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

- (1) US Code of Federal Regulations, Title 47, Part 15
- (2) ISED RSS-Gen, Issue 5
- (3) ISED RSS-247, Issue 2

ANSI C63.10-2013 was used as a test method, with guidance from KBD 558074 D01 v05

SUMMARY			
Standard Section	Test Type and Limit	Result	Remark
FCC 15.203	Unique Antenna Requirement	Pass	PCB antenna
FCC 15.35 RSS-Gen, 6.10	Duty cycle of pulsed emissions	Pass	Duty cycle was not applied
FCC 15.209 RSS-Gen, 7.1	Receiver Radiated Emissions	NA	The EUT has no receiver functionality
FCC 15.247(a)(1)(i) RSS-247, 5.1(c)	Minimum Bandwidth, Limit: Min. 250kHz	Pass	Meets the requirement of the limit.
FCC 15.247(b)(1) RSS-247, 5.1	Maximum Peak Output Power, Limit: Max. 24 dBm	Pass	Meets the requirement of the limit.
FCC 15.209 RSS-Gen, 8.9 RSS-247, 5.5	Transmitter Radiated Emissions	Pass	Meets the requirement of the limit.
FCC 15.247(a) (1) (i) RSS-247, 5.1(c)	Frequency hopping system, Limit: Max. 0.4 Seconds in 20 Second Period	Pass	Meets the requirement of the limit.
FCC 15.209, 15.205 RSS-Gen, 8.9 RSS-247, 5.5	Band Edge Measurement, Limit: 20dB less than the peak value of fundamental frequency	Pass	Meets the requirement of the limit.
FCC 15.207 RSS-Gen. 8.8	Conducted AC Emissions	NA	EUT runs on a replaceable battery



Report Number:	R20190311-21	Rev	0
Prepared for:	Digital Monitoring Product		

2.0 EUT DESCRIPTION

2.1 EQUIPMENT UNDER TEST

Summary

The Equipment Under Test (EUT) was 1168 a Wireless transmitter manufactured by DMP wireless devices. It operates in the 902 to 928 MHz ISM band and has transmit and receive capabilities.

EUT	1168
EUT Received	4/3/2019
EUT Tested	4/3/2019 - 5/22/2019 7/22/2019 (receive mode emissions only)
Serial No.	NCEEETEST1 (Assigned)
Operating Band	902 – 928 MHz
Device Type	FHSS
Power Supply	12 VDC (4 X CR123A (3V Lithium)) – not rechargeable
Antenna	1.0 dBi - PCB trace

NOTE: For more detailed features description, please refer to the manufacturer's specifications or user's manual.



Report Number:	R20190311-21	Rev	0
Prepared for:	Digital Monitoring Product		

2.2 DESCRIPTION OF TEST MODES

The EUT operates on, and was tested at the frequencies below:

Channel	Frequency
Low	903.3
Middle	915.0
High	926.7

These are the only three representative channels tested in the frequency range according to FCC Part 15.31 and RSS-Gen Table A1. See the operational description for a list of all channel frequency and designations.

This EUT was set to transmit in a worse-case scenario with modulation on. The manufacturer modified the unit to transmit continuously on the lowest, highest and one channel in the middle.

2.3 DESCRIPTION OF SUPPORT UNITS

None

3.0 LABORATORY DESCRIPTION

3.1 LABORATORY DESCRIPTION

All testing was performed at the following Facility:

The Nebraska Center for Excellence in Electronics (NCEE Labs)
 4740 Discovery Drive
 Lincoln, NE 68521

A2LA Certificate Number:	1953.01
FCC Accredited Test Site Designation No:	US1060
Industry Canada Test Site Registration No:	4294A-1
NCC CAB Identification No:	US0177

Environmental conditions varied slightly throughout the tests:

Relative humidity of $35 \pm 4\%$
 Temperature of $22 \pm 3^\circ$ Celsius



3.2 TEST PERSONNEL

No.	PERSONNEL	TITLE	ROLE
1	Nic Johnson	Technical Manager	Review of Results
2	Karthik Vepuri	EMC Test Engineer	Testing and Report
3	Chase Jacobson	EMC Test Technician	Testing and Report
4	Fox Lane	EMC Test Technician	Testing and Report

Notes:

All personnel are permanent staff members of NCEE Labs. No testing or review was sub-contracted or performed by sub-contracted personnel.



Report Number:	R20190311-21	Rev	0
Prepared for:	Digital Monitoring Product		

3.3 TEST EQUIPMENT

DESCRIPTION AND MANUFACTURER	MODEL NO.	SERIAL NO.	LAST CALIBRATION DATE	CALIBRATION DUE DATE
Rohde & Schwarz Test Receiver	ES126	100037	30 Jan 2018	30 Jan 2020
EMCO Biconilog Antenna	3142B	1647	02 Aug 2017	02 Aug 2019
EMCO Horn Antenna	3115	6416	26 Jan 2018	26 Jan 2020
EMCO Horn Antenna	3116	2576	31 Jan 2018	31 Jan 2020
Rohde & Schwarz Preamplifier	TS-PR18	3545700803	09 Mar 2018*	09 Mar 2020*
Trilithic High Pass Filter	6HC330	23042	09 Mar 2018*	09 Mar 2020*
Rohde & Schwarz LISN	ESH3-Z5	836679/010	26 Jul 2018	26 Jul 2019
Rohde & Schwarz Test Software	ES-K1	12575	NA	NA
RF Cable (preamplifier to antenna)	MFR-57500	01-07-002	09 Mar 2018*	09 Mar 2020*
RF Cable (antenna to 10m chamber bulkhead)	FSCM 64639	01E3872	09 Mar 2018*	09 Mar 2020*
RF Cable (10m chamber bulkhead to control room bulkhead)	FSCM 64639	01E3874	09 Mar 2018*	09 Mar 2020*
RF Cable (Control room bulkhead to RF switch)	FSCM 64639	01E3871	09 Mar 2018*	09 Mar 2020*
RF Cable (RF switch to test receiver)	FSCM 64639	01F1206	09 Mar 2018*	09 Mar 2020*
RF switch – Rohde and Schwarz	TS-RSP	1113.5503.14	09 Mar 2018*	09 Mar 2020*
N connector bulkhead (10m chamber)	PE9128	NCEEBH1	09 Mar 2018*	09 Mar 2020*
N connector bulkhead (control room)	PE9128	NCEEBH2	09 Mar 2018*	09 Mar 2020*

*Internal Characterization

Notes:


All equipment is owned by NCEE Labs and stored permanently at NCEE Labs facilities.

4.0 DETAILED RESULTS

4.1 DUTY CYCLE



Marker 1 [T1]	RBW	10 MHz	RF Att	10 dB
Ref Lvl	55.32 dBV	VBW	10 MHz	
82 dBV	69.659319 ms	SWT	440 ms	Unit dBV




Date: 8.MAY.2019 14:01:28

Figure 1 – On Time



Delta 1 [T1]	RBW	10 MHz	RF Att	10 dB
Ref Lvl	-1.64 dB	VBW	10 MHz	
82 dBV	4.051703 s	SWT	20 s	Unit dBV



Date: 8.MAY.2019 14:04:07

Figure 2 –Period

Maximum On time in 100 ms window = 14.11 ms

Duty cycle correction factor = $20 \cdot \log((14.11)/100) = -17.01$ dB

4.2 RADIATED EMISSIONS

Test Method: ANSI C63.10:2013, Section 6.5, 6.6

Limits for radiated emissions measurements:

Emissions radiated outside of the specified bands shall be applied to the limits in 15.209 as followed:

FREQUENCIES (MHz)	FIELD STRENGTH ($\mu\text{V/m}$)	MEASUREMENT DISTANCE (m)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	3
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = $20 * \log * \text{Emission level } (\mu\text{V/m})$.
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits by more than 20dB under any condition of modulation.



Report Number:	R20190311-21	Rev	0
Prepared for:	Digital Monitoring Product		

Test procedures:

- a. The EUT was placed on the top of a rotating table above the ground plane in a 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. The table was 0.8m high for measurements form 30MHz-1Ghz and 1.5m for measurements from 1GHz and higher.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna was a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are used to make the measurement.
- d. For each suspected emission, the EUT was arranged to maximize its emissions and then the antenna height was varied from 1 meter to 4 meters and the rotating table was turned from 0 degrees to 360 degrees to find the maximum emission reading.
- e. The test-receiver system was set to use a peak detector with a specified resolution bandwidth. For spectrum analyzer measurements, the composite maximum of several analyzer sweeps was used for final measurements.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- g. The EUT was maximized in all 3 orthogonal positions. The results are presented for the axis that had the highest emissions.
- h. The orientation with the worst-case emissions was used for final measurements.
- i. Receive mode was also tested and no frequencies were measured above the lab's system sensitivity level.

NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Peak detection (PK) and Quasi-peak detection (QP) at frequencies below 1GHz.
2. The resolution bandwidth 1 MHz for all measurements and at frequencies above 1GHz, A peak detector was used for all measurements above 1GHz. Measurements were made with an EMI Receiver.

Deviations from test standard:

No deviation.


Test setup:


Figure 3 - Radiated Emissions Test Setup

EUT operating conditions

The EUT was powered by 12 VDC unless specified and set to transmit continuously on the lowest frequency channel, highest frequency channel and one in the middle of its operating range.


Test results:


Figure 4 - Radiated Emissions Plot, Low Channel

REMARKS:

1. Emission level (dBµV/m) = Raw Value (dBµV) + Correction Factor (dB)
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value
5. The EUT was measured in both the horizontal and vertical orientation. It was found that the Horizontal position produced the highest emissions, and this orientation was used for all testing. See Annex A for test photos.

Report Number:	R20190311-21	Rev	0
Prepared for:	Digital Monitoring Product		

Table 1 - Radiated Emissions Quasi-peak Measurements, Low Channel

Frequency	Level	Limit	Margin	Height	Angle	Pol
MHz	dB μ V/m	dB μ V/m	dB	cm.	deg.	
47.640000	17.29	40.00	22.71	99	136	VERT
903.300000	99.08	NA	NA	100	356	VERT

Table 2 - Radiated Emissions Average Measurements, Low Channel

Frequency	Level	Limit	Margin	Height	Angle	Pol
MHz	dB μ V/m	dB μ V/m	dB	cm.	deg.	
1806.600000	40.31	54.00	13.69	170	15	HORI
2710.000000	35.22	54.00	18.78	180	40	VERT
4516.600000	25.22	54.00	28.78	180	360	HORI
6323.200000	40.88	54.00	13.12	190	182	HORI
7226.600000	45.69	54.00	8.31	123	8	VERT
8130.000000	43.43	54.00	10.57	204	202	HORI
9033.200000	43.01	54.00	10.99	99	30	VERT

The EUT was maximized in all 3 orthogonal axis. The worst-case is shown in the table above.
 Average Level = Peak Level – 17.01(Duty Cycle Correction Factor)

Table 3 - Radiated Emissions Peak Measurements, Low Channel

Frequency	Level	Limit	Margin	Height	Angle	Pol
MHz	dB μ V/m	dB μ V/m	dB	cm.	deg.	
1806.600000	57.32	74.00	18.68	170	15	HORI
2710.000000	52.23	74.00	23.77	180	40	VERT
4516.600000	42.23	74.00	33.77	180	360	HORI
6323.200000	57.89	74.00	18.11	190	182	HORI
7226.600000	62.70	74.00	13.30	123	8	VERT
8130.000000	60.44	74.00	15.56	204	202	HORI
9033.200000	60.02	74.00	15.98	99	30	VERT




Figure 5 - Radiated Emissions Plot, Mid Channel

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB)
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. The EUT was measured in both the horizontal and vertical orientation. It was found that the Horizontal position produced the highest emissions, and this orientation was used for all testing. See Annex A for test photos.

Report Number:	R20190311-21	Rev	0
Prepared for:	Digital Monitoring Product		

Table 4 - Radiated Emissions Quasi-peak Measurements, Mid Channel

Frequency	Level	Limit	Margin	Height	Angle	Pol
MHz	dB μ V/m	dB μ V/m	dB	cm.	deg.	
56.040000	4.53	40.00	35.47	103	178	VERT
58.980000	4.90	40.00	35.10	169	360	VERT
915.000000	96.63	NA	NA	103	0	VERT

Table 5 - Radiated Emissions Average Measurements, Mid Channel

Frequency	Level	Limit	Margin	Height	Angle	Pol
MHz	dB μ V/m	dB μ V/m	dB	cm.	deg.	
1830.000000	42.07	54.00	11.93	186	17	HORI
2745.000000	36.59	54.00	17.41	190	41	VERT
4575.000000	12.28	54.00	41.72	305	64	HORI
5490.000000	9.28	54.00	44.72	153	145	VERT
6405.000000	40.25	54.00	13.75	180	175	HORI
7320.000000	44.00	54.00	10.00	230	8	VERT
8235.000000	41.47	54.00	12.53	177	158	HORI
9150.000000	39.32	54.00	14.68	140	38	VERT

The EUT was maximized in all 3 orthogonal axis. The worst-case is shown in the table above.
Average Level = Peak Level – 17.01(Duty Cycle Correction Factor)

Table 6 - Radiated Emissions Peak Measurements, Mid Channel

Frequency	Level	Limit	Margin	Height	Angle	Pol
MHz	dB μ V/m	dB μ V/m	dB	cm.	deg.	
1830.000000	59.08	74.00	16.92	186	17	HORI
2745.000000	53.60	74.00	22.40	190	41	VERT
4575.000000	29.29	74.00	46.71	305	64	HORI
5490.000000	26.29	74.00	49.71	153	145	VERT
6405.000000	57.26	74.00	18.74	180	175	HORI
7320.000000	61.01	74.00	14.99	230	8	VERT
8235.000000	58.48	74.00	17.52	177	158	HORI
9150.000000	56.33	74.00	19.67	140	38	VERT




Figure 6 - Radiated Emissions Plot, High Channel

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB)
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. The EUT was measured in both the horizontal and vertical orientation. It was found that the Horizontal position produced the highest emissions, and this orientation was used for all testing. See Annex A for test photos.

Table 7 - Radiated Emissions Quasi-peak Measurements, High Channel

Frequency	Level	Limit	Margin	Height	Angle	Pol
MHz	dB μ V/m	dB μ V/m	dB	cm.	deg.	
56.040000	14.87	40.00	25.13	100	285	VERT
59.160000	7.16	40.00	32.84	103	138	VERT
770.640000	38.06	46.00	7.94	101	339	VERT
926.640000	98.06	NA	NA	99	0	VERT

The EUT was maximized in all 3 orthogonal axis. The worst-case is shown in the table above.

Table 8 - Radiated Emissions Average Measurements, High Channel

Frequency	Level	Limit	Margin	Height	Angle	Pol
MHz	dB μ V/m	dB μ V/m	dB	cm.	deg.	
1853.400000	41.54	54.00	12.46	173	15	HORI
2780.000000	35.77	54.00	18.23	173	50	VERT
4575.000000	11.96	54.00	42.04	126	187	HORI
5489.800000	9.77	54.00	44.23	399	182	VERT
6405.200000	38.78	54.00	15.22	187	182	HORI
7319.800000	42.45	54.00	11.55	221	10	VERT
8234.800000	39.78	54.00	14.22	177	158	HORI
9149.800000	35.90	54.00	18.10	100	33	VERT

The EUT was maximized in all 3 orthogonal axis. The worst-case is shown in the table above.

Average Level = Peak Level – 17.01 (Duty Cycle Correction Factor)

Table 9 - Radiated Emissions Peak Measurements, High Channel

Frequency	Level	Limit	Margin	Height	Angle	Pol
MHz	dB μ V/m	dB μ V/m	dB	cm.	deg.	
1853.400000	58.55	74.00	17.45	173	15	HORI
2780.000000	52.78	74.00	23.22	173	50	VERT
4575.000000	28.97	74.00	47.03	126	187	HORI
5489.800000	26.78	74.00	49.22	399	182	VERT
6405.200000	55.79	74.00	20.21	187	182	HORI
7319.800000	59.46	74.00	16.54	221	10	VERT
8234.800000	56.79	74.00	19.21	177	158	HORI
9149.800000	52.91	74.00	23.09	100	33	VERT

Report Number:	R20190311-21	Rev	0
Prepared for:	Digital Monitoring Product		

4.3 PEAK OUTPUT POWER

Test Method: ANSI C63.10, Section(s) 7.8.5

Limits of bandwidth measurements:

For an FHSS system with 25 channels, the output power is required to be less than 250 mW or 24 dBm.

EIRP was calculated from field strength measurements using ANSI C63.10:2013, Section 9.5, Equation (22). The field strength was measured at a 3m distance and maximized.

Test procedures:

All measurements were taken at a distance of 3m from the EUT.

The EUT was maximized in all 3 orthogonal positions in a similar manner as described in Section 4.2.

Deviations from test standard:

No deviation.

Test setup:

See Section 4.2

Measurement device used was power meter

EUT operating conditions:

The EUT was powered by 12 VDC unless specified and set to transmit continuously on the lowest frequency channel, highest frequency channel and one in the middle of its operating range.

Test results:


Peak Output Power

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK OUTPUT POWER EIRP (dBm)	PEAK OUTPUT POWER CONDUCTED * (dBm)	RESULT
Low	903.3	4.14	3.14	PASS
Middle	915	3.63	2.63	PASS
High	926.7	3.40	2.40	PASS

*Measurements were performed as EIRP because there were no provisions for making conducted measurements. Conducted value = Peak power output (dBm EIRP) – Antenna gain (dBi)



Marker 1 [T1]	RBW	10 MHz	RF Att	10 dB
Ref Lvl	-36.03 dBm	VBW	10 MHz	
-20 dBm	903.16856613 MHz	SWT	5 ms	Unit dBm



Date: 21.MAY.2019 14:17:07

Figure 7 – Output Power, Low Channel.

Maximum power = $-36.03 \text{ dBm} + 107 + \text{CL} + \text{AF} - 95.23 = 4.14 \text{ dBm}^*$

CL = cable loss = 4.80 dB


AF = antenna factor = 23.60 dB

107 = conversion from dBm to dBµV on a 50Ω measurement system

-95.23 = Conversion from field strength (dBµV/m) to EIRP (dBm) at a 3m measurement distance



Marker 1 [T1]	RBW	10 MHz	RF Att	10 dB
Ref Lvl	-36.44 dBm	VBW	10 MHz	
-20 dBm	915.37575150 MHz	SWT	5 ms	Unit dBm



Date: 21.MAY.2019 13:55:25

Figure 8 – Output Power, Mid Channel


Maximum power = -36.44 dBm + 107 + CL + AF - 95.23 = 3.63 dBm*

CL = cable loss = 4.80 dB

AF = antenna factor = 23.50 dB

107 = conversion from dBm to dBμV on a 50Ω measurement system

-95.23 = Conversion from field strength (dBμV/m) to EIRP (dBm) at a 3m measurement distance.



Date: 21.MAY.2019 13:18:17

Figure 9 – Output Power, High Channel

Maximum power = $-36.97 \text{ dBm} + 107 + \text{CL} + \text{AF} - 95.23 = 3.40 \text{ dBm}^*$

CL = cable loss = 4.80 dB

AF = antenna factor = 23.80 dB

107 = conversion from dBm to dBμV on a 50Ω measurement system

-95.23 = Conversion from field strength (dBμV/m) to EIRP (dBm) at a 3m measurement distance.



Report Number:	R20190311-21	Rev	0
Prepared for:	Digital Monitoring Product		

4.4 BANDWIDTH

Test Method: ANSI C63.10, Section(s) 6.9.2 (20 dB BW)
ANSI C63.10, Section(s) 6.9.3 (99% BW)

Limits of bandwidth measurements:

From FCC Part 15.247 (1) (i) and RSS-247 5.1(c)

The maximum allowed 20 dB bandwidth of the hopping channel is 500 kHz.

Test procedures:

Bandwidth measurement was taken at a distance of 3m from the EUT. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 3 kHz RBW and 10 kHz VBW.

The 20dB bandwidth is defined as the bandwidth of which is higher than peak power minus 20dB.


The 99% occupied bandwidth was measured using the test receiver's occupied bandwidth function.

Test setup:

All the measurements were done at 3m test distance while an operator was trying to activate the hopping sequence manually. See Section 4.3 for more details.

Deviations from test standard:

No deviation.

Test setup:

Figure 10 - Bandwidth Measurements Test Setup
EUT operating conditions:


The EUT was powered by 12 VDC unless specified and set to transmit continuously on the lowest frequency channel, highest frequency channel and one in the middle of its operating range.

Test results:

CHANNEL	CHANNEL FREQUENCY (MHz)	Bandwidth		RESULT
		20dB BW (kHz)	99% Occupied Bandwidth (kHz)	
Low	905.6	72.33	88.43	PASS
Mid	914.7	71.74	78.96	PASS
High	924.4	72.14	76.55	PASS



Delta 1 [T1] RBW 3 kHz RF Att 10 dB
 Ref Lvl 0.31 dB VBW 10 kHz
 -20 dBm 72.33459585 kHz SWT 135 ms Unit dBm




Date: 21.MAY.2019 14:11:31

Figure 11 – 20 dB Bandwidth, Low Channel



Marker 3 [T1] RBW 3 kHz RF Att 10 dB
 Ref Lvl -20 dBm -61.12 dBm VBW 10 kHz
 -20 dBm 914.96292585 MHz SWT 56 ms Unit dBm




Date: 21.MAY.2019 13:52:54

Figure 12 - 20 dB Bandwidth, Mid Channel



Marker 2 [T1] RBW 3 kHz RF Att 10 dB
 Ref Lvl -62.09 dBm VBW 10 kHz
 -20 dBm 926.63733467 MHz SWT 56 ms Unit dBm




Date: 21.MAY.2019 13:35:56

Figure 13 - 20 dB Bandwidth, High Channel



Marker 1 [T1] RBW 3 kHz RF Att 10 dB
 Ref Lvl -41.50 dBm VBW 10 kHz
 -20 dBm 903.34440229 MHz SWT 135 ms Unit dBm




Date: 21.MAY.2019 14:15:32

Figure 14 - 99% Occupied Bandwidth, Low Channel



Marker 1 [T1]	RBW	3 kHz	RF Att	10 dB
Ref Lvl	-41.83 dBm	VBW	10 kHz	
-20 dBm	915.01823647 MHz	SWT	56 ms	Unit dBm




Date: 21.MAY.2019 13:41:33

Figure 15 - 99% Occupied Bandwidth, Middle Channel



Marker 1 [T1] RBW 3 kHz RF Att 10 dB
 Ref Lvl -42.49 dBm VBW 10 kHz
 -20 dBm 926.69304609 MHz SWT 56 ms Unit dBm



Date: 21.MAY.2019 13:28:04

Figure 16 - 99% Occupied Bandwidth, High Channel



Report Number:	R20190311-21	Rev	0
Prepared for:	Digital Monitoring Product		

4.5 BANDEDGES

Test Method: ANSI C63.10, Section(s) 6.10.6

Limits of bandedge measurements:

For emissions outside of the allowed band of operation (902 – 928MHz), the emission level needs to be 20dB under the maximum fundamental field strength. However, if the emissions fall within one of the restricted bands from 15.205 the field strength levels need to be under that of the limits in 15.209.

Test procedures:

The EUT was tested in the same method as described in section 4.4 - *Bandwidth*. The EUT was oriented as to produce the maximum emission levels. The resolution bandwidth was set to 30kHz and the EMI receiver was used to scan from the bandedge to the fundamental frequency with a quasi-peak detector. The highest emissions level beyond the bandedge was measured and recorded. All band edge measurements were evaluated to the general limits in Part 15.209.

Deviations from test standard:

No deviation.

Test setup:

All the measurements were done at 3m test distance while an operator was trying to activate the hopping sequence manually.

EUT operating conditions:

The EUT was powered by 12 VDC unless specified and set to transmit continuously on the lowest frequency channel, and the highest frequency channel.



Report Number:	R20190311-21	Rev	0
Prepared for:	Digital Monitoring Product		

Test results:

Highest Out of Band Emissions

CHANNEL	Band edge /Measurement Frequency (MHz)	Relative Highest out of band level dBm	Relative Fundamental Level (dBm)	Delta	Min (dBc)	Result
Low, Continuous Restricted	614	-104.24	-36.30	67.94	53.08	PASS
Low Hopping Restricted	614	-103.18	-41.52	61.66	53.08	PASS
High, Continuous Restricted	960	-105.39	-40.74	64.65	52.06	PASS
High, Hopping Restricted	960	-106.47	-43.15	63.32	52.06	PASS
Low, Continuous Unrestricted	902	-78.60	-36.30	42.30	20.00	PASS
Low, Hopping Unrestricted	902	-92.36	-41.52	50.84	20.00	PASS
High, Continuous Unrestricted	928	-83.13	-40.74	42.93	20.00	PASS
High, Hopping Unrestricted	928	-92.18	-43.15	49.03	20.00	PASS

*Minimum delta = [highest fundamental peak field strength from Section 4.2] – [Part 15.209 radiated emissions limit.]

From Section 4.2

Fundamental average field strength at 903.3 MHz for low channel = 99.08 dBµV/m

Fundamental average field strength at 926.6 MHz for high channel = 98.06 dBµV/m


Low channel minimum delta = 99.08 – 46.0 dBµV/m = 53.08 dBc

High channel minimum delta = 98.06 – 46.0 dBµV/m = 52.06 dBc

Measurements do not include correction factors and are intended to be relative measurements only.



Marker 1 [T1]	RBW	100 kHz	RF Att	10 dB
Ref Lvl	-36.30 dBm	VBW	300 kHz	
-20 dBm	903.29859719 MHz	SWT	5 ms	Unit dBm



Date: 21.MAY.2019 14:30:14


Figure 19 - Band-edge Measurement, Low Channel, Fundamental, Continuous Transmit

The plot shows an uncorrected measurement, used for relative measurements only.



Marker 1 [T1] RBW 100 kHz RF Att 10 dB

Ref Lvl -25 dBm -41.52 dBm VBW 300 kHz
 -25 dBm 903.31659319 MHz SWT 5 ms Unit dBm




Date: 21.MAY.2019 14:56:26

Figure 20 - Band-edge Measurement, Low Channel, Fundamental, Hopping Transmit

The plot shows an uncorrected measurement, used for relative measurements only.



Marker 1 [T1] RBW 100 kHz RF Att 0 dB
 Ref Lvl -106.47 dBm VBW 300 kHz
 -35 dBm 990.54108216 MHz SWT 10 ms Unit dBm




Date: 21.MAY.2019 15:01:10

Figure 22 - Band-edge Measurement, High Channel, Restricted Frequency, Hopping

The plot shows an uncorrected measurement, used for relative measurements only.



Marker 1 [T1] RBW 100 kHz RF Att 10 dB
 Ref Lvl -25 dBm -42.39 dBm VBW 300 kHz
 926.64529058 MHz SWT 5 ms Unit dBm




Date: 21.MAY.2019 15:16:40

Figure 23 - Band-edge Measurement, High Channel, Fundamental, Continuous Transmit
 The plot shows an uncorrected measurement, used for relative measurements only.
 Delta = 40.74 dB > 20 dB minimum



Marker 1 [T1] RBW 100 kHz RF Att 10 dB
 Ref Lvl -43.15 dBm VBW 300 kHz
 -25 dBm 926.66122244 MHz SWT 5 ms Unit dBm



Date: 21.MAY.2019 15:03:52

Figure 24 - Band-edge Measurement, High Channel, Fundamental, Hopping Transmit

The plot shows an uncorrected measurement, used for relative measurements only.

Delta = 49.03 dB > 20 dB minimum



Report Number:	R20190311-21	Rev	0
Prepared for:	Digital Monitoring Product		

4.6 CARRIER FREQUENCY SEPERATION, NUMBER OF HOPPING CHANNELS, TIME OF OCCUPANCY

Test Method: ANSI C63.10, Section 7.8.2, 7.8.3, 7.8.4

Limits for Time of Occupancy

Average time of occupancy on any frequency should not to exceed 0.4 seconds within a 20 second period.

Test procedures:

The method from FCC DA 00-705

All measurements were taken at a distance of 3m from the EUT.

Test setup:

All the measurements were done at 3m test distance while an operator was trying to activate the hopping sequence manually.


EUT operating conditions:

The EUT was powered by 12 VDC unless specified and set to transmit continuously on the lowest frequency channel, highest frequency channel and one in the middle of its operating range.

Test results:



Marker 2 [T1] RBW 100 kHz RF Att 10 dB
 Ref Lvl -42.06 dBm VBW 300 kHz
 -25 dBm 906.00821643 MHz SWT 5 ms Unit dBm




Date: 21.MAY.2019 15:09:23

Figure 25 – Frequency Separation, 454.01 kHz



Marker 1 [T1] RBW 100 kHz RF Att 10 dB
 Ref Lvl -41.59 dBm VBW 100 kHz
 -25 dBm 903.30260521 MHz SWT 6.5 ms Unit dBm




Date: 21.MAY.2019 14:51:23

Figure 26 – Hop Count, 53 Hops



Marker 1 [T1]	RBW	10 MHz	RF Att	10 dB
Ref Lvl	55.32 dB μ V	VBW	10 MHz	
82 dB μ V	69.659319 ms	SWT	440 ms	Unit dB μ V




Date: 8.MAY.2019 14:01:28

Figure 27 – Time of Occupancy, On Time, 14.108 ms



Delta 1 [T1]	RBW	10 MHz	RF Att	10 dB
Ref Lvl	-1.64 dB	VBW	10 MHz	
82 dBV	4.051703 s	SWT	20 s	Unit dBV



Date: 8.MAY.2019 14:04:07

Figure 28 – Time of Occupancy, Period

*Maximum of 2 transmissions were captured after multiple attempts, however in worst case scenario there is a possibility that 5 transmissions can occur in a given channel in any 20 s so the average time of occupancy is $14.108 \text{ ms} \times 5 = 70.54 \text{ ms} = 0.07 \text{ s} < 0.4 \text{ s}$ - Pass



Report Number:	R20190311-21	Rev	0
Prepared for:	Digital Monitoring Product		

APPENDIX A: SAMPLE CALCULATION

Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF - (-CF + AG) + AV$$

where FS = Field Strength

- RA = Receiver Amplitude
- AF = Antenna Factor
- CF = Cable Attenuation Factor
- AG = Amplifier Gain
- AV = Averaging Factor (if applicable)

Assume a receiver reading of 55 dB μ V is obtained. The Antenna Factor of 12 and a Cable Factor of 1.1 is added. The Amplifier Gain of 20 dB is subtracted, giving a field strength of 48.1 dB μ V/m.

$$FS = 55 + 12 - (-1.1 + 20) + 0 = 48.1 \text{ dB}\mu\text{V/m}$$

The 48.1 dB μ V/m value can be mathematically converted to its corresponding level in μ V/m.

$$\text{Level in } \mu\text{V/m} = \text{Common Antilogarithm } [(48.1 \text{ dB}\mu\text{V/m})/20] = 254.1 \mu\text{V/m}$$

AV is calculated by the taking the $20 \cdot \log(T_{on}/100)$ where T_{on} is the maximum transmission time in any 100ms window.



Report Number:	R20190311-21	Rev	0
Prepared for:	Digital Monitoring Product		

EIRP Calculations

In cases where direct antenna port measurement is not possible or would be inaccurate, output power is measured in EIRP. The maximum field strength is measured at a specified distance and the EIRP is calculated using the following equation;

$$EIRP (Watts) = [Field Strength (V/m) \times antenna distance (m)]^2 / 30$$

$$Power (watts) = 10^{[Power (dBm)/10]} / 1000$$

$$Voltage (dB\mu V) = Power (dBm) + 107 \text{ (for } 50\Omega \text{ measurement systems)}$$

$$Field Strength (V/m) = 10^{[Field Strength (dB\mu V/m) / 20]} / 10^6$$

$$Gain = 1 \text{ (numeric gain for isotropic radiator)}$$

Conversion from 3m field strength to EIRP (d=3):

$$EIRP = [FS(V/m) \times d^2]/30 = FS [0.3] \quad \text{for } d = 3$$

$$EIRP(dBm) = FS(dB\mu V/m) - 10(\log 10^9) + 10\log[0.3] = FS(dB\mu V/m) - 95.23$$

10log(10^9) is the conversion from micro to milli



Report Number:	R20190311-21	Rev	0
Prepared for:	Digital Monitoring Product		

APPENDIX B – MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been for tests performed in this test report:

Test	Frequency Range	Uncertainty Value (dB)
Radiated Emissions, 3m	30MHz - 1GHz	3.82
Radiated Emissions, 3m	1GHz - 18GHz	4.44
Emissions limits, conducted	30MHz – 18GHz	±3.30 dB

Expanded uncertainty values are calculated to a confidence level of 95%.



Report Number:	R20190311-21	Rev	0
Prepared for:	Digital Monitoring Product		

REPORT END