## Maximum Public Exposure to RF (MPE) CFR 15.247 (i), CFR 1.1310 (e)

The maximum exposure level to the public from the RF power of the EUT shall not exceed a power density, **S** as per the respective limits in Table 1 below, at a distance, d, of 20 cm (Mobile condition) from the EUT.

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm²)	Averaging time (minutes)
Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f <sup>2</sup>	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

## TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

f = frequency in MHz \* = Plane-wave equivalent power density

Therefore, for:

## MPE for 903 - 926 MHz:

Limit: f/1500 mW/cm<sup>2</sup> = 915/1500 = 0.61 mW/cm<sup>2</sup> Peak Power (dBm) = 21.25 dBm Peak Power (Watts) = 0.133 W Gain of Transmit Antenna = 1.9 dB<sub>i</sub> =1.549 numeric (Highest Gain) d = Distance = 20 cm = 0.2 m

**S = (PG/** $4\pi d^2$ ) = EIRP/4A = 0.133(1.549)/4\* $\pi$ \*0.2\*0.2

= 0.2060/0.5030 = 0.4095 W/m<sup>2</sup>

- $= (0.4095 \text{ W/m}^2) (1 \text{ m}^2/\text{W}) (0.1 \text{ m}\text{W/cm}^2)$
- = 0.09095 mW/cm<sup>2</sup>

which is << less than S = 0.61 mW/cm<sup>2</sup>

US Tech Test Report: FCC ID: IC: Test Report Number: Issue Date: Customer: Model: FCC Part 15 Certification/RSS 247 CCKPC0252 5251A-PC0252 24-0308 October 7, 2024 Digital Monitoring Products, Inc. XT75

RF Exposure Evaluation – IC

According to RSS-102, 2.5.2 Exemption Limits for Routine Evaluation

At or above 300 MHz and below 6 GHz and the source-based time averaged maximum EIRP of the device is equal to or less than  $1.31 \times 10^{-2} \times f^{0.6834}$  in Watts (adjusted for tune up tolerance where applicable), where f= frequency in MHz

For 900 MHz Band:

Limit=  $1.31 \times 10^{-2} \times 915^{0.6834} = 1.38$  Watts

Max EIRP= 21.25 dBm + 1.9 dB = 23.15 dBm = 206.53 mW << 1380 mW