


<b>Test Method:</b>	Spurious Case Radiated Emissions, 30 MHz to 9 GHz, Paragraph 2.1053						
<b>Customer:</b>	Samson Technologies	<b>Job No.</b>	R-8512-3				
<b>Test Sample:</b>	UHF Wireless Transmitter						
<b>Model No.:</b>	AH1	<b>FCC ID:</b>	CCRAH1M				
<b>Operating Mode</b>	Continuously transmitting at 803.7 MHz						
<b>Test Specification</b>	FCC Part 2, Paragraph 2.1053, Field Strength of Spurious Radiation						
<b>Technician:</b>	Peter Lananna	<b>Date:</b>	May 17, 2000				
<b>Notes:</b>	Test Distance: D=3 M; Limit in dBuV= 20 log{[(49.2 x P) <sup>1/2</sup> /D] x 10 <sup>6</sup> } - (43+10 log P); P=Power in Watts Detector: Peak						
Test Freq.	Antenna Pol./Height	EUT Orientation	Meter Reading	Correction Factor	Corrected Reading	Converted Reading	Limit
MHz	(V/H) / Meters	Degrees	dBuV	dB	dBuV/m	uv/m	uv/m
30.00							16,596
1607.5	V/1.3	225	76.1	-0.1	76.0	6309.6	
2114.4	V/1.0	225	53.5	-7.5	46.0	199.5	
3215.1	V/1.0	225	57.3	-7.6	49.7	305.5	
4018.5	V/1.5	225	46.2	-4.4	41.8	123.0	
4822.4	V/1.0	225	46.3	-3.2	43.1	142.9	
5626.0	V/1.0	225	47.3	-2.9	44.4	166.0	
V							V
8037.00							16,596
The EUT was scanned from 30 Mhz to 9 Ghz							
The emissions observed from the EUT do not exceed the specified limits.							
All emissions not recorded were more than 20dB below the specified limit.							



**Retlif Testing Laboratories**

Retlif Job Number R-8512-3