





(10 MHz BW, MID channel, QPSK, 3530-3720 MHz



Section 8Testing dataTest nameFCC §96.41(e)(1) Emissions intensitySpecificationFCC Part 96





Report reference ID: REP0023530-2R1TRFWL

Page 40 of 60









(10 MHz BW, MID channel, 64QAM, 3530-3720 MHz

eni

Ref Level 0

| Frequency Sweep | and an and a second | 10 US 01 | 1 1Pm Mail |
|----------------------------------------------|----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------|
| Limit Chebic | PASS | | M1[1] -67.11 dBm |
| The received of the | 11000 | | 954.250 MHz |
| 10 d0m/ | | | |
| 20 10/0 | | | |
| 30 dBm | | | |
| an alian W. At(a) | | | |
| 50 dbm | | | |
| 10 dBm | | | |
| 10 ann mar an Alana an Alana an Alan Anna an | when the second and many horizon | and an in the second | which as an address of the second |
| 60 dbm | | and the second s | |
| ad qpm | | | |
| 80.0 MHz | 1940 ots | 97.0 MHz/ | 1.0.6Hz |



(10 MHz BW, HIGH channel, QPSK, 15000 - 37500 MHz)



(10 MHz BW, MID channel, 64QAM, 2800 - 4400 MHz)

| Ref Level 40.0 Att | 40 dB SWT | 16.00 dB 140 µs (~7.7 ms) | RBW 30 | kHz kHz Mode Auto FFT | | | SGL Count 10/10 |
|-----------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------|-----------------------------|--------------------------|-------------------|--------------------|--------------------|
| DF 'TEST" | and the second states of the s | | 1000 C 200 C 200 C 200 C 20 | The MARY CONSIGN | | | 110000500500500 |
| Frequency St | weep | | 2013 | 10.0 | 114 | | 1Rm Max |
| Limit Ghe | SC ALCON | L'OWN / | 110 | | | MILLI | 20.49 dBr |
| Line FCC | Part 96 di(e) | HIGH | De | | | | 3 622 9740 GH |
| dBm | | | | | | | - |
| | | | 641 | | | | |
| (Pm) | | | I. | | | | |
| | Sector March | manman | College Mark | an an an an an an an an | Marsh Marsh Marsh | and a superior and | |
| | 1 6 | 15 X | | | | | |
| dam | | | | | | | |
| | | | | | | 1 | |
| the set | 1 | | | | | | |
| | 1 | | | | | | 8 |
| | 1 | | | | | | |
| diam'r | 1.7114 | | | | | 800 Ba | The attack which |
| Page 201 (1997) | HUNT | | | | | 100.17 | And aller - ruga |
| | | | | | | | 1 |
| 1 dbm- | | | | | | | 1 |
| and the | | | | | | | R.M. |
| 1 diffe | | | | | | | |
| AVA. | | | | | | | and the |
| | | | | | | | 1 |
| 0 dbm | | | | | | | - |
| | | | | | | | |
| 1 40 m | | | | | | | |
| o dam- | | | | | | | |
| | | | | | | | |
| | | | | | | | |

(10 MHz BW, MID channel, 64QAM, 3619 - 3631 MHz)

| Frequency Sy | veep | | | | | | | | • 1Rm Max |
|--------------------------|-----------------------------------|--------------|-----------------------|----------------|---------------|------------------|---------------|----------------------|----------------------------|
| Limit Cheb Line FCC P | k art 95_41(e) art 95_41(e) | Low | PA | 96 55 48 | | | | M1[1] | *66.78 dBr 2.455.250 GH |
| 10 dlim | roc Parries | 12(#2 - HR5H | | | | | | | - |
| a dêm- | | | | | | | | | |
| ia dam | | | | | - | | | | |
| Part 96_41(e) | 10W | | | | | | | | |
| a dam | | | | | | | | | |
| 0 dbin- | i | | | | | | | | |
| adates Hard | - | handituring | and the second second | | والمرافق والم | فالرز وحرب والجر | identities of | and the state of the | |
| iū dītm | | | 20 | | 3 | | | | |
| kā dām | | | | | | | | | |
| 0.GHz | | | 28000 p | | | 1647/ | | | 15.0 GH |



(10 MHz BW, HIGH channel, QPSK, 2800 - 4400 MHz)













(10 MHz BW, HIGH channel, 64QAM, 3530-3720 MHz

(10 MHz BW, HIGH channel, 64QAM, 3689 - 3701 MHz)

Section 8 Testing data Test name FCC §96.41(e)(1) Emissions intensity Specification FCC Part 96





Report reference ID: REP0023530-2R1TRFWL

Page 44 of 60







(20 MHz BW, LOW channel, 64QAM, 2800 - 4400 MHz)

25 GHz/

(20 MHz BW, LOW channel, 64QAM, 15000 - 37500 MHz)







Report reference ID: REP0023530-2R1TRFWL

Section 8 Testing data Test name FCC §96.41(e)(1) Emissions intensity Specification FCC Part 96





(20 MHz BW, MID channel, 64QAM, 30 - 1000 MHz)

(20 MHz BW, MID channel, 64QAM, 1000 – 15000 MHz)













(20 MHz BW, HIGH channel, 16QAM, 3530-3720 MHz



15.0 GHz

nt 10/10

4.4 GHz

670

Section 8Testing dataTest nameFCC §96.41(e)(1) Emissions intensitySpecificationFCC Part 96





(20 MHz BW, HIGH channel, 64QAM, 3530-3720 MHz

(20 MHz BW, HIGH channel, 64QAM, 3679 - 3701 MHz)



Radiated spurious emissions:

30 – 1000 MHz

All operating modes were investigated and observed to have similar emissions characteristics. Data for the worst case operating mode (all 4 transmitters operating at full power, MID channel, 20 MHz operating bandwidth, GFSK modulation) is presented below. Preliminary scans to were performed with a peak detector to identify suspect frequencies. Identified suspect frequencies were maximized with respect to azimuth, measurement antenna height and polarization and measured with an RMS detector with a 1 MHz resolution bandwidth.



Full Spectrum

Figure 8.8-1: Radiated emissions spectral plot (30 MHz - 1 GHz), MID channel, 20 MHz bandwidth, GFSK modulation

| Table 8.8-1: Radiated emissions results. | MID channel, 20 MHz handwidt | , GESK modulation |
|------------------------------------------|--------------------------------|--------------------|
| | wind channel, 20 winz banawiat | , or sk mouulation |

| Frequency (MHz) | RMS (dBμV/m) | Limit (dBµV/m) | Margin (dB) | Meas. Time (ms) | Bandwidth (kHz) | Height (cm) | Pol | Azimuth (deg) | Corr. (dB/m) |
|--------------------|-----------------|-------------------|----------------|-----------------------|--------------------|----------------|-----|------------------|-----------------|
| 54.268000 | 35.04 | 55.23 | 20.19 | 5000.0 | 1000.000 | 114.0 | V | 275.0 | 14.2 |
| 164.183000 | 30.05 | 55.23 | 25.18 | 5000.0 | 1000.000 | 100.0 | V | 145.0 | 18.5 |
| 320.681000 | 28.59 | 55.23 | 26.64 | 5000.0 | 1000.000 | 292.0 | н | 146.0 | 22.6 |
| 425.127000 | 29.22 | 55.23 | 26.01 | 5000.0 | 1000.000 | 133.0 | V | 223.0 | 26.2 |
| 733.216000 | 36.21 | 55.23 | 19.02 | 5000.0 | 1000.000 | 219.0 | Н | 208.0 | 31.4 |
| 995.502000 | 39.58 | 55.23 | 15.65 | 5000.0 | 1000.000 | 281.0 | V | 120.0 | 34.7 |

Notes: ¹ Field strength (dB V/m) = receiver/spectrum analyzer value (dB V) + correction factor (dB)

² Correction factors = antenna factor ACF (dB) + cable loss (dB)

Section 8Testing dataTest nameFCC §96.41(e)(1) Emissions intensitySpecificationFCC Part 96



1 – 18 GHz:

All operating modes were investigated and observed to have similar emissions characteristics. Data for the worst case operating modes (all 4 transmitters operating at full power, LOW, MID and HIGH channel, 10 and 20 MHz operating bandwidth, GFSK modulation) is presented below. Three channels (LOW, MID and HIGH) are presented to verify performance in the vicinity of the operating band. Preliminary scans to were performed with a peak detector to identify suspect frequencies. Identified suspect frequencies were maximized with respect to azimuth, measurement antenna height and polarization and measured with an RMS detector with a 1 MHz resolution bandwidth.



Full Spectrum

Figure 8.8-2: Radiated emissions spectral plot (1 GHz - 18 GHz), LOW channel, 10 MHz bandwidth, GFSK modulation

| Table 8.8-2: Radiated emissions result | s. I OW channel. | 10 MHz handwidth | GESK modulation |
|----------------------------------------|--------------------------|--------------------|-------------------|
| | <i>5, LOVV Chamiler,</i> | 10 WINE bundwidth, | or six mouulation |

| Frequency (MHz) | RMS (dBµV/m) | Limit (dBµV/m) | Margin (dB) | Meas. Time (ms) | Bandwidth (kHz) | Height (cm) | Pol | Azimuth (deg) | Corr. (dB/m) |
|--------------------|-----------------|-------------------|----------------|-----------------------|--------------------|----------------|-----|------------------|-----------------|
| 1993.777778 | 28.09 | 55.23 | 27.14 | 5000.0 | 1000.000 | 144.0 | V | 82.0 | -10.8 |
| 5239.755556 | 31.07 | 55.23 | 24.16 | 5000.0 | 1000.000 | 382.0 | V | 341.0 | -2.2 |
| 7154.833333 | 32.17 | 55.23 | 23.06 | 5000.0 | 1000.000 | 339.0 | V | 356.0 | 0.8 |
| 9713.477778 | 32.72 | 55.23 | 22.51 | 5000.0 | 1000.000 | 282.0 | V | 10.0 | 3.6 |
| 12317.422222 | 34.08 | 55.23 | 21.15 | 5000.0 | 1000.000 | 343.0 | Н | 171.0 | 7.2 |
| 17081.933333 | 37.55 | 55.23 | 17.68 | 5000.0 | 1000.000 | 126.0 | Н | 226.0 | 13.1 |

Notes:

¹ Field strength (dB V/m) = receiver/spectrum analyzer value (dB V) + correction factor (dB) ² Correction factors = antenna factor ACF (dB) + cable loss (dB)





Figure 8.8-3: Radiated emissions spectral plot (1 GHz - 18 GHz), MID channel, 10 MHz bandwidth, GFSK modulation

| able 8.8-3: Radiated emissions | results, MID channel, | 10 MHz bandwidth, | GFSK modulation |
|--------------------------------|-----------------------|-------------------|-----------------|
|--------------------------------|-----------------------|-------------------|-----------------|

| Frequency (MHz) | RMS (dBµV/m) | Limit (dBµV/m) | Margin (dB) | Meas. Time (ms) | Bandwidth (kHz) | Height (cm) | Pol | Azimuth (deg) | Corr. (dB/m) |
|--------------------|-----------------|-------------------|----------------|-----------------------|--------------------|----------------|-----|------------------|-----------------|
| 5222.033333 | 31.29 | 55.23 | 23.94 | 5000.0 | 1000.000 | 158.0 | Н | 253.0 | -2.3 |
| 7250.077778 | 38.76 | 55.23 | 16.47 | 5000.0 | 1000.000 | 297.0 | н | 114.0 | 0.4 |
| 9733.377778 | 32.57 | 55.23 | 22.66 | 5000.0 | 1000.000 | 117.0 | V | 54.0 | 3.6 |
| 12233.988889 | 35.76 | 55.23 | 19.47 | 5000.0 | 1000.000 | 283.0 | V | 160.0 | 6.9 |
| 13705.133333 | 35.81 | 55.23 | 19.42 | 5000.0 | 1000.000 | 160.0 | V | 42.0 | 9.4 |
| 16322.633333 | 38.64 | 55.23 | 16.59 | 5000.0 | 1000.000 | 377.0 | V | 129.0 | 13.3 |

Notes:

¹ Field strength (dB V/m) = receiver/spectrum analyzer value (dB V) + correction factor (dB)
 ² Correction factors = antenna factor ACF (dB) + cable loss (dB)





Figure 8.8-4: Radiated emissions spectral plot (1 GHz - 18 GHz), HIGH channel, 10 MHz bandwidth, GFSK modulation

| Frequency (MHz) | RMS (dBµV/m) | Limit (dBµV/m) | Margin (dB) | Meas. Time (ms) | Bandwidth (kHz) | Height (cm) | Pol | Azimuth (deg) | Corr. (dB/m) |
|------------------------|-----------------|-------------------|----------------|-----------------------|--------------------|----------------|-----|------------------|-----------------|
| 2552.855556 | 28.23 | 55.23 | 27.00 | 5000.0 | 1000.000 | 290.0 | V | 65.0 | -9.6 |
| 7393.055556 | 43.52 | 55.23 | 11.71 | 5000.0 | 1000.000 | 308.0 | Н | 187.0 | 0.9 |
| 11083.144444 | 42.28 | 55.23 | 12.95 | 5000.0 | 1000.000 | 316.0 | н | 180.0 | 4.0 |
| 14778.133333 | 37.72 | 55.23 | 17.51 | 5000.0 | 1000.000 | 302.0 | Н | 121.0 | 9.8 |
| 16320.377778 | 38.68 | 55.23 | 16.55 | 5000.0 | 1000.000 | 327.0 | V | 238.0 | 13.3 |
| 17110.077778 | 38.39 | 55.23 | 16.84 | 5000.0 | 1000.000 | 253.0 | Н | 0.0 | 13.6 |

Notes:

 1 Field strength (dB V/m) = receiver/spectrum analyzer value (dB V) + correction factor (dB) 2 Correction factors = antenna factor ACF (dB) + cable loss (dB)





Figure 8.8-5: Radiated emissions spectral plot (1 GHz - 18 GHz), LOW channel, 20 MHz bandwidth, GFSK modulation

| Frequency (MHz) | RMS (dBµV/m) | Limit (dBµV/m) | Margin (dB) | Meas. Time (ms) | Bandwidth (kHz) | Height (cm) | Pol | Azimuth (deg) | Corr. (dB/m) |
|--------------------|-----------------|-------------------|----------------|-----------------------|--------------------|----------------|-----|------------------|-----------------|
| 1993.777778 | 28.09 | 55.23 | 27.14 | 5000.0 | 1000.000 | 144.0 | V | 82.0 | -10.8 |
| 5239.755556 | 31.07 | 55.23 | 24.16 | 5000.0 | 1000.000 | 382.0 | V | 341.0 | -2.2 |
| 7154.833333 | 32.17 | 55.23 | 23.06 | 5000.0 | 1000.000 | 339.0 | V | 356.0 | 0.8 |
| 9713.477778 | 32.72 | 55.23 | 22.51 | 5000.0 | 1000.000 | 282.0 | V | 10.0 | 3.6 |
| 12317.422222 | 34.08 | 55.23 | 21.15 | 5000.0 | 1000.000 | 343.0 | Н | 171.0 | 7.2 |
| 17081.933333 | 37.55 | 55.23 | 17.68 | 5000.0 | 1000.000 | 126.0 | Н | 226.0 | 13.1 |

Notes:

¹ Field strength (dB V/m) = receiver/spectrum analyzer value (dB V) + correction factor (dB) ² Correction factors = antenna factor ACF (dB) + cable loss (dB)





Figure 8.8-6: Radiated emissions spectral plot (1 GHz - 18 GHz), MID channel, 20 MHz bandwidth, GFSK modulation

| Table 8.8-6: Radiated emissions | results, MID channel, | 20 MHz bandwidth, | GFSK modulation |
|---------------------------------|-----------------------|-------------------|-----------------|
|---------------------------------|-----------------------|-------------------|-----------------|

| Frequency (MHz) | RMS (dBµV/m) | Limit (dBµV/m) | Margin (dB) | Meas. Time (ms) | Bandwidth (kHz) | Height (cm) | Pol | Azimuth (deg) | Corr. (dB/m) |
|--------------------|-----------------|-------------------|----------------|-----------------------|--------------------|----------------|-----|------------------|-----------------|
| 2625.066667 | 28.11 | 55.23 | 27.12 | 5000.0 | 1000.000 | 127.0 | V | 123.0 | -9.2 |
| 4745.155556 | 30.19 | 55.23 | 25.04 | 5000.0 | 1000.000 | 353.0 | V | 127.0 | -2.1 |
| 7106.088889 | 31.91 | 55.23 | 23.32 | 5000.0 | 1000.000 | 372.0 | н | 264.0 | 0.7 |
| 9689.733333 | 32.75 | 55.23 | 22.48 | 5000.0 | 1000.000 | 188.0 | V | 172.0 | 3.6 |
| 12302.533333 | 35.31 | 55.23 | 19.92 | 5000.0 | 1000.000 | 177.0 | V | 24.0 | 7.1 |
| 16795.833333 | 38.05 | 55.23 | 17.18 | 5000.0 | 1000.000 | 346.0 | V | 212.0 | 14.5 |

Notes:

¹ Field strength (dB V/m) = receiver/spectrum analyzer value (dB V) + correction factor (dB)
 ² Correction factors = antenna factor ACF (dB) + cable loss (dB)

Testing data FCC §96.41(e)(1) Emissions intensity FCC Part 96



Full Spectrum



Figure 8.8-7: Radiated emissions spectral plot (1 GHz - 18 GHz), HIGH channel, 20 MHz bandwidth, GFSK modulation

| Frequency (MHz) | RMS (dBµV/m) | Limit (dBµV/m) | Margin (dB) | Meas. Time (ms) | Bandwidth (kHz) | Height (cm) | Pol | Azimuth (deg) | Corr. (dB/m) |
|--------------------|-----------------|-------------------|----------------|-----------------------|--------------------|----------------|-----|------------------|-----------------|
| 2144.155556 | 26.94 | 55.23 | 28.29 | 5000.0 | 1000.000 | 384.0 | Н | 18.0 | -11.1 |
| 2582.244444 | 27.92 | 55.23 | 27.31 | 5000.0 | 1000.000 | 144.0 | Н | 290.0 | -9.6 |
| 7584.811111 | 31.67 | 55.23 | 23.56 | 5000.0 | 1000.000 | 299.0 | V | 266.0 | 1.1 |
| 9815.255556 | 31.83 | 55.23 | 23.40 | 5000.0 | 1000.000 | 311.0 | V | 57.0 | 3.6 |
| 12269.988889 | 35.38 | 55.23 | 19.85 | 5000.0 | 1000.000 | 388.0 | н | 344.0 | 7.1 |
| 17222.077778 | 37.21 | 55.23 | 18.02 | 5000.0 | 1000.000 | 366.0 | Н | 315.0 | 15.1 |

Notes:

¹ Field strength (dB V/m) = receiver/spectrum analyzer value (dB V) + correction factor (dB) ² Correction factors = antenna factor ACF (dB) + cable loss (dB)



18 – 26.5 GHz

All operating modes were investigated and observed to no significant emissions. Data from a representative operating mode (all 4 transmitters operating at full power, MID channel, 20 MHz operating bandwidth, GFSK modulation) is presented below. Preliminary scans to were performed with a peak detector to identify suspect frequencies. Identified suspect frequencies were maximized with respect to azimuth, measurement antenna height and polarization and measured with an RMS detector with a 1 MHz resolution bandwidth.



Full Spectrum

Figure 8.8-8: Radiated emissions spectral plot (18 GHz - 26.5 GHz), MID channel, 20 MHz bandwidth, GFSK modulation

Table 8.8-8: Radiated emissions results, MID channel, 20 MHz bandwidth, GFSK modulation

| Frequency (MHz) | RMS (dBµV/m) | Limit (dBµV/m) | Margin (dB) | Meas. Time (ms) | Bandwidth (kHz) | Height (cm) | Pol | Azimuth (deg) | Corr. (dB/m) |
|--------------------|-----------------|-------------------|----------------|-----------------------|--------------------|----------------|-----|------------------|-----------------|
| 20715.181250 | 21.37 | 55.23 | 33.86 | 5000.0 | 1000.000 | 368.0 | V | 58.0 | 18.5 |
| 22381.818750 | 20.85 | 55.23 | 34.38 | 5000.0 | 1000.000 | 246.0 | н | 202.0 | 17.4 |
| 23557.700000 | 27.10 | 55.23 | 28.13 | 5000.0 | 1000.000 | 107.0 | н | 283.0 | 23.7 |
| 24174.643750 | 31.26 | 55.23 | 23.97 | 5000.0 | 1000.000 | 366.0 | V | 331.0 | 27.2 |
| 25441.431250 | 26.84 | 55.23 | 28.39 | 5000.0 | 1000.000 | 250.0 | н | 0.0 | 21.7 |
| 26493.831250 | 28.24 | 55.23 | 26.99 | 5000.0 | 1000.000 | 400.0 | V | 151.0 | 23.4 |

Notes:

¹ Field strength (dB V/m) = receiver/spectrum analyzer value (dB V) + correction factor (dB)

² Correction factors = antenna factor ACF (dB) + cable loss (dB)



26.5 – 40 GHz

All operating modes were investigated and observed to no significant emissions. Data from a representative operating mode (all 4 transmitters operating at full power, MID channel, 20 MHz operating bandwidth, GFSK modulation) is presented below. Preliminary scans to were performed with a peak detector to identify suspect frequencies. Identified suspect frequencies were maximized with respect to azimuth, measurement antenna height and polarization and measured with an RMS detector with a 1 MHz resolution bandwidth.



Figure 8.8-9: Radiated emissions spectral plot (26.5 GHz - 40 GHz), MID channel, 20 MHz bandwidth, GFSK modulation

Table 8.8-9: Radiated emissions results, MID channel, 20 MHz bandwidth, GFSK modulation

| Frequency (MHz) | RMS (dBµV/m) | Limit (dBµV/m) | Margin (dB) | Meas. Time (ms) | Bandwidth (kHz) | Height (cm) | Pol | Azimuth (deg) | Corr. (dB/m) |
|--------------------|-----------------|-------------------|----------------|-----------------------|--------------------|----------------|-----|------------------|-----------------|
| 27759.293750 | 33.65 | 55.23 | 21.58 | 5000.0 | 1000.000 | 123.0 | Н | 192.0 | 9.6 |
| 30196.668750 | 34.62 | 55.23 | 20.61 | 5000.0 | 1000.000 | 106.0 | н | 90.0 | 11.8 |
| 35523.881250 | 41.04 | 55.23 | 14.19 | 5000.0 | 1000.000 | 225.0 | н | 164.0 | 19.6 |
| 35911.162500 | 41.85 | 55.23 | 13.38 | 5000.0 | 1000.000 | 204.0 | н | 22.0 | 20.8 |
| 36939.612500 | 37.48 | 55.23 | 17.75 | 5000.0 | 1000.000 | 125.0 | н | 85.0 | 16.4 |
| 37969.556250 | 35.55 | 55.23 | 19.68 | 5000.0 | 1000.000 | 225.0 | V | 293.0 | 15.6 |

Notes:

¹ Field strength (dB V/m) = receiver/spectrum analyzer value (dB V) + correction factor (dB)

² Correction factors = antenna factor ACF (dB) + cable loss (dB) ³ Emissions that were continuously present for a minimum of 1 second and occurred more than once for a



Section 9. Block diagrams of test setups

9.1 Radiated emissions set-up



Figure 9.1-1: Below 1 GHz setup



Figure 9.1-2: Above 1GHz setup