ALARM DEVICE MANUFACTURING COMPANY
165 EILEEN WAY **CFS8DL5804BDU**
SYOSSET, NY 11791 **FCC ID#_____**

DATE: MAY, 09, 2003 TESTED BY: GREG BARBATO APPROVED BY: KEN ADDY

TEST SAMPLE (model): ADEMCO 5804BDU (TRANSMITTER SPECIAL MESSAGE)

TEST METHOD: ANSI C63.4-1992
TEST SPECIFICATION: FCC PART 15, SUBPART C.

NOTES: 1) Fo= 345 MHZ
2) DETECTOR = PEAK.
3) FREQUENCY RANGE SCANNED TO 4 GHz.

4) CONVERTED READING = $10^{\left[\frac{(\text{METER READING} + \text{CABLE /AMP FACTOR} + \text{ANTENNA FACTOR})}{20}\right]}$

5) CORRECTED READING = CONVERTED READING X DUTY CYCLE

6) SIX HIGHEST EMISSIONS RECORDED.

Frequency (MHz)	Antenna Polarity (V-H)	Meter Reading (dB uV)	Cable/Amp Factor (dB)	Antenna Factor (dB/M)	Converted Reading (uV/M)	Duty Cycle (%)	Corrected Reading (uV/M)	Limit @ 3 Meter (uV/M)
30	H					14.3		729
345	V	70.61	2.3	16.11	28,248.8	14.3	4,039.6	7,290
690	V	39.00	3.2	21.46	1,524.0	14.3	217.9	729
1035	H	40.17	3.9	25.47	2,9991	14.3	428.9	500
1380	H	33.67	2.6	29.35	2,404.0	14.3	343.8	500
1725	V	32.33	5.3	31.30	2,795.8	14.3	399.8	729
2070	H	31.00	6.3	28.26	1,896.7	14.3	271.2	729
2415	H	31.00	6.8	29.53	2,325.4	14.3	332.5	729
2760	H	31.00	7.0	30.18	2,564.5	14.3	366.7	729
3105	H	31.00	7.4	30.76	2,870.8	14.3	410.5	729
3450	H	29.67	12.0	31.00	4,461.2	14.3	638.0	729
4000	H					10		729