

HONEYWELL SECURITY & CUSTOM ELECTRONICS**165 EILEEN WAY****SYOSSET, NY 11791****EXHIBIT 5-3****FCC ID # CFS8DL5805-6**

Date : 5/5/2005

Tested by :G. Blakely

Approved by :K.Addy

Test Sample (model) : 5805-6/4

Test method: ANSI C63.4 - 1992

Test specification: FCC Part 15, Sub-part C

Notes: (1) Fo = 345MHz. (2) Detector = Peak (3) Frequency range scanned to 4 GHz.

Emissions not reported were more than 20dB below the specified unit.

[(Meter reading + Cable/Amp factor + Antenna factor) / 20]

(4) Conv. Reading = 10

(5) Corr. Reading = Conv. Reading X Duty Cycle

(6) Six Highest Emissions Recorded

Freq. (MHz)	Antenna Polarity (V/H)	Meter Reading (dB uV)	Cable/Amp Factor (dB)	Antenna Factor (dB/M)	Conv. Reading (uV/M)	Duty Cycle (%)	Corr. Reading (uV/M)	Limit @ 3M (uV/M)
30			CABLE "A"	BICONILOG				729
345	H	68.20	1.3	14.78	16368.2	10.0%	1636.8	7292
690	H	35.80	1.7	19.10	676.1	10.0%	67.6	729
1035	H	35.30	2.3	22.70	1035.1	10.0%	103.5	500
1380	H	30.80	3.0	25.10	881.0	10.0%	88.1	500
1725	H	39.60	3.3	27.55	3330.4	10.0%	333.0	729
2070	H	33.80	3.8	29.42	2243.9	10.0%	224.4	729
2415	H	33.10	4.1	31.85	2834.7	10.0%	283.5	729
2760	H	33.00	4.1	32.20	2917.4	10.0%	291.7	729
3105	H	33.00	5.7	31.75	3330.4	10.0%	333.0	729
3450	H	33.00	6.2	32.28	3749.7	10.0%	375.0	729
4000			CABLE "A"	BICONILOG				

HONEYWELL SECURITY & CUSTOM ELECTRONICS**165 EILEEN WAY****SYOSSET, NY 11791****EXHIBIT 5-3****FCC ID # CFS8DL5805-6**

Date : 5/5/2005

Tested by :G. Blakely

Approved by :K.Addy

Test Sample (model) : 5805-6/4

Test method: ANSI C63.4 - 1992

Test specification: FCC Part 15, Sub-part C

Notes: (1) Fo = 345MHz. (2) Detector = Peak (3) Frequency range scanned to 4 GHz.

Emissions not reported were more than 20dB below the specified unit.

[(Meter reading + Cable/Amp factor + Antenna factor) / 20]

(4) Conv. Reading = 10

(5) Corr. Reading = Conv. Reading X Duty Cycle

(6) Six Highest Emissions Recorded

Freq. (MHz)	Antenna Polarity (V/H)	Meter Reading (dB uV)	Cable/Amp Factor (dB)	Antenna Factor (dB/M)	Conv. Reading (uV/M)	Duty Cycle (%)	Corr. Reading (uV/M)	Limit @ 3M (uV/M)
30			CABLE "A"	BICONILOG				729
345	H	68.20	1.3	14.78	16368.2	14.3%	2340.6	7292
690	H	35.80	1.7	19.10	676.1	14.3%	96.7	729
1035	H	35.30	2.3	22.70	1035.1	14.3%	148.0	500
1380	H	30.80	3.0	25.10	881.0	14.3%	126.0	500
1725	H	39.60	3.3	27.55	3330.4	14.3%	476.3	729
2070	H	33.80	3.8	29.42	2243.9	14.3%	320.9	729
2415	H	33.10	4.1	31.85	2834.7	14.3%	405.4	729
2760	H	33.00	4.1	32.20	2917.4	14.3%	417.2	729
3105	H	33.00	5.7	31.75	3330.4	14.3%	476.3	729
3450	H	33.00	6.2	32.28	3749.7	14.3%	536.2	729
4000			CABLE "A"	BICONILOG				