

HONEYWELL SECURITY & CUSTOM ELECTRONICS

REV 10-17-2011-G

2 Corporate Center Drive**Melville, NY 11747****EXHIBIT 5-3****FCC ID: CFS8DL 5809XT**

Date : 3-Oct 2011

Tested by: Y. MOHAMMED

Approved by: K. Eskildsen

Test Sample (model): 5809XT

Test method: ANSI C63.4 - 2004

Test specification: FCC Part 15, Sub-part C and RSS 210 , Issue 8

PRESCAN: Notes: (1) Fo: 344.94 (2) Detector = Peak (3) Frequency range scanned to 4 GHz.

V/V 78.92 Emissions not reported were more than 20dB below the specified unit.
 H/V 71.46 [(Meter reading + Cable/Amp factor + Antenna factor) / 20]
 V/H 76.57 (4) Conv. Reading = 10
 H/H 79.20 (5) Corr. Reading = Conv. Reading X Duty Cycle
 V/O 60.77 (6) Six Highest Emissions Recorded
 H/O 70.35

Freq. (MHz):	Sense Antenna Polarity (V/H):	THE ORIENTATION OF THE UUT	Meter Reading (dB uV):	Cable/Amp Factor (dB):	Antenna Factor (dB/m):	Conv. Reading (uV/M):	Duty Cycle (%)	Corr. Reading (uV/M):	Limit @ 3M (uV/M):
344.94	H	H	79.2	2.5	15.47	72,193.8	10.0%	7219.4	7288
689.88	H	H	46.8	3.7	19.36	3,118.9	10.0%	311.9	729
1034.82	H	H	44.3	4.7	22.72	3,854.8	10.0%	385.5	500
1379.76	H	V	30.1	5.6	25.47	1,145.5	10.0%	114.6	500
1724.70	H	O	27.4	6.3	27.64	1,161.4	10.0%	116.1	729
2069.64	H	H	23.6	7.3	29.85	1,083.9	10.0%	108.4	729
2414.58	H	H	20.2	8.1	31.89	1,017.4	10.0%	101.7	729
2759.52	H	H	20.7	8.6	32.83	1,279.4	10.0%	127.9	500
3104.46	H	H	19	9.1	32.63	1,088.9	10.0%	108.9	729
3449.40	H	H	19	10.0	33.14	1,275.0	10.0%	127.5	729
4000				LAST CAL 17 OCT 11 CABLE D	LAST CAL 21-AUG-11 BICONILOG S/N:00045682				