

**HONEYWELL SECURITY & CUSTOM ELECTRONICS**

**REV 2011D**

**2 Corporate Center Drive**

**Melville, NY 11747**

**EXHIBIT 5-3**

**FCC ID: CFS8DL 58111**

Date : 7-Sep 2011 Tested by: G. Barbato Approved by K. Eskildsen  
 Test Sample (model): 58111  
 Test method: ANSI C63.4 - 2004  
 Test specification: FCC Part 15, Sub-part C and RSS 210 , Issue 8  
 Notes: (1) Fo: 344.94 (2) Detector = Peak (3) Frequency range scanned to 4 GHz.  
 Emissions not reported were more than 20dB below the specified unit.  
 [(Meter reading + Cable/Amp factor + Antenna factor) / 20 ]  
 (4) Conv. Reading = 10  
 (5) Corr. Reading = Conv. Reading X Duty Cycle  
 (6) Six Highest Emissions Recorded

Freq. (MHz):	Sense Antenna Polarity (V/H):	THE ORENTATION OF THE UUT	Meter Reading (dB uV):	Cable/Amp Factor (dB):	Antenna Factor (dB/m):	Conv. Reading (uV/M):	Duty Cycle (%):	Corr. Reading (uV/M):	Limit @ 3M (uV/M):
344.94	H	H	62.49	2.3	14.92	9,670.5	10.0%	967.1	7289.2
689.88	H	H	41.57	3.2	20.12	1,755.5	10.0%	175.5	729
1034.82	H	H	16.66	4.4	22.89	157.6	10.0%	15.8	500
1379.76	H	H	15.79	4.9	25.71	209.0	10.0%	20.9	500
1724.70	H	H	15.93	5.5	28.58	316.5	10.0%	31.6	729
2069.64	H	H	16.35	6.4	32.39	571.7	10.0%	57.2	729
2414.58	H	H	16.19	6.9	30.49	477.6	10.0%	47.8	729
2759.52	H	H	15.69	7.4	32.33	590.4	10.0%	59.0	500
3104.46	H	H	15.73	7.9	32.63	650.1	10.0%	65.0	729
3449.40	H	H	16.10	9.2	31.94	727.4	10.0%	72.7	729
4000				LAST CAL 05 FEB 11 CABLE C	LAST CAL 17-MAY-11 BICONILOG S/N:00029390				