

HONEYWELL SECURITY & CUSTOM ELECTRONICS
165 EILEEN WAY
SYOSSET, NY 11791

EXHIBIT 5-3

FCC ID # CFS8DL5815LF

Date : 04/8/2008

Tested by :Y. Mohammed

Approved by :K.Addy

Test Sample (model) : 5815LF

Test method: ANSI C63.4 - 2004

Test specification: FCC Part 15, Sub-part C

Notes: (1) Fo = 345MHz. (2) Detector = Peak (3) Frequency range scanned to 4 GHz.

Emissions not reported were more than 20dB below the specified unit.

[(Meter reading + Cable/Amp factor + Antenna factor) / 20]

(4) Conv. Reading = 10

(5) Corr. Reading = Conv. Reading X Duty Cycle

(6) Six Highest Emissions Recorded

Freq. (MHz)	Antenna Polarity (V/H)	Meter Reading (dB uV)	Cable/Amp Factor (dB)	Antenna Factor (dB/m)	Conv. Reading (uV/M)	Duty Cycle (%)	Corr. Reading (uV/M)	Limit @ 3M (uV/M)
30			CABLE "A"	BICONILOG				729
345	H	75.20	2.6	14.78	42559.8	10.0%	4256.0	7292
690	H	35.10	3.7	19.20	794.3	10.0%	79.4	729
1035	H	29.30	4.7	22.72	685.5	10.0%	68.5	500
1380	H	40.80	5.5	25.71	3985.7	10.0%	398.6	500
1725	H	32.50	6.3	28.04	2197.9	10.0%	219.8	729
2070	H	37.60	7.0	30.84	5915.6	10.0%	591.6	729
2415	H	36.20	7.6	31.88	6081.4	10.0%	608.1	729
2760	H	31.70	8.5	32.89	4513.4	10.0%	451.3	500
3105	H	29.80	9.0	32.47	3660.2	10.0%	366.0	729
3450	H	28.60	10.7	33.16	4197.6	10.0%	419.8	729
4000			CABLE "A"	BICONILOG (00045682)				