

HONEYWELL SECURITY & CUSTOM ELECTRONICS**165 EILEEN WAY****SYOSSET, NY 11791****EXHIBIT 5-3****FCC ID # CFS8DL5815-1**

Date : 09/30/2005

Tested by :G. Barbato

Approved by :K.Addy

Test Sample (model) : 5815-1

Test method: ANSI C63.4 - 2004

Test specification: FCC Part 15, Sub-part C

Notes: (1) Fo = 345MHz. (2) Detector = Peak (3) Frequency range scanned to 4 GHz.

Emissions not reported were more than 20dB below the specified unit.

[(Meter reading + Cable/Amp factor + Antenna factor) / 20]]

(4) Conv. Reading = 10

(5) Corr. Reading = Conv. Reading X Duty Cycle

(6) Six Highest Emissions Recorded

Freq. (MHz)	Antenna Polarity (V/H)	Meter Reading (dB uV)	Cable/Amp Factor (dB)	Antenna Factor (dB/m)	Conv. Reading (uV/M)	Duty Cycle (%)	Corr. Reading (uV/M)	Limit @ 3M (uV/M)
30			CABLE "A"	BICONILOG				729
345	V	70.19	1.3	14.80	20630.0	10.0%	2063.0	7292
690	H	39.19	1.7	19.10	998.8	10.0%	99.9	729
1035	H	37.29	2.2	21.90	1173.5	10.0%	117.4	500
1380	H	35.99	2.5	24.50	1410.9	10.0%	141.1	500
1725	H	34.09	2.9	27.60	1696.3	10.0%	169.6	729
2070	H	35.89	3.2	29.40	2657.7	10.0%	265.8	729
2415	H	16.49	3.4	31.50	371.1	10.0%	37.1	729
2760	H	21.29	3.5	32.00	691.0	10.0%	69.1	500
3105	H	17.99	3.7	32.30	500.6	10.0%	50.1	729
3450	H	17.49	3.9	32.30	483.6	10.0%	48.4	729
4000			CABLE "A"	BICONILOG				