

Date : 09/18/2007 Tested by : Yasseen Mohammed Approved by :K.Addy

Test Sample (model) : 5817CB-2

Test method: ANSI C63.4 - 2004

Test specification: FCC Part 15, Sub-part C and RSS 210 , Issue 7

Notes: (1) Fo = 345MHz. (2) Detector = Peak (3) Frequency range scanned to 4 GHz.

Emissions not reported were more than 20dB below the specified unit.

[(Meter reading + Cable/Amp factor + Antenna factor) / 20]

(4) Conv. Reading = 10

(5) Corr. Reading = Conv. Reading X Duty Cycle

(6) Six Highest Emissions Recorded

Freq. (MHz)	Antenna Polarity (V/H)	Meter Reading (dB uV)	Cable/Amp Factor (dB)	Antenna Factor (dB/m)	Conv. Reading (uV/M)	Duty Cycle (%)	Corr. Reading (uV/M)	Limit @ 3M (uV/M)
30			CABLE "A" + "B"	03/12/2007 BICONILOG S/N:00029390				729
345	h	77.60	2.6	14.90	56885.3	10.0%	5688.5	7292
690	h	42.20	3.7	19.30	1819.7	10.0%	182.0	729
1035	h	32.80	4.7	22.70	1023.3	10.0%	102.3	500
1380	h	37.40	5.5	25.80	2722.7	10.0%	272.3	500
1725	h	32.60	6.3	28.00	2213.1	10.0%	221.3	729
2070	h	36.30	7.0	30.30	4786.3	10.0%	478.6	729
2415	h	26.30	7.6	32.00	1972.4	10.0%	197.2	729
2760	h	26.30	8.5	32.80	2398.8	10.0%	239.9	500
3105	h	25.30	9.0	32.50	2187.8	10.0%	218.8	729
3450	h	25.00	10.7	33.00	2722.7	10.0%	272.3	729
4000			CABLE "A" + "B"	03/12/2007 BICONILOG S/N:00029390				