

SHORT RANGE RADIO RADIATED EMISSIONS

HONEYWELL SECURITY & CUSTOM ELECTRONICS

REV 07/23/2013-O

2 Corporate Center Drive

Melville, NY 11747

EXHIBIT 5-3

FCC ID: CFS8DL 5817CBXT

Date : 10-Mar 2014 Tested : Eduardo Sayers Approved by: Mark Schmidt

Test Sample (model): 5817CBXT

Test method: ANSI C63.4 - 2003

Test specification: FCC Part 15, Sub-part C and RSS 210 , Issue 8

PRESCAN:

SENSE / UUT:	EL (cm):	AZ	Meter Reading (dB uV):
V/V	148.7	63.8	79.24
H/V	122.6	138.1	70.17
V/H	194.5	360.0	71.74
H/H	100.0	274.0	76.13
V/O	131.0	178.0	76.47
H/O	100.0	100.0	75.23

Notes:

(1) Fo: 344.94 MHz

(2) Detector = Peak

(3) Frequency range scanned to 4 GHz. (Emissions not reported were n 20dB below the specified unit).

(4) Conv. Read. = 10 [(Meter reading + Cable/Amp factor + Antenna fa)]

(5) Corr. Reading = Conv. Reading X Duty Cycle

(6) Six Highest Emissions Recorded

Freq. (MHz):	Sense Antenna Polarity (V/H):	THE OREN OF THE UUT (V,H):	Meter Reading (dB uV):	Cable/A Factor (dB):	Antenna Factor (dB/m):	Conv. Re (uV/M):	Duty Cycle (%):	Corr. Re (uV/M):	Limit @ 3M (uV/M):
344.94	V	V	79.24	2.5	14.92	68,076.9	10.0%	6807.7	7,289
689.88	V	V	33.44	3.7	20.10	729.5	10.0%	72.9	729
1034.82	V	V	40.31	4.7	24.82	3,101.0	10.0%	310.1	500
1379.76	V	V	28.94	5.6	26.50	1,128.5	10.0%	112.8	500
1724.70	V	V	29.06	6.3	29.00	1,644.4	10.0%	164.4	729
2069.64	V	V	27.13	7.3	30.78	1,811.3	10.0%	181.1	729
2414.58	V	V	27.74	8.1	32.16	2,500.3	10.0%	250.0	729
2759.52	V	V	25.90	8.6	31.84	2,077.3	10.0%	207.7	500
3104.46	V	V	27.46	9.1	32.13	2,721.1	10.0%	272.1	729
3449.40	V	V	23.82	10.0	33.85	2,409.9	10.0%	241.0	729
					LAST CAL JULY-14 BICONILO S/N:000293				