

ALARM DEVICE MANUFACTURING COMPANY
165 EILEEN WAY
SYOSSET, NY 11791

FCC ID # CFS8DL5818MN

Date : __11/19/2003__ Tested by: Greg Barbato

Approved by: Ken Addy

Test Sample (model) : _____ 5818MN

Test method: ANSI C63.4 - 1992

Test specification: FCC Part 15, Sub-part C

Notes: (1) Fo = 345MHz. (2) Detector = Peak (3) Frequency range scanned to 4 GHz.

Emissions not reported were more than 20dB below the specified unit.

[(Meter reading + Cable/Amp factor + Antenna factor) / 20]]

(4) Conv. Reading = 10

(5) Corr. Reading = Conv. Reading X Duty Cycle

(6) Six Highest Emissions Recorded

Freq. (MHz)	Antenna Polarity (V/H)	Meter Reading (dB uV)	Cable/Amp Factor (dB)	Antenna Factor (dB/M)	Conv. Reading (uV/M)	Duty Cycle (%)	Corr. Reading (uV/M)	Limit @ 3M (uV/M)
30								729
345	H	67.29	1.2	17.91	20893.0	10%	2089.3	7292
690	H	29.67	2	22.81	529.7	10%	53.0	729
1035	H	25.39	2.6	25.69	483.1	10%	48.3	500
1380	H	25.39	3	25.51	495.5	10%	49.5	500
1725	H	25.39	3.5	26.25	571.5	10%	57.1	729
2070	H	25.39	3.9	28.31	758.6	10%	75.9	729
2415	H	25.39	4.3	28.57	818.5	10%	81.8	729
2760	H	25.39	4.7	29.52	956.1	10%	95.6	729
3105	H	25.39	4.9	30.83	1137.6	10%	113.8	729
3450	H	25.39	5.1	32.4	1394.8	10%	139.5	729
4000								