

HONEYWELL SECURITY & CUSTOM ELECTRONICS
REV 07/23/2013-O
2 Corporate Center Drive
Melville, NY 11747
EXHIBIT 5-3
FCC ID: CFS8DL5819-1 Perm Change

Date : 22-Aug 2013

Tested by: S. Albrechtsen

Approved by: M. Schmidt

Test Sample (model): Class 2 Perm Change

Test method: ANSI C63.4 - 2003

Test specification: FCC Part 15, Sub-part C and RSS 210 , Issue 8

Notes: (1) Fo: 345.00

(2) Detector = Peak

(3) Frequency range scanned to 4 GHz.

(Emissions not reported were more than 20dB below the specified unit).

[(Meter reading + Cable/Amp factor + Antenna factor) / 20]]

(4) Conv. Reading = 10

(5) Corr. Reading = Conv. Reading X Duty Cycle

(6) Six Highest Emissions Recorded

PRESCAN:			
SENSE / UUT:	EL (cm):	AZ (deg):	Meter Reading (dB uV):
V/V			
H/V			
V/H			
H/H			
V/O			
H/O			

Freq. (MHz):	Sense Antenna Polarity (V/H):	THE ORENTATION OF THE UUT (V,H,O _z):	Meter Reading (dB uV):	Cable/Amp Factor (dB):	Antenna Factor (dB/m):	Conv. Reading (uV/M):	Duty Cycle (%):	Corr. Reading (uV/M):	Limit @ 3M (uV/M):
345.00	H	H	75.90	2.5	15.20	47,863.0	10.0%	4786.3	7,292
690.00	H	H	39.80	3.7	19.20	1,367.7	10.0%	136.8	729
1035.00	H	H	44.00	4.7	22.90	3,801.9	10.0%	380.2	500
1380.00	H	H	35.00	5.6	24.90	1,885.8	10.0%	188.6	500
1725.00	H	H	34.00	6.3	27.70	2,500.3	10.0%	250.0	729
2070.00	H	H	32.00	7.3	29.80	2,834.7	10.0%	283.5	729
2415.00	H	H	31.00	8.1	31.20	3,258.4	10.0%	325.8	729
2760.00	H	H	30.50	8.6	31.40	3,353.5	10.0%	335.4	500
3105.00	H	H	32.00	9.1	31.50	4,270.7	10.0%	427.1	729
3450.00	H	H	31.70	10.0	32.10	4,880.9	10.0%	488.1	729
4000				LAST CAL 15 MAR 13 CABLE D	LAST CAL 08-JULY-13 BICONILOG S/N:00029390				