

HONEYWELL SECURITY & CUSTOM ELECTRONICS

REV 08-21-2012-L

2 Corporate Center Drive

Melville, NY 11747

EXHIBIT 5-3

FCC ID: CFS8DL 5822T

Date : 6-Sep 2012 Tested by: G. BARBATO Approved by: K. Eskildsen

Test Sample (model): 5822T

Test method: ANSI C63.4 - 2003

Test specification: FCC Part 15, Sub-part C and RSS 210 , Issue 8

Notes: (1) Fo: 344.94

| PRESCAN: | | | |
|--------------|----------|-----------|------------------------|
| SENSE / UUT: | EL (cm): | AZ (deg): | Meter Reading (dB uV): |
| V/V | 137.7 | 140.0 | 76.86 |
| H/V | 100.0 | 0/360 | 68.77 |
| V/H | 137.7 | 180.0 | 73.19 |
| H/H | 100.0 | 90.0 | 77.07 |
| V/O | 100.0 | 0/360 | 65.64 |
| H/O | 214.0 | 0/360 | 75.02 |

- (2) Detector = Peak
- (3) Frequency range scanned to 4 GHz.
- (Emissions not reported were more than 20dB below the specified unit).

$$[(\text{Meter reading} + \text{Cable/Amp factor} + \text{Antenna factor}) / 20]$$
- (4) Conv. Reading = 10
- (5) Corr. Reading = Conv. Reading X Duty Cycle
- (6) Six Highest Emissions Recorded

| Freq. (MHz): | Sense Antenna Polarity (V/H): | THE ORENTATION OF THE UUT | Meter Reading (dB uV): | Cable/Amp Factor (dB): | Antenna Factor (dB/m): | Conv. Reading (uV/M): | Duty Cycle (%): | Corr. Reading (uV/M): | Limit @ 3M (uV/M): |
|--------------|-------------------------------|---------------------------|------------------------|-------------------------------------|--|-----------------------|-----------------|-----------------------|--------------------|
| 344.94 | H | H | 76.86 | 2.5 | 15.91 | 58,009.6 | 10.0% | 5801.0 | 7,289 |
| 689.88 | H | H | 27.55 | 3.7 | 21.12 | 416.4 | 10.0% | 41.6 | 729 |
| 1034.82 | H | H | 28.46 | 4.7 | 24.65 | 777.1 | 10.0% | 77.7 | 500 |
| 1379.76 | H | H | 26.63 | 5.6 | 27.53 | 973.9 | 10.0% | 97.4 | 500 |
| 1724.70 | H | H | 25.82 | 6.3 | 30.10 | 1,285.3 | 10.0% | 128.5 | 729 |
| 2069.64 | H | H | 28.27 | 7.3 | 31.04 | 2,128.1 | 10.0% | 212.8 | 729 |
| 2414.58 | H | H | 20.21 | 8.1 | 31.71 | 997.7 | 10.0% | 99.8 | 729 |
| 2759.52 | H | H | 22.17 | 8.6 | 32.29 | 1,424.0 | 10.0% | 142.4 | 500 |
| 3104.46 | H | H | 20.35 | 9.1 | 32.81 | 1,298.7 | 10.0% | 129.9 | 729 |
| 3449.40 | H | H | 22.77 | 10.0 | 34.46 | 2,290.9 | 10.0% | 229.1 | 729 |
| 4000 | | | | LAST CAL 10 JUL 12 CABLE D | LAST CAL 27-JUN-12 BICONILOG S/N:00020971 | | | | |