

ALARM DEVICE MANUFACTURING COMPANY
165 EILEEN WAY
SYOSSET, NY 11791

FCC ID # CFS8DL5827BD-1

Date : _10/01/2003_ Tested by : __GREG_BARBATO_ Approved by : _Ken_Addy__

Test Sample (model) : _____5827BD-1____(RX)_____

Test method: ANSI C63.4 - 1992

Test specification: FCC Part 15, Sub-part C

Notes: (1) Fo = 59.28333MHz. (2) Detector = Peak (3) Frequency range scanned to 4 GHz.

Emissions not reported were more than 20dB below the specified unit.

[(Meter reading + Cable/Amp factor + Antenna factor) / 20]]

(4) Conv. Reading = 10

(5) Corr. Reading = Conv. Reading X Duty Cycle (LO=100%)

(6) Six Highest Emissions Recorded

Freq. (MHz)	Antenna Polarity (V/H)	Meter Reading (dB uV)	Cable/Amp Factor (dB)	Antenna Factor (dB/M)	Conv. Reading (uV/M)	Duty Cycle (%)	Corr. Reading (uV/M)	Limit @ 3M (uV/M)
30								
118.5667	H	22.00	0.9	10.91	49.0	100%	49.0	150
177.85	H	26.67	1	13.66	116.5	100%	116.5	150
237.1333	H	24.33	1.2	16.42	125.2	100%	125.2	200
355.7	H	25.00	1.6	16.58	144.2	100%	144.2	200
414.983	H	25.67	1.7	17.35	172.2	100%	172.2	200
474.267	H	21.67	1.7	19.95	146.6	100%	146.6	200
533.5	H	20.67	1.8	19.3	122.6	100%	122.6	200
592.833	H	22.14	1.9	19.71	154.0	100%	154.0	200
652.177	H	21.67	2.2	20.71	169.4	100%	169.4	200
711.4	H	20.83	2.3	22.2	184.7	100%	184.7	200
4000								