

HONEYWELL SECURITY & CUSTOM ELECTRONICS
REV K JAN 10
2 Corporate Center Drive
Melville, NY 11747
EXHIBIT 5-3
FCC ID
CFS8DL5828V

Date : 01/15/2010

Tested by : G. Barbato

Approved by : K. Eskildsen

Test Sample (model) : 345 MHz 5828V

Test method: ANSI C63.4 - 2004

Test specification: FCC Part 15, Sub-part C and RSS 210 , Issue 7

Notes: (1) Fo = 345 MHz. (2) Detector = Peak (3) Frequency range scanned to 4 GHz.

Emissions not reported were more than 20dB below the specified unit.

$$[(\text{Meter reading} + \text{Cable/Amp factor} + \text{Antenna factor}) / 20]]$$

(4) Conv. Reading = 10

(5) Corr. Reading = Conv. Reading X Duty Cycle

(6) Six Highest Emissions Recorded

Freq. (MHz)	Antenna Polarity (V/H)	Meter Reading (dB uV)	Cable/Amp Factor (dB)	Antenna Factor (dB/m)	Conv. Reading (uV/M)	Duty Cycle (%)	Corr. Reading (uV/M)	Limit @ 3M (uV/M)
30			LAST CAL 16 FEB 09 CABLE C	LAST CAL 10 JUL 09 BICONILOG S/N:0004568 2				729
345	h	72.62	2.3	15.35	32621.2	10.0%	3262.1	7292
690	h	29.78 *	3.2	20.02	446.7	10.0%	44.7	729
1035	h	28.98 *	4.4	24.85	815.6	10.0%	81.6	500
1380	h	29.68 *	4.9	25.93	1060.5	10.0%	106.0	500
1725	h	30.00 *	5.5	26.96	1327.4	10.0%	132.7	729
2070	h	30.21 *	6.4	31.36	2503.2	10.0%	250.3	729
2415	h	29.08 *	6.9	32.15	2549.8	10.0%	255.0	729
2760	h	29.12 *	7.4	32.37	2782.9	10.0%	278.3	500
3105	h	30.99 *	7.9	32.73	3810.7	10.0%	381.1	729
3450	h	30.87 *	9.2	33.00	4503.0	10.0%	450.3	729
4000		NOTE: * = NOISE FLOOR	LAST CAL 16 FEB 09 CABLE C	LAST CAL 10 JUL 09 BICONILOG S/N:0004568 2				