

ALARM DEVICE MANUFACTURING COMPANY
165 EILEEN WAY
SYOSSET, NY 11791

FCC ID # CFS8DL5839US-1

Date : _July, 10, 2003_ Tested by : _Greg_Barbato_____ Approved by : Ken Addy_____

Test Sample (model) : ___5839US-1___(RECEIVER)_____

Test method: ANSI C63.4 - 1992

Test specification: FCC Part 15, Sub-part C

Notes: (1) Fo = 345MHz. (2) Detector = Peak (3) Frequency range scanned to 4 GHz.

Emissions not reported were more than 20dB below the specified unit.

[(Meter reading + Cable/Amp factor + Antenna factor) / 20]

(4) Conv. Reading = 10

(5) Corr. Reading = Conv. Reading X Duty Cycle

(6) Six Highest Emissions Recorded

Freq. (MHz)	Antenna Polarity (V/H)	Meter Reading (dB uV)	Cable/Amp Factor (dB)	Antenna Factor (dB/M)	Conv. Reading (uV/M)	Duty Cycle (%)	Corr. Reading (uV/M)	Limit @ 3M (uV/M)
30								200
366.7	H	25.89	1.2	17.7	173.6	100.0%	173.6	200
770.683	H	19.87	2	23.5	185.6	100.0%	185.6	200
829.966	H	17.97	2.1	23.8	156.1	100.0%	156.1	200
1363.516	H	18.42	2.9	25.4	216.8	100.0%	216.8	500
1422.799	H	17.98	3.1	25.4	210.9	100.0%	210.9	500
4000								