

ALARM DEVICE MANUFACTURING COMPANY
165 EILEEN WAY
SYOSSET, NY 11791

EXHIBIT 5-3

FCC ID # CFS8DL5842

Date : _03/02/2004_____ Tested by : _G.Barbato___ Approved by : __K.Addy_____

Test Sample (model) : _____5842_____

Test method: ANSI C63.4 - 1992

Test specification: FCC Part 15, Sub-part C

Notes: (1) Fo = 345MHz. (2) Detector = Peak (3) Frequency range scanned to 4 GHz.

Emissions not reported were more than 20dB below the specified unit.

[(Meter reading + Cable/Amp factor + Antenna factor) / 20]

(4) Conv. Reading = 10

(5) Corr. Reading = Conv. Reading X Duty Cycle

(6) Six Highest Emissions Recorded

Freq. (MHz)	Antenna Polarity (V/H)	Meter Reading (dB uV)	Cable/Am p Factor (dB)	Antenna Factor (dB/M)	Conv. Reading (uV/M)	Duty Cycle (%)	Corr. Reading (uV/M)	Limit @ 3M (uV/M)
30								729
345	H	74.60	1.2	17.91	48473.0	15%	7271.0	7292
690	H	48.00	2	22.81	4370.2	15%	655.5	729
1035	H	34.06	2.6	25.69	1310.7	15%	196.6	500
1380	H	25.20	3	25.51	484.7	15%	72.7	500
1725	H	26.00	3.5	26.25	613.1	15%	92.0	729
2070	H	25.67	3.9	28.31	783.4	15%	117.5	729
2415	H	25.33	4.3	28.57	812.8	15%	121.9	729
2760	H	24.17	4.7	29.52	830.8	15%	124.6	729
3105	H	23.87	4.9	30.83	955.0	15%	143.2	729
3405	H	24.17	5.1	32.4	1212.0	15%	181.8	729
4000								