

Honeywell International Inc.
165 EILEEN WAY
SYOSSET, NY 11791

EXHIBIT 5-3

FCC ID # CFS8DL5853-2

Date : _11/30/2004_____ Tested by : _G.Barbato___ Approved by : __K.E._____

Test Sample (model) : _____5853-2_____

Test method: ANSI C63.4 - 1992

Test specification: FCC Part 15, Sub-part C

Notes: (1) Fo = 345MHz. (2) Detector = Peak (3) Frequency range scanned to 4 GHz.

Emissions not reported were more than 20dB below the specified unit.

[(Meter reading + Cable/Amp factor + Antenna factor) / 20]

(4) Conv. Reading = 10

(5) Corr. Reading = Conv. Reading X Duty Cycle

(6) Six Highest Emissions Recorded

Freq. (MHz)	Antenna Polarity (V/H)	Meter Reading (dB uV)	Cable/Amp Factor (dB)	Antenna Factor (dB/M)	Conv. Reading (uV/M)	Duty Cycle (%)	Corr. Reading (uV/M)	Limit @ 3M (uV/M)
30			CABLE "A"	BICONOLOG				729
345	h	81.17	1.3	14.78	72861.8	10.0%	7286.2	7292
690	h	37.69	1.7	19.10	840.4	10.0%	84.0	729
1035	h	31.00	2.3	22.70	631.0	10.0%	63.1	500
1380	h	45.20	3.0	25.10	4623.8	10.0%	462.4	500
1725	h	39.89	3.3	27.55	3443.5	10.0%	344.3	729
2070	h	43.50	3.8	29.42	6854.9	10.0%	685.5	729
2415	h	27.89	4.1	31.85	1556.0	10.0%	155.6	729
2760	h	28.00	4.1	32.20	1640.6	10.0%	164.1	729
3105	h	22.00	5.7	31.75	938.6	10.0%	93.9	729
3450	h	22.00	6.2	32.28	1056.8	10.0%	105.7	729
4000			CABLE "A"	BICONOLOG				