

ALARM DEVICE MANUFACTURING COMPANY
165 EILEEN WAY
SYOSSET, NY 11791

FCC ID # CFS8DL5853-1

Date : __11/11/2003__ Tested by: Greg Barbato

Approved by: Ken Addy

Test Sample (model) : _____ 5853-1

Test method: ANSI C63.4 - 1992

Test specification: FCC Part 15, Sub-part C

Notes: (1) Fo = 345MHz. (2) Detector = Peak (3) Frequency range scanned to 4 GHz.

Emissions not reported were more than 20dB below the specified unit.

[(Meter reading + Cable/Amp factor + Antenna factor) / 20]]

(4) Conv. Reading = 10

(5) Corr. Reading = Conv. Reading X Duty Cycle

(6) Six Highest Emissions Recorded

Freq. (MHz)	Antenna Polarity (V/H)	Meter Reading (dB uV)	Cable/Amp Factor (dB)	Antenna Factor (dB/M)	Conv. Reading (uV/M)	Duty Cycle (%)	Corr. Reading (uV/M)	Limit @ 3M (uV/M)
30								729
345	H	78.10	1.2	17.91	72527.0	10%	7252.7	7292
690	H	33.71	2	22.81	843.3	10%	84.3	729
1035	H	34.89	2.6	25.69	1442.1	10%	144.2	500
1380	H	25.00	3	25.51	473.7	10%	47.4	500
1725	H	33.00	3.5	26.25	1372.5	10%	137.2	729
2070	H	25.00	3.9	28.31	725.3	10%	72.5	729
2415	H	25.00	4.3	28.57	782.5	10%	78.3	729
2760	H	25.00	4.7	29.52	914.1	10%	91.4	729
3105	H	25.00	4.9	30.83	1087.7	10%	108.8	729
3450	H	25.00	5.1	32.4	1333.5	10%	133.4	729
4000								