

HONEYWELL SECURITY & CUSTOM ELECTRONICS

2 Corporate Center Drive
Melville, NY 11747

EXHIBIT 5-3
FCC ID:
REV 2011A
CFS8DL5870API1

Date : 31-May 2011

Tested by: G. BARBATO

Approved by: K. Eskildsen

Test Sample (model): 5870API1

Test method: ANSI C63.4 - 2004

Test specification: FCC Part 15, Sub-part C and RSS 210 , Issue 8

Notes: (1) Fo: 344.94 (2) Detector = Peak (3) Frequency range scanned to 4 GHz.

Emissions not reported were more than 20dB below the specified unit.

[(Meter reading + Cable/Amp factor + Antenna factor) / 20]

(4) Conv. Reading = 10

(5) Corr. Reading = Conv. Reading X Duty Cycle

(6) Six Highest Emissions Recorded

Freq. (MHz)	Antenna Polarity (V/H)	UUT ORIENTATION	Meter Reading (dB uV)	Cable/Amp Factor (dB)	Antenna Factor (dB/m)	Conv. Reading (uV/M)	Duty Cycle (%)	Corr. Reading (uV/M)	Limit @ 3M (uV/M)
30				LAST CAL 15 JAN 10 CABLE C	LAST CAL 09-SEP-10 BICONILOG S/N:00045682				729
344.94	V	V	58.27	2.3	14.80	5868.1	10.0%	586.8	7292
689.88	V	V	42.15	3.2	19.80	1809.3	10.0%	180.9	729
1034.82	V	H	23.05	4.4	23.84	366.9	10.0%	36.7	500
1379.76	V	H	21.19	4.9	26.08	406.0	10.0%	40.6	500
1724.70	V	V	22.07	5.5	28.69	650.1	10.0%	65.0	729
2069.64	V	H	22.52	6.4	30.28	912.0	10.0%	91.2	729
2414.58	V	V	22.66	6.9	31.51	1131.1	10.0%	113.1	729
2759.52	V	V	22.97	7.4	31.56	1248.8	10.0%	124.9	500
3104.46	V	V	22.57	7.9	31.93	1318.3	10.0%	131.8	729
3449.40	V	V	23.86	9.2	33.44	2113.5	10.0%	211.3	729
4000				LAST CAL 15 JAN 10 CABLE C	LAST CAL 09-SEP-10 BICONILOG S/N:00045682				

