

HONEYWELL SECURITY & CUSTOM ELECTRONICS

165 EILEEN WAY

SYOSSET, NY 11791

EXHIBIT 5-3

FCC ID # CFS8DL5878

Date : 5/30/2006

Tested by :Y. Mohammed

Approved by :K.Addy

Test Sample (model) : 5878

Test method: ANSI C63.4 - 2003

Test specification: FCC Part 15, Sub-part C

Notes: (1) Fo = 345MHz. (2) Detector = Peak (3) Frequency range scanned to 4 GHz.

Emissions not reported were more than 20dB below the specified unit.

[(Meter reading + Cable/Amp factor + Antenna factor) / 20]

(4) Conv. Reading = 10

(5) Corr. Reading = Conv. Reading X Duty Cycle

(6) Six Highest Emissions Recorded

Freq. (MHz)	Antenna Polarity (V/H)	Meter Reading (dB uV)	Cable/Amp Factor (dB)	Antenna Factor (dB/m)	Conv. Reading (uV/M)	Duty Cycle (%)	Corr. Reading (uV/M)	Limit @ 3M (uV/M)
30			CABLE "A"	BICONILOG				729
345	H	74.60	1.2	14.78	33806.5	14.3%	4834.3	7292
690	H	40.00	1.8	19.10	1109.2	14.3%	158.6	729
1035	H	30.00	2.2	22.70	555.9	14.3%	79.5	500
1380	H	33.00	2.5	24.96	1054.4	14.3%	150.8	500
1725	H	39.00	2.8	27.55	2934.3	14.3%	419.6	729
2070	H	41.00	3.0	29.52	4742.4	14.3%	678.2	729
2415	H	34.00	3.3	31.13	2639.4	14.3%	377.4	729
2760	H	32.00	3.7	31.50	2290.9	14.3%	327.6	500
3105	H	32.00	4.1	31.61	2429.4	14.3%	347.4	729
3450	H	30.00	4.4	32.22	2142.9	14.3%	306.4	729
4000			CABLE "A"	BICONILOG				

HONEYWELL SECURITY & CUSTOM ELECTRONICS165 EILEEN WAY
SYOSSET, NY 11791**EXHIBIT 5-3****FCC ID # CFS8DL5878**

Date : 5/30/2006

Tested by :Y. Mohammed

Approved by :K.Addy

Test Sample (model) : 5878

Test method: ANSI C63.4 - 2003

Test specification: FCC Part 15, Sub-part C

Notes: (1) Fo = 345MHz. (2) Detector = Peak (3) Frequency range scanned to 4 GHz.

Emissions not reported were more than 20dB below the specified unit.

[(Meter reading + Cable/Amp factor + Antenna factor) / 20]

(4) Conv. Reading = 10

(5) Corr. Reading = Conv. Reading X Duty Cycle

(6) Six Highest Emissions Recorded

Freq. (MHz)	Antenna Polarity (V/H)	Meter Reading (dB uV)	Cable/Amp Factor (dB)	Antenna Factor (dB/m)	Conv. Reading (uV/M)	Duty Cycle (%)	Corr. Reading (uV/M)	Limit @ 3M (uV/M)
30			CABLE "A"	BICONILOG				729
345	H	74.60	1.2	14.78	33806.5	10.0%	3380.6	7292
690	H	40.00	1.8	19.10	1109.2	10.0%	110.9	729
1035	H	30.00	2.2	22.70	555.9	10.0%	55.6	500
1380	H	33.00	2.5	24.96	1054.4	10.0%	105.4	500
1725	H	39.00	2.8	27.55	2934.3	10.0%	293.4	729
2070	H	41.00	3.0	29.52	4742.4	10.0%	474.2	729
2415	H	34.00	3.3	31.13	2639.4	10.0%	263.9	729
2760	H	32.00	3.7	31.50	2290.9	10.0%	229.1	500
3105	H	32.00	4.1	31.61	2429.4	10.0%	242.9	729
3450	H	30.00	4.4	32.22	2142.9	10.0%	214.3	729
4000			CABLE "A"	BICONILOG				