

HONEYWELL SECURITY & CUSTOM ELECTRONICS**165 EILEEN WAY****SYOSSET, NY 11791****EXHIBIT 5-3 PAGE 1 of 2****FCC ID # CFS8DL5883-2**

Date : 06/16/2005

Tested by :G. Blakely

Approved by :K.Addy

Test Sample (model) : 5883

Test method: ANSI C63.4 - 1992

Test specification: FCC Part 15, Sub-part C

Notes: (1) Fo = 345MHz. (2) Detector = Peak (3) Frequency range scanned to 4 GHz.

Emissions not reported were more than 20dB below the specified unit.

[(Meter reading + Cable/Amp factor + Antenna factor) / 20]

(4) Conv. Reading = 10

(5) Corr. Reading = Conv. Reading X Duty Cycle

(6) Six Highest Emissions Recorded

Freq. (MHz)	Antenna Polarity (V/H)	Meter Reading (dB uV)	Cable/Amp Factor (dB)	Antenna Factor (dB/M)	Conv. Reading (uV/M)	Duty Cycle (%)	Corr. Reading (uV/M)	Limit @ 3M (uV/M)
30			CABLE "A"	BICONILOG				729
345	H	72.00	1.2	14.78	25061.1	22.0%	5513.4	7292
690	H	35.80	1.8	19.10	683.9	22.0%	150.5	729
1035	H	42.20	2.2	22.70	2264.6	22.0%	498.2	500
1380	H	31.40	2.5	24.96	877.0	22.0%	192.9	500
1725	H	40.00	2.8	27.55	3292.3	22.0%	724.3	729
2070	H	30.10	3.0	29.52	1352.1	22.0%	297.5	729
2415	H	28.60	3.3	31.13	1417.4	22.0%	311.8	729
2760	H	25.00	3.7	31.50	1023.3	22.0%	225.1	729

HONEYWELL SECURITY & CUSTOM ELECTRONICS**165 EILEEN WAY****SYOSSET, NY 11791****EXHIBIT 5-3 PAGE 2 of 2****FCC ID # CFS8DL5883-2**

Date : 06/16/2005

Tested by :G. Blakely

Approved by :K.Addy

Test Sample (model) : 5883

Test method: ANSI C63.4 - 1992

Test specification: FCC Part 15, Sub-part C

Notes: (1) Fo = 345MHz. (2) Detector = Peak (3) Frequency range scanned to 4 GHz.

Emissions not reported were more than 20dB below the specified unit.

[(Meter reading + Cable/Amp factor + Antenna factor) / 20]

(4) Conv. Reading = 10

(5) Corr. Reading = Conv. Reading X Duty Cycle

(6) Six Highest Emissions Recorded

Freq. (MHz)	Antenna Polarity (V/H)	Meter Reading (dB uV)	Cable/Amp Factor (dB)	Antenna Factor (dB/M)	Conv. Reading (uV/M)	Duty Cycle (%)	Corr. Reading (uV/M)	Limit @ 3M (uV/M)
30			CABLE "A"	BICONILOG				729
345	H	75.30	1.2	14.78	36643.8	16.3%	5972.9	7292
690	H	38.10	1.8	19.10	891.3	16.3%	145.3	729
1035	H	44.80	2.2	22.70	3054.9	16.3%	498.0	500
1380	H	29.80	2.5	24.96	729.5	16.3%	118.9	500
1725	H	42.60	2.8	27.55	4441.2	16.3%	723.9	729
2070	H	30.20	3.0	29.52	1367.7	16.3%	222.9	729
2415	H	27.90	3.3	31.13	1307.7	16.3%	213.2	729
2760	H	24.80	3.7	31.50	1000.0	16.3%	163.0	729