

ALARM DEVICE MANUFACTURING COMPANY
165 EILEEN WAY
SYOSSET, NY 11791

FCC ID# CFS8DLS883

DATE: OCT 19, 2000 TESTED BY: Stan Alketch APPROVED BY: Norman Ashby

ADEMCO 5883 TRANSCEIVER (RECIEVER)

TEST SAMPLE (model): _____

TEST METHOD: ANSI C63.4-1992

TEST SPECIFICATION: FCC PART 15, SUBPART B

NOTES: 1) $F_0 = 355.7$ MHZ
2) DETECTOR = PEAK.
3) FREQUENCY RANGE SCANNED TO 4 GHz.

$$\frac{(\text{METER READING} + \text{CABLE /AMP FACTOR} + \text{ANTENNA FACTOR})}{20}$$

4) CONVERTED READING = 10

5) SIX HIGHEST EMISSIONS RECORDED.

Frequency (MHz)	Antenna Polarity (V-H)	Meter Reading (dB uV)	Cable/Amp Factor (dB)	Antenna Factor (dB/M)	Converted Reading (uV/M)	Duty Cycle (%)	Corrected Reading (uV/M)	Limit @ 3 Meter (uV/M)
59	V	21.7	0.9	9.5	40.3	N/A		100
119	V	17.3	1.5	11.1	31.3	N/A		150
296	V	15.0	2.0	23.1	101.2	N/A		200
356	V	23.5	2.1	16.1	121.6	N/A		200
415	H	25.0	2.2	17.4	169.8	N/A		200
474	V	14.4	2.3	18.9	60.3	N/A		200

NOTES: