

HONEYWELL SECURITY & CUSTOM ELECTRONICS**165 EILEEN WAY****SYOSSET, NY 11791****EXHIBIT 5-3****FCC ID # CFS8DL5890PI-1**

Date : 2/1/2005

Tested by :Y. Mohammed

Approved by :K.Addy

Test Sample (model) : 5890/5890PI

Transistor - N10-55GN

Test method: ANSI C63.4 - 1992

Test specification: FCC Part 15, Sub-part C

Notes: (1) Fo = 345MHz. (2) Detector = Peak (3) Frequency range scanned to 4 GHz.

Emissions not reported were more than 20dB below the specified unit.

[(Meter reading + Cable/Amp factor + Antenna factor) / 20]

(4) Conv. Reading = 10

(5) Corr. Reading = Conv. Reading X Duty Cycle

(6) Six Highest Emissions Recorded

Freq. (MHz)	Antenna Polarity (V/H)	Meter Reading (dB uV)	Cable/Amp Factor (dB)	Antenna Factor (dB/M)	Conv. Reading (uV/M)	Duty Cycle (%)	Corr. Reading (uV/M)	Limit @ 3M (uV/M)
30			CABLE "A"	BICONILOG				729
345	H	78.90	1.3	14.78	56104.8	10.0%	5610.5	7292
690	H	53.80	1.7	19.10	5370.3	10.0%	537.0	729
1035	H	47.20	2.3	22.70	4073.8	10.0%	407.4	500
1380	H	40.10	3.0	25.10	2570.4	10.0%	257.0	500
1725	H	42.20	3.3	27.55	4492.6	10.0%	449.3	729
2070	H	38.60	3.8	29.42	3899.4	10.0%	389.9	729
2415	H	37.20	4.1	31.85	4544.6	10.0%	454.5	729
2760	H	36.90	4.1	32.20	4570.9	10.0%	457.1	729
3105	H	37.60	5.7	31.75	5655.9	10.0%	565.6	729
3450	H	38.00	6.2	32.28	6668.1	10.0%	666.8	729
4000			CABLE "A"	BICONILOG				