

HONEYWELL SECURITY & CUSTOM ELECTRONICS**165 EILEEN WAY****SYOSSET, NY 11791****EXHIBIT 5-3****FCC ID # CFS8DL6150RF-3**

Date : 5/11/2005

Tested by :Y. Mohammed

Approved by :K.Addy

Test Sample (model) : 6150RFH-2

Transistor - N10-55GN

Test method: ANSI C63.4 - 1992

Test specification: FCC Part 15, Sub-part C

Notes: (1) Fo = 345MHz. (2) Detector = Peak (3) Frequency range scanned to 4 GHz.

Emissions not reported were more than 20dB below the specified unit.

[(Meter reading + Cable/Amp factor + Antenna factor) / 20]

(4) Conv. Reading = 10

(5) Corr. Reading = Conv. Reading X Duty Cycle

(6) Six Highest Emissions Recorded

Freq. (MHz)	Antenna Polarity (V/H)	Meter Reading (dB uV)	Cable/Amp Factor (dB)	Antenna Factor (dB/M)	Conv. Reading (uV/M)	Duty Cycle (%)	Corr. Reading (uV/M)	Limit @ 3M (uV/M)
30			CABLE "A"	BICONILOG				729
345	H	80.40	1.3	14.78	66680.7	10.0%	6668.1	7292
690	H	41.00	1.7	19.10	1230.3	10.0%	123.0	729
1035	H	43.00	2.3	22.70	2511.9	10.0%	251.2	500
1380	H	35.00	3.0	24.96	1406.0	10.0%	140.6	500
1725	H	27.00	3.3	27.55	780.7	10.0%	78.1	729
2070	H	27.00	3.8	29.52	1037.5	10.0%	103.8	729
2415	H	31.00	4.1	31.13	2048.8	10.0%	204.9	729
2760	H	27.00	4.1	31.50	1349.0	10.0%	134.9	729
3105	H	27.00	5.7	31.61	1642.5	10.0%	164.2	729
3450	H	27.00	6.2	32.22	1866.4	10.0%	186.6	729
4000			CABLE "A"	BICONILOG				