

HONEYWELL SECURITY & CUSTOM ELECTRONICS
2 Corporate Center Drive
Melville, NY 11747

REV I MAR 09

EXHIBIT 5-3

FCC ID CFS8DL6150RFT2

Date : 06/30/2009 Tested by : GREG BARBATO Approved by : K. Eskildsen
 Test Sample (model) : 6150RF NEW BOARD
 Test method: ANSI C63.4 - 2004
 Test specification: FCC Part 15, Sub-part C and RSS 210 , Issue 7
 Notes: (1) Fo = 345MHz. (2) Detector = Peak (3) Frequency range scanned to 4 GHz.
 Emissions not reported were more than 20dB below the specified unit.
 [(Meter reading + Cable/Amp factor + Antenna factor) / 20]
 (4) Conv. Reading = 10
 (5) Corr. Reading = Conv. Reading X Duty Cycle
 (6) Six Highest Emissions Recorded

Freq. (MHz)	Antenna Polarity (V/H)	Meter Reading (dB uV)	Cable/Amp Factor (dB)	Antenna Factor (dB/m)	Conv. Reading (uV/M)	Duty Cycle (%)	Corr. Reading (uV/M)	Limit @ 3M (uV/M)
30			LAST CAL 16 FEB 09 CABLE C	LAST CAL 09 MAR 09 BICONILOG S/N:00029390				729
345	h	76.51	2.3	14.59	46773.5	15.0%	7016.0	7292
690	h	31.58	3.2	19.33	507.6	15.0%	76.1	729
1035	h	35.48	4.4	24.53	1661.5	15.0%	249.2	500
1380	h	20.45	4.9	25.69	356.5	15.0%	53.5	500
1725	h	21.79	5.5	26.72	501.8	15.0%	75.3	729
2070	h	21.59	6.4	29.57	755.1	15.0%	113.3	729
2415	h	20.62	6.9	30.41	788.0	15.0%	118.2	729
2760	h	22.03	7.4	32.01	1180.3	15.0%	177.0	500
3105	h	23.10	7.9	32.54	1503.1	15.0%	225.5	729
3450	h	23.36	9.2	32.96	1888.0	15.0%	283.2	729
4000			LAST CAL 16 FEB 09 CABLE C	LAST CAL 09 MAR 09 BICONILOG S/N:00029390				