

HONEYWELL SECURITY & CUSTOM ELECTRONICS**REV 08-21-2012-L****2 Corporate Center Drive****Melville, NY 11747****EXHIBIT 5-3****FCC ID: CFS8DL****6162RF**

Date :	30-Jan	2013	Tested by:	Greg Barbato	Approved by: S. A.																																
Test Sample (model):	6162RF																																				
Test method:	ANSI C63.4 - 2003																																				
Test specification:	FCC Part 15, Sub-part C and RSS 210 , Issue 8																																				
Notes:	(1) Fo: 344.94 (2) Detector = Peak (3) Frequency range scanned to 4 GHz. (Emissions not reported were more than 20dB below the specified unit). [(Meter reading + Cable/Amp factor + Antenna factor) / 20]] (4) Conv. Reading = 10 (5) Corr. Reading = Conv. Reading X Duty Cycle (6) Six Highest Emissions Recorded																																				
<table border="1"> <thead> <tr> <th colspan="4">PRESCAN:</th> </tr> <tr> <th>SENSE / UUT:</th> <th>EL (cm):</th> <th>AZ (deg):</th> <th>Meter Reading (dB uV):</th> </tr> </thead> <tbody> <tr> <td>V/V</td> <td>152.5</td> <td>0.0</td> <td>74.90</td> </tr> <tr> <td>H/V</td> <td>237.4</td> <td>0.0</td> <td>75.30</td> </tr> <tr> <td>V/H</td> <td>100.0</td> <td>81.0</td> <td>78.49</td> </tr> <tr> <td>H/H</td> <td>100.0</td> <td>81.0</td> <td>81.68</td> </tr> <tr> <td>V/O</td> <td>138.6</td> <td>179.0</td> <td>79.43</td> </tr> <tr> <td>H/O</td> <td>243.0</td> <td>179.4</td> <td>79.47</td> </tr> </tbody> </table>						PRESCAN:				SENSE / UUT:	EL (cm):	AZ (deg):	Meter Reading (dB uV):	V/V	152.5	0.0	74.90	H/V	237.4	0.0	75.30	V/H	100.0	81.0	78.49	H/H	100.0	81.0	81.68	V/O	138.6	179.0	79.43	H/O	243.0	179.4	79.47
PRESCAN:																																					
SENSE / UUT:	EL (cm):	AZ (deg):	Meter Reading (dB uV):																																		
V/V	152.5	0.0	74.90																																		
H/V	237.4	0.0	75.30																																		
V/H	100.0	81.0	78.49																																		
H/H	100.0	81.0	81.68																																		
V/O	138.6	179.0	79.43																																		
H/O	243.0	179.4	79.47																																		

Freq. (MHz):	Sense Antenna Polarity (V/H):	THE ORENTATION OF THE UUT (V,H,O.):	Meter Reading (dB uV):	Cable/Amp Factor (dB):	Antenna Factor (dB/m):	Conv. Reading (uV/M):	Duty Cycle (%):	Corr. Reading (uV/M):	Limit @ 3M (uV/M):
344.94	H	H	74.90	2.5	15.91	46,291.4	15.0%	6943.7	7,289
689.88	H	H	32.56	3.7	21.12	741.3	15.0%	111.2	729
1034.82	H	H	20.39	4.7	24.65	306.9	15.0%	46.0	500
1379.76	H	H	23.98	5.6	27.53	717.8	15.0%	107.7	500
1724.70	H	H	20.45	6.3	30.10	692.6	15.0%	103.9	729
2069.64	H	H	21.74	7.3	31.04	1,003.5	15.0%	150.5	729
2414.58	H	H	21.21	8.1	31.71	1,119.4	15.0%	167.9	729
2759.52	H	H	22.67	8.6	32.29	1,508.3	15.0%	226.3	500
3104.46	H	H	20.44	9.1	32.81	1,312.2	15.0%	196.8	729
3449.40	H	H	21.78	10.0	34.46	2,044.1	15.0%	306.6	729
4000				LAST CAL 10 JUL 12 CABLE D	LAST CAL 27-JUN-12 BICONILOG S/N:00020971				