

ALARM DEVICE MANUFACTURING COMPANY
165 EILEEN WAY
SYOSSET, NY 11791

FCC ID # CFS8DLLYNXREN-1

Date : _July, 24,2003_ Tested by : _G. Barbato___ Approved by : _Ken Addy___

Test Sample (model) : ___LYNXREN-1_____

Test method: ANSI C63.4 - 1992

Test specification: FCC Part 15, Sub-part C

Notes: (1) Fo = 345MHz. (2) Detector = Peak (3) Frequency range scanned to 4 GHz.

Emissions not reported were more than 20dB below the specified unit.

[(Meter reading + Cable/Amp factor + Antenna factor) / 20]

(4) Conv. Reading = 10

(5) Corr. Reading = Conv. Reading X Duty Cycle

(6) Six Highest Emissions Recorded

Freq. (MHz)	Antenna Polarity (V/H)	Meter Reading (dB uV)	Cable/Am p Factor (dB)	Antenna Factor (dB/M)	Conv. Reading (uV/M)	Duty Cycle (%)	Corr. Reading (uV/M)	Limit @ 3M (uV/M)
30								729
345	H	73.39	1.2	17.91	42169.7	15.26%	6435.1	7292
690	H	30.99	2	22.81	616.6	15.26%	94.1	729
1035	H	26.49	2.6	25.69	548.3	15.26%	83.7	500
1380	H	28.09	3	25.51	676.1	15.26%	103.2	500
1725	H	29.79	3.5	26.25	948.4	15.26%	144.7	729
2070	H	26.89	3.9	28.31	901.6	15.26%	137.6	729
2415	H	24.87	4.3	28.57	770.9	15.26%	117.6	729
2760	H	24.87	4.7	29.52	900.5	15.26%	137.4	729
3105	H	24.87	4.9	30.83	1071.5	15.26%	163.5	729
3405	H	24.87	5.1	32.4	1313.7	15.26%	200.5	729
4000								