

HONEYWELL SECURITY & CUSTOM ELECTRONICS**165 EILEEN WAY****SYOSSET, NY 11791****EXHIBIT 5-3****FCC ID # CFS8DLLYNXREN-5**

Date : 4/10/2006

Tested by :Y. Mohammed

Approved by :K.Addy

Test Sample (model) : LYNXR-ENSIA

Test method: ANSI C63.4 - 1992

Test specification: FCC Part 15, Sub-part C

Notes: (1) Fo = 345MHz. (2) Detector = Peak (3) Frequency range scanned to 4 GHz.

Emissions not reported were more than 20dB below the specified unit.

[(Meter reading + Cable/Amp factor + Antenna factor) / 20]

(4) Conv. Reading = 10

(5) Corr. Reading = Conv. Reading X Duty Cycle

(6) Six Highest Emissions Recorded

Freq. (MHz)	Antenna Polarity (V/H)	Meter Reading (dB uV)	Cable/Amp Factor (dB)	Antenna Factor (dB/m)	Conv. Reading (uV/M)	Duty Cycle (%)	Corr. Reading (uV/M)	Limit @ 3M (uV/M)
30			CABLE "A"	BICONILOG				729
345	H	68.00	1.2	14.78	15812.5	15.0%	2371.9	7292
690	H	35.00	1.8	19.10	623.7	15.0%	93.6	729
1035	H	29.00	2.2	22.70	495.5	15.0%	74.3	500
1380	H	28.00	2.5	24.96	592.9	15.0%	88.9	500
1725	H	30.00	2.8	27.55	1041.1	15.0%	156.2	729
2070	H	33.00	3.0	29.52	1888.0	15.0%	283.2	500
2415	H	28.00	3.3	31.13	1322.8	15.0%	198.4	729
2760	H	28.00	3.7	31.50	1445.4	15.0%	216.8	729
3105	H	28.00	4.1	31.61	1532.9	15.0%	229.9	729
3450	H	28.00	4.4	32.22	1702.2	15.0%	255.3	729
4000			CABLE "A"	BICONILOG				