

<b>Prüfbericht-Nr.:</b> <i>Test Report No.:</i>	<b>50157346 001</b>	<b>Auftrags-Nr.:</b> <i>Order No.:</i>	114078743	Seite 1 von 24 Page 1 of 24
<b>Kunden-Referenz-Nr.:</b> <i>Client Reference No.:</i>	N/A	<b>Auftragsdatum:</b> <i>Order date:</i>	13-Jun-2018	
<b>Auftraggeber:</b> <i>Client:</i>	N.V. Nederlandsche Apparatenfabriek "Nedap" , Parallelweg 2, 7141 DC Groenlo, The Netherlands			
<b>Prüfgegenstand:</b> <i>Test item:</i>	Lumen iL33			
<b>Bezeichnung / Typ-Nr.:</b> <i>Identification / Type No.:</i>	ASSY T325R RF+MD+RFID ASSY T325R RF+RFID			
<b>Auftrags-Inhalt:</b> <i>Order content:</i>	IC/FCC Part 15C Test report for 8.2 MHz portion			
<b>Prüfgrundlage:</b> <i>Test specification:</i>	FCC 47CFR Part 15: Subpart C Section 15.223 RSS-210 (08-2016) B.4			
<b>Wareneingangsdatum:</b> <i>Date of receipt:</i>	4-Jul-2018			
<b>Prüfmuster-Nr.:</b> <i>Test sample No.:</i>	A000769422-005, A000769422-006			
<b>Prüfzeitraum:</b> <i>Testing period:</i>	9-Jul-2018 - 17-Jul-2018			
<b>Ort der Prüfung:</b> <i>Place of testing:</i>	EMC/RF Laboratory Taipei			
<b>Prüflaboratorium:</b> <i>Testing laboratory:</i>	TUV Rheinland Taiwan Ltd.			
<b>Prüfergebnis*:</b> <i>Test result*:</i>	Pass			
<b>geprüft von / tested by:</b>		<b>kontrolliert von / reviewed by:</b>		
15-Aug-2018 Ryan W. T. Chen / Project Manager		15-Aug-2018 Rene Charton/Expert		
<b>Datum</b> <i>Date</i>	<b>Name / Stellung</b> <i>Name / Position</i>	<b>Unterschrift</b> <i>Signature</i>	<b>Datum</b> <i>Date</i>	<b>Name / Stellung</b> <i>Name / Position</i>
				<b>Unterschrift</b> <i>Signature</i>
<b>Sonstiges / Other:</b>				
<b>Zustand des Prüfgegenstandes bei Anlieferung:</b> <i>Condition of the test item at delivery:</i>		Prüfmuster vollständig und unbeschädigt <i>Test item complete and undamaged</i>		
* Legende:	1 = sehr gut P(ass) = entspricht o.g. Prüfgrundlage(n)	2 = gut F(ail) = entspricht nicht o.g. Prüfgrundlage(n)	3 = befriedigend N/A = nicht anwendbar	4 = ausreichend N/T = nicht getestet
Legend:	1 = very good P(ass) = passed a.m. test specification(s)	2 = good F(ail) = failed a.m. test specification(s)	3 = satisfactory N/A = not applicable	4 = sufficient N/T = not tested
<p><b>Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens.</b></p> <p><i>This test report only relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</i></p>				

## TEST SUMMARY

### **5.1.1 ANTENNA REQUIREMENT**

*RESULT: Passed*

### **5.1.2 FIELD STRENGTH OF FUNDAMENTAL**

*RESULT: Passed*

### **5.1.3 6dB BANDWIDTH**

*RESULT: Passed*

### **5.1.4 99% BANDWIDTH**

*RESULT: Passed*

### **5.1.5 SPURIOUS EMISSION**

*RESULT: Passed*

### **5.2.1 CONDUCTED EMISSIONS LINE AND NEUTRAL**

*RESULT: Passed*

## Contents

<b>1.</b>	<b>GENERAL REMARKS .....</b>	<b>4</b>
<b>1.1</b>	<b>COMPLEMENTARY MATERIALS .....</b>	<b>4</b>
<b>2.</b>	<b>TEST SITES .....</b>	<b>5</b>
<b>2.1</b>	<b>TEST LABORATORY .....</b>	<b>5</b>
<b>2.2</b>	<b>TEST FACILITY.....</b>	<b>5</b>
<b>2.3</b>	<b>LIST OF TEST AND MEASUREMENT INSTRUMENTS.....</b>	<b>6</b>
<b>2.4</b>	<b>TRACEABILITY .....</b>	<b>7</b>
<b>2.5</b>	<b>CALIBRATION .....</b>	<b>7</b>
<b>2.6</b>	<b>MEASUREMENT UNCERTAINTY .....</b>	<b>7</b>
<b>3.</b>	<b>GENERAL PRODUCT INFORMATION .....</b>	<b>8</b>
<b>3.1</b>	<b>PRODUCT FUNCTION AND INTENDED USE.....</b>	<b>8</b>
<b>3.2</b>	<b>RATINGS AND SYSTEM DETAILS .....</b>	<b>9</b>
<b>3.3</b>	<b>INDEPENDENT OPERATION MODES .....</b>	<b>11</b>
<b>3.4</b>	<b>NOISE GENERATING AND NOISE SUPPRESSING PARTS .....</b>	<b>11</b>
<b>3.5</b>	<b>SUBMITTED DOCUMENTS .....</b>	<b>11</b>
<b>4.</b>	<b>TEST SET-UP AND OPERATION MODES .....</b>	<b>12</b>
<b>4.1</b>	<b>PRINCIPLE OF CONFIGURATION SELECTION.....</b>	<b>12</b>
<b>4.2</b>	<b>TEST OPERATION AND TEST SOFTWARE.....</b>	<b>12</b>
<b>4.3</b>	<b>SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT .....</b>	<b>12</b>
<b>4.4</b>	<b>COUNTERMEASURES TO ACHIEVE EMC COMPLIANCE.....</b>	<b>12</b>
<b>5.</b>	<b>TEST RESULTS .....</b>	<b>13</b>
<b>5.1</b>	<b>TRANSMITTER REQUIREMENT &amp; TEST SUITES .....</b>	<b>13</b>
5.1.1	<i>Antenna Requirement.....</i>	<i>13</i>
5.1.2	<i>Field strength of fundamental.....</i>	<i>14</i>
5.1.3	<i>6dB Bandwidth.....</i>	<i>15</i>
5.1.4	<i>99% Bandwidth.....</i>	<i>17</i>
5.1.5	<i>Spurious Emission.....</i>	<i>19</i>
<b>5.2</b>	<b>MAINS CONDUCTED EMISSIONS.....</b>	<b>20</b>
5.2.1	<i>Conducted Emissions Line and Neutral.....</i>	<i>20</i>
<b>6.</b>	<b>PHOTOGRAPHS OF THE TEST SET-UP .....</b>	<b>21</b>
<b>7.</b>	<b>LIST OF TABLES .....</b>	<b>24</b>
<b>8.</b>	<b>LIST OF PHOTOGRAPHS .....</b>	<b>24</b>

## 1. General Remarks

### 1.1 Complementary Materials

These attachments are integral parts of this test report.:

**Appendix P: Photo Documentation**

(File Name: 50157346APPENDIX P)

**Appendix D: Test Result of Radiated Emissions**

(File Name: 50157346APPENDIX D)

Test Specifications

The following standards were applied.

**Table 1: Applied Standard and Test Levels**

<b>Radio</b>
--------------

FCC CFR47 Part 15: Subpart C Section 15.223 RSS-210 Issue 9 August 2016 ANSI C63.4:2014, ANSI C63.10:2013
-----------------------------------------------------------------------------------------------------------------

## 2. Test Sites

### 2.1 Test Laboratory

TUV Rheinland Taiwan Ltd.  
Taichung Branch Office

No.9, Lane 36, Minsheng Rd., Sec. 3, Daya District,  
Taichung City 428  
Taiwan (R.O.C.)

### 2.2 Test Facility

TUV Rheinland Taiwan Ltd.  
Taipei Office

11F. No.758, Sec. 4, Bade Rd., Songshan Dist.  
Taipei City 105  
Taiwan (R.O.C.)

FCC Registration No.: 340738  
IC Canada Registration No.: 9465A-1  
TAF Accredited NCC Test Lab. No.:0759  
TAF ISO17025 Certification effective periods: 2016-Jul-1st to 2019-Jun-30th



**Testing Laboratory**  
**0759**

## 2.3 List of Test and Measurement Instruments

**Table 2: List of Test and Measurement Equipment**

Kind of Equipment	Manufacturer	Type	S/N	Last Calibration	Next Calibration
Test Software	Farad	EZ_EMC	Ver. TUV3A1	N/A	N/A
EMI Test Receiver	R&S	ESR 7	101549	2017/11/10	2018/11/10
Spectrum Analyzer	R&S	FSV 40	100921	2018/05/02	2019/05/02
EXA Signal Analyzer	KEYSIGHT	N9010A	MY52221334	2018/02/05	2019/02/04
Preamplifier (30MHz -1GHz)	HP	8447F	2805A03335	2017/08/14	2018/08/14
Preamplifier (18 GHz -40 GHz)	COM-POWER	PAM-840	461257	2018/01/18	2019/01/18
Pre-Amplifier (1GHz~18GHz)	EM Electronics	EM01G18G	60558	2017/11/21	2018/11/21
Bilog Antenna	TESEQ	CBL6111D	29804	2017/08/18	2018/08/18
Horn Antenna	ETS-Lindgren	3117	201918	2017/08/18	2018/08/18
Horn Antenna (18GHz~40GHz)	COM-POWER	AH-840	101029	2017/11/28	2018/11/28
Loop Antenna	Schwarzbeck	FMZB 1513	1513-076	2018/06/14	2019/06/14
EMI Test Receiver	R&S	ESR 7	101549	2017/11/10	2018/11/10

## 2.4 Traceability

All measurement equipment calibrations are traceable to NML(Taiwan)/NIST(USA) or where calibration is performed outside Taiwan, to equivalent nationally recognized standards organizations.

## 2.5 Calibration

Equipment requiring calibration is calibrated periodically by the manufacturer or according to manufacturer's specifications. Additionally all equipment is verified for proper performance on a regular basis using in house standards or comparisons.

## 2.6 Measurement Uncertainty

The estimated combined standard uncertainty for radiated emissions and conducted emissions measurements are  $\pm 3$ dB.

**Table 3: Emission Measurement Uncertainty**

Parameter	Uncertainty
Radio Frequency	$\pm 1 \times 10^{-7}$
RF power, conducted	$\pm 1.5$ dB
Adjacent channel power	$\pm 3$ dB
Radiated emission of transmitter, valid up to 26 GHz	$\pm 6$ dB
Radiated emission of receiver, valid up to 26 GHz	$\pm 6$ dB
Temperature	$\pm 2$ °C
Humidity	$\pm 10$ %

## 3. General Product Information

### 3.1 Product Function and Intended Use

The EUT is an Electronic Article Surveillance System. There are 2 models with different features implemented. The fully featured version model ASSY T325R RF+MD+RFID incorporates an UHF RFID reader, a Tag detector working in the 7-8 MHz Band and a metal detector that works at a frequency around 125 kHz.

The alternative version model ASSY T325R RF+RFID does not have the 125 kHz current generator and field sensing module for the metal detector installed, but the antenna system is the same for both versions.

This test report relates to the 7-8 MHz portion of the device.  
Tests were performed on model ASSY T325R RF+MD+RFID.

For details refer to the User Guide.



## 3.2 Ratings and System Details

**Table 4: Basic Information of EUT**

Item	EUT information	
Kind of Equipment	Lumen iL33	
Type Designation	ASSY T325R RF+MD+RFID ASSY T325R RF+RFID	
	with metal detector	without metal detector
FCC ID	CGDT325RRFMDID	CGDT325RRFID
Canada ID	1444A-T325RRFMDID	1444A-T325RRFID
HVIN	ASSY T325R RF+MD+RFID	ASSY T325R RF+RFID

**Table 5: Technical Specification of EUT**

Technical Specification	Value
Operating Frequency	7565 kHz to 8571.25 kHz
Channel number	24
Operation Voltage	120V (PoE adapter)
Modulation	Hopping

**Prüfbericht - Nr.: 50157346 001**  
Test Report No.Seite 10 von 24  
Page 10 of 24

No operation in restricted bands:

Nr.	Frequency (kHz)	Nr.	Frequency (kHz)	Nr.	Frequency (kHz)
1	7565.00	9	7915.00	17	8265.00
2	7608.75	10	7958.75	18	8308.75
3	7652.50	11	8002.50	19	8352.50
4	7696.25	12	8046.25	20	8396.25
5	7740.00	13	8090.00	21	8440.00
6	7783.75	14	8133.75	22	8483.75
7	7827.50	15	8177.50	23	8527.50
8	7871.25	16	8221.25	24	8571.25

The fundamental emission are outside of the bands listed in Section 15.205 (a).

### **3.3 Independent Operation Modes**

Basic operation modes are:

- A. Transmitting
  - 1. Low channel
  - 2. Middle channel
  - 3. High channel

### **3.4 Noise Generating and Noise Suppressing Parts**

Refer to the Circuit Diagram.

### **3.5 Submitted Documents**

- Circuit Diagram
- Instruction Manual
- Rating Label
- Technical Description

## 4. Test Set-up and Operation Modes

### 4.1 Principle of Configuration Selection

The equipment under test (EUT) was configured to measure its maximum emission level. The test modes were adapted accordingly in reference to the instructions for use.

### 4.2 Test Operation and Test Software

Setup for testing: Test samples are modified to continuous transmitter mode which makes it possible to transmit when power on.

Both alarming and non-alarming have been evaluated; only the worst-case situation is shown.

### 4.3 Special Accessories and Auxiliary Equipment

The product has been tested together with the following additional accessories:

Kind of Equipment	Manufacturer	Model Name	S/N
--	--	--	--

### 4.4 Countermeasures to achieve EMC Compliance

The test sample which has been tested contained the noise suppression parts as described in the Constructional Data Form or the Technical Construction File. No additional measures were employed to achieve compliance.

## 5. Test Results

### 5.1 Transmitter Requirement & Test Suites

#### 5.1.1 Antenna Requirement

**RESULT:****Passed**

Standard : Part 15.203 and RSS-Gen 7.1.4  
Requirement : use of approved antennas only

The antenna and the transmitter are one assembly with no possibility of replacement with a non-approved antenna by a normal the end-user. Therefore, the EUT is considered to comply with this provision.

Refer to EUT photo for details.

## 5.1.2 Field strength of fundamental

**RESULT:**
**Passed**

Test standard : FCC Part 15.223  
RSS-210 B.3

Basic standard : ANSI C63.10:2013

**Test setup**

Test Frequency : Low. High  
Operation Mode : A

Atmospheric pressure : 100-103 kPa

**Applicable Limit:**

Frequency (MHz)	Field strength AV ( $\mu\text{V}/\text{m}$ )	Field strength AV (dB $\mu\text{V}/\text{m}$ )	Field strength Pk (dB $\mu\text{V}/\text{m}$ )	Measurement Distance (m)
1.705 - 10	100	40	60	30
1.705 - 10	10000	80	100	3

The center frequency is 8068 kHz.  
The 6 dB BW is more than 810 kHz

**Table 6: Field strength of fundamental, maximal level found**

Frequency (MHz)	Level(3m) (dB $\mu\text{V}/\text{m}$ )	Detector	Limit(3m) (dB $\mu\text{V}/\text{m}$ )	Level(30m) (dB $\mu\text{V}/\text{m}$ )	Limit(30m) (dB $\mu\text{V}/\text{m}$ )	Remark	Result
7.6	<80	PK	100	<40	60	Same PAR as 8.4920 MHz	Pass
8.4920	71.09	PK	100	40.22	60	--	Pass
8.4920	54	AV	80	25.10	40	--	Pass
8.6	<80	PK	100	<40	60	Same PAR as 8.4920 MHz	Pass

Remark: For details refer to Appendix D

### 5.1.3 6dB Bandwidth

**RESULT:****Passed**


Test standard : FCC Part 15.223  
RSS-210 B.3  
Basic standard : ANSI C63.10:2013,  
Kind of test site : Shielded room

**Test setup**

Test Channel : Low/ High  
Operation Mode : A  
  
Ambient temperature : 22-26 °C  
Relative humidity : 50-65 %  
Atmospheric pressure : 100-103 kPa

**Table 7: Test result of 6dB Bandwidth**

Antenna type	Channel Frequency low(MHz)	Channel Frequency high(MHz)	6dB Bandwidth (MHz)
integrated	7.4935	8.5694	1.1998

**6dB Bandwidth Measurement:**


Date: 12.JUL.2018 21:47:35



**5.1.4 99% Bandwidth****RESULT:****Passed**


Test standard : RSS-Gen  
Basic standard : ANSI C63.10:2013  
Kind of test site : Shielded room

**Test setup**

Test Channel : Sweep on  
Operation Mode : A  
Ambient temperature : 22-26 °C  
Relative humidity : 50-65 %  
Atmospheric pressure : 100-103 kPa

**Table 8: Test result of 99% Bandwidth**

Antenna type	99% Bandwidth (kHz)
integrated	2125

**Test Plot of 99% Bandwidth,**


Date: 12.JUL.2018 21:54:54

### 5.1.5 Spurious Emission

**RESULT:****Passed**

Test standard	:	FCC Part 15.223 RSS-Gen
Basic standard Limits	:	ANSI C63.10: 2013 The field strength of emissions outside of the band 1.705–10.0 MHz shall not exceed the general radiated emission limits in § 15.209 Outside of the swept frequency band, the out-of-band emission limits in sections A2.5 and A2.6, or the general field strength limits listed in RSS-Gen apply, whichever are less stringent. This test is to be carried out with the frequency sweep in operation
Kind of test site	:	3m Semi-Anechoic Chamber
<b>Test setup</b>		
Test Channel	:	Sweep on
Operation mode	:	A

Remark: Testing was carried out within frequency range 30MHz to more than the tenth harmonic.

For details refer to Appendix D.

## 5.2 Mains Conducted Emissions

### 5.2.1 Conducted Emissions Line and Neutral

**RESULT:****Passed**

Test standard : LP0002: 2.3  
FCC Part 15.207  
FCC Part 15.107  
RSS-Gen

Limits : Mains Conducted emissions as defined in  
LP0002: 2.3 , must comply with the mains  
conducted emission limits specified in LP0002:  
2.3

Kind of test site : Shielded Room

**Test setup**

Test Channel : Sweep on  
Operation mode : Normal


Remark: For details refer to Appendix D.

## 6. Photographs of the Test Set-Up


Photograph 1: Set-up for Radiated Emissions TX (Front View)



**Photograph 2: Set-up for Radiated Emissions (Back View 1)**



**Photograph 3: Set-up for Radiated Emissions (Back View 2)**



**Photograph 4: Set-up for for Mains Conducted testing Back**



**Photograph 5: Set-up for for Mains Conducted testing Front**



## 7. List of Tables

Table 1: Applied Standard and Test Levels .....	4
Table 2: List of Test and Measurement Equipment.....	6
Table 3: Emission Measurement Uncertainty.....	7
Table 4: Basic Information of EUT .....	9
Table 5: Technical Specification of EUT .....	9
Table 6: Field strength of fundamental, maximal level found .....	14
Table 7: Test result of 6dB Bandwidth .....	15
Table 8: Test result of 99% Bandwidth.....	17

## 8. List of Photographs

Photograph 1: Set-up for Radiated Emissions TX (Front View) .....	21
Photograph 2: Set-up for Radiated Emissions (Back View 1) .....	22
Photograph 3: Set-up for Radiated Emissions (Back View 2) .....	22
Photograph 4: Set-up for for Mains Conducted testing Back.....	23
Photograph 5: Set-up for for Mains Conducted testing Front .....	23